

ETSI TS 138 104 V16.6.0 (2021-01)



**5G;
NR;
Base Station (BS) radio transmission and reception
(3GPP TS 38.104 version 16.6.0 Release 16)**

<https://standards.iteh.ai/catalog/standards/sist/70b11a6a-71cb-46bf-b87c-4a805d6fca18/etsi-ts-138-104-v16-6-0-2021-01>



ReferenceRTS/TSGR-0438104vg60

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Important notice

<https://standards.iteh.ai/catalog/standards/sist/70b11a6a-71cb-46bf-b87c-4a8c6d6a18/sist-ts-138-104-v16-6-0-2021-01>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

<https://standards.iteh.ai/catalog/standards/sist/70b11a6a-71cb-46bf-b87c-4a805d6fca18/etsi-ts-138-104-v16-6-0-2021-01>

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	14
2 References	14
3 Definitions, symbols and abbreviations	15
3.1 Definitions	15
3.2 Symbols.....	19
3.3 Abbreviations	21
4 General	23
4.1 Relationship with other core specifications.....	23
4.2 Relationship between minimum requirements and test requirements	23
4.3 Conducted and radiated requirement reference points	23
4.3.1 BS type 1-C	23
4.3.2 BS type 1-H	24
4.3.3 BS type 1-O and BS type 2-O	25
4.4 Base station classes	25
4.5 Regional requirements.....	26
4.6 Applicability of requirements.....	27
4.7 Requirements for contiguous and non-contiguous spectrum	27
4.8 Requirements for BS capable of multi-band operation	28
4.9 OTA co-location with other base stations	29
5 Operating bands and channel arrangement.....	31
5.1 General	31
5.2 Operating bands	31
5.3 BS channel bandwidth	33
5.3.1 General.....	33
5.3.2 Transmission bandwidth configuration	33
5.3.3 Minimum guardband and transmission bandwidth configuration	34
5.3.4 RB alignment.....	35
5.3.5 BS channel bandwidth per operating band	36
5.3A BS channel bandwidth for CA.....	39
5.3A.1 Transmission bandwidth configuration for CA	39
5.3A.2 Minimum guardband and transmission bandwidth configuration for CA	39
5.4 Channel arrangement.....	41
5.4.1 Channel spacing.....	41
5.4.1.1 Channel spacing for adjacent NR carriers	41
5.4.1.2 Channel spacing for CA	41
5.4.2 Channel raster	42
5.4.2.1 NR-ARFCN and channel raster.....	42
5.4.2.1A NB-IoT carrier frequency numbering.....	43
5.4.2.2 Channel raster to resource element mapping.....	43
5.4.2.3 Channel raster entries for each operating band.....	43
5.4.3 Synchronization raster	46
5.4.3.1 Synchronization raster and numbering.....	46
5.4.3.3 Synchronization raster entries for each operating band.....	47
6 Conducted transmitter characteristics	51
6.1 General	51
6.2 Base station output power	51
6.2.1 General.....	51
6.2.2 Minimum requirement for BS type 1-C.....	52

6.2.3	Minimum requirement for <i>BS type 1-H</i>	52
6.2.4	Additional requirements (regional).....	52
6.3	Output power dynamics.....	52
6.3.1	General.....	52
6.3.2	RE power control dynamic range	52
6.3.2.1	General	52
6.3.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	52
6.3.3	Total power dynamic range	53
6.3.3.1	General	53
6.3.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	53
6.3.4	NB-IoT RB power dynamic range for NB-IoT operation in NR in-band	53
6.3.4.1	General	53
6.3.4.2	Minimum Requirement	54
6.4	Transmit ON/OFF power	54
6.4.1	Transmitter OFF power	54
6.4.1.1	General	54
6.4.1.2	Minimum requirement for <i>BS type 1-C</i>	54
6.4.1.3	Minimum requirement for <i>BS type 1-H</i>	54
6.4.2	Transmitter transient period	54
6.4.2.1	General	54
6.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	55
6.4.2.3	Void.....	55
6.5	Transmitted signal quality	55
6.5.1	Frequency error.....	55
6.5.1.1	General	55
6.5.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	56
6.5.2	Modulation quality.....	56
6.5.2.1	General	56
6.5.2.2	Minimum Requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	56
6.5.2.3	EVM frame structure for measurement.....	56
6.5.3	Time alignment error	57
6.5.3.1	General	57
6.5.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	57
6.6	Unwanted emissions.....	57
6.6.1	General.....	57
6.6.2	Occupied bandwidth	58
6.6.2.1	General	58
6.6.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	58
6.6.3	Adjacent Channel Leakage Power Ratio	58
6.6.3.1	General	58
6.6.3.2	Limits and <i>Basic limits</i>	59
6.6.3.3	Minimum requirement for <i>BS type 1-C</i>	62
6.6.3.4	Minimum requirement for <i>BS type 1-H</i>	62
6.6.4	Operating band unwanted emissions	62
6.6.4.1	General	62
6.6.4.2	<i>Basic limits</i>	64
6.6.4.2.1	<i>Basic limits</i> for Wide Area BS (Category A)	64
6.6.4.2.2	<i>Basic limits</i> for Wide Area BS (Category B)	65
6.6.4.2.3	<i>Basic limits</i> for Medium Range BS (Category A and B).....	66
6.6.4.2.4	<i>Basic limits</i> for Local Area BS (Category A and B).....	67
6.6.4.2.4A	<i>Basic limits</i> for Local Area and Medium Range BS for band n46 and n96 (Category A and B)	67
6.6.4.2.5	<i>Basic limits</i> for additional requirements	70
6.6.4.3	Minimum requirements for <i>BS type 1-C</i>	71
6.6.4.4	Minimum requirements for <i>BS type 1-H</i>	71
6.6.5	Transmitter spurious emissions.....	71
6.6.5.1	General	71
6.6.5.2	<i>Basic limits</i>	72
6.6.5.2.1	General transmitter spurious emissions requirements	72
6.6.5.2.2	Protection of the BS receiver of own or different BS	73
6.6.5.2.3	Additional spurious emissions requirements	73
6.6.5.2.4	Co-location with other base stations.....	82
6.6.5.3	Minimum requirements for <i>BS type 1-C</i>	87

6.6.5.4	Minimum requirements for <i>BS type 1-H</i>	87
6.7	Transmitter intermodulation	88
6.7.1	General	88
6.7.2	Minimum requirements for <i>BS type 1-C</i>	88
6.7.2.1	Co-location minimum requirements	88
6.7.2.2	Additional requirements	89
6.7.3	Minimum requirements for <i>BS type 1-H</i>	89
6.7.3.1	Co-location minimum requirements	89
6.7.3.2	Intra-system minimum requirements	90
6.7.3.3	Additional requirements	90
7	Conducted receiver characteristics	91
7.1	General	91
7.2	Reference sensitivity level	91
7.2.1	General	91
7.2.2	Minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	91
7.3	Dynamic range	95
7.3.1	General	95
7.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	95
7.4	In-band selectivity and blocking	103
7.4.1	Adjacent Channel Selectivity (ACS)	103
7.4.1.1	General	103
7.4.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	103
7.4.1.3	Void	105
7.4.1.4	Void	105
7.4.2	In-band blocking	105
7.4.2.1	General	105
7.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	105
7.4.2.3	Void	109
7.4.2.4	Void	109
7.5	Out-of-band blocking	109
7.5.1	General	109
7.5.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	109
7.5.3	Co-location minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	110
7.5.4	Void	111
7.6	Receiver spurious emissions	111
7.6.1	General	111
7.6.2	<i>Basic limits</i>	111
7.6.3	Minimum requirement for <i>BS type 1-C</i>	112
7.6.4	Minimum requirement for <i>BS type 1-H</i>	112
7.7	Receiver intermodulation	112
7.7.1	General	112
7.7.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	113
7.8	In-channel selectivity	117
7.8.1	General	117
7.8.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	117
8	Conducted performance requirements	125
8.1	General	125
8.1.1	Scope and definitions	125
8.1.2	Void	125
8.2	Performance requirements for PUSCH	125
8.2.1	Requirements for PUSCH with transform precoding disabled	125
8.2.1.1	General	125
8.2.1.2	Minimum requirements	126
8.2.2	Requirements for PUSCH with transform precoding enabled	134
8.2.2.1	General	134
8.2.2.2	Minimum requirements	134
8.2.3	Requirements for UCI multiplexed on PUSCH	135
8.2.3.1	General	135
8.2.3.2	Minimum requirements	136
8.2.4	Requirements for PUSCH for high speed train	137

8.2.4.1	General	137
8.2.4.2	Minimum requirements	138
8.2.5	Requirements for UL timing adjustment	140
8.2.5.1	Minimum requirements	141
8.2.6	Requirements for PUSCH 0.001% BLER	142
8.2.6.1	General	142
8.2.6.2	Minimum requirements	142
8.2.7	Requirements for PUSCH repetition Type A	144
8.2.7.1	General	144
8.2.7.2	Minimum requirements	144
8.2.8	Requirements for PUSCH mapping Type B with non-slot transmission	146
8.2.8.1	General	146
8.2.8.2	Minimum requirements	146
8.2.9	Requirements of PUSCH for 2-step RA type	147
8.2.9.1	General	147
8.2.9.2	Minimum requirements	148
8.3	Performance requirements for PUCCH	149
8.3.1	DTX to ACK probability	149
8.3.1.1	General	149
8.3.1.2	Minimum requirement	149
8.3.2	Performance requirements for PUCCH format 0	149
8.3.2.1	General	149
8.3.2.2	Minimum requirements	150
8.3.3	Performance requirements for PUCCH format 1	150
8.3.3.1	NACK to ACK requirements	150
8.3.3.1.1	General	150
8.3.3.1.2	Minimum requirements	151
8.3.3.2	ACK missed detection requirements	152
8.3.3.2.1	General	152
8.3.3.2.2	Minimum requirements	152
8.3.4	Performance requirements for PUCCH format 2	153
8.3.4.1	ACK missed detection requirements	153
8.3.4.1.1	General	153
8.3.4.1.2	Minimum requirements	153
8.3.4.2	UCI BLER performance requirements	154
8.3.4.2.1	General	154
8.3.4.2.2	Minimum requirements	154
8.3.5	Performance requirements for PUCCH format 3	155
8.3.5.1	General	155
8.3.5.2	Minimum requirements	155
8.3.6	Performance requirements for PUCCH format 4	156
8.3.6.1	General	156
8.3.6.2	Minimum requirement	156
8.3.7	Performance requirements for multi-slot PUCCH	157
8.3.7.1	General	157
8.3.7.2	Performance requirements for multi-slot PUCCH format 1	157
8.3.7.2.1	NACK to ACK requirements	157
8.3.7.2.1.1	General	157
8.3.7.2.1.2	Minimum requirements	158
8.3.7.2.2	ACK missed detection requirements	158
8.4	Performance requirements for PRACH	159
8.4.1	PRACH False alarm probability	159
8.4.1.1	General	159
8.4.1.2	Minimum requirement	159
8.4.2	PRACH detection requirements	159
8.4.2.1	General	159
8.4.2.2	Minimum requirements for Normal Mode	159
8.4.2.3	Minimum requirements for high speed train	160
9	Radiated transmitter characteristics	162
9.1	General	162
9.2	Radiated transmit power	162

9.2.1	General.....	162
9.2.2	Minimum requirement for <i>BS type 1-H</i> and <i>BS type 1-O</i>	162
9.2.3	Minimum requirement for <i>BS type 2-O</i>	163
9.3	OTA base station output power	163
9.3.1	General.....	163
9.3.2	Minimum requirement for <i>BS type 1-O</i>	163
9.3.3	Minimum requirement for <i>BS type 2-O</i>	164
9.3.4	Additional requirements (regional).....	164
9.4	OTA output power dynamics	164
9.4.1	General.....	164
9.4.2	OTA RE power control dynamic range	164
9.4.2.1	General	164
9.4.2.2	Minimum requirement for <i>BS type 1-O</i>	164
9.4.3	OTA total power dynamic range.....	164
9.4.3.1	General.....	164
9.4.3.2	Minimum requirement for <i>BS type 1-O</i>	164
9.4.3.3	Minimum requirement for <i>BS type 2-O</i>	165
9.5	OTA transmit ON/OFF power.....	165
9.5.1	General.....	165
9.5.2	OTA transmitter OFF power.....	165
9.5.2.1	General	165
9.5.2.2	Minimum requirement for <i>BS type 1-O</i>	165
9.5.2.3	Minimum requirement for <i>BS type 2-O</i>	165
9.5.3	OTA transient period	165
9.5.3.1	General	165
9.5.3.2	Minimum requirement for <i>BS type 1-O</i>	166
9.5.3.3	Minimum requirement for <i>BS type 2-O</i>	166
9.6	OTA transmitted signal quality	166
9.6.1	OTA frequency error	166
9.6.1.1	General	166
9.6.1.2	Minimum requirement for <i>BS type 1-O</i>	166
9.6.1.3	Minimum requirement for <i>BS type 2-O</i>	166
9.6.2	OTA modulation quality	167
9.6.2.1	General	167
9.6.2.2	Minimum Requirement for <i>BS type 1-O</i>	167
9.6.2.3	Minimum Requirement for <i>BS type 2-O</i>	167
9.6.2.3.1	EVM frame structure for measurement	167
9.6.3	OTA time alignment error	167
9.6.3.1	General	167
9.6.3.2	Minimum requirement for <i>BS type 1-O</i>	167
9.6.3.3	Minimum requirement for <i>BS type 2-O</i>	168
9.7	OTA unwanted emissions	168
9.7.1	General.....	168
9.7.2	OTA occupied bandwidth.....	169
9.7.2.1	General	169
9.7.2.2	Minimum requirement for <i>BS type 1-O</i> and <i>BS type 2-O</i>	169
9.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR)	169
9.7.3.1	General	169
9.7.3.2	Minimum requirement for <i>BS type 1-O</i>	169
9.7.3.3	Minimum requirement for <i>BS type 2-O</i>	169
9.7.4	OTA operating band unwanted emissions	171
9.7.4.1	General	171
9.7.4.2	Minimum requirement for <i>BS type 1-O</i>	171
9.7.4.2.1	Additional requirements	172
9.7.4.3	Minimum requirement for <i>BS type 2-O</i>	172
9.7.4.3.1	General	172
9.7.4.3.2	OTA operating band unwanted emission limits (Category A)	173
9.7.4.3.3	OTA operating band unwanted emission limits (Category B).....	174
9.7.4.3.4	Additional OTA operating band unwanted emission requirements	174
9.7.5	OTA transmitter spurious emissions.....	175
9.7.5.1	General	175
9.7.5.2	Minimum requirement for <i>BS type 1-O</i>	175

9.7.5.2.1	General	175
9.7.5.2.2	General OTA transmitter spurious emissions requirements	175
9.7.5.2.3	Protection of the BS receiver of own or different BS	175
9.7.5.2.4	Additional spurious emissions requirements	175
9.7.5.2.5	Co-location with other base stations	176
9.7.5.3	Minimum requirement for <i>BS type 2-O</i>	176
9.7.5.3.1	General	176
9.7.5.3.2	General OTA transmitter spurious emissions requirements	176
9.7.5.3.3	Additional OTA transmitter spurious emissions requirements	177
9.8	OTA transmitter intermodulation	178
9.8.1	General	178
9.8.2	Minimum requirement for <i>BS type 1-O</i>	178
10	Radiated receiver characteristics	180
10.1	General	180
10.2	OTA sensitivity	181
10.2.1	<i>BS type 1-H</i> and <i>BS type 1-O</i>	181
10.2.1.1	General	181
10.2.1.2	Minimum requirement	181
10.2.2	<i>BS type 2-O</i>	181
10.3	OTA reference sensitivity level	182
10.3.1	General	182
10.3.2	Minimum requirement for <i>BS type 1-O</i>	182
10.3.3	Minimum requirement for <i>BS type 2-O</i>	183
10.4	OTA dynamic range	184
10.4.1	General	184
10.4.2	Minimum requirement for <i>BS type 1-O</i>	184
10.5	OTA in-band selectivity and blocking	193
10.5.1	OTA adjacent channel selectivity	193
10.5.1.1	General	193
10.5.1.2	Minimum requirement for <i>BS type 1-O</i>	193
10.5.1.3	Minimum requirement for <i>BS type 2-O</i>	194
10.5.2	OTA in-band blocking	195
10.5.2.1	General	195
10.5.2.2	Minimum requirement for <i>BS type 1-O</i>	195
10.5.2.3	Minimum requirement for <i>BS type 2-O</i>	198
10.6	OTA out-of-band blocking	198
10.6.1	General	198
10.6.2	Minimum requirement for <i>BS type 1-O</i>	198
10.6.2.1	General minimum requirement	198
10.6.2.2	Co-location minimum requirement	199
10.6.3	Minimum requirement for <i>BS type 2-O</i>	200
10.6.3.1	General minimum requirement	200
10.7	OTA receiver spurious emissions	200
10.7.1	General	200
10.7.2	Minimum requirement for <i>BS type 1-O</i>	200
10.7.3	Minimum requirement for <i>BS type 2-O</i>	201
10.8	OTA receiver intermodulation	202
10.8.1	General	202
10.8.2	Minimum requirement for <i>BS type 1-O</i>	202
10.8.3	Minimum requirement for <i>BS type 2-O</i>	206
10.9	OTA in-channel selectivity	207
10.9.1	General	207
10.9.2	Minimum requirement for <i>BS type 1-O</i>	207
10.9.3	Minimum requirement for <i>BS type 2-O</i>	210
11	Radiated performance requirements	211
11.1	General	211
11.1.1	Scope and definitions	211
11.1.2	OTA demodulation branches	211
11.1.3	Void	212
11.2	Performance requirements for PUSCH	212

11.2.1	Requirements for <i>BS type 1-O</i>	212
11.2.1.1	Requirements for PUSCH with transform precoding disabled	212
11.2.1.2	Requirements for PUSCH with transform precoding enabled	212
11.2.1.3	Requirements for UCI multiplexed on PUSCH	212
11.2.1.4	Requirements for PUSCH for high speed train	212
11.2.1.5	Requirements for UL timing adjustment	212
11.2.1.6	Requirements for PUSCH 0.001% BLER	212
11.2.1.7	Requirements for PUSCH repetition Type A	212
11.2.1.8	Requirements for PUSCH mapping Type B with non-slot transmission	212
11.2.1.9	Requirements for PUSCH for 2-step RA type	212
11.2.2	Requirements for <i>BS type 2-O</i>	212
11.2.2.1	Requirements for PUSCH with transform precoding disabled	212
11.2.2.1.1	General	212
11.2.2.1.2	Minimum requirements	213
11.2.2.2	Requirements for PUSCH with transform precoding enabled	216
11.2.2.2.1	General	216
11.2.2.2.2	Minimum requirements	216
11.2.2.3	Requirements for UCI multiplexed on PUSCH	217
11.2.2.3.1	General	217
11.2.2.3.2	Minimum requirements	218
11.2.2.4	Requirements for PUSCH for 2-step RA type	220
11.2.2.4.1	General	220
11.2.2.4.2	Minimum requirements	220
11.3	Performance requirements for PUCCH	221
11.3.1	Requirements for <i>BS type 1-O</i>	221
11.3.1.1	DTX to ACK probability	221
11.3.1.2	Performance requirements for PUCCH format 0	221
11.3.1.3	Performance requirements for PUCCH format 1	221
11.3.1.4	Performance requirements for PUCCH format 2	221
11.3.1.5	Performance requirements for PUCCH format 3	221
11.3.1.6	Performance requirements for PUCCH format 4	221
11.3.2	Requirements for <i>BS type 2-O</i>	221
11.3.2.1	DTX to ACK probability	221
11.3.2.2	Performance requirements for PUCCH format 0	221
11.3.2.2.1	General	221
11.3.2.2.2	Minimum requirements	222
11.3.2.3	Performance requirements for PUCCH format 1	222
11.3.2.3.1	NACK to ACK requirements	222
11.3.2.3.2	ACK missed detection requirements	223
11.3.2.4	Performance requirements for PUCCH format 2	224
11.3.2.4.1	ACK missed detection requirements	224
11.3.2.4.2	UCI BLER performance requirements	225
11.3.2.5	Performance requirements for PUCCH format 3	226
11.3.2.5.1	General	226
11.3.2.5.2	Minimum requirements	226
11.3.2.6	Performance requirements for PUCCH format 4	227
11.3.2.6.1	General	227
11.3.2.6.2	Minimum requirements	227
11.4	Performance requirements for PRACH	228
11.4.1	Requirements for <i>BS type 1-O</i>	228
11.4.1.1	PRACH False alarm probability	228
11.4.1.2	PRACH detection requirements	228
11.4.2	Requirements for <i>BS type 2-O</i>	228
11.4.2.1	PRACH False alarm probability	228
11.4.2.1.1	General	228
11.4.2.1.2	Minimum requirement	228
11.4.2.2	PRACH detection requirements	228
11.4.2.2.1	General	228
11.4.2.2.2	Minimum requirements	229

Annex A (normative):	Reference measurement channels	230
-----------------------------	---	------------

A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3).....	230
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	232
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	234
A.3A	Fixed Reference Channels for performance requirements (QPSK, R=99/1024)	240
A.3B	Fixed Reference Channels for performance requirements (QPSK, R=308/1024)	241
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	241
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	246
A.6	PRACH Test preambles	248
A.7	Fixed Reference Channels for performance requirements (16QAM, R=434/1024)	249
A.8	Fixed Reference Channels for performance requirements (QPSK, R=157/1024)	250
Annex B (normative):	Error Vector Magnitude (FR1)	251
B.1	Reference point for measurement.....	251
B.2	Basic unit of measurement	251
B.3	Modified signal under test.....	252
B.4	Estimation of frequency offset	252
B.5	Estimation of time offset	252
B.5.1	General	252
B.5.2	Window length	253
B.6	Estimation of TX chain amplitude and frequency response parameters	254
B.7	Averaged EVM	255
Annex C (normative):	Error Vector Magnitude (FR2)	257
C.1	Reference point for measurement.....	257
C.2	Basic unit of measurement	257
C.3	Modified signal under test.....	258
C.4	Estimation of frequency offset	258
C.5	Estimation of time offset	258
C.5.1	General	258
C.5.2	Window length	259
C.6	Estimation of TX chain amplitude and frequency response parameters	259
C.7	Averaged EVM	261
Annex D (normative):	Characteristics of the interfering signals.....	263
Annex E: Void	264	
Annex F (normative):	Relationship between EIRP based regulatory requirements and 3GPP requirements.....	265
F.1	General	265
F.2	Relationship between EIRP based regulatory requirements and conducted requirements.....	265
F.3	Relationship between EIRP based regulatory requirements and OTA requirements.....	266
Annex G (Normative):	Propagation conditions.....	267

G.1	Static propagation condition.....	267
G.2	Multi-path fading propagation conditions.....	267
G.2.1	Delay profiles	267
G.2.1.1	Delay profiles for FR1	268
G.2.1.2	Delay profiles for FR2	269
G.2.2	Combinations of channel model parameters	270
G.2.3	MIMO Channel Correlation Matrices	271
G.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA)	271
G.2.3.1.1	Definition of MIMO Correlation Matrices.....	271
G.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level	275
G.2.3.2	Multi-Antenna channel models using cross polarized antennas	277
G.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas	278
G.2.3.2.2	Spatial Correlation Matrices at UE and gNB sides	278
G.2.3.2.2.1	Spatial Correlation Matrices at UE side	278
G.2.3.2.2.2	Spatial Correlation Matrices at gNB side	279
G.2.3.2.3	MIMO Correlation Matrices using cross polarized antennas	279
G.3	High speed train condition	279
G.4	Moving propagation conditions.....	283
Annex H (informative):	Change history	285
History		295

iTeh STANDARD PREVIEW (standards.iteh.ai)

ETSI TS 138 104 V16.6.0 (2021-01)

<https://standards.iteh.ai/catalog/standards/sist/70b11a6a-71cb-46bf-b87c-4a805d6fca18/etsi-ts-138-104-v16-6-0-2021-01>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ETSI TS 138 104 V16.6.0 (2021-01)

<https://standards.iteh.ai/catalog/standards/sist/70b11a6a-71cb-46bf-b87c-4a805d6fca18/etsi-ts-138-104-v16-6-0-2021-01>

1 Scope

The present document establishes the minimum RF characteristics and minimum performance requirements of NR and NB-IoT operation in NR in-band Base Station (BS).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] ITU-R Recommendation SM.329: "Unwanted emissions in the spurious domain".
- [3] Recommendation ITU-R SM.328: "Spectra and bandwidth of emissions".
- [4] 3GPP TR 25.942: "RF system scenarios".
- [5] 3GPP TS 38.141-1: "NR; Base Station (BS) conformance testing; Part 1: Conducted conformance testing".
- [6] 3GPP TS 38.141-2: "NR; Base Station (BS) conformance testing; Part 2: Radiated conformance testing".
- [7] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [8] "Title 47 of the Code of Federal Regulations (CFR)", Federal Communications Commission.
- [9] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [10] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [11] 3GPP TS 38.331: "NR; Radio Resource Control (RRC); Protocol specification".
- [12] ECC/DEC/(17)06: "The harmonised use of the frequency bands 1427-1452 MHz and 1492-1518 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".
- [13] 3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [14] 3GPP TS 37.105: "Active Antenna System (AAS) Base Station (BS) transmission and reception".
- [15] 3GPP TS 38.212: "NR; Multiplexing and channel coding".
- [16] 3GPP TR 38.901: "Study on channel model for frequencies from 0.5 to 100 GHz".
- [17] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone".
- [18] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [19] ERC Recommendation 74-01, "Unwanted emissions in the spurious domain".