

ETSI EN 303 851 V1.1.1 (2025-04)



**Radio Frequency Identification;
Equipment operating in the band 2 446 MHz to 2 454 MHz
with power levels up to a maximum of 500 mW e.i.r.p.
and up to a maximum of 4 W e.i.r.p.;
Harmonised Standard for access to radio spectrum**

[ETSI EN 303 851 V1.1.1 \(2025-04\)](https://standards.iteh.ai/catalog/standards/etsi/cb2bf617-f037-4efe-b87a-d0ae1c719af1/etsi-en-303-851-v1-1-1-2025-04)

<https://standards.iteh.ai/catalog/standards/etsi/cb2bf617-f037-4efe-b87a-d0ae1c719af1/etsi-en-303-851-v1-1-1-2025-04>

Reference

DEN/ERM-TG34-269

Keywords

harmonised standard, radio, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	11
3.1 Terms.....	11
3.2 Symbols.....	13
3.3 Abbreviations	13
4 Technical requirements specifications	14
4.0 General	14
4.1 Environmental profile.....	14
4.2 General conditions for operating	14
4.2.1 Conformance requirements.....	14
4.2.2 Designated frequencies	14
4.2.2.1 EU wide harmonised national radio interface 2 446 MHz to 2 454 MHz.....	14
4.2.2.2 National Radio Interfaces not EU wide harmonised from 2 446 MHz to 2 454 MHz	15
4.2.3 Operating conditions.....	15
4.3 Transmitter requirements	16
4.3.1 Transmitter measurement requirements.....	16
4.3.1.1 Applicability.....	16
4.3.1.2 Methods of measurement and limits for transmitter parameters	16
4.3.2 Equivalent isotropically radiated power (e.i.r.p.).....	16
4.3.2.1 Indoor and outdoor transmitters of 500 mW or less.....	16
4.3.2.1.1 Applicability	16
4.3.2.1.2 Definition.....	16
4.3.2.1.3 Limits	17
4.3.2.1.4 Conformance.....	17
4.3.2.2 Indoor transmitters of 4 W or less	17
4.3.2.2.1 Applicability	17
4.3.2.2.2 Definition.....	17
4.3.2.2.3 Limits	18
4.3.2.2.4 Conformance	18
4.3.3 Permitted range of operating frequencies	18
4.3.3.1 Applicability.....	18
4.3.3.2 Definition	18
4.3.3.3 Limits	18
4.3.3.4 Conformance.....	18
4.3.4 Transmitter spectrum masks	18
4.3.4.1 Applicability.....	18
4.3.4.2 Definition	19
4.3.4.3 Limits	19
4.3.4.4 Conformance.....	19
4.3.5 Unwanted emissions in the spurious domain	19
4.3.5.1 Applicability.....	19
4.3.5.2 Definition	19
4.3.5.3 Limits	19
4.3.5.4 Conformance.....	20
4.3.6 Duty cycle.....	20
4.3.6.1 Applicability.....	20
4.3.6.2 Definition	20
4.3.6.3 Limits	20

4.3.6.4	Conformance.....	20
4.3.7	Additional requirements for FHSS equipment.....	21
4.3.7.1	Applicability.....	21
4.3.7.2	Definition	21
4.3.7.3	Limits	21
4.3.7.4	Conformance.....	21
4.4	Receiver requirements	21
4.4.1	General performance criteria	21
4.4.2	Blocking or desensitization.....	21
4.4.2.1	Applicability.....	21
4.4.2.2	Definition	21
4.4.2.3	Limits	21
4.4.2.4	Conformance.....	22
4.4.3	Spurious radiations	22
4.4.3.1	Applicability.....	22
4.4.3.2	Definition	22
4.4.3.3	Limits	22
4.4.3.4	Conformance.....	22
4.4.4	Receiver sensitivity.....	22
4.4.4.1	Applicability.....	22
4.4.4.2	Definition	22
4.4.4.3	Limits	22
4.4.4.4	Conformance.....	22
4.4.5	Adjacent channel selectivity	23
4.4.5.1	Applicability.....	23
4.4.5.2	Definition	23
4.4.5.3	Limits	23
4.4.5.4	Conformance.....	23
4.4.6	Receiver spurious response rejection.....	23
4.4.6.1	Applicability.....	23
4.4.6.2	Definition	23
4.4.6.3	Limits	23
4.4.6.4	Conformance.....	23
4.4.7	Receiver maximum input signal level.....	23
4.4.7.1	Applicability.....	23
4.4.7.2	Definition	23
4.4.7.3	Limits	24
4.4.7.4	Conformance.....	24
5	Testing for compliance with technical requirements.....	24
5.0	General	24
5.1	Environmental conditions for testing	24
5.2	Presentation of equipment for testing purposes.....	24
5.2.1	General.....	24
5.2.2	Choice of model for testing	24
5.2.3	Testing of equipment with alternative power levels	25
5.2.4	Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)	25
5.2.4.1	Equipment with an internal permanent or temporary antenna connector or using a dedicated test fixture	25
5.2.4.2	Equipment with a temporary antenna connector	25
5.2.5	Testing of devices using duty cycle	25
5.3	Mechanical and electrical design.....	25
5.3.1	General.....	25
5.3.2	Transmitter shut-off facility	26
5.3.3	Receiver mute or squelch.....	26
5.4	Auxiliary test equipment	26
5.5	Test power source.....	26
5.5.1	General.....	26
5.5.2	External test power source	26
5.5.3	Internal test power source	26
5.6	Normal test conditions.....	27

5.6.1	Normal temperature and humidity	27
5.6.2	Normal test power source	27
5.6.2.1	Mains voltage	27
5.6.2.2	Battery power sources	27
5.6.2.3	Other power sources.....	27
5.7	Extreme test conditions	27
5.7.1	Extreme temperatures	27
5.7.1.1	Procedure for tests at extreme temperatures.....	27
5.7.1.1.1	General	27
5.7.1.1.2	Procedure for equipment designed for continuous operation	28
5.7.1.1.3	Procedure for equipment designed for intermittent operation	28
5.7.1.2	Extreme temperature ranges.....	28
5.7.2	Extreme test source voltages.....	28
5.7.2.1	Mains voltage	28
5.7.2.2	Battery power sources	28
5.7.2.3	Power sources using other types of batteries.....	29
5.7.2.4	Other power sources.....	29
5.8	General conditions.....	29
5.8.1	Normal test signals and test modulation	29
5.8.1.1	General	29
5.8.1.2	Normal test signals for data.....	30
5.8.2	Artificial antenna	30
5.8.3	Test fixture.....	30
5.8.3.1	General	30
5.8.3.2	Validation of the test-fixtue in the temperature chamber.....	31
5.8.3.3	Mode of use.....	33
5.8.4	Test sites and general arrangements for radiated measurements	33
5.8.5	Measuring receiver	33
5.9	Transmitter requirements	33
5.9.1	Transmitter measurement requirements.....	33
5.9.1.1	Methods of measurement and limits for transmitter parameters	33
5.9.2	Equivalent isotropically radiated power (e.i.r.p.).....	34
5.9.2.1	Method of measurement.....	34
5.9.2.1.1	General requirements.....	34
5.9.2.1.2	Non spread spectrum transmitters with a -6 dB bandwidth of up to 20 MHz and spread spectrum transmitters with channel bandwidth of up to 1 MHz	34
5.9.2.1.3	Transmitters other than those defined in clause 5.9.2.1.2.....	35
5.9.2.1.4	Tests for indoor transmitters of 4 W.....	36
5.9.3	Permitted range of operating frequencies	36
5.9.3.1	Method of measurement.....	36
5.9.3.2	Method of measurement for equipment using FHSS modulation	37
5.9.4	Transmitter spectrum mask.....	37
5.9.4.1	Method of measurement.....	37
5.9.5	Unwanted emissions in the spurious domain	38
5.9.5.1	Method of measurement.....	38
5.9.5.1.1	General Requirements	38
5.9.5.1.2	Conducted spurious emission	39
5.9.5.1.3	Method of measurement - cabinet spurious radiation.....	39
5.9.5.1.4	Method of measurement - radiated spurious emission	40
5.9.5.1.5	Additional requirements for equipment employing FHSS modulation	41
5.9.6	Duty cycle.....	41
5.9.6.1	Method of measurement.....	41
5.9.7	Additional requirements for FHSS equipment.....	41
5.9.7.1	Method of measurement.....	41
5.9.7.1.0	General	41
5.9.7.1.1	Total number of hops and maximum separation of hops.....	41
5.9.7.1.2	Dwell time	42
5.10	Receiver requirements	42
5.10.1	General performance criteria	42
5.10.2	Blocking or desensitization.....	42
5.10.2.1	Method of measurement.....	42
5.10.2.2	Method of measurement for blocking or desensitization	42

5.10.2.2.1	Test Conditions.....	42
5.10.2.2.2	Conducted measurement.....	42
5.10.2.2.3	Radiated measurement.....	43
5.10.2.2.4	Measurement procedure	43
5.10.3	Spurious radiations	43
5.10.3.1	Method of measurement for spurious radiation.....	43
5.10.3.1.1	General Requirements	43
5.10.3.1.2	Method of measurement conducted spurious components	44
5.10.3.1.3	Method of measurement cabinet radiation.....	44
5.10.3.1.4	Method of measurement radiated spurious components.....	45
5.10.4	Receiver sensitivity.....	45
5.10.4.1	Method of measurement for receiver sensitivity	45
5.10.4.1.1	Test Conditions.....	45
5.10.4.1.2	Method of measurement conducted receiver sensitivity.....	45
5.10.4.1.3	Method of measurement radiated receiver sensitivity	45
5.10.4.1.4	Measurement procedure	45
5.10.5	Adjacent channel selectivity	46
5.10.5.1	Method of measurement for adjacent channel selectivity	46
5.10.5.1.1	Test conditions	46
5.10.5.1.2	Conducted measurement.....	46
5.10.5.1.3	Radiated measurement.....	46
5.10.5.1.4	Measurement procedure	46
5.10.6	Receiver spurious response rejection.....	47
5.10.6.1	Method of measurement for receiver spurious response rejection	47
5.10.6.1.1	Test conditions	47
5.10.6.1.2	Conducted measurement.....	47
5.10.6.1.3	Radiated measurement.....	47
5.10.6.1.4	Measurement procedure	48
5.10.7	Receiver maximum input signal level.....	48
5.10.7.1	Method of measurement for receiver maximum input signal level.....	48
5.10.7.1.1	Test conditions	48
5.10.7.1.2	Conducted measurement.....	48
5.10.7.1.3	Radiated measurement.....	48
5.10.7.1.4	Measurement procedure	49

Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	50
-------------------------------	---	-----------

Annex B (informative):	Selection of technical parameters	52
-------------------------------	--	-----------

B.1	Introduction	52
-----	--------------------	----

Annex C (normative):	Radiated measurements	53
-----------------------------	------------------------------------	-----------

C.1	General requirements for measurements involving the use of radiated fields.....	53
-----	---	----

C.2	Test Sites	53
-----	------------------	----

C.2.0	General	53
-------	---------------	----

C.2.1	Indoor test site	54
-------	------------------------	----

C.2.2	Shielded anechoic test site.....	55
-------	----------------------------------	----

C.2.2.0	General.....	55
---------	--------------	----

C.2.2.1	Influence of parasitic reflections in anechoic chambers	55
---------	---	----

C.2.2.2	Calibration of the shielded RF anechoic chamber	55
---------	---	----

C.3	Antennas.....	58
-----	---------------	----

C.3.1	Test antenna.....	58
-------	-------------------	----

C.3.2	Substitution antenna	58
-------	----------------------------	----

C.3.3	Artificial antenna.....	58
-------	-------------------------	----

C.4	Test Practice and Auxiliary Test Equipment.....	59
-----	---	----

C.5	Measuring distance.....	59
-----	-------------------------	----

C.5.0	General	59
-------	---------------	----

C.5.1	Standard position.....	59
-------	------------------------	----

C.5.2	Auxiliary cables.....	59
Annex D (normative):	General description of measurement methods.....	60
D.0	General	60
D.1	Conducted measurements.....	60
D.2	Radiated measurements.....	60
D.3	Radiated measurement for receivers	61
Annex E (informative):	Example of implementation for restriction of 4 W RFID to in-building use only.....	62
Annex F (informative):	Selection of receiver parameters.....	64
F.0	Introduction	64
F.1	Receiver sensitivity	64
F.2	Receiver co-channel rejection	64
F.3	Receiver adjacent signal selectivity	64
F.4	Receiver spurious response rejection	64
F.5	Receiver blocking.....	64
F.6	Receiver radio-frequency intermodulation.....	65
F.7	Receiver dynamic range	65
F.8	Desensitization	65
F.9	Receiver unwanted emissions in the spurious domain	65
Annex G (informative):	Interpretation of the measurement results.....	66
Annex H (informative):	Change history	67
History		68