ETSI GS CIM 009 V1.5.1 (2021-11)

Context Information Management (CIM); NGSI-LD API

Disclaimer

The present document has been produced and approved by the cross-cutting Context Information Management (CIM) ETSI Industry Specification Group (ISG) and represents the views of those members who participated in this ISG.
It does not necessarily represent the views of the entire ETSI membership.

Reference

RGS/CIM-009v151

Keywords

API, architecture, digital twins, GAP, information model, interoperability, NGSI-LD, smart agriculture, smart city, smart water, WoT

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00   Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Contents

Intellectual Property Rights 15
Foreword 15
Modal verbs terminology 15
Executive summary 15
Introduction 16
1 Scope 17
2 References 17
2.1 Normative references 17
2.2 Informative references 19
3 Definition of terms, symbols and abbreviations 21
3.1 Terms 21
3.2 Symbols 23
3.3 Abbreviations 23
4 Context Information Management Framework 24
4.1 Introduction 24
4.2 NGSI-LD Information Model 24
4.2.1 Introduction 24
4.2.2 NGSI-LD Meta Model 25
4.2.3 Cross Domain Ontology 26
4.2.4 NGSI-LD domain-specific models and instantiation 27
4.2.5 UML representation 28
4.3 NGSI-LD Architectural Considerations 28
4.3.1 Introduction 28
4.3.2 Centralized architecture 29
4.3.3 Distributed architecture 29
4.3.4 Federated architecture 30
4.3.5 NGSI-LD API Structure and Implementation Options 31
4.4 Core NGSI-LD @context 34
4.5 NGSI-LD Data Representation 35
4.5.1 NGSI-LD Entity Representation 35
4.5.2 NGSI-LD Property Representation 36
4.5.3 NGSI-LD Relationship Representation 36
4.5.4 Simplified Representation 37
4.5.5 Multi-Attribute Support 37
4.5.6 Temporal Representation of an Entity 38
4.5.7 Temporal Representation of a Property 38
4.5.8 Temporal Representation of a Relationship 38
4.5.9 Simplified Temporal Representation of an Entity 38
4.5.10 Entity Type List Representation 39
4.5.11 Detailed Entity Type List Representation 39
4.5.12 Entity Type Information Representation 39
4.5.13 Attribute List Representation 40
4.5.14 Detailed Attribute List Representation 40
4.5.15 Attribute Information Representation 40
4.5.16 GeoJSON Representation of Entities 40
4.5.16.0 Foreword 40
4.5.16.1 Top-level "geometry" field selection algorithm 41
4.5.16.2 GeoJSON Representation of an individual Entity 41
4.5.16.3 GeoJSON Representation of Multiple Entities 41
4.5.17 Simplified GeoJSON Representation of Entities 42
4.5.17.0 Foreword 42
4.5.17.1 Simplified GeoJSON Representation of an individual Entity 42
4.5.17.2 Simplified GeoJSON Representation of multiple Entities 42

4.5.18 NGSI-LD LanguageProperty Representation 42
4.5.19 Aggregated Temporal Representation of an Entity 43
4.5.19.0 Foreword 43
4.5.19.1 Supported behaviours for aggregation functions 44
4.6 Data Representation Restrictions 46
4.6.1 Supported text encodings 46
4.6.2 Supported names 46
4.6.3 Supported data types for Values 46
4.6.4 Supported Entity Content 47
4.6.5 Supported data types for LanguageMaps 48
4.6.6 Ordering of Entities in arrays having more than one instance of the same Entity 48
4.7 Geospatial Properties 48
4.7.1 GeoJSON Geometries 48
4.7.2 Representation of GeoJSON Geometries in JSON-LD 49
4.8 Temporal Properties 49
4.9 NGSI-LD Query Language 49
4.10 NGSI-LD Geoquery Language 55
4.11 NGSI-LD Temporal Query Language 56
4.12 NGSI-LD Pagination 57
4.13 Counting the Number of Results 58
4.14 Supporting Multiple Tenants 58
4.15 NGSI-LD Language Filter 59
4.16 Supporting Multiple Entity Types 59
4.17 NGSI-LD Entity Type Selection Language 60
4.18 NGSI-LD Scopes 60
4.19 NGSI-LD Scope Query Language 61
5 API Operation Definition 61
5.1 Introduction 61
5.2 Data Types 62
5.2.1 Introduction 62
5.2.2 Common members 62
5.2.3 @context 62
5.2.4 Entity 62
5.2.5 Property 63
5.2.6 Relationship 63
5.2.7 GeoProperty 64
5.2.8 EntityInfo 64
5.2.9 CsourceRegistration 65
5.2.10 RegistrationInfo 67
5.2.11 TimeInterval 67
5.2.12 Subscription 67
5.2.13 GeoQuery 69
5.2.14 NotificationParams 69
5.2.14.1 NotificationParams data type definition 69
5.2.14.2 Additional members 70
5.2.15 Endpoint 70
5.2.16 BatchOperationResult 71
5.2.17 BatchEntityError 71
5.2.18 UpdateResult 71
5.2.19 NotUpdatedDetails 71
5.2.20 EntityTemporal 72
5.2.21 TemporalQuery 72
5.2.22 KeyValuePair 72
5.2.23 Query 72
5.2.24 EntityTypeList 73
5.2.25 EntityType 73
5.2.26 EntityTypeInfo 74
5.2.27 AttributeList 74
5.2.28 Attribute 74
5.2.29 Feature 75
5.2.30 FeatureCollection 75

5.2.31 FeatureProperties 76
5.2.32 LanguageProperty 76
5.2.33 EntitySelector 76
5.3 Notification data types 77
5.3.1 Notification 77
5.3.2 CsourceNotification 77
5.3.3 TriggerReasonEnumeration 78
5.4 NGSI-LD Fragments 78
5.5 Common Behaviours 79
5.5.1 Introduction 79
5.5.2 Error types 79
5.5.3 Error response payload body 79
5.5.4 General NGSI-LD validation 80
5.5.5 Default @context assignment 80
5.5.6 Operation execution 80
5.5.7 Term to URI expansion or compaction 80
5.5.8 JSON-LD Merge Patch Behaviour 81
5.5.9 Pagination Behaviour 81
5.5.10 Multi-Tenant Behaviour 82
5.5.11 More than one instance of the same Entity in an Entity array 82
5.5.11.0 Foreword 82
5.5.11.1 Batch Entity Creation case 83
5.5.11.2 Batch Entity Creation or Update (Upsert) case 83
5.5.11.3 Batch Entity Update case 83
5.5.11.4 Batch Entity Delete case 83
5.6 Context Information Provision 83
5.6.1 Create Entity 83
5.6.1.1 Description 83
5.6.1.2 Use case diagram 84
5.6.1.3 Input data 84
5.6.1.4 Behaviour 84
5.6.1.5 Output data 84
5.6.2 Update Entity Attributes 84
5.6.2.1 Description 84
5.6.2.2 Use case diagram 84
5.6.2.3 Input data 85
5.6.2.4 Behaviour 85
5.6.2.5 Output data 85
5.6.3 Append Entity Attributes 85
5.6.3.1 Description 85
5.6.3.2 Use case diagram 86
5.6.3.3 Input data 86
5.6.3.4 Behaviour 86
5.6.3.5 Output data 87
5.6.4 Partial Attribute update 87
5.6.4.1 Description 87
5.6.4.2 Use case diagram 87
5.6.4.3 Input data 88
5.6.4.4 Behaviour 88
5.6.4.5 Output data 88
5.6.5 Delete Entity Attribute 88
5.6.5.1 Description 88
5.6.5.2 Use case diagram 88
5.6.5.3 Input data 89
5.6.5.4 Behaviour 89
5.6.5.5 Output data 90
5.6.6 Delete Entity 90
5.6.6.1 Description 90
5.6.6.2 Use case diagram 90
5.6.6.3 Input data 90
5.6.6.4 Behaviour 90
5.6.6.5 Output data 90

5.6.7 Batch Entity Creation....90
5.6.7.1 Description....90
5.6.7.2 Use case diagram....91
5.6.7.3 Input data....91
5.6.7.4 Behaviour....91
5.6.7.5 Output data....91
5.6.8 Batch Entity Creation or Update (Upsert)....92
5.6.8.1 Description....92
5.6.8.2 Use case diagram....92
5.6.8.3 Input data....92
5.6.8.4 Behaviour....92
5.6.8.5 Output data....93
5.6.9 Batch Entity Update....93
5.6.9.1 Description....93
5.6.9.2 Use case diagram....93
5.6.9.3 Input data....93
5.6.9.4 Behaviour....94
5.6.9.5 Output data....94
5.6.10 Batch Entity Delete....94
5.6.10.1 Description....94
5.6.10.2 Use case diagram....94
5.6.10.3 Input data....95
5.6.10.4 Behaviour....95
5.6.10.5 Output data....95
5.6.11 Create or Update Temporal Representation of an Entity....95
5.6.11.1 Description....95
5.6.11.2 Use case diagram....95
5.6.11.3 Input data....96
5.6.11.4 Behaviour....96
5.6.11.5 Output data....96
5.6.12 Add Attributes to Temporal Representation of an Entity....96
5.6.12.1 Description....96
5.6.12.2 Use case diagram....96
5.6.12.3 Input data....97
5.6.12.4 Behaviour....97
5.6.12.5 Output data....97
5.6.13 Delete Attribute from Temporal Representation of an Entity....97
5.6.13.1 Description....97
5.6.13.2 Use case diagram....98
5.6.13.3 Input data....98
5.6.13.4 Behaviour....98
5.6.13.5 Output data....99
5.6.14 Partial update Attribute instance in Temporal Representation of an Entity....99
5.6.14.1 Description....99
5.6.14.2 Use case diagram....99
5.6.14.3 Input data....99
5.6.14.4 Behaviour....99
5.6.14.5 Output data....100
5.6.15 Delete Attribute instance from Temporal Representation of an Entity....100
5.6.15.1 Description....100
5.6.15.2 Use case diagram....100
5.6.15.3 Input data....101
5.6.15.4 Behaviour....101
5.6.15.5 Output data....101
5.6.16 Delete Temporal Representation of an Entity....101
5.6.16.1 Description....101
5.6.16.2 Use case diagram....101
5.6.16.3 Input data....102
5.6.16.4 Behaviour....102
5.6.16.5 Output data....102
5.7 Context Information Consumption....102
5.7.1 Retrieve Entity....102

5.7.1.1 Description 102
5.7.1.2 Use case diagram 102
5.7.1.3 Input data 103
5.7.1.4 Behaviour 103
5.7.1.5 Output data 104
5.7.2 Query Entities 104
5.7.2.1 Description 104
5.7.2.2 Use case diagram 104
5.7.2.3 Input data 104
5.7.2.4 Behaviour 105
5.7.2.5 Output data 106
5.7.3 Retrieve Temporal Evolution of an Entity 106
5.7.3.1 Description 106
5.7.3.2 Use case diagram 106
5.7.3.3 Input data 107
5.7.3.4 Behaviour 107
5.7.3.5 Output data 108
5.7.4 Query Temporal Evolution of Entities 108
5.7.4.1 Description 108
5.7.4.2 Use case diagram 108
5.7.4.3 Input data 108
5.7.4.4 Behaviour 109
5.7.4.5 Output Data 110
5.7.5 Retrieve Available Entity Types 110
5.7.5.1 Description 110
5.7.5.2 Use case diagram 110
5.7.5.3 Input data 111
5.7.5.4 Behaviour 111
5.7.5.5 Output data 111
5.7.6 Retrieve Details of Available Entity Types 111
5.7.6.1 Description 111
5.7.6.2 Use case diagram 111
5.7.6.3 Input data 112
5.7.6.4 Behaviour 112
5.7.6.5 Output data 112
5.7.7 Retrieve Available Entity Type Information 112
5.7.7.1 Description 112
5.7.7.2 Use case diagram 112
5.7.7.3 Input data 113
5.7.7.4 Behaviour 113
5.7.7.5 Output data 113
5.7.8 Retrieve Available Attributes 113
5.7.8.1 Description 113
5.7.8.2 Use case diagram 113
5.7.8.3 Input data 114
5.7.8.4 Behaviour 114
5.7.8.5 Output data 114
5.7.9 Retrieve Details of Available Attributes 114
5.7.9.1 Description 114
5.7.9.2 Use case diagram 114
5.7.9.3 Input data 115
5.7.9.4 Behaviour 115
5.7.9.5 Output data 115
5.7.10 Retrieve Available Attribute Information 115
5.7.10.1 Description 115
5.7.10.2 Use case diagram 115
5.7.10.3 Input data 116
5.7.10.4 Behaviour 116
5.7.10.5 Output data 116
5.7.11 Architecture-related aspects of retrieval of entity types and attributes 116
5.8 Context Information Subscription 117
5.8.1 Create Subscription 117

5.8.1.1 Description 117
5.8.1.2 Use case diagram 117
5.8.1.3 Input data 117
5.8.1.4 Behaviour 117
5.8.1.5 Output data 118
5.8.2 Update Subscription 118
5.8.2.1 Description 118
5.8.2.2 Use case diagram 118
5.8.2.3 Input data 119
5.8.2.4 Behaviour 119
5.8.2.5 Output data 119
5.8.3 Retrieve Subscription 119
5.8.3.1 Description 119
5.8.3.2 Use case diagram 119
5.8.3.3 Input data 120
5.8.3.4 Behaviour 120
5.8.3.5 Output data 120
5.8.4 Query Subscriptions 120
5.8.4.1 Description 120
5.8.4.2 Use case diagram 120
5.8.4.3 Input data 121
5.8.4.4 Behaviour 121
5.8.4.5 Output data 121
5.8.5 Delete Subscription 121
5.8.5.1 Description 121
5.8.5.2 Use case diagram 121
5.8.5.3 Input data 122
5.8.5.4 Behaviour 122
5.8.5.5 Output data 122
5.8.6 Notification behaviour 122
5.9 Context Source Registration 123
5.9.1 Introduction 123
5.9.2 Register Context Source 123
5.9.2.1 Description 123
5.9.2.2 Use case diagram 123
5.9.2.3 Input data 124
5.9.2.4 Behaviour 124
5.9.2.5 Output data 124
5.9.3 Update Context Source Registration 124
5.9.3.1 Description 124
5.9.3.2 Use case diagram 125
5.9.3.3 Input data 125
5.9.3.4 Behaviour 125
5.9.3.5 Output data 125
5.9.4 Delete Context Source Registration 125
5.9.4.1 Description 125
5.9.4.2 Use case diagram 126
5.9.4.3 Input data 126
5.9.4.4 Behaviour 126
5.9.4.5 Output data 126
5.10 Context Source Discovery 126
5.10.1 Retrieve Context Source Registration 126
5.10.1.1 Description 126
5.10.1.2 Use case diagram 126
5.10.1.3 Input data 127
5.10.1.4 Behaviour 127
5.10.1.5 Output data 127
5.10.2 Query Context Source Registrations 127
5.10.2.1 Description 127
5.10.2.2 Use case diagram 128
5.10.2.3 Input data 128
5.10.2.4 Behaviour 129

5.10.2.5 Output data 130
5.11 Context Source Registration Subscription 130
5.11.1 Introduction 130
5.11.2 Create Context Source Registration Subscription 130
5.11.2.1 Description 130
5.11.2.2 Use case diagram 130
5.11.2.3 Input data 130
5.11.2.4 Behaviour 131
5.11.2.5 Output data 131
5.11.3 Update Context Source Registration Subscription 131
5.11.3.1 Description 131
5.11.3.2 Use case diagram 132
5.11.3.3 Input data 132
5.11.3.4 Behaviour 132
5.11.3.5 Output data 132
5.11.4 Retrieve Context Source Registration Subscription 132
5.11.4.1 Description 132
5.11.4.2 Use case diagram 133
5.11.4.3 Input data 133
5.11.4.4 Behaviour 133
5.11.4.5 Output data 133
5.11.5 Query Context Source Registration Subscriptions 133
5.11.5.1 Description 133
5.11.5.2 Use case diagram 133
5.11.5.3 Input data 134
5.11.5.4 Behaviour 134
5.11.5.5 Output data 134
5.11.6 Delete Context Source Registration Subscriptions 134
5.11.6.1 Description 134
5.11.6.2 Use case diagram 134
5.11.6.3 Input data 135
5.11.6.4 Behaviour 135
5.11.6.5 Output data 135
5.11.7 Notification behaviour 135
5.12 Matching Context Source Registrations 136
5.13 Storing, Managing and Serving @contexts 137
5.13.1 Introduction 137
5.13.2 Add @context 138
5.13.2.1 Description 138
5.13.2.2 Use case diagram 138
5.13.2.3 Input data 138
5.13.2.4 Behaviour 138
5.13.2.5 Output data 138
5.13.3 List @contexts 139
5.13.3.1 Description 139
5.13.3.2 Use case diagram 139
5.13.3.3 Input data 139
5.13.3.4 Behaviour 139
5.13.3.5 Output data 139
5.13.4 Serve @context 140
5.13.4.1 Description 140
5.13.4.2 Use case diagram 140
5.13.4.3 Input data 140
5.13.4.4 Behaviour 141
5.13.4.5 Output data 141
5.13.5 Delete and Reload @context 141
5.13.5.1 Description 141
5.13.5.2 Use case diagram 141
5.13.5.3 Input data 141
5.13.5.4 Behaviour 142
5.13.5.5 Output data 142

6 API HTTP Binding 142
6.1 Introduction 142
6.2 Global Definitions and Resource Structure 142
6.3 Common Behaviours 145
6.3.1 Introduction 145
6.3.2 Error Types 145
6.3.3 Reporting errors 146
6.3.4 HTTP request preconditions 146
6.3.5 JSON-LD @context resolution 147
6.3.6 HTTP response common requirements 147
6.3.7 Simplified representation of entities 148
6.3.8 Notification behaviour 148
6.3.9 Csource Notification behaviour 148
6.3.10 Pagination behaviour 149
6.3.11 Including system-generated attributes 150
6.3.12 Simplified or aggregated temporal representation of entities 150
6.3.13 Counting number of results 151
6.3.14 Tenant specification 151
6.3.15 GeoJSON representation of spatially bound entities 151
6.3.16 Expiration time for cached @contexts 151
6.4 Resource: entities/ 152
6.4.1 Description 152
6.4.2 Resource definition 152
6.4.3 Resource methods 152
6.4.3.1 POST 152
6.4.3.2 GET 153
6.5 Resource: entities/{entityId} 155
6.5.1 Description 155
6.5.2 Resource definition 155
6.5.3 Resource methods 155
6.5.3.1 GET 155
6.5.3.2 DELETE 157
6.6 Resource: entities/{entityId}/attrs/ 157
6.6.1 Description 157
6.6.2 Resource definition 157
6.6.3 Resource methods 158
6.6.3.1 POST 158
6.6.3.2 PATCH 158
6.7 Resource: entities/{entityId}/attrs/{attrId} 159
6.7.1 Description 159
6.7.2 Resource definition 159
6.7.3 Resource methods 160
6.7.3.1 PATCH 160
6.7.3.2 DELETE 160
6.8 Resource: csourceRegistrations/ 161
6.8.1 Description 161
6.8.2 Resource definition 161
6.8.3 Resource methods 161
6.8.3.1 POST 161
6.8.3.2 GET 162
6.9 Resource: csourceRegistrations/{registrationId} 164
6.9.1 Description 164
6.9.2 Resource definition 164
6.9.3 Resource methods 164
6.9.3.1 GET 164
6.9.3.2 PATCH 165
6.9.3.3 DELETE 166
6.10 Resource: subscriptions/ 167
6.10.1 Description 167
6.10.2 Resource definition 167
6.10.3 Resource methods 167
6.10.3.1 POST 167

6.10.3.2 GET 168
6.11 Resource: subscriptions/{subscriptionId} 168
6.11.1 Description 168
6.11.2 Resource definition 168
6.11.3 Resource methods 169
6.11.3.1 GET 169
6.11.3.2 PATCH 169
6.11.3.3 DELETE 170
6.12 Resource: csourceSubscriptions/ 171
6.12.1 Description 171
6.12.2 Resource definition 171
6.12.3 Resource methods 171
6.12.3.1 POST 171
6.12.3.2 GET 172
6.13 Resource: csourceSubscriptions/{subscriptionId} 173
6.13.1 Description 173
6.13.2 Resource definition 173
6.13.3 Resource methods 173
6.13.3.1 GET 173
6.13.3.2 PATCH 174
6.13.3.3 DELETE 175
6.14 Resource: entityOperations/create 175
6.14.1 Description 175
6.14.2 Resource definition 176
6.14.3 Resource methods 176
6.14.3.1 POST 176
6.15 Resource: entityOperations/upsert 177
6.15.1 Description 177
6.15.2 Resource definition 177
6.15.3 Resource methods 177
6.15.3.1 POST 177
6.16 Resource: entityOperations/update 178
6.16.1 Description 178
6.16.2 Resource definition 178
6.16.3 Resource methods 178
6.16.3.1 POST 178
6.17 Resource: entityOperations/delete 179
6.17.1 Description 179
6.17.2 Resource definition 179
6.17.3 Resource methods 180
6.17.3.1 POST 180
6.18 Resource: temporal/entities/ 180
6.18.1 Description 180
6.18.2 Resource definition 181
6.18.3 Resource methods 181
6.18.3.1 POST 181
6.18.3.2 GET 182
6.19 Resource: temporal/entities/{entityId} 183
6.19.1 Description 183
6.19.2 Resource definition 183
6.19.3 Resource methods 184
6.19.3.1 GET 184
6.19.3.2 DELETE 185
6.20 Resource: temporal/entities/{entityId}/attrs/ 185
6.20.1 Description 185
6.20.2 Resource definition 186
6.20.3 Resource methods 186
6.20.3.1 POST 186
6.21 Resource: temporal/entities/{entityId}/attrs/{attrId} 187
6.21.1 Description 187
6.21.2 Resource definition 187
6.21.3 Resource methods 187

6.21.3.1 DELETE 187
6.22 Resource: temporal/entities/{entityId}/attrs/{attrId}/ {instanceId} 188
6.22.1 Description 188
6.22.2 Resource definition 188
6.22.3 Resource methods 188
6.22.3.1 PATCH 188
6.22.3.2 DELETE 189
6.23 Resource: entityOperations/query 190
6.23.1 Description 190
6.23.2 Resource definition 190
6.23.3 Resource methods 190
6.23.3.1 POST 190
6.24 Resource: temporal/entityOperations/query 191
6.24.1 Description 191
6.24.2 Resource definition 191
6.24.3 Resource methods 191
6.24.3.1 POST 191
6.25 Resource: types/ 192
6.25.1 Description 192
6.25.2 Resource definition 192
6.25.3 Resource methods 192
6.25.3.1 GET 192
6.26 Resource: types/{type} 193
6.26.1 Description 193
6.26.2 Resource definition 194
6.26.3 Resource methods 194
6.26.3.1 GET 194
6.27 Resource: attributes/ 195
6.27.1 Description 195
6.27.2 Resource definition 195
6.27.3 Resource methods 195
6.27.3.1 GET 195
6.28 Resource: attributes/{attrId} 196
6.28.1 Description 196
6.28.2 Resource definition 196
6.28.3 Resource methods 196
6.28.3.1 GET 196
6.29 Resource: jsonldContexts/ 197
6.29.1 Description 197
6.29.2 Resource definition 197
6.29.3 Resource methods 197
6.29.3.1 POST 197
6.29.3.2 GET 198
6.30 Resource: jsonldContexts/{contextId} 199
6.30.1 Description 199
6.30.2 Resource definition 199
6.30.3 Resource methods 199
6.30.3.1 GET 199
6.30.3.2 DELETE 200
7 API MQTT Notification Binding 201
7.1 Introduction 201
7.2 Notification behaviour 201
Annex A (normative): NGSI-LD identifier considerations 203
A.1 Introduction 203
A.2 Entity identifiers 203
A.3 NGSI-LD namespace 203
Annex B (normative): Core NGSI-LD @context definition 204

Annex C (informative): Examples of using the API 208

C.1 Introduction 208

C.2 Entity Representation 208
C.2.1 Property Graph 208
C.2.2 Vehicle Entity 209
C.2.3 Parking Entity 211
C.2.4 @context 214

C.3 Context Source Registration 215

C.4 Context Subscription 216

C.5 HTTP REST API Examples 217
C.5.1 Introduction 217
C.5.2 Create Entity of Type Vehicle 217
C.5.2.1 HTTP Request 217
C.5.2.2 HTTP Response 217
C.5.3 Query Entities 217
C.5.3.1 Introduction 217
C.5.3.2 HTTP Request 217
C.5.3.3 HTTP Response 217
C.5.4 Query Entities (Pagination) 218
C.5.4.1 Introduction 218
C.5.4.2 HTTP Request 218
C.5.4.3 HTTP Response 218
C.5.5 Temporal Query 218
C.5.5.1 Introduction 218
C.5.5.2 HTTP Request 218
C.5.5.3 HTTP Response 219
C.5.6 Temporal Query (Simplified Representation) 219
C.5.6.1 Introduction 219
C.5.6.2 HTTP Request 219
C.5.6.3 HTTP Response 219
C.5.7 Retrieve Available Entity Types 220
C.5.7.1 Introduction 220
C.5.7.2 HTTP Request 220
C.5.7.3 HTTP Response 220
C.5.8 Retrieve Details of Available Entity Types 221
C.5.8.1 Introduction 221
C.5.8.2 HTTP Request 221
C.5.8.3 HTTP Response 221
C.5.9 Retrieve Available Entity Type Information 222
C.5.9.1 Introduction 222
C.5.9.2 HTTP Request 222
C.5.9.3 HTTP Response 222
C.5.10 Retrieve Available Attributes 223
C.5.10.1 Introduction 223
C.5.10.2 HTTP Request 223
C.5.10.3 HTTP Response 223
C.5.11 Retrieve Details of Available Attributes 223
C.5.11.1 Introduction 223
C.5.11.2 HTTP Request 223
C.5.11.3 HTTP Response 224
C.5.12 Retrieve Available Attribute Information 224
C.5.12.1 Introduction 224
C.5.12.2 HTTP Request 224
C.5.12.3 HTTP Response 225
C.5.13 Query Entities (Natural Language Filtering) 225
C.5.13.1 Introduction 225
C.5.13.2 HTTP Request 225
C.5.13.3 HTTP Response 225

C.5.14 Temporal Query (Aggregated Representation) 226
C.5.14.1 Introduction....226
C.5.14.2 HTTP Request 226
C.5.14.3 HTTP Response 226
C.5.15 Scope Queries....227
C.5.15.1 Introduction....227
C.5.15.2 HTTP Request 227
C.5.15.3 HTTP Response 227
C.5.16 Temporal Scope Queries 228
C.5.16.1 Introduction....228
C.5.16.2 HTTP Request 228
C.5.16.3 HTTP Response 228
C.6 Date Representation 230
C.7 @context utilization clarifications 230
C.8 Link header utilization clarifications....232
C.9 @context processing clarifications....233
Annex D (informative): Transformation Algorithms....235
D.1 Introduction 235
D.2 Algorithm for transforming an NGSI-LD Entity into a JSON-LD document (ALG1)....235
D.3 Algorithm for transforming an NGSI-LD Property into JSON-LD (ALG1.1) 236
D.4 Algorithm for transforming an NGSI-LD Relationship into JSON-LD (ALG1.2) 237
Annex E (informative): RDF-compatible specification of NGSI-LD meta-model....238
Annex F (informative): Conventions and syntax guidelines....239
Annex G (informative): Localization and Internationalization Support....240
G.0 Foreword 240
G.1 Introduction 240
G.1.0 Foreword 240
G.1.1 Associating an Entity with a Natural Language 240
G.1.2 Associating a Property with a Natural Language 240
G.1.3 Associating as equivalent entity 241
G.2 Natural Language Collation Support....241
G.2.0 Foreword 241
G.2.1 Maintain collations as metadata 242
G.2.2 Route language sensitive queries via a proxy....242
G.3 Localization of Dates, Currency formats, etc.....242
G.3.0 Foreword 242
G.3.1 Localizing Dates....242
Annex H (informative): Change history 244
History 245

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**® and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Group Specification (GS) has been produced by ETSI Industry Specification Group (ISG) cross-cutting Context Information Management (CIM).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Executive summary

The present document formally describes the Context Information Management API (NGSI-LD) Specification. The Context Information Management API allows users to provide, consume and subscribe to context information in multiple scenarios and involving multiple stakeholders. Context information is modelled as attributes (properties and relationships) of context entities, also referred to as "digital twins", representing real-world assets. It enables close to real-time access to information coming from many different sources (not only IoT data sources).