

Second edition
2011-06-01

AMENDMENT 3
2012-10-15

**Graphical symbols — Safety colours and
safety signs — Registered safety signs**

AMENDMENT 3:

*Symboles graphiques — Couleurs de sécurité et signaux de sécurité —
Signaux de sécurité enregistrés*

AMENDEMENT 3:

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 7010:2011/Amd 3:2012

[https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-
b52d-f26b99d3c699/iso-7010-2011-amd-3-2012](https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-b52d-f26b99d3c699/iso-7010-2011-amd-3-2012)



Reference number
ISO 7010:2011/Amd.3:2012(E)

© ISO 2012

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 7010:2011/Amd 3:2012](https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-b52d-f26b99d3c699/iso-7010-2011-amd-3-2012)

<https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-b52d-f26b99d3c699/iso-7010-2011-amd-3-2012>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 3 to ISO 7010:2011 was prepared by Technical Committee ISO/TC 145, *Graphical symbols*, Subcommittee SC 2, *Safety identification, signs, shapes, symbols and colours*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 7010:2011/Amd 3:2012](https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-b52d-f26b99d3c699/iso-7010-2011-amd-3-2012)

<https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-b52d-f26b99d3c699/iso-7010-2011-amd-3-2012>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 7010:2011/Amd 3:2012](#)

<https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-b52d-f26b99d3c699/iso-7010-2011-amd-3-2012>

Graphical symbols — Safety colours and safety signs — Registered safety signs

AMENDMENT 3:

IMPORTANT — The colours represented in the electronic file of this International Standard can be neither viewed on screen nor printed as true representations. Although the copies of this International Standard printed by ISO have been produced to correspond (with an acceptable tolerance as judged by the naked eye) to the requirements of ISO 3864-4, it is not intended that these printed copies be used for colour matching. Instead consult ISO 3864-4 which provides colorimetric and photometric properties together with, as a guideline, references from colour order systems.

Add the following safety signs:

- M033: Close safety bar of chairlift
- M034: Open safety bar of chairlift
- M035: Immediately leave the tow-track in the event of falling
- M036: Lift ski tips
- P037: Do not leave the tow-track
- P038: Do not swing the chair

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[ISO 7010:2011/Amd 3:2012](https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-f53d-f26b99d3c699/iso-7010-2011-amd-3-2012)

[https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-](https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-f53d-f26b99d3c699/iso-7010-2011-amd-3-2012)

[f53d-f26b99d3c699/iso-7010-2011-amd-3-2012](https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-f53d-f26b99d3c699/iso-7010-2011-amd-3-2012)


Safety sign M033: Close safety bar of chairlift

	Reference No. <p style="text-align: center;">ISO 7010-M033</p>
	Referent <p style="text-align: center;">Close safety bar of chairlift</p>
	Function To signify that the safety bar of the chairlift must be closed
	Image content Human figure, chairlift with safety bar up, curved arrow pointing downwards
<p style="text-align: center; color: red; font-weight: bold;">iTeH STANDARD PREVIEW (standards.iteh.ai)</p> <p style="text-align: center; color: red;">ISO 7010:2011/Amd 3:2012 https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-b52d-f26b99d3c699/iso-7010-2011-amd-3-2012</p>	
Hazard Safety bar closed too late Human behaviour that is intended to be caused after understanding the safety sign's meaning Closing the safety bar of a chairlift	
Related referents ISO 7010-M034	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Safety sign M034: Open safety bar of chairlift

	Reference No. <p style="text-align: center;">ISO 7010-M034</p>
	Referent <p style="text-align: center;">Open safety bar of chairlift</p>
	Function To signify that the safety bar of the chairlift must be opened
	Image content Human figure, chairlift with safety bar down, curved arrow pointing upwards
<p style="text-align: center; color: red; font-weight: bold;">iTech STANDARD PREVIEW</p> <p style="text-align: center; color: red; font-weight: bold;">(standards.iteh.ai)</p> <p>Hazard Safety bar opened too early</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning Opening the safety bar of a chairlift ISO 7010:2011/Amd 3:2012</p> <p>Related referents https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-b52d-f26b99d3c699/iso-7010-2011-amd-3-2012 ISO 7010-M033</p> <p>Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p>	

Safety sign M035: Immediately leave the tow-track in the event of falling

	Reference No. <p style="text-align: center;">ISO 7010-M035</p>
	Referent <p style="text-align: center;">Immediately leave the tow-track in the event of falling</p>
	Function <p>To signify that the tow-track must be left immediately in the event of falling</p>
	Image content <p>Human figure on ski, two parallel straight lines, arrow pointing to the right</p>
<p>iTeh STANDARD PREVIEW (standards.iteh.ai)</p>	
Hazard <p>Obstruction on the tow-track</p>	
Human behaviour that is intended to be caused after understanding the safety sign's meaning <p>Leaving the tow-track after falling</p>	
Related referents <p>—</p>	
Additional information <p>Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p>	

Safety sign M036: Lift ski tips

	Reference No. <p style="text-align: center;">ISO 7010-M036</p>
	Referent <p style="text-align: center;">Lift ski tips</p>
	Function To signify that ski tips must be lifted
	Image content Human figure with ski, chairlift, arrow pointing upwards
<p style="text-align: center;">ITeh STANDARD PREVIEW (standards.iteh.ai)</p> <p>Hazard Crashing of the ski tips into technical parts of the cableway</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning Lifting the ski tips</p> <p>Related referents —</p> <p>Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p>	

<https://standards.iteh.ai/catalog/standards/sist/57679a0b-0505-4796-b52d-f26b99d3c699/iso-7010-2011-amd-3-2012>
 ISO 7010:2011/Amd 3:2012