



Designation: F2241–05 Designation: F 2241 – 05a (Reapproved 2008)

Standard Specification for Continued Airworthiness System for Powered Parachute Aircraft¹

This standard is issued under the fixed designation F 2241; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 The following continued airworthiness requirements apply for the manufacture of powered parachute aircraft and their qualification for possible certification.

1.2 This specification applies to powered parachute aircraft seeking civil aviation authority approval, in the form of flight certificates, flight permits, or other like documentation.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

F 2240 Specification for Manufacturer Quality Assurance Program for Powered Parachute Aircraft

F 2241 Specification for Continued Airworthiness System for Powered Parachute Aircraft

F 2242 Specification for Production Acceptance Testing System for Powered Parachute Aircraft

F 2243 Specification for Required Product Information to be Provided with Powered Parachute Aircraft

F 2244 Specification for Design and Performance Requirements for Powered Parachute Aircraft

3. Terminology

3.1 Definitions:

3.1.1 *powered parachute, n*—aircraft comprised of a flexible or semi-rigid wing connected to a fuselage in such a way that the wing is not in position for flight until the aircraft is in motion. That aircraft has a fuselage with seats, engine, and wheels (or floats), such that the wing and engine cannot be flown without the wheels (or floats) and seat(s). Unique to the powered parachute is the large displacement between the center of lift (high) and the center of gravity (low), which is pendulum effect. Pendulum effect limits angle of attack changes, provides stall resistance and maintains flight stability.

4. Current Operators List Documentation

4.1A current operators list will be maintained by the manufacturer that includes all aircraft in service by serial number, registration number, together with the name and address of the owner/operator. In order for the special airworthiness certificate for any light sport aircraft to be valid, the new owner of an aircraft that has transferred ownership must notify the manufacturer and have the current operators list appropriately updated to include the new owners name.

4.1 The manufacturer shall maintain a list of registered aircraft owners that includes all aircraft in service by serial number, registration number, together with the name and address of the owner.

4.2 In cases where the appropriate Civil Aviation Authority maintains records of registered owners sufficient for tracking aircraft and the manufacturer has access to such records, the manufacturer may elect to utilize such records for complying with this section.

5. Monitoring, Investigation and Remedial Action

5.1 The manufacturer shall maintain contact with dealers and owners who report incidents or other situations that might relate to safety, operations, or maintenance of aircraft produced and placed in service. The manufacturer will promptly investigate all reported failures, malfunctions, or defects and develop the appropriate corrective action. The magnitude of the service problem will

¹ This specification is under the jurisdiction of ASTM Committee F37 on Light Sport Aircraft and is the direct responsibility of Subcommittee F37.30 on Power Parachute. Current edition approved March 1, 2005. Published March 2005. Originally approved in 2003. Last previous edition approved in 2003 as F2241–03. Current edition approved May 15, 2008. Published July 2008. Originally approved in 2003. Last previous edition approved in 2005 as F 2241 – 05a.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.