TECHNICAL SPECIFICATION

ISO/TS 15638-12

First edition 2013-08-15

Intelligent transport systems —
Framework for collaborative Telematics
Applications for Regulated commercial
freight Vehicles (TARV) —

Part 12:

Vehicle mass monitoring (VMM) iTeh STANDARD PREVIEW

Systèmes intelligents de transport — Cadre pour applications télématiques collaboratives pour véhicules de fret commercial réglementé (TARV) —

Partie 12 15638-12:2013
https://standards.iteh.a/catalog/standards/sist/12b43438-01f6-4083-b963-f4d848167dff/iso-ts-15638-12-2013



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/TS 15638-12:2013 https://standards.iteh.ai/catalog/standards/sist/12b43438-01f6-4083-b963-f4d848167dff/iso-ts-15638-12-2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

1	Scope	1
2	Conformance	1
3	Normative references	2
4	Terms and definitions	2
5	Symbols (and abbreviated terms)	8
6	General overview and framework requirements	
7	Requirements for services using generic vehicle data	
8	Application services that require data in addition to basic vehicle data	
8.1	General	.10
8.2	Quality of service requirements	
8.3	Test requirements	
8.4	Marking, labelling and packaging	.10
9	Common features of regulated TARV application services	.10
9.1	General	.10
9.2	Common role of the jurisdiction, approval authority, service provider and user	.11
9.3	Common characteristics for instantiations of regulated application services	.11
9.4	Common sequence of operations for regulated application services	.11
9.5	Quality of service	.12
9.6	Information security	
9.7	Data naming content and quality of standards/sist/12b43438-016-4083-b963-	
9.8	Software engineering quality systems 0-15-15-15-15-15-15-15-15-15-15-15-15-15-	.12
9.9	Quality monitoring station	
9.10	Audits	
9.11	Access control to data policy	
9.12	Approval of IVSs and service providers	.12
10	Vehicle mass monitoring (VMM)	.12
10.1	TARV VMM service description and scope	
10.1.1	TARV VMM use case	.12
10.1.2	Description of TARV VMM regulated application service	
10.1.3	Description of TARV 'Vehicle mass monitoring' (TARV VMM) application service	
10.2	Concept of operations for TARV VMM	
	General	
	Strategies, tactics, policies, and constraints affecting the TARV VMM system	.15
10.2.4	Organisations, activities, and interactions among participants and stakeholders for TARV VMM	16
10.2.5	Clear statement of responsibilities and authorities delegated for TARV VMM	17
	Equipment required for TARV VMM	
	Calibration of mass sensors	
	Alarm Records for TARV VMM	
	Operational processes for the TARV VMM system	
	Role of the jurisdiction for TARV VMM	
10.2.11	1Role of the TARV VMM prime service provider	. 26
	Role of the TARV VMM application service provider	
10.2.13	Role of the TARV VMM user	.27
	Generic characteristics for all instantiations of the TARV VMM application service	
10.3	Sequence of operations for TARV VMM	
10.3.1	General	.27

ISO/TS 15638-12:2013(E)

10.4 TARV VMM service elements	29	
10.4.1 TARV VMM service element (SE) 1: Establish 'Vehicle mass monitoring' regulati		
requirements, and Approval arrangements	29	
10.4.2 TARV VMM SE2: Request system approval	29	
10.4.3 TARV VMM SE3: User (operator) contracts with prime service provider	29	
10.4.4 TARV VMM SE4: User (operator) equips vehicle with a devices to provide load		
information		
10.4.5 TARV VMM SE5: User contracts with application service provider	29	
10.4.6 TARV VMM SE6: application service provider uploads software into the TARV ed	quipped	
vehicles of the operator	29	
10.4.7 TARV VMM SE7: Time series or application service instigated recording of vehic	cle load29	
10.4.8 TARV VMM SE8: 'Interrogated' request for vehicle mass monitoring data	30	
10.5 Generic TARV VMM data naming content and quality	31	
10.6 TARV VMM application service specific provisions for quality of service	32	
10.6.1 General	32	
10.6.2 Tamper evidency		
10.7 TARV VMM application service specific provisions for test requirements	33	
10.8 TARV VMM application specific rules for the Approval of IVSs and 'Service Prov	iders'33	
11 Declaration of patents and intellectual property	33	
Annex A (Informative) Independent testing of the protocols defined in this Part of ISO 1	15638 3/	
A.1 Objectives		
A.2 TEST SCRIPT 6 SERVICE: VMM VEHICLE MASS MONITORING	36	
CTP 6.1.1 Instigated Vehicle Mass Monitoring using 2G		
CTP 6.1.2 Interrogated Vehicle Mass Monitoring using 2G		
CTP 6.1.3 Interrogated Vehicle Mass Monitoring using 5.9GHz and responding using 20 CTP 6.2.1 Instigated Vehicle Mass Monitoring using 3G	44	
CTP 6.2.2 Interrogated at 5.9 GHz and send of Vehicle Mass Monitoring using 3G		
CTP 6.3.1 Instigated Vehicle Mass Monitoring using 802.11p (WAVE) 5.9 GHz		
CTP 6.3.2 Interrogated Vehicle Mass Monitoring using 802.11p (WAVE) 5.9 GHz		
CTP 6.4.1 Instigated Vehicle Mass Monitoring using Mesh WiFi3	54	
f2d848167dff/iso_ts_15638_12_2013		
Sibliography5		

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement eh STANDARD PREVIEW

The committee responsible for this document is ISO/TC 204. Intelligent transport systems

ISO 15638 consists of the following parts, under the general title Intelligent transport systems — Framework for collaborative Telematics Applications for Regulated commercial freight Vehicles (TARV):
https://standards.iteh.ai/catalog/standards/sist/12b43438-01f6-4083-b963-

- Part 1 Framework and architecture 48167 dff/iso-ts-15638-12-2013
- Part 2: Common platform parameters using CALM
- Part 3: Operating requirements, 'Approval Authority' procedures, and enforcement provisions for the providers of regulated services
- Part 5: Generic vehicle information
- Part 6: Regulated applications [Technical Specification]
- Part 7: Other applications
- Part 8: Vehicle access monitoring (VAM) [Technical Specification]
- Part 9: Remote electronic tachograph monitoring (RTM) [Technical Specification]
- Part 10: Emergency messaging system/eCall (EMS) [Technical Specification]
- Part 11: Driver work records (work and rest hours compliance) (DWR) [Technical Specification]
- Part 12: Vehicle mass monitoring (VMM) [Technical Specification]
- Part 14: Vehicle access control (VAC) [Technical Specification]
- Part 15: Vehicle location monitoring (VLM) [Technical Specification]

ISO/TS 15638-12:2013(E)

- Part 16: Vehicle speed monitoring (VSM) [Technical Specification]
- Part 17: Consignment and location monitoring (CLM) [Technical Specification]
- Part 18: ADR (Dangerous Goods) transport monitoring (ADR) [Technical Specification]
- Part 19: Vehicle parking facilities (VPF) [Technical Specification]
- The following parts are under preparation:
- Part 4: System security requirements [Technical Specification]
- Part 13: 'Mass' information for jurisdictional control and enforcement

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/TS 15638-12:2013 https://standards.iteh.ai/catalog/standards/sist/12b43438-01f6-4083-b963-f4d848167dff/iso-ts-15638-12-2013

Introduction

Many ITS technologies have been embraced by commercial transport *operators* (4.36) and freight owners, in the areas of fleet management, safety and security. *Telematics* (4.49) applications have also been developed for governmental use. Such regulatory services in use or being considered vary from *jurisdiction* (4.30) to *jurisdiction*, but include electronic on-board recorders, digital *tachograph* (4.47), on-board *mass* (4.34) monitoring, 'mass' data for regulatory control and management (4.35), vehicle *access* (4.1) *methods*, *hazardous goods* tracking and e-call (4.20). Additional applications with a regulatory impact being developed include, fatigue management, speed monitoring and heavy vehicle penalties and levies imposed.

In such an emerging environment of regulatory and *commercial applications* (4.13), it is timely to consider an overall *architecture* (4.9) (business and functional) that could support these functions from a single platform within a commercial freight vehicle that operate within such regulations. International Standards will allow for a speedy development and *specification* (4.46) of new applications that build upon the functionality of a generic specification platform. A suite of standards documents is required to describe and define the *framework* (4.23) and requirements so that the on board equipment and back office systems can be commercially designed in an open market to meet common requirements of *jurisdictions* (4.30).

This suite of standards addresses and defines the *framework* (4.23) for a range of cooperative *telematics* (4.49) applications for *regulated commercial freight vehicles* (4.41) (such as *access methods* (4.4), driver *f*atigue management, speed monitoring, on-board *mass* (4.34), 'mass' data for regulatory control and management (4.34)). The overall scope includes the concept of operation, legal and regulatory issues, and the generic cooperative provision of services to *regulated commercial freight vehicles* (4.41), using an on-board ITS platform. The *framework* is based on a (multiple) *service provider* (4.44) oriented approach with provisions for the *approval* (4.6) and *auditing* (4.10) of *service providers*.

ISO/TS 15638-12:2013

This suite of standards documents will: /catalog/standards/sist/12b43438-01f6-4083-b963-

- provide the basis for future development of cooperative telematics (4.49) applications for regulated vehicles (4.41). Many elements to accomplish this are already available. Existing relevant standards will be referenced, and the specifications (4.46) will use existing standards (such as CALM) wherever practicable.
- allow for a powerful platform for highly cost-effective delivery of a range of *telematics* applications for *regulated vehicles* (4.41) .
- a business architecture (4.9) based on a (multiple) service provider (4.44) oriented approach
- address legal and regulatory aspects for the approval (4.6) and auditing (4.10) of service providers.

This suite of standards deliverables is timely as many governments (Europe, North America, Asia and Australia/New Zealand) are considering the use of *telematics* (4.49) for a range of regulatory purposes. Ensuring that a single in-vehicle platform can deliver a range of services to both government and industry through open standards and competitive markets is a strategic objective.

This part of the ISO 15638 family of standards documents provides *specifications* (4.46) for vehicle 'mass' monitoring.

NOTE: The definition of what comprises a 'regulated' vehicle is regarded as an issue for national decision, and may vary from *jurisdiction* (4.30) to *jurisdiction*. This suite of standards documents does not impose any requirements on nations in respect of how they define a *regulated vehicle* (4.41).

NOTE: The definition of what comprises a 'regulated' service is regarded as an issue for national decision, and may vary from *jurisdiction (4.30)* to *jurisdiction*. This suite of standards documents does not impose any requirements on nations in respect of which services for *regulated vehicles (4.41) jurisdictions* will require, or support as an option, but will provide standardised sets of requirements descriptions for identified services to enable consistent and cost efficient implementations where implemented.

© ISO 2013 – All rights reserved

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/TS 15638-12:2013 https://standards.iteh.ai/catalog/standards/sist/12b43438-01f6-4083-b963-f4d848167dff/iso-ts-15638-12-2013

Intelligent transport systems — Framework for collaborative Telematics Applications for Regulated commercial freight Vehicles (TARV) —

Part 12:

Vehicle mass monitoring (VMM)

1 Scope

This part of ISO 15638 addresses the provision of "Vehicle 'Mass' Monitoring" and specifies the form and content of such data required to support such systems, and access methods (4.4) to that data.

This part of ISO 15638 provides *specifications* (4.46) for common communications and data exchange aspects of the *application service* (4.3) "Vehicle 'Mass' Monitoring" that a *regulator* (4.42) may elect to require or support as an option, including: **Teh STANDARD PREVIEW**

a) high level definition of the service that a service provider (4.44) has to provide, (The service definition describes common service elements, but does not define the detail of how such an application service (4.3) is instantiated, not the acceptable value ranges of the data concepts defined)

ISO/TS 15638-12:2013

- b) means to realise/thenserviceh.ai/catalog/standards/sist/12b43438-01f6-4083-b963-f4d848167dff/iso-ts-15638-12-2013
- c) application data, naming content and quality that an IVS (4.26)) has to deliver.

The definition of what comprises a 'regulated' service is regarded as an issue for National decision, and may vary from *jurisdiction* (4.30) to *jurisdiction*. This document does not impose any requirements on nations in respect of which services for *regulated commercial freight vehicles* (4.41) *jurisdictions* will require, or support as an option, but provides standardised sets of requirements descriptions for identified services to enable consistent and cost efficient implementations where instantiated.

ISO 15638 has been developed for use in the context of regulated commercial freight vehicles (hereinafter referred to as 'regulated vehicles' (4.41)). There is nothing however to prevent a jurisdiction extending or adapting the scope to include other types of regulated vehicles, as it deems appropriate.

2 Conformance

Requirements to demonstrate conformance to any of the general provisions or specific *application services* (4.3) described in this part of ISO 15638 shall be within the regulations imposed by the *jurisdiction* (4.30) where they are instantiated. Conformance requirements to meet the provisions of this International Standard are therefore deemed to be under the control of, and to the specification of, the *jurisdiction* where the *application service*(s)is/are instantiated.

The protocols defined in this Part of ISO 15638 have been independently tested. Annex A (Informative) provides results of these tests. In any conformance assurance process undertaken by candidate systems, where appropriate the results may be used as part of its process of conformance compliance.

© ISO 2013 – All rights reserved

3 Normative references

The following referenced documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15638-1	Intelligent transport systems — Framework for collaborative Telematics Applications for Regulated commercial freight Vehicles (TARV) — Part 1: Framework and architecture
ISO 15638 -2	Intelligent transport systems — Framework for collaborative Telematics Applications for Regulated commercial freight Vehicles (TARV) — Part 2: Common platform parameters using CALM
ISO 15638 -3	Intelligent transport systems — Framework for collaborative telematics applications for regulated commercial freight vehicles (TARV) — Part 3: Operating requirements, 'Approval Authority' procedures, and enforcement provisions for the providers of regulated services
ISO 15638 -4	Intelligent transport systems — Framework for collaborative Telematics Applications for Regulated commercial freight Vehicles (TARV) — Part 4: System security requirements ¹
ISO 15638 -5	Intelligent transport systems — Framework for collaborative Telematics Applications for Regulated commercial freight Vehicles (TARV) — Part 5: Generic vehicle information
ISO 15638 -6	Intelligent transport systems — Framework for collaborative Telematics Applications for Regulated commercial freight Vehicles (TARV) — Part 6: Regulated applications

4 Terms and definitions

ISO/TS 15638-12:2013

https://standards.iteh.ai/catalog/standards/sist/12b43438-01f6-4083-b963-

For the purposes of this document, the terms and definitions given in ISO 15638-1 and the following apply.

4.1

access methods

procedures and protocols to provision and retrieve data

4.2

app

small (usually) $Java^{TM}$ (4.29) applets, organised as software bundles, that support application services (4.3) by keeping the data pantry (4.17) provisioned with up-to-date data

4.3

application service

service provided by a *service provider* (4.44) enabled by accessing data from the *IVS* (4.26) of a *regulated* vehicle (4.41) via a wireless communications network

4.4

application service provider

ASP

party that provides an application service (4.3)

2

Under preparation.

app library

separately secure area of memory in *IVS* (4.26) where apps are stored [with different access controls to *data* pantry (4.17)]

4.6

approval

formal affirmation that an applicant has satisfied all the requirements for appointment as an *application service* provider (4.4) or that an application service delivers the required service levels.

4.7

approval agreement

written agreement made between an approval authority (regulatory) (4.8) and a service provider (4.44)

NOTE An approval authority (regulatory) (4.8) approval agreement recognises the fact that a service provider (4.44), having satisfied the approval authority's requirements for appointment as a service provider, is appointed in that capacity, and sets out the legal obligations of the parties with respect to the on-going role of the service provider.

4.8

approval authority (regulatory)

organisation (usually independent) which conducts *approval* (4.6) and ongoing *audit* (4.10) for *service providers* (4.44) on behalf of a *jurisdiction* (4.30)

4.9

architecture

formalised description of the design of the structure of TARV and its framework (4.23)

4.10

(standards.iteh.ai)

audit/auditing

review of a party's capacity to meet, or continue to meet, the initial and ongoing *approval agreements* (4.7) as a service provider (4.44)

https://standards.iteh.ai/catalog/standards/sist/12b43438-01f6-4083-b963-

4.11

f4d848167dff/iso-ts-15638-12-2013

basic vehicle data

data that shall be maintained/provided by all IVS (4.26) [regardless of jurisdiction (4.30)]

4.12

CALM communications access for land mobiles

layered solution that enables continuous or quasi continuous communications between vehicles and the infrastructure, or between vehicles, using such (multiple) wireless telecommunications media that are available in any particular location, and which have the ability to migrate to a different available media where required and where media selection is at the discretion of *user* (4.50) determined parameters by using a suite of standards based on ISO 21217 (*CALM* architecture) and ISO21210 (*CALM* networking) that provide a common platform for a number of standardised media using *ITS-stations* (4.28) to provide wireless support for applications, such that the application is independent of any particular wireless medium

4.13

commercial application(s)

ITS applications in regulated vehicles (4.41) for commercial (non-regulated) purposes

EXAMPLE Asset tracking, vehicle and engine monitoring, cargo security, driver management etc.

4.14

consignment

shipment of goods/cargo to a destination

cooperative ITS

C-ITS

ITS applications for both regulatory and commercial purposes that require the exchange of data between uncontracted parties using multiple *ITS-stations* (4.28) communicating with each other and sharing data with other parties with whom they have no direct contractual relationship to provide one or more *ITS services* (4.27)

4.16

core data

basic vehicle data (4.11) plus any additional data required to provide an implemented regulated application service (4.40)

4.17

data pantry

secure area of memory in *IVS* (4.26) where data values are stored [with different access control to data to *app library* (4.5)]

4.18

driver

person driving the regulated vehicle at any specific point in time

4 19

driver work records

DWR

collection, collation, and transfer of *driver* (4.18) work and rest hours data from an *in-vehicle system* (4.26) to an application service provider (4.4) Teh STANDARD PREVIEW

4.20

(standards.iteh.ai)

eCall

specialised instantiation of an *EMS* (4.21) that provides incident messaging and communication with a public service assistance point via priority wireless telephone communications using its emergency call capabilities https://standards.itch.ai/catalog/standards/sist/12b43438-016-4083-b963-

4.21 £4d848167dff/iso-ts-15638-12-2013

emergency message system

EMS

collection, collation, and transfer of emergency message data from an *in-vehicle system* (4.26) to an *application* service provider (4.4)

4.22

facilities

layer that sits on top of the communication stack and helps to provide data interoperability and reuse, and to manage applications and enable dynamic real time loading of new applications

4.23

framework

particular set of beliefs, ideas referred to in order to describe a scenario or solve a problem

4.24

global navigation satellite system

GNSS

comprises several networks of satellites that transmit radio signals containing time and distance data that can be picked up by a receiver, allowing the user to identify the location of its receiver anywhere around the globe

4.25

global positioning system

ĞPS

instantiation of GNSS (4.24) controlled by the US Department of Defence

in-vehicle system

ITS-station (4.28) and connected equipment on board a vehicle

4.27

ITS service

communication functionality offered by an ITS-station (4.28) to an ITS-station application

4.28

ITS-station

ITS-s

entity in a communication network, comprised of application, facilities (4.22), networking and access layer components specified in ISO 21217 that operate within a bounded secure management domain

4.29

Java™

object oriented open source operating language developed by SUN systems

jurisdiction

government, road or traffic authority which owns the regulatory applications (4.39)

Country, state, city council, road authority, government department (customs, treasury, transport), etc.

jurisdiction regulator iTeh STANDARD PREVIEW agent of the jurisdiction (4.30) appointed to regulate and manage TARV within the domain of the jurisdiction; may or may not be the approval authority (regulatory) (4.8)

ISO/TS 15638-12:2013 4.32

local data tree

https://standards.iteh.ai/catalog/standards/sist/12b43438-01f6-4083-b963-

LDT

f4d848167dff/iso-ts-15638-12-2013

frequently updated data concept stored in the on on-board data pantry (4.17) containing a collection of data values deemed essential for either a) TARV regulated application service (4.40), or b) cooperative intelligent transport systems (4.15)

4.33

man

spatial dataset that defines the road system

4.34

mass

mass of a given heavy vehicle as measured by equipment affixed to the regulated vehicle (4.41)

4.35

'mass' data for regulatory control and management

MRC

collection, collation, and transfer of vehicle mass (4.34) data from an in-vehicle system (4.26) to an application service provider (4.4) to enable data provision to jurisdictions (4.30) for the control and management of equipped vehicles based on the mass of the regulated vehicle (4.41), or use of such data to enable compliance with the provisions of regulations.

4.36

operator

fleet manager of a regulated vehicle

prime mover

heavy-duty commercial vehicle tractor unit which serves as a method of moving trailers (most often semi-trailers) by coupling to the trailer using some sort of mechanical lock system, usually a fifth wheel coupling; tractor units can couple to different types of trailers

4.38

prime service provider

service provider (4.44) who is the first contractor to provide regulated application services (4.40) to the regulated vehicle (4.41), or a nominated successor on termination of that initial contract

NOTE The prime service provider (4.38) is also responsible to maintain the installed IVS (4.26); if the IVS was not installed during the manufacture of the vehicle the prime service provider (4.38) is also responsible to install and commission the IVS (4.26).

4.39

regulated/regulatory application

application arrangement using TARV utilised by *jurisdictions* (4.30) for granting certain categories of commercial vehicles rights to operate in regulated circumstances subject to certain conditions, or indeed to permit a vehicle to operate within the *jurisdiction*

NOTE This can be mandatory or voluntary at the discretion of the *jurisdiction*.

4.40

regulated application service

TARV application service to meet the requirements of a regulated application that is mandated by a regulation imposed by a jurisdiction (4.30), or is an option supported by a jurisdiction

(standards.iteh.ai)

regulated commercial freight vehicle/regulated vehicle (4.41)

vehicle that is subject to regulations determined by the jurisdiction (430) as to its use on the road system of the jurisdiction in regulated circumstances, itsubject to scentain siconditions, oand 4 in 3-compliance with specific regulations for that class of regulated vehicle d848167dff/iso-ts-15638-12-2013

NOTE At the option of *jurisdictions*; this may require the provision of information via *TARV* or provide the option to do so.

4.42

regulator

see jurisdiction regulator (4.31)

4.43

remote tachograph monitoring (RTM)

collection, collation, and transfer of data from an on-board electronic *tachograph* (4.47) system to an application service provider (4.4)

4.44

service provider

party which is approved by an approval authority (regulatory) (4.8) as suitable to provide regulated or commercial ITS application services (4.3)

4.45

session

wireless communication exchange between the *ITS-station* (4.28) of an *IVS* (4.26) and the *ITS-station* of its application service provider (4.4) to achieve data update, data provision, upload apps, or otherwise manage the provision of the application service (4.3), or a wireless communication provision of data to the *ITS-station* of an *IVS* (4.26) from any other *ITS-station*

specification

explicit and detailed description of the nature and functional requirements and minimum performance of equipment, service or a combination of both

4.47

tachograph

sender unit mounted to a vehicle gearbox, a tachograph head and a digital driver card, which records the regulated vehicle (4.41) speed and the times at which it was driven and aspects of the driver's (4.18) activity selected from a choice of modes

4.48

tamper/tampering

conduct towards *IVS* (4.26) or a service provider's (4.44) system which is intended to prevent the *IVS* (4.26) or the service provider's system from functioning correctly

4.49

telematics

use of wireless media to obtain and transmit (data) from a distant source

4.50

user

individual or party that enrols in and operates within a regulated or commercial application (4.13) service (4.3)

EXAMPLE Driver (4.18), transport operator (4.36), freight owner, etc.

iTeh STANDARD PREVIEW

4.51

vehicle access control

(standards.iteh.ai)

VAC

control of *regulated vehicles* ingress to and egress from controlled areas and associated regulatory control and management

https://standards.iteh.ai/catalog/standards/sist/12b43438-01f6-4083-b963-

4.52

f4d848167dff/iso-ts-15638-12-2013

vehicle access management

VAM

monitoring and management of regulated vehicles approaching or within sensitive and controlled areas

4.53

vehicle location monitoring

VLM

collection, collation, and transfer of vehicle location data from an *in-vehicle system* (4.26) to an *application* service provider (4.4)

4.54

vehicle mass monitoring

VMM

collection, collation, and transfer of vehicle *mass* (4.34) data from an *in-vehicle system* (4.26) to an *application* service provider (4.4)

4.55

vehicle parking facility

VPF

system for booking and access (4.1) to and egress from a vehicle parking facility (VPF) (4.55)

4.56

vehicle speed monitoring

VSM

collection, collation, and transfer of vehicle speed data from an *in-vehicle system* (4.26) to an *application* service provider (4.4)