
Infrastruktura za plin - Posledice zaradi vodika v infrastrukturi za plin in ugotavljanje s tem povezanih potreb po standardizaciji na področju CEN/TC 234

Gas infrastructure - Consequences of hydrogen in the gas infrastructure and identification of related standardisation need in the scope of CEN/TC 234

Gasinfrastruktur - Auswirkungen von Wasserstoff in der Gasinfrastruktur und Identifikation des zugehörigen Normungsbedarfs im Zuständigkeitsbereich des CEN/TC 234

Infrastructure gazière - Consequences d'hydrogen dans l'infrastructure gazière et l'identification des besoins relatifs à la normalisation dans le domaine d'application de CEN/TC 234

Ta slovenski standard je istoveten z: CEN/TR 17797:2022

ICS:

01.120	Standardizacija. Splošna pravila	Standardization. General rules
75.180.01	Oprema za industrijo nafte in zemeljskega plina na splošno	Equipment for petroleum and natural gas industries in general

SIST-TP CEN/TR 17797:2022**en**

TECHNICAL REPORT

CEN/TR 17797

RAPPORT TECHNIQUE

TECHNISCHER BERICHT

March 2022

ICS 01.120; 75.180.01

English Version

Gas infrastructure - Consequences of hydrogen in the gas infrastructure and identification of related standardisation need in the scope of CEN/TC 234

Infrastructure gazière - Conséquences d'hydrogène dans l'infrastructure gazière et l'identification des besoins relatifs à la normalisation dans le domaine d'application de CEN/TC 234

Gasinfrastruktur - Auswirkungen von Wasserstoff in der Gasinfrastruktur und Identifikation des zugehörigen Normungsbedarfs im Zuständigkeitsbereich des CEN/TC 234

This Technical Report was approved by CEN on 24 January 2022. It has been drawn up by the Technical Committee CEN/TC 234.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

(standards.iteh.ai)

[SIST-TP CEN/TR 17797:2022](https://standards.iteh.ai/catalog/standards/sist/4d670047-c83c-4945-8ba8-88a0983d9089/sist-tp-cen-tr-17797-2022)

<https://standards.iteh.ai/catalog/standards/sist/4d670047-c83c-4945-8ba8-88a0983d9089/sist-tp-cen-tr-17797-2022>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents		Page
European foreword		5
Introduction		6
1	Scope.....	7
2	Normative references.....	7
3	Terms, definitions and abbreviations	7
3.1	Terms and definitions.....	7
3.2	Symbols and abbreviations	10
4	Executive summary	10
5	General considerations for the entire gas infrastructure	12
5.1	Explosion protection and prevention.....	12
5.1.1	General principles	12
5.1.2	Safety characteristics of natural gas-hydrogen mixtures and their impact on explosion prevention.....	13
5.1.3	Consequences of H ₂ and H ₂ NG in NG infrastructure for explosion protection related to identified H ₂ concentrations.....	14
5.2	N ₂ NG mixtures in contact with materials — Pressure integrity, gas tightness and functionality.....	15
5.2.1	General.....	15
5.2.2	Steel.....	18
5.2.3	PE and PA-U.....	26
5.2.4	Alloys.....	26
5.2.5	Information on deterioration and chemical aggression of elastomers.....	26
5.2.6	Others.....	26
5.3	Volume in relation to energy content — consequences for the capacity and function of the gas transportation, underground gas storage and distribution system.....	26
6	Technical considerations per topic applicable for the different parts of the gas infrastructure (along chain)	27
6.1	General.....	27
6.2	Gas quality	27
6.2.1	Scope of considerations — Gas quality — EN 16726.....	27
6.2.2	Technical considerations — Identified H ₂ NG	28
6.3	Gas compression	33
6.3.1	Scope of consideration — Gas compression.....	33
6.3.2	Technical considerations — Identified H ₂ NG aspects — Gas compression	34
6.4	Gas pipelines with MOP over 16 bar — Gas transmission	34
6.4.1	Scope of consideration — Gas transmission — EN 1594.....	34
6.4.2	Hydrogen piping and pipelines — ASME B31.12	34
6.4.3	Technical considerations — Identified H ₂ NG aspect — Gas transmission.....	35
6.5	Gas pressure control.....	38
6.5.1	Scope of consideration — Gas pressure control — EN 12186 and EN 12279	38
6.6	Gas metering.....	39
6.6.1	Scope of consideration — Gas metering — EN 1776	39
6.6.2	Technical considerations — Identified H ₂ NG aspects — Gas metering.....	39
6.7	Gas supply systems up to and including 16 bar and pressure testing.....	40

6.7.1	Statement for gas pipelines with MOP up to and including 16 bar for all concentrations.....	40
6.7.2	Requalifying existing pipelines for hydrogen service.....	41
6.7.3	Technical consideration — Scoping considerations — EN 2007-1 to -4, CEN/TS 12007-6, EN 12327 and EN 12732.....	41
6.8	Service lines.....	45
6.8.1	Scoping considerations — Service lines — EN 12007-5.....	45
6.8.2	Technical considerations — Identified H ₂ NG aspects integrity and safety, reliability and operation.....	46
6.9	Industrial piping.....	47
6.9.1	Scope of consideration - Industrial piping - EN 15001-1 and EN 15001-2.....	47
6.9.2	Technical considerations — Industrial piping.....	48
6.10	Gas pipework for buildings.....	49
6.10.1	Scope of consideration — Gas pipework for buildings - EN 1775.....	49
6.10.2	Technical considerations — Gas pipework for buildings.....	49
6.11	Underground gas storage.....	49
6.11.1	Scope of consideration for underground gas storage — Generals EN 1918-1 to -5....	49
6.11.2	Technical considerations — Underground gas storage.....	50
6.11.3	Identified H ₂ NG impacts — Underground gas storage.....	51
6.12	Safety management and integrity management.....	52
6.12.1	Scope of considerations.....	52
6.12.2	Safety management system — Management of change.....	52
6.12.3	Pipeline integrity management system.....	53
7	Conclusions — H ₂ suitability of components, materials and procedures used in the gas infrastructure related to identified H ₂ concentrations.....	54
7.1	General.....	54
7.2	H ₂ suitability — Gas quality.....	55
7.2.1	H-gas quality - Admixture of H ₂	55
7.2.2	Hydrogen quality in converted natural gas grids.....	56
7.3	H ₂ suitability — Gas compressor stations.....	57
7.3.1	General.....	57
7.3.2	Less than 1 % hydrogen in natural gas.....	58
7.3.3	Over 1 Vol.-% up to 5 Vol.-% H ₂ in natural gas.....	58
7.4	H ₂ suitability — Gas transmission pipelines with MOP over 16 bar.....	61
7.5	H ₂ suitability — Gas pressure control.....	62
7.5.1	Introduction.....	62
7.5.2	General.....	63
7.5.3	Up to 10 Vol.-% H ₂ in natural gas.....	63
7.5.4	Over 10 Vol.-% up to 100 % H ₂ in natural gas.....	64
7.6	H ₂ suitability — Gas metering.....	65
7.7	H ₂ suitability — Gas pipelines with MOP up to and including 16 bar.....	65
7.7.1	A Summary of findings for gas pipeline systems up to and including 16 bar and pressure testing (CEN/TC 234 WG 2).....	65
7.8	H ₂ suitability — Service lines.....	66
7.9	H ₂ suitability — Industrial piping.....	66
7.10	H ₂ suitability — Gas pipework for buildings.....	67
7.11	H ₂ suitability — Underground gas storage.....	67
7.11.1	Between 0 % and 1 % hydrogen in natural gas.....	67
7.11.2	Between 1 % and 20 % hydrogen in natural gas.....	68
7.11.3	Above 20 % hydrogen up to full replacement of natural gas by hydrogen (100 % hydrogen).....	68

CEN/TR 17797:2022 (E)

8	Revision needs of existing CEN/TC 234 standards and additional deliverables for the H₂-readiness of the gas infrastructure	68
8.1	Action need.....	68
8.2	Gas quality — Expected revision of EN 16726:2015+A1:2018.....	69
8.3	Gas compression — Expected revision of EN 12583:2014.....	69
8.4	Pipelines for maximum operating pressure over 16 bar — Expected revisions of EN 1594:2013	70
8.5	Gas pressure control — Expected revisions of EN 12186:2014 and EN 12279:2000	71
8.6	Gas measuring systems — Expected revision of EN 1776:2015	73
8.7	Pipelines for maximum operating pressure up to and including 16 bar — Expected revision of EN 12007 Parts 1 to 4 and EN 12327:2012	74
8.8	Pressure testing, commissioning and decommissioning procedures — Expected revision of EN 12327:2012	77
8.9	Welding of steel — Expected revision of EN 12732:2013	78
8.10	Service lines — Expected revision of EN 12007-5:2014	78
8.11	Gas installation pipework- Expected revision of FprEN 15001-1:2019 and EN 15001-2:2019	81
8.12	Gas pipework for buildings — Expected revision of EN 1775	85
8.13	Underground gas storage- Expected revision of EN 1918-1:2016 to -5:2016.....	86
8.14	Safety and Integrity Management System — Expected revision of EN 16348 and EN 15399 by prEN 17649 (merged standard)	91
Annex A (informative)	Any issue coming up during the discussion and outside of the TC 234 scope.....	92
Annex B (informative)	Safety characteristics of natural gas-hydrogen mixtures.....	93
Annex C (informative)	Operating principles for gas warning devices [2].....	94
Annex D (informative)	Hydrogen pressure versus hydrogen percentage	96
Annex E (informative)	Hydrogen pressure versus hydrogen fugacity	97
Annex F (informative)	An example of the use of an existing gas pipeline for hydrogen gas	99
Annex G (informative)	Use of polyamide (PA-U) in gas piping systems in relation to hydrogen, methane or their mixtures.....	101
Annex H (informative)	Netbeheer Nederland Study for biomethane and 100 % hydrogen	112
Annex I (informative)	Responsibility of CEN/TC 234 'Gas infrastructure' Working groups for the parts of the gas infrastructure along the chain	114
Annex J (informative)	Symbols and abbreviations.....	115
Bibliography	118

European foreword

This document (CEN/TR 17797:2022) has been prepared by Technical Committee CEN/TC 234 “Gas infrastructure”, the secretariat of which is held by DIN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users’ national standards body. A complete listing of these bodies can be found on the CEN website.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST-TP CEN/TR 17797:2022

<https://standards.iteh.ai/catalog/standards/sist/4d670047-c83c-4945-8ba8-88a0983d9089/sist-tp-cen-tr-17797-2022>

Introduction

The injection of hydrogen in natural gas infrastructures demands considerations with regard to the integrity, safety and performance of the systems facing increasing hydrogen levels, its fluctuation and variation.

There is extensive research on the use of hydrogen as an admixture with natural gas in various percentages or as pure hydrogen. Impact studies already completed or in progress are focusing on the use of existing gas networks but also of dedicated gas networks for hydrogen. They also include the impact of the introduction of hydrogen in various percentages into the gas infrastructure on all the existing technologies within the gas supply chain.

Accepting hydrogen into the natural gas network requires input from many gas TCs at CEN, i.e. CEN/TC 234 and particularly from the manufacturers of essential components, e.g. valves, gas pressure regulators, gas meters, safety control devices, leak detection devices, and many more (see Annex A). Many of these manufacturers are assessing the potential impact of hydrogen on existing components in natural gas service.

Co-operation with these other CEN and ISO/TCs for various essential components and applications will be necessary to ensure that projects to introduce hydrogen have all the essential elements of the gas chain fully co-ordinated into the plan. The positive co-operation of the component manufacturers will be particularly important.

In the transition scheme to hydrogen, there is a large body of knowledge and experience available from the hydrogen industry for gas production and use. The long-established safety requirements in this sector will aid the amendment of natural gas standards and codes of practice and the development of any new standards

This report is written for

- CEN/TC 234 as basis for definition of a TC roadmap for standardisation
- CEN/TC 234 WGs as a guideline for the standardisation work
- interested parties to get an insight in the decision process of CEN/TC 234's hydrogen standardisation.

NOTE This document has been elaborated in co-operation between the Working Group convenors, secretaries and experts, TC chair and secretariat of CEN/TC 234. Respecting different working group contributions, the way in which the content is presented and the level of details differs for the different topics. This is acceptable as the real technical work will take place in the dedicated working groups with co-ordination of the TC 234 Convenors/Secretaries group to ensure the final coherence of the resulting standardisation deliverables.

1 Scope

This document is written in preparation of future standardization and provides guidance on how injection of H₂ into the gas infrastructure can impact processes from the input of gas into the on-shore transmission network up to the inlet connection of gas appliances.

NOTE 1 Gas infrastructure includes gas installation pipework between the delivery point of the gas and the inlet connection to the gas appliance in buildings and on industrial sites.

The assessments refer to the concentrations of 2, 5, 10, 20 and up to 100 Vol.- % hydrogen in natural gas.

Furthermore, it identifies the expected revision need of the existing CEN/TC 234 standards as well as the need of further new standardisation deliverables.

It examines the effects on each part of the gas infrastructure in the scope of the CEN/TC 234 Working Groups 1 to 12 inclusive, based on available studies, reports and research. Due to several limitations at different hydrogen concentrations, the impacts are specified.

For some specific impacts, pre-standardization research is needed.

By convention, for this technical report, the injection of pure hydrogen, i. e. without trace and/or minor components is considered. Awareness is given that there is the need to consider trace and/or minor components and limits set on the gas quality on European and national level, too.

The information from this report is intended to define the CEN/TC 234 work program for the coverage of H₂NG in relation to the scope of the CEN/TC 234 and its WGs.

NOTE 2 Progress on hydrogen will develop over time. In principle this will be reflected in the standardisation process in CEN/TC 234.

2 Normative references

There are no normative references in this document.

3 Terms, definitions and abbreviations

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

The International Gas Union glossary on Underground Gas Storage [1] can be useful too:

3.1 Terms and definitions

3.1.1

hydrogen embrittlement

HE

interaction of hydrogen atoms and steel can have a negative effect on the mechanical behaviour of steel.

Note 1 to entry: The general term for this degrading effect is called hydrogen embrittlement

CEN/TR 17797:2022 (E)

3.2.2

explosive atmosphere

mixture with air, under atmospheric conditions, of flammable substances in the form of gases, vapours, mists or dusts in which, after ignition has occurred, combustion spreads to the entire unburned mixture

[SOURCE: EN 13723:2013, 3.28]

3.2.3

hazardous explosive atmosphere

explosive atmosphere present in such quantities that precautions against ignition are required

[SOURCE: IEC 61340-4-4:2018, 3.6]

3.2.4

hazardous area

area in which an explosive atmosphere is present, or can be expected to be present, in quantities such as to require special precautions for the construction, installation and use of equipment

[SOURCE: IEC 60079-0:2013]

3.2.5

explosion group

ranking of flammable gas-air mixtures with respect to the Maximum Experimental Safe Gap (MESG)

[SOURCE: EN ISO 16852:2016, 3.12.2]

3.2.6

temperature class

temperature range used for:

- classification of equipment, protective system for explosive atmospheres based on its maximum surface temperature; or
- classification of flammable gases and vapours based on their auto ignition

[SOURCE: EN 13237:2012, 3.63]

3.2.7

explosion pressure

highest pressure occurring in a closed vessel during the explosion of a specific mixture of flammable substances with air or air and inert gases determined under specified test conditions

[SOURCE: EN 15967:2011]

3.2.8

ignition temperature

lowest temperature (of a hot surface) at which under specified test conditions an ignition of a flammable gas or flammable vapour in mixture with air or air/inert gas occurs

[SOURCE: EN 14522:2005]

3.2.9**limiting oxygen concentration****LOC**

maximum oxygen concentration in a mixture of a flammable substance and air and an inert gas, in which an explosion will not occur, determined under specified test conditions

[SOURCE: EN 13237:2012, 3.49]

3.2.10**lower explosion limit****LEL**

lowest concentration of the explosion range at which an explosion can occur

[SOURCE: EN 13237:2012, 3.19.1]

3.2.11**maximum experimental safe gap****MESG**

maximum gap of the joint between the two parts of the interior chamber of a test apparatus which, when the internal gas mixture is ignited and under specified conditions, prevents ignition of the external gas mixture through a 25 mm long joint, for all concentrations of the tested gas or vapour in air

[SOURCE: EN 13237:2012, 3.51]

3.2.12**maximum explosion pressure**

maximum value of explosion pressure measured in the tests for explosion pressure when the content of the flammable substances in the mixture is varied

[SOURCE: EN 13237:2012, 3.2]

3.2.13**minimum ignition energy****MIE**

lowest electrical energy stored in a capacitor, which upon discharge is sufficient to effect ignition of the most ignitable atmosphere under specified test conditions

[SOURCE: EN 13237:2012, 3.54]

3.2.14**upper explosion limit****UEL**

highest concentration of the explosion range at which an explosion can occur

[SOURCE: EN 13237:2012, 3.19.2]

CEN/TR 17797:2022 (E)

3.2.15

ventilation

movement of air and its replacement with fresh air due to the effects of wind, temperature gradients, or artificial means (for example, fans or extractors)

[SOURCE: IEC 60079-10-0:2015]

3.2 Symbols and abbreviations

Symbols and abbreviations should be selected from those already established in relevant ISO and/or CEN standards. New symbols and abbreviations should be defined only where there is no suitable alternative and recorded in CEN/TC 234 Doc N 776 (so called N 215).

The symbols and abbreviations used in this document are listed in Annex J.

4 Executive summary

Intention of the European gas industry is to enable the use of natural gas infrastructure for hydrogen.

For the use of hydrogen in the natural gas infrastructure it is reasonable to identify:

- the similarities (what is equal) and differences (what is different) between methane (natural gas) and hydrogen and – based on these
- the consequences or the impact of hydrogen on the gas system (e.g. materials, safety, maintenance).

NOTE 1 Acknowledging the impact of the similarities on applications, in this document only the impact on gas infrastructure is considered as in the scope of CEN/TC 234.

NOTE 2 Natural gas is a mixture of hydrocarbon gases and other gases (e.g. nitrogen). Its main component is methane.

The following similarities and differences of the properties of methane and hydrogen need consideration:

Table 1 gives common properties of hydrogen and natural gas whereas Table 2 shows differences in the nominal values of the common properties of hydrogen and methane.

Table 1 — Common properties of hydrogen and natural gas

Characteristic	Methane (natural gas)	Hydrogen
gaseous	yes	yes
colourless	yes	yes
odourless	yes	yes
toxic	no	no
flammable	yes	yes
explosive	yes	yes
corrosive	no	no

Table 2 — Properties of hydrogen and methane — differences

Parameter	Methane	Hydrogen
Relative density (air = 1)	0,55	0,07
Flammability limits [Mol.- %]	4,4–17	4,0–77
Ignition energy [mJ]	0,26	0,017
Combustion energy up/low) [MJ/m ³]	40/36	13/11
Wobbe number [MJ/m ³]	upper: 54 lower: 48	48–41
Gross calorific value [kJ/mol, at 20 °C]	891	286
Flame colour	blue	colourless
Molecular mass [g/mol]	16	2
Molecule size [pm]	220	75
Diffusion coefficient in air [10 ⁻⁴ m ² /s]	0,61	0,20
Infrared absorption	yes	no
Joule-Thomson coefficient [K/bar]	0,4	–0,03
Sound velocity [m/s]	388 ^a	1 203
NOTE 1 This Table is meant as indication of general differences between methane (CH ₄) and hydrogen (H ₂) without referring to the specific conditions.		
NOTE 2 More details related to mixtures of methane with hydrogen are given in Table B.1.		
^a High caloric natural gas https://www.cen.eu/catalog/standards/sist/4d670047-c83c-4945-8ba8-		

In Clause 6, a detailed evaluation of technical safety and integrity and performance aspects is given per part of the natural gas infrastructure.

In Clause 7, the suitability of the different parts of the gas infrastructure for hydrogen and hydrogen admixtures are summarised in form of tables.

As a conclusion, the following aspects need specific attention:

1) materials

- embrittlement of steel (5.2.2)
- diffusion and/or permeation of the gas through materials
- deterioration of elastomers
- suitability of sealing materials
- ...

NOTE 3 Consideration should be given also to historic materials remaining in networks such as grey cast iron and ductile cast iron.

CEN/TR 17797:2022 (E)

2) safety aspects of hydrogen/, explosion prevention and protection

- ATEX requirements
- purging
- venting
- proof of gas tightness
- detection of hydrogen and admixtures
- odorization
- fire detection

3) technical system

- compression
- biochemical reactions in reservoirs and caverns
- metering
- gas preheating
- Joule-Thomson-Dehydration
- ...

4) Other aspects

- Volume in relation to energy content (5.3)
- Gas quality

The existing standards of CEN/TC 234 can be amended to cover natural gas infrastructure used for hydrogen services. For some aspects new CEN deliverables are needed.

The revision needs of the CEN/TC 234 standards respectively the need to elaborate additional standards is documented in Clause 8. The extent and timeframe of revision differs for the single aspects and for some aspects rely on further research results.

The involvement of the competent experts will be ensured by calls to the NSB, with the new work item proposals and beyond. Strong involvement of the sector is required.

NOTE 4 CEN/TC 234 intends to elaborate the related revisions in cooperation with the relevant TCs (e.g. CEN-CLC/JTC 6) and stakeholders. Preparations and first work items are already in process in the dedicated working groups.

5 General considerations for the entire gas infrastructure

5.1 Explosion protection and prevention

5.1.1 General principles

The general principles for the prevention of and protection against explosions are laid down in the European Directive 1999/92/EC (ATEX II). It addresses employers in order to protect workers and other persons from explosion hazards. The provisions given in this European Directive are detailed in national

regulations. However, operators of plants and equipment also apply the general principles given of Directive 1999/92/EC with regard to third party protection.

With a view to preventing and providing protection against explosions, technical and/or organizational measures need to be taken, in order of priority and in accordance with the following basic principles:

- prevention of the formation of explosive atmospheres, or where the nature of the activity does not allow that,
- avoidance of the ignition of explosive atmospheres, and
- mitigation of the detrimental effects of an explosion to ensure the health and safety of workers.

Safety measures of the gas industry include safe gas infrastructure as well as safe gas utilisation and does focus on the prevention of unsafe situations, as explosions, by preventing the formation of explosive atmosphere and avoidance of the ignition where the formation of hazardous explosive atmospheres cannot be safely excluded. For pipework in buildings, also prevention measures in case of external fire are required. These basic principles are applying equally to natural gas, hydrogen and any admixtures of these. Public and workers safety is the prime consideration.

5.1.2 Safety characteristics of natural gas-hydrogen mixtures and their impact on explosion prevention

5.1.2.1 General

The safety characteristics of natural gas and hydrogen are well known. In a detailed study the safety characteristics of natural gas – hydrogen mixtures were examined in order to determine possible risks relating to occupational safety and health for hydrogen concentrations of up to 10 Vol.-%. The results of the measurements are given in Annex B.

A safety design for hydrogen can fully be used for natural gas application. Gas detecting equipment needs special consideration as detailed in Annex C.

5.1.2.2 Prevention of the formation of explosive atmospheres

Basic requirement for the prevention of the formation of explosive atmospheres is the gas tightness of the gas system. Wherever possible, the gas bearing part of the gas infrastructure is designed and operated to be permanently technically gastight. The gas tightness of the gas system is proven by tightness tests.

On components of the system for natural gas tightness test are carried out with air. If components of the gas system are specified for higher contents of hydrogen the test gases for the tightness tests need to be specified to verify the gas tightness against hydrogen leakage. For existing systems, the gas tightness can be verified with operating gas after the overall gas tightness test with inert gas, e.g. nitrogen.

Gas releases from the gas system can occur e.g. from:

- shaft sealing systems of valves or rotating equipment
- joints (e.g. pipe joints)
- venting of block and bleed systems
- depressurization and opening of equipment for maintenance activities
- emergency shut down with depressurization
- equipment failure