

SLOVENSKI STANDARD SIST EN 45510-3-2:2000

01-junij-2000

Guide for procurement of power station equipment - Part 3-2: Boilers - Shell boilers

Guide for procurement of power station equipment -- Part 3-2: Boilers - Shell boilers

Leitfaden für die Beschaffung von Ausrüstungen für Kraftwerke -- Teil 3-2: Kessel - Großwasserraumkessel

iTeh STANDARD PREVIEW

Guide pour l'acquisition d'équipements destinés aux centrales de production d'électricité -- Partie 3-2: Chaudières - Chaudières à tubes de fumées

SIST EN 45510-3-2:2000

Ta slovenski standard je istoveten z: 6f/sist-ei-45510-3-2:1999

ICS:

27.060.30 Grelniki vode in prenosniki Boilers and heat exchangers

toplote

27.100 Elektrarne na splošno Power stations in general

SIST EN 45510-3-2:2000 en

SIST EN 45510-3-2:2000

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 45510-3-2:2000</u> https://standards.iteh.ai/catalog/standards/sist/00639b2f-e6f3-436c-9f62-6feaec6b3f6f/sist-en-45510-3-2-2000 **EUROPEAN STANDARD**

EN 45510-3-

NORME EUROPÉENNE **EUROPÄISCHE NORM**

October 1999

ICS

English version

Guide for procurement of power station equipment - Part 3-2: Boilers - Shell boilers

Guide pour l'acquisition d'équipements destinés aux centrales de production d'électricité - Partie 3-2: Chaudières - Chaudières à tubes de fumées

Leitfaden für die Beschaffung von Ausrüstungen für Kraftwerke - Teil 3-2: Kessel - Großwasserraumkessel

This European Standard was approved by CEN/CENELEC on 1 October 1999.

CEN/CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN/CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN/CENELEC member into its own language and notified to the Central Secretariat has the same status as

CEN/CENELEC members are the national standards bodies and national electrotechnical committees, respectively, of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom. SIST EN 45510-3-2:2000

> https://standards.iteh.ai/catalog/standards/sist/00639b2f-e6f3-436c-9f62-6feaec6b3f6f/sist-en-45510-3-2-2000





CEN Central Secretariat: rue de Stassart, 36 B-1050 Brussels

CENELEC Central Secretariat: rue de Stassart, 35 B-1050 Brussels

Page 2 EN 45510-3-2:1999

CONTENTS

Forew	ord	4
1	Scope	6
2	Normative references	6
3	Definitions	
3.1	Organisational terms	6
<i>3.2</i>	Technical terms	7
<i>3.3</i>	General terms	8
4	Brief overall project description	8
4.1	Role and organisation of purchaser	8
4.2	Site location	
4.3	Equipment task	9
4.4	Equipment to be purchased	
4.5	Control and instrumentation systems	
4.6	Electrical supplies and other services	
4.7	Other interfaces	
4.8	Project programme	
4.9	Equipment identification systems	
5	Extent of supply iTeh STANDARD PREVIEW	. 10
6	Terminal points (standards.iteh.ai)	. 12
7 7.1	Operational requirements	. 12 . 12
7.2	Manning levels 6feaec6b3f6f/sist-en-45510-3-2-2000	1.3
7.3	Normal operation	13
7.4	Operating hours	
7.5	Start-up and shut-down	
7.6	Abnormal conditions	
7.7	Further operational requirements	
8	Life expectancy	. 16
8.1	Design life	. 16
8.2	Components requiring periodic maintenance	. 16
9	Performance requirements	. 16
9.1	Duty	. 16
9.2	Performance	
9.3	Equipment margins	
9.4	Availability	
9.5	Levels of component redundancy	
9.6	Further performance requirements	
10	Design and fabrication	. 19
10.1	Specific equipment features	. 19
10.2	Design justification	
10.3	Material selection	
10.4	Safety	
10. 4 10.5	Interchangeability	
10.6	Fabrication methods	
11	Maintenance requirements	. 22

11.1	Planned maintenance	
11.2	Personnel safety	
11.3	Requirements for access	
11.4	Lifting requirements	
11.5	Special tools	
11.6	Test equipment	
<i>11.7</i>	Spare parts strategy	
11.8	Special precautions	<i>23</i>
12	Technical documentation requirements	
12.1	Tender documentation	23
12.2	Contract documentation	23
13	Applicable legislation, regulations, standards and further requirements	24
13.1	Legislation and regulations	24
13.2	Standards	24
13.3	Further requirements	
14	Evaluation criteria	24
14.1	General	24
14.2	Technical Criteria	25
<i>15</i>	Quality measures	
<i>15.1</i>	GeneralApprovals procedure	25
<i>15.2</i>	Approvals procedure	25
<i>15.3</i>	Inspection requirements	25
<i>15.4</i>	Inspection requirements	25
16	Site factorsSIST EN 45510-3-2:2000	2 6
16.1	Access wishandarch inchreiden technichte betracht und sich in 1900 1900 1-1900	
<i>16.2</i>	Facilities	26
<i>16.3</i>	Site specific requirements	26
17	Verification of specified performance	26
17.1	General	
17.2	Works tests	
17.3	Test during installation and commissioning	
17.4	Technical conditions for trial run	
17.5	Functional and performance tests	27
Bibliog	rraphy	29

Page 4 EN 45510-3-2:1999

Foreword

This European Standard has been prepared by Technical Committee CEN/CLC FTPFE "Joint Task Force Power Engineering", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2000, and conflicting national standards shall be withdrawn at the latest by April 2000.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

This standard takes the form of a recommendation and is therefore entitled a "Guide".

This Guide for procurement has been prepared under mandates given to CEN and CENELEC by the European Commission and the European Free Trade Association.

This Guide for procurement is a part of a series of Guides mandated to cover the procurement of power station plant and equipment in conformity with European Procurement Directives. The Guides are:

EN 45510 Guide for procurement of power station equipment

	:Tab		DD	DD	
Part 1: Common Clauses	1 1 en		KU	rn	

- Part 2-1: Electrical equipment Power transformers and siteh.ai)
- Part 2-2: Electrical equipment Uninterruptable power supplies
- Part 2-3: Electrical equipment Stationary batteries and chargers under chargers (https://standards.tich.avcatalog/standards/sist/00639b2f-e6f3-436c-9f62-
- Part 2-4: Electrical equipment High power static converters 45510-3-2-2000
- Part 2-5: Electrical equipment Motors
- Part 2-6: Electrical equipment Generators
- Part 2-7: Electrical equipment Switchgears and controlgear
- Part 2-8: Electrical equipment Power cables
- Part 2-9: Electrical equipment Cabling systems
- Part 3-1: Boilers Water tube boilers
- Part 3-2: Boilers Shell boilers
- Part 3-3: Boilers Boilers with fluidized bed firing
- Part 4-1: Boiler auxiliaries Equipment for reduction of dust emissions
- Part 4-2: Boiler auxiliaries Gas-air, steam-air and gas-gas heaters
- Part 4-3: Boiler auxiliaries Draught plant
- Part 4-4: Boiler auxiliaries Fuel preparation equipment
- Part 4-5: Boiler auxiliaries Coal handling and bulk storage plant
- Part 4-6: Boiler auxiliaries Flue gas desulphurisation (De-SO,) plant
- Part 4-7: Boiler auxiliaries Ash handling plant
- Part 4-8: Boiler auxiliaries Dust handling plant
- Part 4-9: Boiler auxiliaries Sootblowers
- Part 4-10: Boiler auxiliaries Flue gas denitrification (De-NO) plant

- Part 5-1: Turbines Steam turbines
- Part 5-2: Turbines Gas turbines
- Part 5-3: Turbines Wind turbines
- Part 5-4: Turbines Hydraulic turbines, storage pumps and pump-turbines
- Part 6-1: Turbine auxiliaries Deaerators
- Part 6-2: Turbine auxiliaries Feedwater heaters
- Part 6-3: Turbine auxiliaries Condenser plant
- Part 6-4: Turbine auxiliaries Pumps
- Part 6-5: Turbine auxiliaries Dry cooling systems
- Part 6-6: Turbine auxiliaries Wet and wet/dry cooling towers
- Part 6-7: Turbine auxiliaries Moisture separator reheaters
- Part 6-8: Turbine auxiliaries Cranes
- Part 6-9: Turbine auxiliaries Cooling water systems
- Part 7-1: Pipework and valves High pressure piping systems
- Part 7-2: Pipework and valves Boiler and high pressure piping valves
- Part 8-1: Control and instrumentation NDARD PREVIEW

(standards.iteh.ai)

EN 45510 Part 1 contains those clauses common to all the above Guides giving the provisions of a non equipment specific nature for use in the procurement of power station plants. EN 45510 is the responsibility of JTFPE. The so called common clauses as appropriate, also appear in italics in the documents specific to particular equipment.

66eaec6b3f6f/sist-en-45510-3-2-2000

Where minor changes have been made to sentences in the "common clauses" these are marked by a vertical line in the left margin.

In this Guide, words in bold type indicate that they have the meaning given in the definitions, clause 3.

In this Guide, words and sentences not in italics are specific to this Guide and refer to the particular **equipment** covered.

Page 6 EN 45510-3-2:1999

1 Scope

This standard gives guidance on writing the technical **specification** for the procurement of fired and unfired **shell boilers** for use in electricity generating stations (power stations). This Guide for Procurement is not applicable to **equipment** for use in the nuclear reactor plant area of nuclear power stations. Other possible applications of such **equipment** have not been considered in the preparation of this Guide.

This Guide covers shell boilers:

- using solid, liquid or gaseous or derived fuels, waste heat utilisation
- with firing equipment for solid fuels, gas or oil firing
- providing saturated steam, superheated steam or hot water.

The **equipment** covered by this Guide is defined by its function rather than design type. Therefore, the guidance to the **specification** is stated in **performance** terms rather than being specified by a detailed description of the **equipment** to be supplied.

This Guide indicates to potential purchasers how their specification should be prepared so that :

- the equipment type and capacity interfaces correctly with other elements of the systems
- predicted performance is achieved
- ancillary equipment is properly sized
- reliability, availability and safety requirements are achieved
- proper consideration is given to the evaluation process and the quality measures to be applied.

This Guide does not determine the type of **specification** (e.g. detailed, performance, functional) or the extent of supply for any given contract which is normally decided on the basis of the **purchaser**'s project strategy. It does not cover:

- any commercial, contractual or legal issues which are normally in separate parts of the enquiry
- any allocation of responsibilities which are determined by the contract.

This Guide does not prescribe the arrangement of the documents in the enquiry.

NOTE: As a comprehensive European environmental policy is still under preparation, this Guide does not address the environmental implications of the **equipment**.

2 Normative references

This Guide for Procurement incorporates by dated or undated reference, provisions from other publications.

These normative references are cited in the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this Guide only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

EN ISO 9001 Quality systems - Model for quality assurance in design, development, production, installation and continuous (ISO 0001:1004)

installation and servicing (ISO 9001:1994)

EN ISO 9002 Quality systems - Model for quality assurance in production, installation and servicing

(ISO 9001:1994)

IEC 60050-191 International electrotechnical vocabulary - Chapter 191: Dependability and quality of service

3 Definitions

For the purposes of this Guide, the following definitions apply.

3.1 Organisational terms

3.1.1 purchaser : Recipient of a product and/or a service provided by a supplier.

- supplier: Person or organisation that provides a product and/or a service to the purchaser. 3.1.2
- specification: Document stating technical requirements of the purchaser. It may form part of an 3.1.3 enquiry issued by a purchaser.
- enquiry: Invitation to tender issued by a purchaser. It will normally include a specification together 3.1.4 with the necessary contractual and commercial conditions.
- 3.1.5 tender: Offer made by a tenderer in response to an enquiry.
- tenderer: Person or organisation submitting a tender for the equipment in response to the enquiry. 3.1.6
- site: Place to which the equipment is to be delivered or where work is to be done by the supplier, 3.1.7 together with so much of the area surrounding as the supplier may, with the consent of the purchaser, use for the purposes of the contract.
 - NOTE: Further definitions of useful organisational terms may be found in EN ISO 8402 (see Bibliography).

3.2 Technical terms

- shell boiler: A closed vessel containing water in which flames and hot gases pass through the inside 3.2.1 of tubes located within the shell to generate steam or hot water. Together with all connected components and systems, it forms a functional unit.
- terminal conditions: Conditions imposed on the plant at the terminal points of the shell boiler. These 3.2.2 may typically comprise:
 - feedwater conditions TANDARD PREVIEW
 - spray water conditions standards.iteh.ai)
 - steam conditions
 - combustion air conditions SIST EN 45510-3-2:2000
 - - 6feaec6b3f6f/sist-en-45510-3-2-2000
 - fuel conditions
- specified or rated terminal conditions: Steam/water conditions at the terminal points of the shell 3.2.3 boiler to be achieved at MCR and other specified operating points.
- design conditions: Values of conditions used in design calculations such as the design pressure 3.2.4 and temperature for a pressure vessel.
- Conditions which define the thermodynamic and chemical state of steam. steam conditions: 3.2.5 normally pressure and temperature or dryness fraction.
- main steam conditions: Steam conditions measured at inlet to shell boiler stop valve or at an agreed point.
- feedwater conditions: Feedwater conditions measured after feedwater non return valve or at an 3.2.7 agreed point.
- steam tables: Tables or algebraic formulations of the values of the thermodynamic properties of 3.2.8 steam and water
- maximum continuous rating (MCR): Output at which the shell boiler may be operated for an 3.2.9 unlimited time not exceeding the design life at the specified terminal conditions.
- maximum capability: The maximum output that shell boiler can produce with specified operation conditions e. g. with increased steam pressure.
- shell boiler efficiency: Ratio of useful heat output (e. g. in steam or hot water) to net heat input. 3.2.11
- base load operation: Operation of the shell boiler at maximum continuous rating (MCR) or a high fraction of this throughout a given period.
- two shift operation: Operation of the shell boiler at MCR or a high fraction of this for about 16 3.2.13 hours continuously out of 24 hours, the shell boiler being shut down for the remaining time.

Page 8 EN 45510-3-2:1999

- **3.2.14** one shift operation: Operation of the shell boiler at MCR or a high fraction of this for about 8 hours continuously out of 24 hours, the shell boiler being shut down for the remaining time.
- **3.2.15 load cycling**: Transient operation of the **shell boiler** alternating between high and low levels of load, depending on a specified load programme.
- **3.2.16 peak load operation :** Operation of the **shell boiler** above **MCR** for short periods, typically 1 to 3 hours, at times of peak demand from a steam/hot water system.
- **3.2.17 constant pressure operation :** Operation in which **shell boiler** outlet steam/hot water pressure is maintained constant over the load range.
- **3.2.18 automatic operation :** Operation under the influence of automatic systems. This also may include start-up and shut-down operation and operation without direct observation by the operator.
- 3.2.19 running hours: The number of hours during which the shell boiler has been in operation (fired).
- 3.3 General terms
- **3.3.1 equipment**: Plant, component, system and/or associated auxiliaries and/or services to be provided in response to the **enquiry**.
- 3.3.2 conformity: Fulfilment of specified requirements.
- 3.3.3 performance : Obligations verified by specified tests.
- 3.3.4 operating period: Time between planned outages or maintenance periods during which the equipment is in operation and/or does not restrict operational requirements of the power station.
- 3.3.5 life expectancy: Continuous time period over which the equipment might be expected to operate with planned maintenance but without replacement of a significant component, for example, superheater surface is a significant component.
- 3.3.6 design life: Operating hours of the equipment on which design calculations are based.
- 3.3.7 acceptability: Compliance with criteria defined by the purchaser for assessing the suitability of equipment.

 https://standards.iteh.ai/catalog/standards/sist/00639b2f-e6f3-436c-9f62-
- 3.3.8 equipment margins: Allowance for design, fabrication or operating contingency defined in the specification. These are separate to those normally included by the supplier for his own purposes.
- 3.3.9 proven equipment: Equipment which may be demonstrated to be similar to that offered and has operated for a sufficient time to have demonstrated performance and availability.
- 3.3.10 availability: As defined in IEC 60050-191
- 3.3.11 reliability: As defined in IEC 60050-191
- 3.3.12 maintainability: As defined in IEC 60050-191

4 Brief overall project description

4.1 Role and organisation of purchaser

The **enquiry** should define the **purchaser**'s role in the project, including whether the **purchaser** will assume responsibility for the planning and technical coordination of the project, or whether other organisations will be appointed to carry out all or part of this function. The **enquiry** should define all organisational **interfaces** and the procedures to be employed for managing the contract and the **site**.

4.2 Site location

The **specification** should describe the geographical location of the **site** which may include surveying points, the previous use of the **site** and any local features such as impact of industrial or military activities and planning restrictions.

Where applicable, the **specification** should indicate **site** datum on **specification** drawings and specify **site** and drawing orientation and define co-ordinate axes (x, y, z) and numbering order to ensure consistency between **suppliers** of connected **equipment**.

Page 9 EN 45510-3-2:1999

Where appropriate, the **specification** should define the permitted ground loading, dimensional and time restrictions on access routes up to but not including public roads or railways.

The **specification** should identify, where appropriate, the environment of the **site** in which the **equipment** will operate. The following factors may normally be included if appropriate:

- climatic : e.g. atmospheric pressure, annual variation of air and cooling water temperature, relative humidity, rain fall, icing, snow, wind velocity (normal and maximum) lightning
- geological: e.g. seismic conditions and characteristics of subsoil (e.g. caverns, gliding stratifications, load bearing capability of subsoils)
- geographic : e.g. elevation, influence of local topography and structures
- hydrological : e.g. flooding and tides.

4.3 Equipment task

The **specification** should describe in general terms the function, task or role of the **equipment** to be purchased. e.g. whether it is part of a new power generation plant, a modification to an existing power generation plant, or replacement equipment.

Where appropriate, the **specification** should define the function and any known limitations, if any, in the **equipment** connected to that which is being supplied so that the **equipment** may avoid imposing adverse conditions or the **supplier** may suggest modifications to connected equipment which would ensure satisfactory operation.

4.4 Equipment to be purchased DARD PREVIEW

The **specification** may define the **equipment** type or arrangement to be purchased. (Standards.iteh.ai)

For example:

- type of firing system for solid fuel pulverised fuel stoker etc.
- type of ash discharge system of feaec6b3f6f/sist-en-45510-3-2-2000
- single or multiple main auxiliaries
- arrangement of steam/hot water outlets

The **specification** should define whether a complete **shell boiler** is to be supplied comprising, for example all the **equipment** from fuel supply point to discharge of flue gas to the chimney, from feed water supply to high pressure steam outlet or whether some equipment is to be purchased under separate contracts, for example, equipment for control of dust emissions, etc.

Before deciding to purchase equipment and services under contracts separate from the **shell boiler** contract, the **purchaser** should be satisfied that the performance of the equipment not provided within the **shell boiler** contract can be unambiguously demonstrated and that the **supplier** can provide all the data necessary for the design of the separately purchased equipment and services. Where there is likely to be significant interaction between equipment, for example between burners and furnace, it may be preferable to purchase the equipment within the **shell boiler** contract.

The **specification** may also define preferences for **equipment** types (or give information) regarding compatibility with existing equipment, if required.

The **specification** should define the intended methods or local practice for maintenance, inspection and operation.

The **specification** should define requirements with regard to the general appearance of the **equipment** (e.g. dimensions, shape or colour) to meet local planning requirements or specific criteria, where such requirements exist.

NOTE: Attention is drawn to European, national and/or local legislation which may place restrictions in this area.

Page 10 EN 45510-3-2:1999

4.5 Control and instrumentation systems

The **specification** should define the general requirements for the control and instrumentation system, the level of operator intervention allowed or required, integration with other control systems, localised control loops, commonality and redundancy.

NOTE: Guidance on the procurement of control and instrumentation systems for power stations, including advice on interfaces can be found in EN 45510 Part 8-1.

4.6 Electrical supplies and other services

The **specification** should define the electrical supplies available for the operation of the **equipment**, their voltages and frequencies, with their range of variation, phases available and, where appropriate, the acceptable values of maximum load (kW) and short circuit level at each voltage level and the harmonic content. Requirements for terminals and terminal boxes should be stated; these should be to a recognised European or international standard.

The **specification** should define the type and capacity of other services for the operation of the **equipment** such as compressed air, cooling air, cooling water, auxiliary steam, etc., available to the **supplier** (normally not available during the installation period).

4.7 Other interfaces

The **specification** should define the interfaces with existing ancillary or new ancillary equipment to be supplied under separate contracts which interact directly with the **equipment**, for example, civil works, boiler house steelwork and equipment or services provided under separate contracts.

The **specification** should state, if applicable, whether the **supplier** is to provide data or information to enable the **purchaser** to purchase equipment or services under separate contracts.

(Standards.iten.al)

4.8 Project programme

The **specification** should describe the overall programme and timescale in which the project is to be carried out. This may include the principal dates associated with tendering, placement of orders, access to **site**, start and completion of installation, commissioning, take-over and final acceptance.

4.9 Equipment identification systems

The **specification** may specify the equipment identification system for use during the operating life of the plant. If applicable to the project, a recognised European or international system should be used.

The **specification** may also define the extent to which the identification system will be applied on labels, in documentation, on operator displays and within computer software and data bases.

5 Extent of supply

The specification should define the extent of supply of all the equipment.

This may include:

Main equipment

- pressure parts; shell, heating surface, headers, interconnecting pipework, valves and fittings, safety valves including silencers
- firing equipment; mills, crushers and coal feeders, stokers, oil pumps and heaters, fuel pipework, burners
- ash discharge system
- combustion air system; fans, ducts, dampers
- flue gas system; fans, ducts, dampers, silencers, chimney
- equipment for reduction of dust emissions
- sootblowers
- feedwater pumps