

ISO/TC 94/SC 6

Secretariat: BSI

Voting begins on:  
2019-12-03

Voting terminates on:  
2020-01-28

---

---

## Eye and face protection for sports use —

### Part 1: Requirements for downhill skiing and snowboarding goggles

*Protection des yeux et du visage à usage sportif —*

*Partie 1: Exigences relatives aux lunettes de ski alpin et de surf des  
neiges*

*ITeH STANDARD PREVIEW  
(standards.iteh.ai)  
Full standard:  
https://standards.iteh.ai/catalog/standards/sist/991207-4403-91c6-0b52b7d2f93c/iso-fdis-18527-1*

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

**ISO/CEN PARALLEL PROCESSING**



Reference number  
ISO/FDIS 18527-1:2019(E)

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/4fd91abe-4f57-4d03-91c6-0b52b7d2f93c/iso-fdis-18527-1>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>v</b>
<b>Introduction</b> .....	<b>vi</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 General requirements for goggles</b> .....	<b>2</b>
4.1 Physiological compatibility.....	2
4.2 Construction and adjustment.....	2
4.3 Cleaning and/or disinfection.....	3
4.4 Lens material and surface quality.....	3
4.5 Headform(s).....	3
4.6 Retention by headband and harnesses (sit and fit).....	3
4.7 Mandatory and optional requirements.....	3
<b>5 Transmittance of the lenses</b> .....	<b>3</b>
5.1 General.....	3
5.2 Transmittance categories.....	3
5.3 Solar ultraviolet transmittance.....	4
5.4 General transmittance requirements.....	4
5.4.1 Uniformity of luminous transmittance and transmittance matching.....	4
5.4.2 Ultraviolet transmittance of the frame or housing.....	5
5.5 Special transmittance requirements.....	5
5.5.1 Photochromic lenses.....	5
5.5.2 Polarizing lenses.....	5
5.5.3 Gradient-tinted lenses.....	6
5.6 Claimed transmittance and reflectance properties (Optional requirements).....	6
5.6.1 General.....	6
5.6.2 Solar blue-light absorption/transmittance.....	6
5.6.3 Solar UV absorption/transmittance.....	6
5.6.4 Anti-reflective coated lenses.....	7
5.6.5 Reduced reflection coated lenses.....	7
5.6.6 Enhanced infrared absorption.....	7
<b>6 Scattered light</b> .....	<b>7</b>
<b>7 Refractive power</b> .....	<b>7</b>
7.1 General.....	7
7.2 Spherical and cylindrical power.....	8
7.3 Spatial deviation.....	8
7.4 Prism imbalance.....	8
7.5 Goggles with inserts to carry prescription lenses.....	8
<b>8 Mechanical testing</b> .....	<b>8</b>
8.1 Temperature range.....	8
8.2 Mechanical strength level 2.....	8
8.2.1 Complete goggles.....	8
8.2.2 Goggles with inserts to carry prescription lenses.....	9
8.2.3 Failure criteria after impact.....	9
<b>9 Resistance to solar ultraviolet radiation</b> .....	<b>9</b>
<b>10 Resistance to ignition</b> .....	<b>10</b>
<b>11 Protection against water and snow</b> .....	<b>10</b>
<b>12 Field of view</b> .....	<b>10</b>
<b>13 Minimum area to be protected</b> .....	<b>10</b>

# ISO/FDIS 18527-1:2019(E)

13.1	Assessment of frontal protection	10
13.2	Assessment of lateral protection	11
<b>14</b>	<b>Optional requirements</b>	<b>12</b>
14.1	Extended low temperature range	12
14.2	Resistance to fogging	12
14.3	Resistance to abrasion	12
<b>15</b>	<b>Marking and information to be supplied by the manufacturer</b>	<b>12</b>
15.1	Assessment	12
15.2	Mandatory markings on goggles	13
15.3	Information to be supplied with goggles by the manufacturer	13
15.4	Additional information to be available from the manufacturer	15
<b>16</b>	<b>Selection of test samples</b>	<b>15</b>
16.1	General	15
16.2	Preparation and conditioning of test samples	16
<b>Annex A (informative) Selection and use of downhill skiing and snowboarding goggles</b>		<b>18</b>
<b>Annex ZA (informative) Relationship between this European Standard and the essential requirements of Regulation 2016/425 aimed to be covered</b>		<b>21</b>
<b>Bibliography</b>		<b>23</b>

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/4fd91abe-4f57-4d03-91c6-0b52b7d2f93c/iso-fdis-18527-1>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 94, *Personal safety — Personal protective equipment*, Subcommittee SC 6, *Eye and face protection*.

A list of all parts in the ISO 18527 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

This family of documents comprised of the ISO 16321 series, the ISO 18526 series and the ISO 18527 series was developed in response to the worldwide stakeholders' demand for minimum requirements and test methods for eye and face protectors traded internationally. ISO 4007 gives the terms and definitions for all the various product types. The test methods are given in the ISO 18526 series, while the requirements for occupational eye and face protectors are given in the ISO 16321 series. Eye protectors for specific sports are mostly dealt with by the ISO 18527 series. A guidance document, ISO 19734, for the selection, use and maintenance of eye and face protectors is under preparation.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/4fd91abe-4f57-4d03-91c6-0b52b7d2f93c/iso-fdis-18527-1>

# Eye and face protection for sports use —

## Part 1: Requirements for downhill skiing and snowboarding goggles

### 1 Scope

This document applies to all goggles with plano lenses, intended for eye protection against hazards including ultraviolet and visible solar radiation, rain, snow and wind, during downhill skiing, snowboarding and other similar activities.

This document applies to downhill skiing and snowboarding goggles fitted with an insert to carry prescription lenses.

It specifies requirements and testing for materials, performance, marking of goggles and information to be supplied by the manufacturer.

Information on the selection and use of downhill skiing and snowboarding goggles is given in [Annex A](#).

This document does not apply to

- a) eye protectors for protection when operating or travelling on a motorized vehicle,
- b) eye protectors for protection against optical radiation from artificial sources, such as those used in solaria,
- c) eye protectors for direct observation of the sun, and
- d) eye protectors intended for sports with unrelated hazards and risks.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4007, *Personal protective equipment — Eye and face protection — Vocabulary*

ISO 8980-5, *Ophthalmic optics — Uncut finished spectacle lenses — Part 5: Minimum requirements for spectacle lens surfaces claimed to be abrasion-resistant*

ISO 11664-2, *Colorimetry — Part 2: CIE standard illuminants*

ISO 18526-1:—<sup>1)</sup>, *Eye and face protection — Test methods — Part 1: Geometrical optical properties*

ISO 18526-2:—<sup>2)</sup>, *Eye and face protection — Test methods — Part 2: Physical optical properties*

ISO 18526-3:—<sup>3)</sup>, *Eye and face protection — Test methods — Part 3: Physical and mechanical properties*

---

1) Under preparation (Stage at the time of publication ISO/FDIS 18526-1:2019).

2) Under preparation (Stage at the time of publication ISO/FDIS 18526-2:2019).

3) Under preparation (Stage at the time of publication ISO/FDIS 18526-3:2019).

ISO 18526-4, *Eye and face protection — Test methods — Part 4: Headforms*<sup>4)</sup>

ISO 21987, *Ophthalmic optics — Mounted spectacle lenses*

### **3 Terms and definitions**

For the purposes of this document, the terms and the definitions given in ISO 4007 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

### **4 General requirements for goggles**

#### **4.1 Physiological compatibility**

Goggles shall be designed and manufactured in such a way that, when used under the conditions and for the purposes intended, they will not compromise the health or safety of the wearer. The risks posed by substances leaking or evaporating from the goggles that can come into prolonged contact with the wearer shall be reduced by the manufacturer to within the limits of any applicable regulatory requirement.

Special attention shall be given to substances that are allergenic, carcinogenic, mutagenic or toxic to reproduction.

NOTE 1 Excessive pressure due to a poor fit on the head, chemical irritation or allergy are known to produce reactions. Rare or idiosyncratic reactions to any material are known to occur and the individual wearer is well advised to avoid those types of frame materials.

Substances recommended for cleaning, maintenance or disinfection shall be known to be unlikely to have any adverse effect upon the wearer, when applied in accordance with the instructions given in the information to be supplied by the manufacturer.

Manufacturers/suppliers shall perform an appropriate risk analysis on potentially harmful substances contained in the goggles such that, when the goggles are used under the conditions and for the purposes intended, the health (and safety) of the wearer shall not be compromised.

The following are examples of documents that represent the appropriate information:

- a) specification of the material(s);
- b) safety data sheets relating to the materials;
- c) information relating to the suitability of the materials for use with food, in medical devices, or other relevant applications;
- d) information relating to toxicological, allergenic, carcinogenic, toxic to reproduction, or mutagenic investigations on the materials.

NOTE 2 Specific national regulations with regard to the restriction of certain chemical substances need to be observed, for example release of nickel.

#### **4.2 Construction and adjustment**

Areas of the goggles that may, during intended use, come into contact with the wearer shall be free from projections, sharp edges or other features likely to cause discomfort or injury to the wearer.

---

4) Under preparation (Stage at the time of publication ISO/FDIS 18526-4:2019).



Any part of the goggles that can be adjusted or removed by the wearer for the purpose of replacement (in accordance with the instructions given in the information to be supplied by the manufacturer) shall facilitate adjustment, removal and attachment without the use of tools.

Any adjustment system incorporated in the goggles shall maintain the intended fit for the foreseeable conditions of use.

The test shall be carried out by physical inspection according to ISO 18526-3:—, 6.1.

### 4.3 Cleaning and/or disinfection

The goggles shall be cleaned only once according to the cleaning and/or disinfection procedures in the information to be supplied by the manufacturer before being subjected to testing.

### 4.4 Lens material and surface quality

In a circular area 30 mm diameter centred on the reference point(s) but excluding a marginal area 5 mm wide around the edge of the lens if this overlaps with the circular area, lenses shall be free from defects likely to impair vision in use (such as bubbles, scratches, inclusions, dull spots, pitting, mould marks, scouring, grains, pocking, scaling and undulation) when examined according to ISO 18526-3:—, 6.6.

### 4.5 Headform(s)

Unless the manufacturer specifies the headform(s) according to ISO 18526-4 that is/are compatible with the goggles, the test methods where (a) headform(s) is/are required shall use the headform 1-M according to ISO 18526-4 as the default.

### 4.6 Retention by headband and harnesses (sit and fit)

Goggles shall sit in the intended position during normal use and shall adapt to the contours of the face. The headband shall be designed to be flexible or adjustable and sit securely on the back of the head or a helmet. The headband assembly shall not cause any discomfort nor exhibit any insecurity when tested in accordance with ISO 18526-3:—, 6.5.

### 4.7 Mandatory and optional requirements

In this document both optional and mandatory requirements are described. Depending on the intended use and/or the manufacturer's claimed specification, some requirements marked as optional become mandatory.

## 5 Transmittance of the lenses

### 5.1 General

Transmittance values shall be determined in accordance with ISO 18526-2:—, Clauses 6 to 11, as appropriate. Luminous transmittance shall be calculated using CIE standard illuminant D65 in accordance with ISO 11664-2 (see also ISO 4007:2018, 3.10.1.32).

### 5.2 Transmittance categories

Depending upon the mean luminous transmittance,  $\tau_{vD65}$ , at their reference points lenses for downhill skiing and snowboarding use shall be attributed to one of the five tint categories in Table 1.

The ranges of the luminous transmittance  $\tau_{vD65}$  of these five categories is given by the values in Table 1. There are only three descriptive groups for use by consumers as shown in Table 7. An overlap of the transmittance values shall be not more than  $\pm 2\%$  (absolute) between the categories 0, 1, 2 and 3. There is no overlap in transmittance values between categories 3 and 4.

If the manufacturer and/or supplier declares a luminous transmittance value, the maximum deviation for this value shall be  $\pm 3\%$  absolute for transmittance values falling in categories 0 to 3 and  $\pm 30\%$  relative to the stated value for transmittance values falling in tint category 4.

When describing the transmittance properties of a lens with changeable tint, e.g. photochromic, two categories for the luminous transmittance values are generally used. These two values correspond to the highest and lowest transmittance states of the lens. Lenses or filters with temperature sensitive transmittance shall also be tested  $(+5 \pm 2)^\circ\text{C}$ . If the performance at  $(+5 \pm 2)^\circ\text{C}$  results in a category change, then this category shall also attributed.

In the case of a gradient-tinted lens, the mean luminous transmittance  $\tau_{vD65}$  at the reference points shall be used to characterize the luminous transmittance and the tint category.

For a gradient-tinted lens, the overlap in luminous transmittance allowed between categories shall be double that for uniformly tinted lenses.

### 5.3 Solar ultraviolet transmittance

When tested within a 10 mm radius circle centred on the reference point according to ISO 18526-2:—, Clause 8, the solar UV-A,  $\tau_{\text{SUVA}}$ , solar UV-B,  $\tau_{\text{SUVB}}$ , and mean spectral (380 to 400) nm,  $\tau_{m380-400}$  transmittances shall conform with the requirements in Table 1, based on the mean luminous transmittance  $\tau_{vD65}$  at the reference points of the lens(es).

**Table 1 — Transmittance requirements for downhill skiing and snowboarding lenses**

Tint category	Wavelength range from 280 nm to 400 nm			Visible spectral range	Optional infrared spectral range
	Maximum solar UV-B transmittance $\tau_{\text{SUVB}}$ $280 \text{ nm} \leq \lambda \leq 315 \text{ nm}$	Maximum solar UV-A transmittance $\tau_{\text{SUVA } 380}$ $315 \text{ nm} \leq \lambda \leq 380 \text{ nm}$	Maximum mean 380 nm to 400 nm spectral transmittance $\tau_{m380-400}$ $380 \text{ nm} \leq \lambda \leq 400 \text{ nm}$	Luminous transmittance $\tau_{vD65}$ $380 \text{ nm} \leq \lambda \leq 780 \text{ nm}$	Maximum solar IR transmittance $\tau_{\text{SIR}}$ $780 \text{ nm} \leq \lambda \leq 2\,000 \text{ nm}$
S0	0,03 $\tau_{vD65}$	0,30 $\tau_{vD65}$	0,75 $\tau_{vD65}$	$\tau_{vD65} > 80\%$	$\tau_{vD65}$
S1				$43\% < \tau_{vD65} \leq 80\%$	$\tau_{vD65}$
S2			0,5 $\tau_{vD65}$	$18\% < \tau_{vD65} \leq 43\%$	$\tau_{vD65}$
S3		$8\% < \tau_{vD65} \leq 18\%$		$\tau_{vD65}$	
S4		0,15 $\tau_{vD65}$	0,5 % absolute or 0,15 $\tau_{vD65}$ whichever is greater	$3\% < \tau_{vD65} \leq 8\%$	$\tau_{vD65}$

NOTE Some national requirements can stipulate a different requirement for the long wavelength limit of UV-A.

### 5.4 General transmittance requirements

#### 5.4.1 Uniformity of luminous transmittance and transmittance matching

##### 5.4.1.1 Uniformly tinted lenses

Lenses that are intended to be uniformly tinted shall appear to be visually uniform within circles 30 mm diameter centred on the reference points or to the edge of the lens less the marginal zone 5 mm wide (whichever is greater), and appear to have the same transmittance at the two reference points when inspected against a white background in accordance with ISO 18526-3:—, 6.6. Where there is visible non-uniformity, then, when tested according to ISO 18526-2:—, 7.4, the relative difference in

the luminous transmittance value between any two points of the lens shall not be greater than 15 % (relative to the higher value), except for tint category S4 where it shall not be greater than 20 %.

Where there are visibly mismatched transmittances at the reference points, when measured in accordance with ISO 18526-2:—, 7.5, the difference in luminous transmittance values at the reference points for the right and left eyes shall not exceed 15 % (relative to the higher transmittance).

#### 5.4.1.2 Linear gradient-tinted lenses

In the case of mounted linear gradient-tinted lenses, when inspected against a white background in accordance with ISO 18526-3:—, 6.6, the luminous transmittances shall appear constant in the horizontal direction and having equal transmittance at the reference points. Where there is visible rotation of the gradient or visibly mismatched transmittances at the reference points, when measured in accordance with ISO 18526-2:—, 7.5, the difference in the luminous transmittances between at the reference points and between pairs of points on the lens at 15 mm to the left, to the right, above and below the reference points shall not exceed 15 % (relative to the higher value in each direction).

#### 5.4.1.3 Radial gradient-tinted lenses

When measured in accordance with ISO 18526-2:—, 7.5, the difference in the luminous transmittances at the reference points and between pairs of points on the lens 15 mm to the left, to the right, above and below the reference points shall not exceed 15 % (relative to the higher value).

#### 5.4.1.4 Variations due to thickness variations

Changes of luminous transmittance that are caused by thickness variations due to the design of the lens are permitted. For verification, the test method in ISO 18526-2:—, 7.4.1.4 shall be used.

#### 5.4.2 Ultraviolet transmittance of the frame or housing

When tested in accordance with ISO 18526-2:—, Clause 6, non-lens areas of goggles shall provide at least the same level of protection against ultraviolet radiation, for the area to be protected according [Clause 12](#), as given by a lens of any tint category declared usable with the goggles by the manufacturer or supplier.

### 5.5 Special transmittance requirements

#### 5.5.1 Photochromic lenses

The tint categories of photochromic lenses shall be determined by the luminous transmittance in the faded state,  $\tau_{v0}$ , and the luminous transmittance in the darkened state,  $\tau_{v1}$ , achieved after 15 min irradiation measured according to ISO 18526-2:—, Clause 16, at a temperature of  $(5 \pm 2)$  °C. In both states, the requirements specified in [5.2](#) and [5.3](#) shall be met. The photochromic response  $PR = \tau_{v0}/\tau_{v1}$  shall be  $\geq 1,25$ .

#### 5.5.2 Polarizing lenses

##### 5.5.2.1 Plane of transmission

If the lenses in the goggles are claimed to be polarizing, the lenses shall be fitted in the frame so that their planes of transmission, when tested according to ISO 18526-2:—, 15.1, shall not deviate from the vertical by more than  $\pm 5^\circ$ . When the goggles are fitted with two separate lenses, any misalignment between the planes of transmission of the left and right lenses shall not be greater than  $6^\circ$ .