### FINAL DRAFT

## INTERNATIONAL STANDARD

ISO/FDIS 18527-2.2

ISO/TC 94/SC 6

Secretariat: BSI

Voting begins on: **2020-08-18** 

Voting terminates on: **2020-10-13** 

Eye and face protection for sports use —

Part 2:

Requirements for eye protectors for squash and eye protectors for racquetball and squash 57

Protection des yeux et du visage à usage sportif —

Partie 2: Exigences relatives aux protecteurs de l'oeil pour le squash et aux protecteurs de l'oeil pour le racquetball et le squash 57

https://standards.iteh.ai/catalog/standards/sist/74cfbf61-872b-4b6d-bb5b-d74599902246/iso-fdis-18527-2-2

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

## ISO/CEN PARALLEL PROCESSING



Reference number ISO/FDIS 18527-2.2:2020(E)

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 18527-2.2 https://standards.iteh.ai/catalog/standards/sist/74cfbf61-872b-4b6d-bb5b-d74599902246/iso-fdis-18527-2-2



#### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

| Coı   | <b>Contents</b>                         |   |        |  |  |  |  |
|-------|---|---|--------|--|--|--|--|
|       |   |   |        |  |  |  |  |
| Intro | oductio                                 | n   | vii    |  |  |  |  |
| 1     | Scop                                    | e   | 1      |  |  |  |  |
| 2     | Norn                                    | native references   | 1      |  |  |  |  |
| 3     | Tern                                    | Terms and definitions   |        |  |  |  |  |
| 4     | General requirements for eye protectors |   |        |  |  |  |  |
|       | 4.1                                     | J O   |        |  |  |  |  |
|       | 4.2                                     | Construction and adjustment   |        |  |  |  |  |
|       | 4.3                                     | Cleaning and/or disinfection  |        |  |  |  |  |
|       | 4.4                                     | Lens material and surface quality   |        |  |  |  |  |
|       | 4.5<br>4.6                              | Headform(s)Retention by headband and harnesses (sit and fit)                          |        |  |  |  |  |
|       | 4.7                                     | Mandatory and optional requirements   | 3      |  |  |  |  |
| _     |   | smittance of the lenses   |        |  |  |  |  |
| 5     | 5.1                                     | General   |        |  |  |  |  |
|       | 5.2                                     | Transmittance categories  |        |  |  |  |  |
|       | 5.3                                     | Solar ultraviolet transmittance   |        |  |  |  |  |
|       | 5.4                                     | General transmittance requirements  |        |  |  |  |  |
|       |   | 5.4.1 Uniformity of luminous transmittance and transmittance matching                 | 4      |  |  |  |  |
|       |   | 5.4.2 Variations due to thickness variations  |        |  |  |  |  |
|       | 5.5                                     | Special transmittance requirements it chair air                                       | 5      |  |  |  |  |
|       |   | 5.5.1 Photochromic lenses   | 5      |  |  |  |  |
|       |   | 5.5.2 Polarizing lenses 5.5.3 Gradient-tinted lenses 18527-2.2                        | 5<br>5 |  |  |  |  |
|       | 5.6                                     | Claimed transmittance and reflectance properties (on floor appearing and reflectance) | 5<br>5 |  |  |  |  |
|       | 5.0                                     | Claimed transmittance and reflectance properties (optional requirements)              | 5      |  |  |  |  |
|       |   | 5.6.2 Solar blue-light absorption/transmittance                                       | 5      |  |  |  |  |
|       |   | 5.6.3 Solar UV absorption/transmittance   | 6      |  |  |  |  |
|       |   | 5.6.4 Anti-reflective coated lenses   |        |  |  |  |  |
|       |   | 5.6.5 Reduced reflection coated lenses  | 6      |  |  |  |  |
| 6     | Scatt                                   | ered light  | 6      |  |  |  |  |
| 7     | Refra                                   | active power  | 7      |  |  |  |  |
|       | 7.1                                     | Non-prescription eye protectors   |        |  |  |  |  |
|       |   | 7.1.1 Spherical and cylindrical power   |        |  |  |  |  |
|       |   | 7.1.2 Spatial deviation   |        |  |  |  |  |
|       | 7.2                                     | 7.1.3 Prism imbalance   |        |  |  |  |  |
| •     |   |   |        |  |  |  |  |
| 8     | Mechanical strength                     |   |        |  |  |  |  |
|       | 8.1<br>8.2                              | Mechanical strength of squash eye protectors  |        |  |  |  |  |
|       | 8.3                                     | Failure criteria after impact   |        |  |  |  |  |
| 9     |   | stance to solar ultraviolet radiation   |        |  |  |  |  |
| 10    |   | Resistance to ignition  |        |  |  |  |  |
| 11    |   | Field of view   |        |  |  |  |  |
| 12    |   |   |        |  |  |  |  |
|       | 12.1                                    | mum area to be protected  Assessment of frontal protection                            |        |  |  |  |  |
|       | 12.1                                    | Assessment of lateral protection  |        |  |  |  |  |
| 13    |   | •   |        |  |  |  |  |
| 13    | 13.1                                    | onal requirements   |        |  |  |  |  |
|       | 10.1                                    |   |        |  |  |  |  |

### ISO/FDIS 18527-2.2:2020(E)

|        | 13.2                 | Resistance to abrasion  | 11         |
|--------|----------------------|---|------------|
| 14     | 14.1<br>14.2<br>14.3 | ng and information to be supplied by the manufacturer  Assessment  Mandatory markings on eye protectors  Information to be supplied with each eye protector by the manufacturer  Additional information to be available from the manufacturer | 11<br>12   |
| 15     | Select<br>15.1       | ion of test samples General Preparation and conditioning of test samples  | 1 <b>3</b> |
| Annex  | -                    | ormative) Use of squash eye protectors and racquetball and squash 57 eye  | 16         |
| Annex  |                      | ormative) Selection of squash eye protectors and racquetball and squash 57 otectors for prescription lens wearers   | 18         |
| Annex  |                      | formative) Relationship between this European Standard and the essential rements of Regulation 2016/425 aimed to be covered   | 19         |
| Biblio | graphy               | ,   | 21         |

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/FDIS 18527-2.2</u> https://standards.iteh.ai/catalog/standards/sist/74cfbf61-872b-4b6d-bb5b-d74599902246/iso-fdis-18527-2-2

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>. (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 94, *Personal safety — Personal protective equipment*, Subcommittee SC 6, *Eye and face protection*. 2

https://standards.iieh.ai/catalog/standards/sist/74cfbf61-872b-4b6d-bb5b-

A list of all parts of ISO 18527 can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

### ISO/FDIS 18527-2.2:2020(E)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/FDIS 18527-2.2</u> https://standards.iteh.ai/catalog/standards/sist/74cfbf61-872b-4b6d-bb5b-d74599902246/iso-fdis-18527-2-2

### Introduction

This family of documents comprised of the ISO 16321 series, the ISO 18526 series and the ISO 18527 series was developed in response to the worldwide stakeholders' demand for minimum requirements and test methods for eye and face protectors traded internationally. ISO 4007 gives the terms and definitions for all the various product types. The test methods are given in the ISO 18526 series, while the requirements for occupational eye and face protectors are given in the ISO 16321 series. Eye protection for specific sports are mostly dealt with by the ISO 18527 series. A guidance document, ISO 19734, for the selection, use and maintenance of eye and face protectors is under preparation.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 18527-2.2 https://standards.iteh.ai/catalog/standards/sist/74cfbf61-872b-4b6d-bb5b-d74599902246/iso-fdis-18527-2-2

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/FDIS 18527-2.2</u> https://standards.iteh.ai/catalog/standards/sist/74cfbf61-872b-4b6d-bb5b-d74599902246/iso-fdis-18527-2-2

## Eye and face protection for sports use —

### Part 2:

## Requirements for eye protectors for squash and eye protectors for racquetball and squash 57

### 1 Scope

This document applies to all eye protectors intended for eye protection against hazards during playing or instructing in the sports of squash, racquetball and squash 57 and sports with similar hazards and no greater risks. It applies to eye protectors that incorporate prescription lenses but has no specific tests for eye protectors designed for use over spectacles.

It specifies requirements and testing for materials, performance, marking of eye protectors and information to be supplied by the manufacturer.

Information on the selection and use of eye protectors for squash, racquetball and squash 57 is given in Annex A.

This document does not apply to TANDARD PREVIEW

- a) sports eye protectors designed for use over prescription spectacles,
- b) eye protectors for other occupational applications,
- c) eye protectors without lands its h.ai/catalog/standards/sist/74cfbf61-872b-4b6d-bb5b-d74599902246/iso-fdis-18527-2-2
- d) eye protectors for sports where the hazards are unrelated to the hazards in or involve greater risks than squash, racquetball and squash 57, and
- e) eye protectors with gradient-tinted lenses because they are not appropriate for squash, racquetball and squash 57.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4007, Personal protective equipment — Eye and face protection — Vocabulary

ISO 8980-5, Ophthalmic optics — Uncut finished spectacle lenses — Part 5: Minimum requirements for spectacle lens surfaces claimed to be abrasion-resistant

ISO 11664-2, Colorimetry — Part 2: CIE standard illuminants

ISO 18526-1:2020, Eye and face protection — Test methods — Part 1: Geometrical optical properties

ISO 18526-2:2020, Eye and face protection — Test methods — Part 2: Physical optical properties

ISO 18526-3:2020, Eye and face protection — Test methods — Part 3: Physical and mechanical properties

ISO 18526-4, Eye and face protection — Test methods — Part 4: Headforms

ISO 21987, Ophthalmic optics — Mounted spectacle lenses

#### 3 Terms and definitions

For the purposes of this document, the terms and the definitions given in ISO 4007 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="http://www.electropedia.org/">http://www.electropedia.org/</a>

#### 4 General requirements for eye protectors<sup>1)</sup>

### 4.1 Physiological compatibility

Eye protectors shall be designed and manufactured in such a way that, when used under the conditions and for the purposes intended, they will not compromise the health or safety of the wearer. The risks posed by substances leaking or evaporating from the eye protector that can come into prolonged contact with the wearer, shall be reduced by the manufacturer to within the limits of any applicable regulatory requirement.

Special attention shall be given to substances that are allergenic, carcinogenic, mutagenic or toxic to reproduction.

NOTE 1 Excessive pressure due to a poor fit on the head, chemical irritation or allergy are known to produce reactions. Rare or idiosyncratic reactions to any material are known to occur and the individual wearer is well advised to avoid those types of frame materials.

Substances recommended for cleaning, maintenance or disinfection shall be known to be unlikely to have any adverse effect upon the wearer, when applied in accordance with the instructions given in the information to be supplied by the manufacture SO/FDIS 18527-2.2

https://standards.iteh.ai/catalog/standards/sist/74cfbf61-872b-4b6d-bb5b-

Manufacturers/suppliers shall perform an appropriate risk analysis on potentially harmful substances contained in the eye protector such that, when the protector is used under the conditions and for the purposes intended, the health (and safety) of the wearer shall not be compromised.

The following are examples of documents that represent the appropriate information:

- a) specification of the material(s);
- b) safety data sheets relating to the materials;
- c) information relating to the suitability of the materials for use with food, in medical devices, or other relevant applications;
- d) information relating to toxicological, allergenic, carcinogenic, toxic to reproduction, or mutagenic investigations on the materials.

NOTE 2 Specific national regulations with regard to the restriction of certain chemical substances need to be observed, for example release of nickel.

#### 4.2 Construction and adjustment

Areas of the eye protectors that may, during intended use, come into contact with the wearer or other players on the court shall be smooth, without sharp protuberances that may cause discomfort or injury to the wearer or other players on the court.

<sup>1)</sup> For the purposes of this document, "eye protector" is used to mean eye protectors for squash, racquetball and squash 57.

Any part of the eye protector that can be adjusted or removed by the wearer for the purpose of replacement (in accordance with the instructions given in the information to be supplied by the manufacturer) shall facilitate adjustment, removal and attachment without the use of tools.

Any adjustment system incorporated in the eye protectors shall maintain the intended fit for the foreseeable conditions of use.

The test shall be carried out by physical inspection according to ISO 18526-3:2020, 6.1.

#### 4.3 Cleaning and/or disinfection

The eye protector shall be cleaned only once according to the cleaning and/or disinfection procedures in the information to be supplied by the manufacturer before being subjected to testing.

#### 4.4 Lens material and surface quality

In a circular area  $30^{+0.5}_{-0}$  mm diameter centred on the reference point(s) but excluding a marginal area  $5^{+0}_{-0.5}$  mm wide around the edge of the lens if this overlaps with the circular area, lenses shall be free from defects likely to impair vision in use (such as bubbles, scratches, inclusions, dull spots, pitting, mould marks, scouring, grains, pocking, scaling and undulation) when examined according to ISO 18526-3:2020, 6.6.

## 4.5 Headform(s) iTeh STANDARD PREVIEW

Unless the manufacturer specifies the headform(s) according to ISO 18526-4 that is/are compatible with the eye protector, the test methods where (a) headform(s) is/are required shall use the headform 1-M according to ISO 18526-4 as the default.

ISO/FDIS 18527-2.2

## **4.6 Retention by headband and harnesses (sit and fit)** 2b-4b6d-bb5b-d74599902246/iso-fdis-18527-2-2

Eye protectors shall sit in the intended position during normal use and shall adapt to the contours of the face. The surfaces in contact with the face shall be made of soft flexible material. Any headband shall be designed to be flexible or adjustable and sit securely on the back of the head. Any headband assembly shall not cause any discomfort nor exhibit any insecurity when tested in accordance with ISO 18526-3:2020, 6.5.

#### 4.7 Mandatory and optional requirements

In this document both optional and mandatory requirements are described. Depending on the intended use and/or the manufacturer's claimed specification, some requirements marked as optional become mandatory.

#### 5 Transmittance of the lenses

#### 5.1 General

Transmittance values shall be determined in accordance with ISO 18526-2:2020, Clauses 6 to 11, as appropriate. Luminous transmittance shall be calculated using CIE Standard Illuminant D65 in accordance with ISO 11664-2 (see also ISO 4007:2018, 3.10.1.32).

#### 5.2 Transmittance categories

Depending upon the mean luminous transmittance,  $\tau_{v \, D65}$ , at their reference points and at (23 ± 1) °C in the case of temperature sensitive transmittance, lenses for squash, racquetball and squash 57 use shall be attributed to one of the five tint categories in <u>Table 1</u>.

The ranges of the luminous transmittance,  $\tau_{v\,D65}$ , of these five categories is given by the values in <u>Table 1</u>. An overlap of the transmittance values shall be not more than ±2 % absolute between the categories 0, 1, 2 and 3. There is no overlap in transmittance values between categories 3 and 4.

If the manufacturer and/or supplier declare a luminous transmittance value, the maximum deviation for this value shall be  $\pm 3$  % absolute for the transmittance values falling in categories 0 to 3 and  $\pm 30$  % relative to the stated value for the transmittance values falling in category 4.

When describing the transmittance properties of lenses with changeable tint, e.g. photochromic, two categories for luminous transmittance values are generally used. These two values correspond to the highest and lowest luminous transmittance state of the lens.

#### 5.3 Solar ultraviolet transmittance

When tested within a 10 mm radius circle centred on the reference point according to ISO 18526-2:2020, Clause 8, the solar UV-A,  $\tau_{\rm SUVA}$ , solar UV-B,  $\tau_{\rm SUVB}$ , and mean spectral (380 to 400) nm,  $\tau_{\rm m380-400}$ , transmittances shall conform with the requirements in <u>Table 1</u>, based on the mean luminous transmittance,  $\tau_{\rm v D65}$ , at the reference points of the lens(es).

Table 1 — Transmittance requirements for the lenses of squash, racquetball and squash 57 eye protectors

|  | Wavelen   | Visible spectral range   |   |  |  |  |  |
|--|---|--|---|--|--|--|--|
| Tint category  | Maximum<br>solar UV-B<br>transmittance              | Maximum<br>eh solar UV-AD A<br>transmittance                         | Maximum mean R 380 nm to 400 nm spectral transmittance      | Luminous<br>transmittance                                      |  |  |  |
|  | $\tau_{\rm SUVB}$ 280 nm $\leq \lambda \leq$ 315 nm | $\tau_{SUVA380}$ dar $315 \text{ nm} \le \lambda \le 380 \text{ nm}$ | ds.iter <sub>m380</sub> 240)<br>380 nm ≤ λ ≤ 400 nm         | $\tau_{\rm v~D65}$ $380~{\rm nm} \le \lambda \le 780~{\rm nm}$ |  |  |  |
| S0, R0 or<br>SR0   | https://st  | ISO/FDIS<br>andards.iteh.ai/catalog/stand                            | 18527-2.2<br>lards/sist/74cffeff_1-872b-4b6d-               | $\tau_{\rm v \ D65} > 80 \ \%$                                 |  |  |  |
| S1, R1 or<br>SR1   |   | $0.30 \frac{d74599902246/1}{\tau_{v D65}}$                           | so-fdis-18527-2v-p65  | $43 \% < \tau_{v D65} \le 80 \%$                               |  |  |  |
| S2, R2 or<br>SR2   | 0,03 $	au_{ m vD65}$                                |  | 0.50.5  | $18 \% < \tau_{v D65} \le 43 \%$                               |  |  |  |
| S3, R3 or<br>SR3   |   | 0,15 $	au_{ m vD65}$   | $0,50~	au_{\mathrm{vD65}}$                                  | $8 \% < \tau_{v D65} \le 18 \%$                                |  |  |  |
| S4, R4 or<br>SR4   |   |  | 0,5 % absolute or 0,15 $	au_{ m vD65}$ whichever is greater | $3 \% < \tau_{v D65} \le 8 \%$                                 |  |  |  |
| NOTE Some national requirements can stipulate a different requirement for the long wavelength limit of UV-A. |   |  |   |  |  |  |  |

#### 5.4 General transmittance requirements

#### 5.4.1 Uniformity of luminous transmittance and transmittance matching

Lenses shall appear to be visually uniform within circles  $30^{+0.5}_{-0.0}$  mm diameter centred on the reference points or to the edge of the lens less the marginal zone  $5^{+0}_{-0.5}$  mm wide (whichever is greater), and appear to have the same transmittance at the two reference points when inspected against a white background in accordance with ISO 18526-3:2020, 6.6. Where there is visible non-uniformity, then, when tested according to ISO 18526-2:2020, 7.4, the relative difference in the luminous transmittance value between any two points of the lens shall not be greater than 15 % (relative to the higher value), except for tint category S4, R4 or SR4 where it shall not be greater than 20 %.

Where there are visibly mismatched transmittances at the reference points, when measured in accordance with ISO 18526-2:2020, 7.5, the difference in luminous transmittance values at the reference points for the right and left eyes shall not exceed 15% (relative to the higher transmittance).