

ETSI TS 138 104 V16.7.0 (2021-04)



**5G;
NR;
Base Station (BS) radio transmission and reception
(3GPP TS 38.104 version 16.7.0 Release 16)**

<https://standards.iteh.ai/catalog/standards/sist/a43013e2-427c-4bc4-bd6a-f89b42c5599e/etsi-ts-138-104-v16-7-0-2021-04>



Reference

RTS/TSGR-0438104vg70

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITh STANDARD PREVIEW
(standards.iteh.ai)

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	14
2 References	14
3 Definitions, symbols and abbreviations	15
3.1 Definitions	15
3.2 Symbols.....	19
3.3 Abbreviations	21
4 General	23
4.1 Relationship with other core specifications.....	23
4.2 Relationship between minimum requirements and test requirements	23
4.3 Conducted and radiated requirement reference points	23
4.3.1 BS type 1-C	23
4.3.2 BS type 1-H	24
4.3.3 BS type 1-O and BS type 2-O	25
4.4 Base station classes	25
4.5 Regional requirements.....	26
4.6 Applicability of requirements.....	29
4.7 Requirements for contiguous and non-contiguous spectrum	29
4.8 Requirements for BS capable of multi-band operation	30
4.9 OTA co-location with other base stations	31
5 Operating bands and channel arrangement.....	33
5.1 General	33
5.2 Operating bands	33
5.3 BS channel bandwidth	35
5.3.1 General.....	35
5.3.2 Transmission bandwidth configuration	35
5.3.3 Minimum guardband and transmission bandwidth configuration	36
5.3.4 RB alignment.....	37
5.3.5 BS channel bandwidth per operating band	38
5.3A BS channel bandwidth for CA.....	41
5.3A.1 Transmission bandwidth configuration for CA	41
5.3A.2 Minimum guardband and transmission bandwidth configuration for CA	41
5.4 Channel arrangement.....	43
5.4.1 Channel spacing.....	43
5.4.1.1 Channel spacing for adjacent NR carriers	43
5.4.1.2 Channel spacing for CA	43
5.4.2 Channel raster	44
5.4.2.1 NR-ARFCN and channel raster.....	44
5.4.2.1A NB-IoT carrier frequency numbering.....	45
5.4.2.2 Channel raster to resource element mapping.....	45
5.4.2.3 Channel raster entries for each operating band.....	45
5.4.3 Synchronization raster	48
5.4.3.1 Synchronization raster and numbering.....	48
5.4.3.3 Synchronization raster entries for each operating band.....	49
6 Conducted transmitter characteristics	53
6.1 General	53
6.2 Base station output power	53
6.2.1 General.....	53
6.2.2 Minimum requirement for BS type 1-C.....	54

6.2.3	Minimum requirement for <i>BS type 1-H</i>	54
6.2.4	Additional requirements (regional).....	54
6.3	Output power dynamics.....	54
6.3.1	General.....	54
6.3.2	RE power control dynamic range	54
6.3.2.1	General	54
6.3.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	54
6.3.3	Total power dynamic range	55
6.3.3.1	General	55
6.3.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	55
6.3.4	NB-IoT RB power dynamic range for NB-IoT operation in NR in-band	55
6.3.4.1	General	55
6.3.4.2	Minimum Requirement	56
6.4	Transmit ON/OFF power	56
6.4.1	Transmitter OFF power	56
6.4.1.1	General	56
6.4.1.2	Minimum requirement for <i>BS type 1-C</i>	56
6.4.1.3	Minimum requirement for <i>BS type 1-H</i>	56
6.4.2	Transmitter transient period	56
6.4.2.1	General	56
6.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	57
6.4.2.3	Void.....	57
6.5	Transmitted signal quality	57
6.5.1	Frequency error.....	57
6.5.1.1	General	57
6.5.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	58
6.5.2	Modulation quality.....	58
6.5.2.1	General	58
6.5.2.2	Minimum Requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	58
6.5.2.3	EVM frame structure for measurement.....	58
6.5.3	Time alignment error	59
6.5.3.1	General	59
6.5.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	59
6.6	Unwanted emissions.....	59
6.6.1	General.....	59
6.6.2	Occupied bandwidth	60
6.6.2.1	General	60
6.6.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	60
6.6.3	Adjacent Channel Leakage Power Ratio	60
6.6.3.1	General	60
6.6.3.2	Limits and <i>Basic limits</i>	61
6.6.3.3	Minimum requirement for <i>BS type 1-C</i>	64
6.6.3.4	Minimum requirement for <i>BS type 1-H</i>	64
6.6.4	Operating band unwanted emissions	64
6.6.4.1	General	64
6.6.4.2	<i>Basic limits</i>	66
6.6.4.2.1	<i>Basic limits</i> for Wide Area BS (Category A)	66
6.6.4.2.2	<i>Basic limits</i> for Wide Area BS (Category B)	67
6.6.4.2.3	<i>Basic limits</i> for Medium Range BS (Category A and B).....	69
6.6.4.2.4	<i>Basic limits</i> for Local Area BS (Category A and B).....	69
6.6.4.2.4A	<i>Basic limits</i> for Local Area and Medium Range BS for band n46 and n96 (Category A and B)	70
6.6.4.2.5	<i>Basic limits</i> for additional requirements	73
6.6.4.3	Minimum requirements for <i>BS type 1-C</i>	74
6.6.4.4	Minimum requirements for <i>BS type 1-H</i>	74
6.6.5	Transmitter spurious emissions.....	75
6.6.5.1	General	75
6.6.5.2	<i>Basic limits</i>	75
6.6.5.2.1	General transmitter spurious emissions requirements	75
6.6.5.2.2	Protection of the BS receiver of own or different BS	76
6.6.5.2.3	Additional spurious emissions requirements	76
6.6.5.2.4	Co-location with other base stations.....	85
6.6.5.3	Minimum requirements for <i>BS type 1-C</i>	90

6.6.5.4	Minimum requirements for <i>BS type 1-H</i>	90
6.7	Transmitter intermodulation	91
6.7.1	General	91
6.7.2	Minimum requirements for <i>BS type 1-C</i>	91
6.7.2.1	Co-location minimum requirements	91
6.7.2.2	Additional requirements	92
6.7.3	Minimum requirements for <i>BS type 1-H</i>	92
6.7.3.1	Co-location minimum requirements	92
6.7.3.2	Intra-system minimum requirements	93
6.7.3.3	Additional requirements	93
7	Conducted receiver characteristics	95
7.1	General	95
7.2	Reference sensitivity level	95
7.2.1	General	95
7.2.2	Minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	95
7.3	Dynamic range	99
7.3.1	General	99
7.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	99
7.4	In-band selectivity and blocking	107
7.4.1	Adjacent Channel Selectivity (ACS)	107
7.4.1.1	General	107
7.4.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	107
7.4.1.3	Void	109
7.4.1.4	Void	109
7.4.2	In-band blocking	109
7.4.2.1	General	109
7.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	109
7.4.2.3	Void	113
7.4.2.4	Void	113
7.5	Out-of-band blocking	113
7.5.1	General	113
7.5.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	113
7.5.3	Co-location minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	114
7.5.4	Void	115
7.6	Receiver spurious emissions	115
7.6.1	General	115
7.6.2	<i>Basic limits</i>	116
7.6.3	Minimum requirement for <i>BS type 1-C</i>	116
7.6.4	Minimum requirement for <i>BS type 1-H</i>	116
7.7	Receiver intermodulation	117
7.7.1	General	117
7.7.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	117
7.8	In-channel selectivity	122
7.8.1	General	122
7.8.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	122
8	Conducted performance requirements	130
8.1	General	130
8.1.1	Scope and definitions	130
8.1.2	Void	130
8.2	Performance requirements for PUSCH	130
8.2.1	Requirements for PUSCH with transform precoding disabled	130
8.2.1.1	General	130
8.2.1.2	Minimum requirements	131
8.2.2	Requirements for PUSCH with transform precoding enabled	139
8.2.2.1	General	139
8.2.2.2	Minimum requirements	139
8.2.3	Requirements for UCI multiplexed on PUSCH	140
8.2.3.1	General	140
8.2.3.2	Minimum requirements	141
8.2.4	Requirements for PUSCH for high speed train	142

8.2.4.1	General	142
8.2.4.2	Minimum requirements	143
8.2.5	Requirements for UL timing adjustment	145
8.2.5.1	Minimum requirements for high speed train	146
8.2.5.2	Minimum requirements for normal mode	147
8.2.6	Requirements for PUSCH 0.001% BLER	148
8.2.6.1	General	148
8.2.6.2	Minimum requirements	149
8.2.7	Requirements for PUSCH repetition Type A	150
8.2.7.1	General	150
8.2.7.2	Minimum requirements	151
8.2.8	Requirements for PUSCH mapping Type B with non-slot transmission	152
8.2.8.1	General	152
8.2.8.2	Minimum requirements	153
8.2.9	Requirements of PUSCH for 2-step RA type	154
8.2.9.1	General	154
8.2.9.2	Minimum requirements	154
8.3	Performance requirements for PUCCH	155
8.3.1	DTX to ACK probability	155
8.3.1.1	General	155
8.3.1.2	Minimum requirement	155
8.3.2	Performance requirements for PUCCH format 0	156
8.3.2.1	General	156
8.3.2.2	Minimum requirements	156
8.3.3	Performance requirements for PUCCH format 1	157
8.3.3.1	NACK to ACK requirements	157
8.3.3.1.1	General	157
8.3.3.1.2	Minimum requirements	157
8.3.3.2	ACK missed detection requirements	158
8.3.3.2.1	General	158
8.3.3.2.2	Minimum requirements	158
8.3.4	Performance requirements for PUCCH format 2	159
8.3.4.1	ACK missed detection requirements	159
8.3.4.1.1	General	159
8.3.4.1.2	Minimum requirements	159
8.3.4.2	UCI BLER performance requirements	160
8.3.4.2.1	General	160
8.3.4.2.2	Minimum requirements	160
8.3.5	Performance requirements for PUCCH format 3	161
8.3.5.1	General	161
8.3.5.2	Minimum requirements	161
8.3.6	Performance requirements for PUCCH format 4	162
8.3.6.1	General	162
8.3.6.2	Minimum requirement	163
8.3.7	Performance requirements for multi-slot PUCCH	164
8.3.7.1	General	164
8.3.7.2	Performance requirements for multi-slot PUCCH format 1	164
8.3.7.2.1	NACK to ACK requirements	164
8.3.7.2.1.1	General	164
8.3.7.2.1.2	Minimum requirements	165
8.3.7.2.2	ACK missed detection requirements	165
8.4	Performance requirements for PRACH	165
8.4.1	PRACH False alarm probability	165
8.4.1.1	General	165
8.4.1.2	Minimum requirement	166
8.4.2	PRACH detection requirements	166
8.4.2.1	General	166
8.4.2.2	Minimum requirements for Normal Mode	166
8.4.2.3	Minimum requirements for high speed train	167
9	Radiated transmitter characteristics	169
9.1	General	169

9.2	Radiated transmit power.....	169
9.2.1	General.....	169
9.2.2	Minimum requirement for <i>BS type 1-H</i> and <i>BS type 1-O</i>	169
9.2.3	Minimum requirement for <i>BS type 2-O</i>	170
9.3	OTA base station output power.....	170
9.3.1	General.....	170
9.3.2	Minimum requirement for <i>BS type 1-O</i>	170
9.3.3	Minimum requirement for <i>BS type 2-O</i>	171
9.3.4	Additional requirements (regional).....	171
9.4	OTA output power dynamics	171
9.4.1	General.....	171
9.4.2	OTA RE power control dynamic range	171
9.4.2.1	General.....	171
9.4.2.2	Minimum requirement for <i>BS type 1-O</i>	171
9.4.3	OTA total power dynamic range.....	171
9.4.3.1	General.....	171
9.4.3.2	Minimum requirement for <i>BS type 1-O</i>	171
9.4.3.3	Minimum requirement for <i>BS type 2-O</i>	172
9.5	OTA transmit ON/OFF power.....	172
9.5.1	General.....	172
9.5.2	OTA transmitter OFF power.....	172
9.5.2.1	General	172
9.5.2.2	Minimum requirement for <i>BS type 1-O</i>	172
9.5.2.3	Minimum requirement for <i>BS type 2-O</i>	172
9.5.3	OTA transient period	172
9.5.3.1	General	172
9.5.3.2	Minimum requirement for <i>BS type 1-O</i>	173
9.5.3.3	Minimum requirement for <i>BS type 2-O</i>	173
9.6	OTA transmitted signal quality.....	173
9.6.1	OTA frequency error	173
9.6.1.1	General	173
9.6.1.2	Minimum requirement for <i>BS type 1-O</i>	173
9.6.1.3	Minimum requirement for <i>BS type 2-O</i>	173
9.6.2	OTA modulation quality.....	174
9.6.2.1	General	174
9.6.2.2	Minimum Requirement for <i>BS type 1-O</i>	174
9.6.2.3	Minimum Requirement for <i>BS type 2-O</i>	174
9.6.2.3.1	EVM frame structure for measurement	174
9.6.3	OTA time alignment error	174
9.6.3.1	General	174
9.6.3.2	Minimum requirement for <i>BS type 1-O</i>	174
9.6.3.3	Minimum requirement for <i>BS type 2-O</i>	175
9.7	OTA unwanted emissions	175
9.7.1	General.....	175
9.7.2	OTA occupied bandwidth.....	176
9.7.2.1	General	176
9.7.2.2	Minimum requirement for <i>BS type 1-O</i> and <i>BS type 2-O</i>	176
9.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR)	176
9.7.3.1	General.....	176
9.7.3.2	Minimum requirement for <i>BS type 1-O</i>	176
9.7.3.3	Minimum requirement for <i>BS type 2-O</i>	176
9.7.4	OTA operating band unwanted emissions	178
9.7.4.1	General	178
9.7.4.2	Minimum requirement for <i>BS type 1-O</i>	178
9.7.4.2.1	Additional requirements	179
9.7.4.3	Minimum requirement for <i>BS type 2-O</i>	179
9.7.4.3.1	General	179
9.7.4.3.2	OTA operating band unwanted emission limits (Category A)	180
9.7.4.3.3	OTA operating band unwanted emission limits (Category B).....	181
9.7.4.3.4	Additional OTA operating band unwanted emission requirements	181
9.7.5	OTA transmitter spurious emissions.....	182
9.7.5.1	General	182

9.7.5.2	Minimum requirement for <i>BS type 1-O</i>	182
9.7.5.2.1	General	182
9.7.5.2.2	General OTA transmitter spurious emissions requirements	182
9.7.5.2.3	Protection of the BS receiver of own or different BS	182
9.7.5.2.4	Additional spurious emissions requirements	182
9.7.5.2.5	Co-location with other base stations	183
9.7.5.3	Minimum requirement for <i>BS type 2-O</i>	183
9.7.5.3.1	General	183
9.7.5.3.2	General OTA transmitter spurious emissions requirements	183
9.7.5.3.3	Additional OTA transmitter spurious emissions requirements	184
9.8	OTA transmitter intermodulation	185
9.8.1	General.....	185
9.8.2	Minimum requirement for <i>BS type 1-O</i>	185
10	Radiated receiver characteristics	187
10.1	General	187
10.2	OTA sensitivity	188
10.2.1	<i>BS type 1-H</i> and <i>BS type 1-O</i>	188
10.2.1.1	General	188
10.2.1.2	Minimum requirement	188
10.2.2	<i>BS type 2-O</i>	188
10.3	OTA reference sensitivity level	189
10.3.1	General.....	189
10.3.2	Minimum requirement for <i>BS type 1-O</i>	189
10.3.3	Minimum requirement for <i>BS type 2-O</i>	190
10.4	OTA dynamic range	191
10.4.1	General.....	191
10.4.2	Minimum requirement for <i>BS type 1-O</i>	191
10.5	OTA in-band selectivity and blocking.....	200
10.5.1	OTA adjacent channel selectivity.....	200
10.5.1.1	General	200
10.5.1.2	Minimum requirement for <i>BS type 1-O</i>	200
10.5.1.3	Minimum requirement for <i>BS type 2-O</i>	201
10.5.2	OTA in-band blocking	202
10.5.2.1	General	202
10.5.2.2	Minimum requirement for <i>BS type 1-O</i>	202
10.5.2.3	Minimum requirement for <i>BS type 2-O</i>	205
10.6	OTA out-of-band blocking	205
10.6.1	General.....	205
10.6.2	Minimum requirement for <i>BS type 1-O</i>	205
10.6.2.1	General minimum requirement	205
10.6.2.2	Co-location minimum requirement	206
10.6.3	Minimum requirement for <i>BS type 2-O</i>	207
10.6.3.1	General minimum requirement	207
10.7	OTA receiver spurious emissions.....	207
10.7.1	General.....	207
10.7.2	Minimum requirement for <i>BS type 1-O</i>	207
10.7.3	Minimum requirement for <i>BS type 2-O</i>	208
10.8	OTA receiver intermodulation	209
10.8.1	General.....	209
10.8.2	Minimum requirement for <i>BS type 1-O</i>	209
10.8.3	Minimum requirement for <i>BS type 2-O</i>	213
10.9	OTA in-channel selectivity.....	214
10.9.1	General.....	214
10.9.2	Minimum requirement for <i>BS type 1-O</i>	214
10.9.3	Minimum requirement for <i>BS type 2-O</i>	217
11	Radiated performance requirements.....	218
11.1	General	218
11.1.1	Scope and definitions.....	218
11.1.2	OTA demodulation branches	218
11.1.3	Void	219

11.2	Performance requirements for PUSCH	219
11.2.1	Requirements for <i>BS type 1-O</i>	219
11.2.1.1	Requirements for PUSCH with transform precoding disabled	219
11.2.1.2	Requirements for PUSCH with transform precoding enabled	219
11.2.1.3	Requirements for UCI multiplexed on PUSCH	219
11.2.1.4	Requirements for PUSCH for high speed train	219
11.2.1.5	Requirements for UL timing adjustment	219
11.2.1.6	Requirements for PUSCH 0.001% BLER	219
11.2.1.7	Requirements for PUSCH repetition Type A	219
11.2.1.8	Requirements for PUSCH mapping Type B with non-slot transmission	219
11.2.1.9	Requirements for PUSCH for 2-step RA type	219
11.2.2	Requirements for <i>BS type 2-O</i>	219
11.2.2.1	Requirements for PUSCH with transform precoding disabled	219
11.2.2.1.1	General	219
11.2.2.1.2	Minimum requirements	220
11.2.2.2	Requirements for PUSCH with transform precoding enabled	223
11.2.2.2.1	General	223
11.2.2.2.2	Minimum requirements	223
11.2.2.3	Requirements for UCI multiplexed on PUSCH	224
11.2.2.3.1	General	224
11.2.2.3.2	Minimum requirements	225
11.2.2.4	Requirements for PUSCH for 2-step RA type	227
11.2.2.4.1	General	227
11.2.2.4.2	Minimum requirements	227
11.2.2.5	Requirements for PUSCH repetition Type A	228
11.2.2.5.1	General	228
11.2.2.5.2	Minimum requirements	228
11.2.2.6	Requirements for PUSCH mapping Type B with non-slot transmission	229
11.2.2.6.1	General	229
11.2.2.6.2	Minimum requirements	230
11.3	Performance requirements for PUCCH	231
11.3.1	Requirements for <i>BS type 1-O</i>	231
11.3.1.1	DTX to ACK probability	231
11.3.1.2	Performance requirements for PUCCH format 0	231
11.3.1.3	Performance requirements for PUCCH format 1	231
11.3.1.4	Performance requirements for PUCCH format 2	231
11.3.1.5	Performance requirements for PUCCH format 3	231
11.3.1.6	Performance requirements for PUCCH format 4	231
11.3.2	Requirements for <i>BS type 2-O</i>	231
11.3.2.1	DTX to ACK probability	231
11.3.2.2	Performance requirements for PUCCH format 0	231
11.3.2.2.1	General	231
11.3.2.2.2	Minimum requirements	232
11.3.2.3	Performance requirements for PUCCH format 1	232
11.3.2.3.1	NACK to ACK requirements	232
11.3.2.3.2	ACK missed detection requirements	233
11.3.2.4	Performance requirements for PUCCH format 2	234
11.3.2.4.1	ACK missed detection requirements	234
11.3.2.4.2	UCI BLER performance requirements	235
11.3.2.5	Performance requirements for PUCCH format 3	236
11.3.2.5.1	General	236
11.3.2.5.2	Minimum requirements	236
11.3.2.6	Performance requirements for PUCCH format 4	237
11.3.2.6.1	General	237
11.3.2.6.2	Minimum requirements	237
11.4	Performance requirements for PRACH	238
11.4.1	Requirements for <i>BS type 1-O</i>	238
11.4.1.1	PRACH False alarm probability	238
11.4.1.2	PRACH detection requirements	238
11.4.2	Requirements for <i>BS type 2-O</i>	238
11.4.2.1	PRACH False alarm probability	238
11.4.2.1.1	General	238

11.4.2.1.2	Minimum requirement	238
11.4.2.2	PRACH detection requirements	238
11.4.2.2.1	General	238
11.4.2.2.2	Minimum requirements	239
Annex A (normative):	Reference measurement channels	240
A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3)	240
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3)	242
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	244
A.3A	Fixed Reference Channels for performance requirements (QPSK, R=99/1024)	250
A.3B	Fixed Reference Channels for performance requirements (QPSK, R=308/1024)	252
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	253
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	257
A.6	PRACH Test preambles	259
A.7	Fixed Reference Channels for performance requirements (16QAM, R=434/1024)	260
A.8	Fixed Reference Channels for performance requirements (QPSK, R=157/1024)	261
Annex B (normative):	Error Vector Magnitude (FR1)	262
B.1	Reference point for measurement	262
B.2	Basic unit of measurement	262
B.3	Modified signal under test	263
B.4	Estimation of frequency offset	263
B.5	Estimation of time offset	263
B.5.1	General	263
B.5.2	Window length	264
B.6	Estimation of TX chain amplitude and frequency response parameters	265
B.7	Averaged EVM	266
Annex C (normative):	Error Vector Magnitude (FR2)	268
C.1	Reference point for measurement	268
C.2	Basic unit of measurement	268
C.3	Modified signal under test	269
C.4	Estimation of frequency offset	269
C.5	Estimation of time offset	269
C.5.1	General	269
C.5.2	Window length	270
C.6	Estimation of TX chain amplitude and frequency response parameters	270
C.7	Averaged EVM	272
Annex D (normative):	Characteristics of the interfering signals	274
Annex E:	Void	275
Annex F (normative):	Relationship between EIRP based regulatory requirements and 3GPP requirements	276
F.1	General	276

F.2	Relationship between EIRP based regulatory requirements and conducted requirements.....	276
F.3	Relationship between EIRP based regulatory requirements and OTA requirements.....	277
Annex G (Normative):	Propagation conditions.....	278
G.1	Static propagation condition.....	278
G.2	Multi-path fading propagation conditions	278
G.2.1	Delay profiles	278
G.2.1.1	Delay profiles for FR1	279
G.2.1.2	Delay profiles for FR2	280
G.2.2	Combinations of channel model parameters	281
G.2.3	MIMO Channel Correlation Matrices	282
G.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA)	282
G.2.3.1.1	Definition of MIMO Correlation Matrices.....	282
G.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level	286
G.2.3.2	Multi-Antenna channel models using cross polarized antennas	288
G.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas	289
G.2.3.2.2	Spatial Correlation Matrices at UE and gNB sides	289
G.2.3.2.2.1	Spatial Correlation Matrices at UE side	289
G.2.3.2.2.2	Spatial Correlation Matrices at gNB side	290
G.2.3.2.3	MIMO Correlation Matrices using cross polarized antennas.....	290
G.3	High speed train condition	290
G.4	Moving propagation conditions.....	294
Annex H (informative):	Change history	296
History		306

<https://standards.iteh.ai/catalog/standards/sist/a43013e2-427c-4bc4-bd6a-f89b42c5599e/etsi-ts-138-104-v16-7-0-2021-04>
 ETSI TS 138 104 V16.7.0 (2021-04)

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- | | |
|------------------|---|
| shall | indicates a mandatory requirement to do something |
| shall not | indicates an interdiction (prohibition) to do something |

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- | | |
|-------------------|--|
| should | indicates a recommendation to do something |
| should not | indicates a recommendation not to do something |
| may | indicates permission to do something |
| need not | indicates permission not to do something |

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- | | |
|---------------|--|
| can | indicates that something is possible |
| cannot | indicates that something is impossible |

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- | | |
|-----------------|--|
| will | indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document |
| will not | indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document |
| might | indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document |

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ETSI TS 138 104 V16.7.0 (2021-04)

<https://standards.iteh.ai/catalog/standards/sist/a43013e2-427c-4bc4-bd6a-f89b42c5599e/etsi-ts-138-104-v16-7-0-2021-04>

1 Scope

The present document establishes the minimum RF characteristics and minimum performance requirements of NR and NB-IoT operation in NR in-band Base Station (BS).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] ITU-R Recommendation SM.329: "Unwanted emissions in the spurious domain".
- [3] Recommendation ITU-R SM.328: "Spectra and bandwidth of emissions".
- [4] 3GPP TR 25.942: "RF system scenarios".
- [5] 3GPP TS 38.141-1: "NR; Base Station (BS) conformance testing; Part 1: Conducted conformance testing".
- [6] 3GPP TS 38.141-2: "NR; Base Station (BS) conformance testing; Part 2: Radiated conformance testing".
- [7] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [8] "Title 47 of the Code of Federal Regulations (CFR)", Federal Communications Commission.
- [9] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [10] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [11] 3GPP TS 38.331: "NR; Radio Resource Control (RRC); Protocol specification".
- [12] ECC/DEC/(17)06: "The harmonised use of the frequency bands 1427-1452 MHz and 1492-1518 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".
- [13] 3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [14] 3GPP TS 37.105: "Active Antenna System (AAS) Base Station (BS) transmission and reception".
- [15] 3GPP TS 38.212: "NR; Multiplexing and channel coding".
- [16] 3GPP TR 38.901: "Study on channel model for frequencies from 0.5 to 100 GHz".
- [17] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone".
- [18] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [19] ERC Recommendation 74-01, "Unwanted emissions in the spurious domain".