

ETSI TS 136 141 V13.16.0 (2021-04)



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
Base Station (BS) conformance testing
(3GPP TS 36.141 version 13.16.0 Release 13)

<https://standards.iteh.ai/catalog/standards/sist/96cbf043-22bc-418e-9ce7-c04f707b3e4b/etsi-ts-136-141-v13-16-0-2021-04>



Reference

RTS/TSGR-0436141vdg0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITih STANDARD PREVIEW
(standards.iteh.ai)

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	15
1 Scope	16
2 References	16
3 Definitions, symbols and abbreviations	17
3.1 Definitions	17
3.2 Symbols.....	20
3.3 Abbreviations	21
4 General test conditions and declarations	23
4.1 Measurement uncertainties and Test Requirements	23
4.1.1 General.....	23
4.1.2 Acceptable uncertainty of Test System.....	23
4.1.2.1 Measurement of transmitter	24
4.1.2.2 Measurement of receiver	25
4.1.2.3 Measurement of performance requirement	29
4.1.3 Interpretation of measurement results.....	33
4.2 Base station classes	34
4.3 Regional requirements.....	34
4.4 Selection of configurations for testing.....	37
4.5 BS Configurations	37
4.5.1 Transmit configurations	37
4.5.1.1 Transmission with multiple transmitter antenna connectors.....	38
4.5.2 Receive configurations.....	38
4.5.2.1 Reception with multiple receiver antenna connectors, receiver diversity	38
4.5.3 Duplexers.....	39
4.5.4 Power supply options.....	39
4.5.5 Ancillary RF amplifiers	39
4.5.6 BS with integrated Iuant BS modem	40
4.5.7 BS using antenna arrays.....	40
4.5.7.1 Receiver tests	40
4.5.7.2 Transmitter tests.....	41
4.6 Manufacturer's declarations of regional and optional requirements	41
4.6.1 Operating band and frequency range	41
4.6.2 Channel bandwidth	42
4.6.3 Base station output power.....	42
4.6.4 Spurious emissions Category.....	42
4.6.5 Additional operating band unwanted emissions	42
4.6.6 Co-existence with other systems.....	43
4.6.7 Co-location with other base stations	43
4.6.8 Manufacturer's declarations of supported RF configurations	43
4.6.9 NB-IoT sub-carrier spacing	44
4.6.10 NB-IoT power dynamic range	44
4.7 Specified frequency range and supported channel bandwidth.....	45
4.7.1 Base Station RF Bandwidth position for multi-carrier and/or CA testing	45
4.7.2 Aggregated Channel Bandwidth position for Contiguous CA occupied bandwidth testing	46
4.7.3 NB-IoT testing.....	46
4.8 Format and interpretation of tests.....	46
4.9 Applicability of requirements.....	47
4.10 Test configurations for multi-carrier and/or CA operation.....	48
4.10.1 ETC1: Contiguous spectrum operation.....	48
4.10.1.1 ETC1 generation	48
4.10.1.2 ETC1 power allocation	48

4.10.2	ETC2: Contiguous CA occupied bandwidth.....	48
4.10.2.1	ETC2 generation	48
4.10.2.2	ETC2 power allocation	49
4.10.3	ETC3: Non-contiguous spectrum operation	49
4.10.3.1	ETC3 generation	49
4.10.3.2	ETC3 power allocation	49
4.10.3.24	VOID.....	50
4.10.4	ETC4: Multi-band test configuration for full carrier allocation.....	50
4.10.4.1	ETC4 generation	50
4.10.4.2	ETC4 power allocation	50
4.10.5	ETC5: Multi-band test configuration with high PSD per carrier	50
4.10.5.1	ETC5 generation	50
4.10.5.2	ETC5 power allocation	51
4.10.6	ETC6: NB-IoT standalone multi-carrier operation	51
4.10.6.1	ETC6 generation	51
4.10.6.2	ETC6 power allocation	51
4.10.7	ETC7: E-UTRA and NB-IoT standalone multi-carrier operation.....	51
4.10.7.1	ETC7 generation	51
4.10.7.2	ETC7 power allocation	52
4.10.8	ETC8: E-UTRA and NB-IoT in-band multi-carrier operation.....	52
4.10.8.1	ETC8 generation	52
4.10.8.2	ETC8 power allocation	52
4.10.9	ETC9: E-UTRA and NB-IoT guard-band multi-carrier operation.....	52
4.10.9.1	ETC9 generation	52
4.10.9.2	ETC9 power allocation	53
4.11	Applicability of test configurations	53
4.12	Requirements for BS capable of multi-band operation	59
5	Operating bands and channel arrangement.....	60
5.1	General	60
5.2	Void.....	60
5.3	Void.....	60
5.4	Void.....	60
5.5	Operating bands.....	60
5.6	Channel bandwidth.....	74
5.7	Channel arrangement.....	78
5.7.1	Channel spacing.....	78
5.7.1A	CA Channel spacing	78
5.7.2	Channel raster	79
5.7.3	Carrier frequency and EARFCN.....	79
5.8	Requirements for contiguous and non-contiguous spectrum.....	82
6	Transmitter characteristics	83
6.1	General	83
6.1.1	E-UTRA Test Models.....	83
6.1.1.1	E-UTRA Test Model 1.1 (E-TM1.1).....	83
6.1.1.2	E-UTRA Test Model 1.2 (E-TM1.2).....	84
6.1.1.3	E-UTRA Test Model 2 (E-TM2)	87
6.1.1.3a	E-UTRA Test Model 2a (E-TM2a).....	88
6.1.1.4	E-UTRA Test Model 3.1 (E-TM3.1).....	88
6.1.1.4a	E-UTRA Test Model 3.1a (E-TM3.1a).....	89
6.1.1.5	E-UTRA Test Model 3.2 (E-TM3.2).....	89
6.1.1.6	E-UTRA Test Model 3.3 (E-TM3.3).....	92
6.1.2	Data content of Physical channels and Signals for E-TM.....	95
6.1.2.1	Reference signals	95
6.1.2.2	Primary Synchronization signal	95
6.1.2.3	Secondary Synchronization signal	95
6.1.2.4	PBCH.....	95
6.1.2.5	PCFICH.....	96
6.1.2.6	PHICH.....	96
6.1.2.7	PDCCH	96
6.1.2.8	PDSCH.....	96

6.1.3	NB-IoT Test Model	97
6.1.4	Data content of Physical channels and Signals for N-TM	97
6.1.4.1	Reference signals	98
6.1.4.2	Synchronization signals	98
6.1.4.3	NPBCH	98
6.1.4.4	NPDCCH	98
6.1.4.5	NPDSCH	98
6.1.5	Test Model for NB-IoT guard band operation	99
6.1.6	Test Model for NB-IoT in-band operation	99
6.2	Base station output power	99
6.2.1	Definition and applicability	99
6.2.2	Minimum Requirement	100
6.2.3	Test purpose	100
6.2.4	Method of test	100
6.2.4.1	Initial conditions	100
6.2.4.2	Procedure	101
6.2.5	Test Requirements	101
6.2.6	Home BS output power for adjacent UTRA channel protection	102
6.2.6.1	Definition and applicability	102
6.2.6.2	Minimum Requirement	102
6.2.6.3	Test purpose	103
6.2.6.4	Method of test	103
6.2.6.4.1	Initial conditions	103
6.2.6.4.2	Procedure	103
6.2.6.5	Test Requirements	104
6.2.7	Home BS output power for adjacent E-UTRA channel protection	104
6.2.7.1	Definition and applicability	104
6.2.7.2	Minimum Requirement	105
6.2.7.3	Test purpose	105
6.2.7.4	Method of test	105
6.2.7.4.1	Initial conditions	105
6.2.7.4.2	Procedure	105
6.2.7.5	Test Requirements	106
6.2.8	Home BS output power for co-channel E-UTRA protection	106
6.2.8.1	Definition and applicability	106
6.2.8.2	Minimum Requirement	107
6.2.8.3	Test purpose	107
6.2.8.4	Method of test	107
6.2.8.4.1	Initial conditions	107
6.2.8.4.2	Procedure	108
6.2.8.5	Test Requirements	108
6.3	Output power dynamics	109
6.3.1	RE Power control dynamic range	109
6.3.1.1	Definition and applicability	109
6.3.1.2	Minimum Requirement	109
6.3.1.3	Method of test	109
6.3.2	Total power dynamic range	109
6.3.2.1	Definition and applicability	109
6.3.2.2	Minimum Requirement	109
6.3.2.3	Test purpose	109
6.3.2.4	Method of test	109
6.3.2.4.1	Initial conditions	109
6.3.2.4.2	Procedure	110
6.3.2.5	Test Requirement	110
6.3.3	NB-IoT RB power dynamic range for in-band or guard band operation	110
6.3.3.1	Definition and applicability	110
6.3.3.2	Minimum Requirement	110
6.3.3.3	Test purpose	111
6.3.3.4	Method of test	111
6.3.3.5	Test Requirement	111
6.4	Transmit ON/OFF power	111
6.4.1	Transmitter OFF power	111

6.4.1.1	Definition and applicability.....	111
6.4.1.2	Minimum Requirement	111
6.4.1.3	Test purpose	111
6.4.1.4	Method of test	111
6.4.1.4.1	Void.....	111
6.4.1.4.2	Void.....	111
6.4.1.5	Test requirement	111
6.4.2	Transmitter transient period.....	112
6.4.2.1	Definition and applicability.....	112
6.4.2.2	Minimum Requirement	112
6.4.2.3	Test purpose	112
6.4.2.4	Method of test	112
6.4.2.4.1	Initial conditions.....	112
6.4.2.4.2	Procedure.....	113
6.4.2.5	Test requirement	113
6.5	Transmitted signal quality.....	113
6.5.1	Frequency error.....	113
6.5.1.1	Definition and applicability.....	113
6.5.1.2	Minimum Requirement	113
6.5.1.3	Test purpose	113
6.5.1.4	Method of test	114
6.5.1.5	Test requirement	114
6.5.2	Error Vector Magnitude.....	114
6.5.2.1	Definition and applicability.....	114
6.5.2.2	Minimum Requirement	114
6.5.2.3	Test purpose	114
6.5.2.4	Method of test.....	114
6.5.2.4.1	Initial conditions.....	114
6.5.2.4.2	Procedure.....	115
6.5.2.5	Test requirement	115
6.5.3	Time alignment error.....	116
6.5.3.1	Definition and applicability.....	116
6.5.3.2	Minimum Requirement	116
6.5.3.3	Test Purpose.....	116
6.5.3.4	Method of Test.....	116
6.5.3.4.1	Initial Conditions.....	116
6.5.3.4.2	Procedure.....	117
6.5.3.5	Test Requirement	117
6.5.4	DL RS power.....	118
6.5.4.1	Definition and applicability.....	118
6.5.4.2	Minimum Requirement	118
6.5.4.3	Test purpose	118
6.5.4.4	Method of test	118
6.5.4.4.1	Initial conditions.....	118
6.5.4.4.2	Procedure.....	118
6.5.4.5	Test requirement	118
6.6	Unwanted emissions.....	119
6.6.1	Occupied bandwidth	119
6.6.1.1	Definition and applicability.....	119
6.6.1.2	Minimum Requirements.....	119
6.6.1.3	Test purpose	119
6.6.1.4	Method of test	119
6.6.1.4.1	Initial conditions.....	119
6.6.1.4.2	Procedure.....	120
6.6.1.5	Test requirements.....	121
6.6.2	Adjacent Channel Leakage power Ratio (ACLR)	121
6.6.2.1	Definition and applicability.....	121
6.6.2.2	Minimum Requirement	121
6.6.2.3	Test purpose	122
6.6.2.4	Method of test	122
6.6.2.4.1	Initial conditions.....	122
6.6.2.4.2	Procedure.....	122

6.6.2.5	Test Requirement	123
6.6.2.6	Cumulative ACLR test requirement in non-contiguous spectrum	125
6.6.3	Operating band unwanted emissions	127
6.6.3.1	Definition and applicability.....	127
6.6.3.2	Minimum Requirement	128
6.6.3.3	Test purpose	128
6.6.3.4	Method of test	128
6.6.3.4.1	Initial conditions	128
6.6.3.4.2	Procedure.....	128
6.6.3.5	Test requirement	129
6.6.3.5.1	Test requirements for Wide Area BS (Category A).....	130
6.6.3.5.2	Test requirements for Wide Area BS (Category B).....	134
6.6.3.5.2A	Test requirements for Local Area BS (Category A and B).....	140
6.6.3.5.2B	Test requirements for Home BS (Category A and B).....	142
6.6.3.5.2C	Test requirements for Medium Range BS (Category A and B).....	144
6.6.3.5.2D	Minimum requirements for Local Area and Medium Range BS in Band 46 (Category A and B).....	148
6.6.3.5.2E	Minimum requirements for stand-alone NB-IoT Wide Area BS.....	149
6.6.3.5.3	Additional requirements	150
6.6.4	Transmitter spurious emissions.....	153
6.6.4.1	Definition and applicability.....	153
6.6.4.2	Minimum Requirements.....	154
6.6.4.3	Test Purpose	154
6.6.4.4	Method of Test	154
6.6.4.4.1	Initial conditions	154
6.6.4.4.2	Procedure.....	154
6.6.4.5	Test requirements.....	155
6.6.4.5.1	Spurious emissions (Category A).....	155
6.6.4.5.2	Spurious emissions (Category B).....	155
6.6.4.5.3	Protection of the BS receiver of own or different BS	156
6.6.4.5.4	Co-existence with other systems in the same geographical area	156
6.6.4.5.5	Co-location with other base stations.....	169
6.7	Transmitter intermodulation	179
6.7.1	Definition and applicability.....	179
6.7.2	Minimum Requirement.....	179
6.7.2A	Additional requirement for Band 41	179
6.7.3	Test purpose.....	180
6.7.4	Method of test	180
6.7.4.1	Initial conditions	180
6.7.4.2	Procedures.....	180
6.7.5	Test Requirements	181
6.7.6	Additional test requirements for Band 41	181
7	Receiver characteristics	182
7.1	General	182
7.2	Reference sensitivity level.....	182
7.2.1	Definition and applicability	182
7.2.2	Minimum Requirement	182
7.2.3	Test purpose.....	182
7.2.4	Method of testing	182
7.2.4.1	Initial conditions	182
7.2.4.2	Procedure	183
7.2.5	Test requirement	183
7.3	Dynamic range	185
7.3.1	Definition and applicability	185
7.3.2	Minimum Requirement	185
7.3.3	Test purpose.....	185
7.3.4	Method of testing	185
7.3.4.1	Initial conditions	185
7.3.4.2	Procedure	185
7.3.5	Test Requirements	186
7.4	In-channel selectivity	189

7.4.1	Definition and applicability	189
7.4.2	Minimum Requirement	189
7.4.3	Test purpose	189
7.4.4	Method of testing	189
7.4.4.1	Initial conditions	189
7.4.4.2	Procedure	190
7.4.5	Test Requirements	191
7.5	Adjacent Channel Selectivity (ACS) and narrow-band blocking	193
7.5.1	Definition and applicability	193
7.5.2	Minimum Requirement	194
7.5.3	Test purpose	194
7.5.4	Method of test	194
7.5.4.1	Initial conditions	194
7.5.4.2	Procedure for Adjacent Channel Selectivity	194
7.5.4.3	Procedure for narrow-band blocking	195
7.5.5	Test Requirements	196
7.6	Blocking	202
7.6.1	Definition and applicability	202
7.6.2	Minimum Requirements	202
7.6.3	Test purpose	202
7.6.4	Method of test	202
7.6.4.1	Initial conditions	202
7.6.4.2	Procedure	203
7.6.5	Test Requirements	204
7.6.5.1	General requirement	204
7.6.5.2	Co-location with other base stations	212
7.7	Receiver spurious emissions	222
7.7.1	Definition and applicability	222
7.7.2	Minimum Requirements	222
7.7.3	Test purpose	222
7.7.4	Method of test	223
7.7.4.1	Initial conditions	223
7.7.4.2	Procedure	223
7.7.5	Test requirements	223
7.8	Receiver intermodulation	224
7.8.1	Definition and applicability	224
7.8.2	Minimum Requirement	224
7.8.3	Test purpose	224
7.8.4	Method of test	225
7.8.4.1	Initial conditions	225
7.8.4.2	Procedures	225
7.8.5	Test requirements	226
8	Performance requirement	233
8.1	General	233
8.2	Performance requirements for PUSCH	233
8.2.1	Performance requirements of PUSCH in multipath fading propagation conditions transmission on single antenna port	233
8.2.1.1	Definition and applicability	233
8.2.1.2	Minimum Requirement	234
8.2.1.3	Test Purpose	234
8.2.1.4	Method of test	234
8.2.1.4.1	Initial Conditions	234
8.2.1.4.2	Procedure	234
8.2.1.5	Test Requirement	234
8.2.1A	Performance requirements of PUSCH in multipath fading propagation conditions transmission on two antenna ports	246
8.2.1A.1	Definition and applicability	246
8.2.1A.2	Minimum Requirement	246
8.2.1A.3	Test Purpose	246
8.2.1A.4	Method of test	246
8.2.1A.4.1	Initial Conditions	246

8.2.1A.4.2	Procedure	246
8.2.1A.5	Test Requirement	247
8.2.2	Performance requirements for UL timing adjustment.....	249
8.2.2.1	Definition and applicability.....	249
8.2.2.2	Minimum Requirement	249
8.2.2.3	Test Purpose	249
8.2.2.4	Method of test	249
8.2.2.4.1	Initial Conditions	249
8.2.2.4.2	Procedure.....	249
8.2.2.5	Test Requirement	250
8.2.3	Performance requirements for HARQ-ACK multiplexed on PUSCH.....	251
8.2.3.1	Definition and applicability.....	251
8.2.3.2	Minimum Requirement	251
8.2.3.3	Test Purpose	251
8.2.3.4	Method of test	251
8.2.3.4.1	Initial Conditions	251
8.2.3.4.2	Procedure.....	251
8.2.3.5	Test Requirement	252
8.2.4	Performance requirements for High Speed Train conditions.....	253
8.2.4.1	Definition and applicability.....	253
8.2.4.2	Minimum Requirement	253
8.2.4.3	Test Purpose	253
8.2.4.4	Method of test	254
8.2.4.4.1	Initial Conditions	254
8.2.4.4.2	Procedure.....	254
8.2.4.5	Test Requirement	255
8.2.5	Performance requirements for PUSCH with TTI bundling and enhanced HARQ pattern.....	255
8.2.5.1	Definition and applicability.....	255
8.2.5.2	Minimum Requirement	256
8.2.5.3	Test Purpose	256
8.2.5.4	Method of test	256
8.2.5.4.1	Initial Conditions	256
8.2.5.4.2	Procedure.....	256
8.2.5.5	Test Requirement	257
8.2.6	Enhanced performance requirements type A of PUSCH in multipath fading propagation conditions with synchronous interference	257
8.2.6.1	Definition and applicability.....	257
8.2.6.2	Minimum Requirement	258
8.2.6.3	Test Purpose	258
8.2.6.4	Method of test	258
8.2.6.4.1	Initial Conditions	258
8.2.6.4.2	Procedure.....	258
8.2.6.5	Test Requirement	259
8.2.6A	Enhanced performance requirements type A of PUSCH in multipath fading propagation conditions with asynchronous interference	261
8.2.6A.1	Definition and applicability.....	261
8.2.6A.2	Minimum Requirement	262
8.2.6A.3	Test Purpose	262
8.2.6A.4	Method of test	262
8.2.6A.4.1	Initial Conditions	262
8.2.6A.4.2	Procedure.....	262
8.2.6A.5	Test Requirement	263
8.2.7	Performance requirements of PUSCH in multipath fading propagation conditions transmission on single antenna port for coverage enhancement.....	265
8.2.7.1	Definition and applicability.....	265
8.2.7.2	Minimum Requirement	265
8.2.7.3	Test Purpose	265
8.2.7.4	Method of test	265
8.2.7.4.1	Initial Conditions	265
8.2.7.4.2	Procedure.....	265
8.2.7.5	Test Requirement	266
8.3	Performance requirements for PUCCH.....	267

8.3.1	ACK missed detection for single user PUCCH format 1a transmission on single antenna port.....	267
8.3.1.1	Definition and applicability.....	267
8.3.1.2	Minimum Requirement	267
8.3.1.3	Test purpose	267
8.3.1.4	Method of test	267
8.3.1.4.1	Initial Conditions	267
8.3.1.4.2	Procedure.....	268
8.3.1.5	Test Requirement	268
8.3.2	CQI performance requirements for PUCCH format 2 transmission on single antenna port.....	269
8.3.2.1	Definition and applicability.....	269
8.3.2.2	Minimum Requirement	269
8.3.2.3	Test purpose	269
8.3.2.4	Method of test	269
8.3.2.4.1	Initial Conditions	269
8.3.2.4.2	Procedure.....	269
8.3.2.5	Test Requirement	270
8.3.3	ACK missed detection for multi user PUCCH format 1a	270
8.3.3.1	Definition and applicability.....	270
8.3.3.2	Minimum Requirement	270
8.3.3.3	Test purpose	271
8.3.3.4	Method of test	271
8.3.3.4.1	Initial Conditions	271
8.3.3.4.2	Procedure.....	271
8.3.3.5	Test Requirement	271
8.3.4	ACK missed detection for PUCCH format 1b with Channel Selection.....	272
8.3.4.1	Definition and applicability.....	272
8.3.4.2	Minimum Requirement	272
8.3.4.3	Test purpose	272
8.3.4.4	Method of test	272
8.3.4.4.1	Initial Conditions	272
8.3.4.4.2	Procedure.....	272
8.3.4.5	Test Requirement	273
8.3.5	ACK missed detection for PUCCH format 3.....	273
8.3.5.1	Definition and applicability.....	273
8.3.5.2	Minimum Requirement	274
8.3.5.3	Test purpose	274
8.3.5.4	Method of test	274
8.3.5.4.1	Initial Conditions	274
8.3.5.4.2	Procedure.....	274
8.3.5.5	Test Requirement	274
8.3.6	NACK to ACK detection for PUCCH format 3.....	275
8.3.6.1	Definition and applicability.....	275
8.3.6.2	Minimum Requirement	276
8.3.6.3	Test purpose	276
8.3.6.4	Method of test	276
8.3.6.4.1	Initial Conditions	276
8.3.6.4.2	Procedure.....	276
8.3.6.5	Test Requirement	276
8.3.7	ACK missed detection for PUCCH format 1a transmission on two antenna ports	277
8.3.7.1	Definition and applicability.....	277
8.3.7.2	Minimum Requirement	277
8.3.7.3	Test purpose	277
8.3.7.4	Method of test	277
8.3.7.4.1	Initial Conditions	277
8.3.7.4.2	Procedure.....	277
8.3.7.5	Test Requirement	278
8.3.8	CQI performance requirements for PUCCH format 2 transmission on two antenna ports.....	278
8.3.8.1	Definition and applicability.....	278
8.3.8.2	Minimum Requirement	278
8.3.8.3	Test purpose	279
8.3.8.4	Method of test	279
8.3.8.4.1	Initial Conditions	279

8.3.8.4.2	Procedure.....	279
8.3.8.5	Test Requirement.....	279
8.3.9	CQI performance requirements for PUCCH format 2 with DTX detection.....	280
8.3.9.1	Definition and applicability.....	280
8.3.9.2	Minimum Requirement.....	280
8.3.9.3	Test purpose.....	280
8.3.9.4	Method of test.....	280
8.3.9.4.1	Initial Conditions.....	280
8.3.9.4.2	Procedure.....	280
8.3.9.5	Test Requirement.....	281
8.3.10	ACK missed detection for PUCCH format 1a transmission on single antenna port for coverage enhancement.....	281
8.3.10.1	Definition and applicability.....	281
8.3.10.2	Minimum Requirement.....	282
8.3.10.3	Test purpose.....	282
8.3.10.4	Method of test.....	282
8.3.10.4.1	Initial Conditions.....	282
8.3.10.4.2	Procedure.....	282
8.3.10.5	Test Requirement.....	283
8.3.11	CQI performance requirements for PUCCH format 2 transmission on single antenna port for coverage enhancement.....	283
8.3.11.1	Definition and applicability.....	283
8.3.11.2	Minimum Requirement.....	283
8.3.11.3	Test purpose.....	283
8.3.11.4	Method of test.....	284
8.3.11.4.1	Initial Conditions.....	284
8.3.11.4.2	Procedure.....	284
8.3.11.5	Test Requirement.....	284
8.3.12	ACK missed detection for PUCCH format 4.....	285
8.3.12.1	Definition and applicability.....	285
8.3.12.2	Minimum Requirement.....	285
8.3.12.3	Test purpose.....	285
8.3.12.4	Method of test.....	286
8.3.12.4.1	Initial Conditions.....	286
8.3.12.4.2	Procedure.....	286
8.3.12.5	Test Requirement.....	286
8.3.13	ACK missed detection for PUCCH format 5.....	287
8.3.13.1	Definition and applicability.....	287
8.3.13.2	Minimum Requirement.....	287
8.3.13.3	Test purpose.....	287
8.3.13.4	Method of test.....	288
8.3.13.4.1	Initial Conditions.....	288
8.3.13.4.2	Procedure.....	288
8.3.13.5	Test Requirement.....	288
8.4	Performance requirements for PRACH.....	289
8.4.1	PRACH false alarm probability and missed detection.....	289
8.4.1.1	Definition and applicability.....	289
8.4.1.2	Minimum Requirement.....	289
8.4.1.3	Test purpose.....	289
8.4.1.4	Method of test.....	289
8.4.1.4.1	Initial Conditions.....	289
8.4.1.4.2	Procedure.....	289
8.4.1.5	Test Requirement.....	290
8.5	Performance requirements for Narrowband IoT.....	292
8.5.1	Performance requirements for NPUSCH format 1.....	292
8.5.1.2	Minimum Requirement.....	292
8.5.1.3	Test Purpose.....	292
8.5.1.4	Method of test.....	292
8.5.1.5	Test Requirement.....	293
8.5.2	ACK missed detection for NPUSCH format 2.....	294
8.5.2.1	Definition and applicability.....	294
8.5.2.2	Minimum Requirement.....	294

8.5.2.3	Test purpose	295
8.5.2.4	Method of test	295
8.5.2.4.1	Initial Conditions	295
8.5.2.4.2	Procedure.....	295
8.5.2.5	Test Requirement	295
8.5.3	Performance requirements for NPRACH	296
8.5.3.1	Definition and applicability.....	296
8.5.3.2	Minimum Requirement	297
8.5.3.3	Test purpose	297
8.5.3.4	Method of test	297
8.5.3.4.1	Initial Conditions	297
8.5.3.4.2	Procedure.....	297
8.5.3.5	Test Requirement	297
9	Channel access procedures.....	298
9.1	Downlink channel access procedure.....	298
9.1.1	Definition and applicability	298
9.1.2	Minimum requirement	298
9.1.3	Test purpose.....	298
9.1.4	Method of test	298
9.1.4.1	Initial conditions	298
9.1.4.2	Procedure	298
9.1.5	Test Requirements	299
Annex A (normative):	Reference Measurement channels.....	300
A.0	General	300
A.1	Fixed Reference Channels for reference sensitivity and in-channel selectivity (QPSK, R=1/3).....	301
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	301
A.3	Fixed Reference Channels for performance requirements (QPSK 1/3)	302
A.4	Fixed Reference Channels for performance requirements (16QAM 3/4).....	302
A.5	Fixed Reference Channels for performance requirements (64QAM 5/6)	303
A.6	PRACH Test preambles	303
A.7	Fixed Reference Channels for UL timing adjustment (Scenario 1)	304
A.8	Fixed Reference Channels for UL timing adjustment (Scenario 2)	304
A.9	Multi user PUCCH test.....	305
A.10	PUCCH transmission on two antenna ports test.....	305
A.11	Fixed Reference Channel for PUSCH with TTI bundling and enhanced HARQ pattern	305
A.14	Fixed Reference Channels for NB-IOT reference sensitivity ($\pi/2$ BPSK, R=1/3).....	306
A.14.1	Void.....	307
A.15	Fixed Reference Channels for NB-IoT dynamic range ($\pi/4$ QPSK, R=2/3).....	307
A.16	Fixed Reference Channels for NB-IoT NPUSCH format 1	308
A.16.1	One PRB.....	308
Annex B (normative):	Propagation conditions.....	309
B.1	Static propagation condition.....	309
B.2	Multi-path fading propagation conditions	309
B.3	High speed train condition	310
B.4	Moving propagation conditions.....	311
B.5	Multi-Antenna channel models	312
B.5.1	Definition of MIMO Correlation Matrices.....	312

B.5.2	MIMO Correlation Matrices at High, Medium and Low Level	313
B.5A	Multi-Antenna channel models using cross polarized antennas.....	315
B.5A.1	Definition of MIMO Correlation Matrices using cross polarized antennas.....	316
B.5A.2	Spatial Correlation Matrices at UE and eNB sides.....	316
B.5A.2.1	Spatial Correlation Matrices at UE side.....	316
B.5A.2.2	Spatial Correlation Matrices at eNB side.....	317
B.5A.3	MIMO Correlation Matrices using cross polarized antennas	317
B.6.1	Dominant interferer proportion	318
B.6.2	Interference model for synchronous scenario.....	318
B.6.3	Interference model for asynchronous scenario.....	318
Annex C (normative):	Characteristics of the interfering signals.....	319
Annex D (normative):	Environmental requirements for the BS equipment	320
D.1	General	320
D.2	Normal test environment.....	320
D.3	Extreme test environment.....	320
D.3.1	Extreme temperature	320
D.4	Vibration.....	321
D.5	Power supply	321
D.6	Measurement of test environments.....	321
Annex E (normative):	General rules for statistical testing.....	322
Annex F (normative):	Global In-Channel TX Test.....	323
F.1	General	323
F.2.1	Basic principle.....	323
F.2.2	Output signal of the TX under test.....	323
F.2.3	Reference signal.....	323
F.2.4	Measurement results.....	323
F.2.5	Measurement points	324
F.3.1	Pre FFT minimization process.....	324
F.3.2	Timing of the FFT window	325
F.3.3	Resource Element TX power.....	325
F.3.4	Post FFT equalisation.....	326
F.4.1	EVM.....	327
F.4.2	Averaged EVM	328
F.4.2.1	Averaged EVM (TDD).....	329
Annex G (informative):	Test Tolerances and Derivation of Test Requirements	330
G.1	Measurement of transmitter.....	331
G.2	Measurement of receiver	337
G.3	Measurement of Performance Requirements	342
Annex H (Informative):	E-UTRAN Measurement Test Cases.....	345
Annex I (Informative):	Measurement system set-up.....	346
I.1	Transmitter	346
I.1.1	Base station output power, output power dynamics, transmitted signal quality, Frequency error, EVM, DL RS power, Unwanted emissions.....	346
I.1.2	Transmitter intermodulation.....	346
I.1.3	Time alignment error.....	347
I.1.4	Home BS output power for adjacent channel protection.....	347
I.1.5	Home BS output power for co-channel E-UTRA protection	347

I.2	Receiver.....	348
I.2.1	Reference sensitivity level.....	348
I.2.2	Dynamic range	349
I.2.3	In-channel selectivity	349
I.2.4	Adjacent Channel Selectivity (ACS) and narrowband blocking	350
I.2.5	Blocking characteristics	350
I.2.6	Receiver spurious emission	351
I.2.7	Intermodulation characteristics	351
I.3	Performance requirement	352
I.3.1	Performance requirements for PRACH in static conditions	352
I.3.2	Performance requirements for PUSCH, PRACH, single user PUCCH in multipath fading conditions and for High Speed Train conditions	352
I.3.3	Performance requirements for multi user PUCCH in multipath fading conditions	353
I.3.4	Performance requirement for UL timing adjustment.....	353
I.3.5	Performance requirements for PUCCH transmission on two antenna ports in multipath fading conditions	354
I.3.6	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	355
I.3.7	Enhanced performance requirements type A of PUSCH in multipath fading propagation conditions with synchronous or asynchronous interference.....	356
I.4	Channel access procedures.....	360
Annex J (Informative): Unwanted emission requirements for multi-carrier BS		361
J.1	General	361
J.2	Multi-carrier BS of different E-UTRA channel bandwidths.....	361
J.3	Multi-carrier BS of E-UTRA and UTRA.....	361
Annex K (informative): Change history		362
History	ETSI TS 136 141 V13.16.0 (2021-04)	374

<https://standards.iteh.ai/catalog/standards/sist/96cbf043-22bc-418e-9ce7-c04f707b3e4b/etsi-ts-136-141-v13-16-0-2021-04>