



**Universal Mobile Telecommunications System (UMTS);
LTE;
(standards; iteh.ai)**
**IP Multimedia Subsystem (IMS);
Multimedia telephony;
Media handling and interaction
(3GPP TS 26.114 version 15.8.0 Release 15)**



Reference

RTS/TSGS-0426114vf80

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITih STANDARD PREVIEW
(standards.iteh.ai)

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	15
Introduction	15
1 Scope	16
2 References	16
3 Definitions and abbreviations.....	23
3.1 Definitions	23
3.2 Abbreviations	24
4 System description	26
4.1 System	26
4.2 Client	27
4.3 MRFP and MGW	28
5 Media codecs.....	28
5.1 Media components	28
5.2 Codecs for MTSI clients in terminals.....	29
5.2.1 Speech.....	29
5.2.1.1 General codec requirements.....	29
5.2.1.2 Detailed codec requirements, AMR.....	29
5.2.1.3 Detailed codec requirements, AMR-WB	29
5.2.1.4 Detailed codec requirements, EVS.....	30
5.2.1.5 Offering multiple audio bandwidths and multiple channels.....	30
5.2.1.6 Codec preference order	30
5.2.2 Video	30
5.2.3 Real-time text.....	32
6 Media configuration	32
6.1 General	32
6.2 Session setup procedures.....	33
6.2.1 General.....	33
6.2.1a RTP profile negotiation	33
6.2.1a.1 General	33
6.2.1a.2 Using SDPCapNeg in SDP offer.....	33
6.2.1a.3 Answering to an SDP offer using SDPCapNeg	34
6.2.2 Speech.....	34
6.2.2.1 General	34
6.2.2.2 Generating SDP offers	35
6.2.2.3 Generating SDP answer	38
6.2.3 Video	46
6.2.3.1 Introduction.....	46
6.2.3.2 Common Session Setup Procedures.....	47
6.2.3.3 Coordination of Video Orientation (CVO)	48
6.2.3.4 Video Region-of-Interest (ROI)	48
6.2.3.5 RTP Retransmission.....	51
6.2.3.6 Forward Error Correction (FEC).....	51
6.2.4 Text.....	51
6.2.5 Bandwidth negotiation.....	52
6.2.5.1 General	52
6.2.5.2 Speech	54
6.2.5.3 Video.....	56
6.2.6 The Synchronization Info attribute "3gpp_sync_info"	57
6.2.7 Negotiated QoS parameters	58

6.2.7.1	General	58
6.2.7.2	Alignment of negotiated QoS parameters and b=AS bandwidth modifier	58
6.2.7.3	Alignment of negotiated QoS parameters and a=bw-info attribute	59
6.3	Session control procedures	59
7	Data transport	60
7.1	General	60
7.2	RTP profiles	60
7.3	RTCP usage	60
7.3.1	General	60
7.3.2	Speech	61
7.3.3	Video	62
7.3.4	Real-time text	63
7.3.5	Void	63
7.3.6	Reduced-Size RTCP	63
7.3.7	Video Region-of-Interest (ROI) Signaling	64
7.4	RTP payload formats for MTSI clients	67
7.4.1	General	67
7.4.2	Speech	67
7.4.3	Video	68
7.4.4	Real-time text	68
7.4.5	Coordination of Video Orientation	69
7.4.6	RTP Retransmission	71
7.4.7	Forward Error Correction (FEC)	71
7.5	Media flow	71
7.5.1	General	71
7.5.2	Media specific	71
7.5.2.1	Speech	71
7.5.2.1.1	General	71
7.5.2.1.2	Default operation	71
7.5.2.1.2.1	General	71
7.5.2.1.2.2	Codec Mode Requests	72
7.5.2.1.2.3	Frame aggregation and redundancy	72
7.5.2.1.3	HSPA	72
7.5.2.1.4	EGPRS	73
7.5.2.1.5	GIP	73
7.5.2.1.6	Initial codec mode for AMR and AMR-WB	73
7.5.2.1.7	E-UTRAN and NR	74
7.5.2.1.8	Initial codec mode for EVS	74
7.5.2.1.9	Dual-mono	74
7.5.2.2	Video	74
7.5.2.3	Text	74
7.5.3	Media synchronization	75
7.5.3.1	General	75
7.5.3.2	Text	75
7.5.4	ECN usage in RTP sessions	75
7.5.5	Handling of bit-rate variations	75
7.5.5.1	General	75
7.5.5.2	Video	76
7.5.5.3	Speech	76
8	Jitter buffer management in MTSI clients in terminals	76
8.1	General	76
8.2	Speech	76
8.2.1	Terminology	76
8.2.2	Functional requirements for jitter-buffer management	78
8.2.3	Minimum performance requirements for jitter-buffer management	78
8.2.3.1	General	78
8.2.3.2	Objective performance requirements	79
8.2.3.2.1	General	79
8.2.3.2.2	Jitter buffer delay criteria	79
8.2.3.2.3	Jitter induced concealment operations	80

8.2.3.3	Delay and error profiles	81
8.2.3.4	Speech material for JBM minimum performance evaluation.....	81
8.3	Video	81
8.4	Text	81
9	Packet-loss handling.....	82
9.1	General	82
9.2	Speech	82
9.2.1	General.....	82
9.2.2	Transmitting redundant frames	82
9.2.3	Receiving redundant frames	85
9.3	Video	86
9.3.1	General.....	86
9.3.2	Receiver behaviour	86
9.3.3	Sender behaviour	86
9.3.4	Recommendations for packet loss recovery mechanisms usage	87
9.4	Text	88
10	Adaptation	88
10.1	General	88
10.2	Speech	88
10.2.0	General.....	88
10.2.1	RTCP-APP with codec control requests	90
10.2.1.1	General	90
10.2.1.2	General Format of RTCP-APP packet with codec control requests.....	90
10.2.1.2a	Padding	91
10.2.1.3	Redundancy Request.....	91
10.2.1.4	Frame Aggregation Request.....	92
10.2.1.5	Codec Mode Request	92
10.2.1.6	Generation of RTP payloads for multiple codec control requests	93
10.2.1.7	EVS Primary Rate Request	94
10.2.1.8	EVS Bandwidth Request	95
10.2.1.9	EVS Channel Aware Request	95
10.2.1.10	EVS Primary mode to EVS AMR-WB IO mode Switching Request	96
10.2.1.11	EVS AMR-WB IO mode to EVS Primary mode Switching Request	97
10.2.2	Example use cases	97
10.2.3	SDP negotiation for RTCP-APP	99
10.3	Video	101
10.3.1	General.....	101
10.3.2	Signaling mechanisms	101
10.3.3	Adaptation triggers	102
10.3.4	Sender behavior, downswitching	103
10.3.4.1	Downswitching divided into phases.....	103
10.3.4.2	Rate reduction phase	103
10.3.4.3	Delay recovery phase	104
10.3.5	Sender behavior, up-switching.....	104
10.3.6	Receiver behavior, down-switching.....	104
10.3.7	Receiver behavior, up-switch.....	104
10.3.8	ECN triggered adaptation	105
10.4	Text	106
10.5	Explicit Congestion Notification.....	106
10.6	Using the a=bw-info attribute for adaptation	106
10.7	Access network bitrate recommendation.....	107
10.7.1	General.....	107
10.7.2	Relation to session signaling bitrate information.....	107
10.7.3	Use with dynamic bitrate adaptation.....	108
10.7.3.1	General	108
10.7.3.2	Adaptation of sent media	108
10.7.3.3	Adaptation of received media	111
10.7.4	Message mapping for LTE access	112
10.7.5	Message mapping for NR access	112
11	Front-end handling	112

11.1	General	112
12	Inter-working.....	113
12.1	General	113
12.2	3G-324M	114
12.2.1	General.....	114
12.2.2	Codec usage	114
12.2.2.1	General	114
12.2.2.2	Text	114
12.2.3	Payload format	114
12.2.4	MTSI media gateway trans-packetization.....	114
12.2.4.1	General	114
12.2.4.2	Speech de-jitter buffer.....	114
12.2.4.3	Video bitrate equalization	114
12.2.4.4	Data loss detection	115
12.2.4.5	Data integrity indication.....	115
12.2.4.6	Packet size considerations	115
12.2.4.6.0	General	115
12.2.4.6.1	The Maximum Receive SDU Size attribute "3gpp_MaxRecvSDUSize"	115
12.2.4.7	Setting RTP timestamps	116
12.2.4.8	Protocol termination.....	116
12.2.4.9	Media synchronization	116
12.2.5	Session control.....	116
12.3	GERAN/UTRAN CS inter-working.....	117
12.3.0	3G-324M	117
12.3.1	Codecs for MTSI media gateways.....	117
12.3.1.1	Speech interworking between 3GPP PS access and CS GERAN/UTRAN	117
12.3.1.1a	Speech inter-working between fixed access and CS GERAN/UTRAN.....	118
12.3.1.2	Text	118
12.3.2	RTP payload formats for MTSI media gateways.....	118
12.3.2.1	Speech.....	118
12.3.2.2	Text	119
12.3.3	Explicit Congestion Notification.....	120
12.3.4	Codec switching procedures with SRVCC.....	120
12.4	PSTN.....	120
12.4.1	3G-324M	120
12.4.2	Text.....	120
12.5	GIP inter-working.....	121
12.5.1	Text.....	121
12.5.2	Speech.....	121
12.6	Void.....	121
12.6.1	Void	121
12.6.2	Void	121
12.7	Inter-working with other IMS and non-IMS IP networks	121
12.7.1	General.....	121
12.7.2	Speech.....	122
12.7.2.1	General	122
12.7.2.2	Speech codecs and formats	122
12.7.2.2.1	MTSI MGW for interworking between MTSI client in terminal using 3GPP access and other IMS or non-IMS IP networks	122
12.7.2.2.2	MTSI MGW for interworking between MTSI client in terminal using fixed access and other IMS or non-IMS IP networks	122
12.7.2.2.3	Common procedures.....	123
12.7.2.3	Codec preference order for session negotiation	123
12.7.2.4	RTP profiles	123
12.7.2.5	RTP payload formats.....	123
12.7.2.6	Packetization	124
12.7.2.7	RTCP usage and adaptation	124
12.7.2.8	RTP usage	125
12.7.2.9	Session setup and session modification.....	125
12.7.2.10	Audio level alignment	125
12.7.3	Explicit Congestion Notification	126

12.7.4	Text.....	126
12.7.5	Inter-working IPv4 and IPv6 networks.....	126
12.8	MGW handling for NO_REQ interworking.....	126
13	Void.....	127
13a	Media types, codecs and formats used for MSRP transport.....	127
13a.1	General.....	127
13a.2	Difference relative to 3GPP TS 26.141.....	127
13a.2.1	Video.....	127
14	Supplementary services.....	128
14.1	General.....	128
14.2	Media formats and transport.....	128
14.3	Media handling in hold procedures.....	128
15	Network preference management object.....	128
15.1	General.....	128
15.2	Nodes Definition.....	129
15.3	Example Configuration of 3GPP MTSINP MO.....	141
16	Quality of Experience.....	143
16.1	General.....	143
16.2	Metrics Definition.....	143
16.2.1	Corruption duration metric.....	143
16.2.2	Successive loss of RTP packets.....	144
16.2.3	Frame rate.....	144
16.2.4	Jitter duration.....	145
16.2.5	Sync loss duration.....	145
16.2.6	Round-trip time.....	145
16.2.7	Average codec bitrate.....	146
16.2.8	Codec information.....	146
16.3	Metric Configuration.....	146
16.3.1	QoE metrics reporting management object.....	147
16.3.2	QoE metric reporting configuration.....	153
16.3.3	QoE reporting rule definition.....	153
16.4	Metrics Reporting.....	154
16.4.1	XML schema for QoE report message.....	155
16.4.2	Example XML for QoE report message.....	156
16.5	QoE Measurement Collection Functionalities.....	157
16.5.1	Configuration and reporting.....	157
16.5.2	XML configuration.....	158
17	Management of Media Adaptation.....	160
17.1	General.....	160
17.2	Media adaptation management object.....	160
17.3	Management procedures.....	183
17.3.1	Management of speech adaptation.....	183
17.3.2	Management of video adaptation.....	185
18	MTSI client in terminal using fixed access.....	187
18.1	General.....	187
18.2	Media codecs.....	187
18.2.1	General.....	187
18.2.2	Speech.....	187
18.2.2.1	Speech codecs.....	187
18.2.2.2	Error concealment procedures.....	188
18.2.2.3	Source controlled rate operation.....	188
18.2.3	Video.....	188
18.2.4	Real-time text.....	189
18.3	Media configuration.....	189
18.3.1	General.....	189
18.3.2	Session setup procedures.....	189
18.3.2.1	General.....	189

18.3.2.2	Speech	189
18.3.2.3	Video	190
18.3.2.4	Text	190
18.3.2.5	Bandwidth negotiation	190
18.3.3	Session control procedures	190
18.4	Data transport	191
18.4.1	General	191
18.4.2	Packetization	191
18.4.3	RTP payload format	191
18.5	Jitter buffer management	192
18.6	Packet-loss handling	192
18.7	Adaptation	192
18.8	Front-end handling	192
18.9	Supplementary services	192
19	Additional bandwidth information	193
19.1	General	193
19.2	Bandwidth properties	193
19.2.1	General description	193
19.2.2	Maximum Supported Bandwidth	194
19.2.3	Maximum Desired Bandwidth	194
19.2.4	Minimum Desired Bandwidth	195
19.2.5	Minimum Supported Bandwidth	195
19.2.6	IP version	195
19.2.7	Maximum Packet Rate	196
19.2.8	Minimum Packet Rate	196
19.3	SDP attribute	196
19.3.1	Definition	196
19.3.2	SDP grammar	197
19.3.3	Declarative use	198
19.3.4	Usage in offer/answer	198
19.4	Modifications of the bandwidth information by intermediate network nodes	199
Annex A (informative):	Examples of SDP offers and answers	201
A.1	SDP offers for speech sessions initiated by MTSI client in terminal	201
A.1.1	HSPA or unknown access technology	201
A.1.1.1	Only AMR-NB supported by MTSI client in terminal	201
A.1.1.2	AMR and AMR-WB are supported by MTSI client in terminal	202
A.1.1.2.1	One-phase approach	202
A.1.1.2.2	Two-phase approach	203
A.1.2	EGPRS	204
A.1.3	Generic Access	205
A.2	SDP offers for speech sessions initiated by media gateway	205
A.2.1	General	205
A.2.2	MGW between GERAN UE and MTSI	205
A.2.3	MGW between legacy UTRAN UE and MTSI	206
A.2.4	MGW between CS UE and MTSI	206
A.2.5	MGW between GERAN UE and MTSI when wideband speech is supported	207
A.3	SDP answers to SDP speech session offers	207
A.3.1	General	207
A.3.1a	SDP answer from an MTSI client in terminal when only narrowband speech was offered	208
A.3.2	SDP answer from an MTSI client in terminal	208
A.3.2a	SDP answer from a non-MTSI UE with AVP	209
A.3.3	SDP answer from an MTSI client in terminal supporting only AMR	210
A.3.4	SDP answer from an MTSI client in terminal using EGPRS access when both AMR and AMR-WB are supported	211
A.3.4a	SDP answer from an MTSI client in terminal using EGPRS access when only AMR is supported	212
A.3.4b	SDP answer from an MTSI client in terminal using WLAN	212
A.3.5	SDP answer from MTSI MGW supporting only one codec mode set for AMR and AMR-WB each	213
A.3.5a	SDP answer from MTSI MGW supporting only one codec mode set for AMR	215

A.3.6	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing UE on GERAN.....	215
A.3.7	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing legacy UE on UTRAN	216
A.4	SDP offers and answers for video sessions	217
A.4.1	Void.....	217
A.4.2	Void.....	217
A.4.2a	H.264/AVC	217
A.4.2b	High Granularity CVO example.....	219
A.4.2c	RTP Retransmission.....	219
A.4.2d	RTP Forward Error Correction (FEC).....	220
A.4.2e	SDP Examples with ROI.....	221
A.4.3	Void.....	227
A.4.4	Void.....	227
A.4.4a	H.264/AVC with "imageattr" attribute.....	227
A.4.4a.1	H.264/AVC with "imageattr" attribute – different image sizes in SDP offer and answer	229
A.4.4a.2	H.264/AVC with "imageattr" attribute – different payload type numbers in offer and answer	230
A.4.4b	H.264/AVC with "imageattr" attribute with multiple rtpmaps.....	231
A.4.5	H.264 with asymmetric video streams	233
A.4.6	H.264/AVC with "imageattr" attribute for non-CVO operation.....	234
A.4.7	H.264 (AVC) and H.265 (HEVC).....	236
A.4.7.1	MTSI client with 848x480 resolution 5 inch display.....	236
A.4.7.2	MTSI client with 1280x720 resolution 5 inch display.....	237
A.4.7.3	MTSI client with 848x480 resolution 10 inch display.....	238
A.4.7.4	MTSI client with 1280x720 resolution 10 inch display.....	239
A.4.8	H.264 (AVC) and H.265 (HEVC) with asymmetric video streams.....	240
A.5	SDP offers for text.....	241
A.5.1	T.140 with and without redundancy	241
A.6	SDP example with bandwidth information	243
A.6.1	General	243
A.6.2	SDP examples with bandwidth information declared with bandwidth modifiers.....	243
A.6.3	SDP examples giving additional bandwidth information using the a=bw-info attribute.....	244
A.7	SDP examples with "3gpp_sync_info" attribute	247
A.7.1	Synchronized streams.....	247
A.7.2	Nonsynchronized streams.....	247
A.8	SDP example with QoS negotiation.....	248
A.9	Void.....	252
A.9a	SDP offer/answer regarding the use of Reduced-Size RTCP.....	252
A.10	Examples of SDP offers and answers for inter-working with other IMS or non-IMS IP networks	253
A.10.1	General	253
A.10.2	Session initiated by MTSI client in terminal	253
A.10.2.1	SDP offers from an MTSI client in terminal.....	253
A.10.2.2	SDP offers modified by MTSI MGW when pre-emptively adding inter-working formats	254
A.10.2.3	SDP modified by MGW when adding inter-working formats only when the original SDP offer was rejected.....	255
A.11	Adding or removing a video component to/from an on-going video call session.....	257
A.12	SDP examples when using ECN	261
A.12.1	SDP examples when using ECN for speech.....	261
A.12.1.1	With RTP/AVP and zero RTCP bandwidth.....	261
A.12.1.2	With RTP/AVPF and non-zero RTCP bandwidth	262
A.12.1.3	With RTCP ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients	263
A.12.2	SDP examples when using ECN for video in RTP.....	264
A.12.2.1	Without RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports	264

A.12.2.2	With RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients	265
A.13	SDP examples for MTSI client in terminal using fixed access	266
A.13.1	General	266
A.13.2	SDP examples for PCM	266
A.13.3	SDP example for G.722.....	267
A.13.4	SDP example for EVS, AMR-WB, G.722, AMR, PCM and DTMF	267
A.14	SDP offers and answers for speech sessions with EVS	268
A.14.1	SDP offers initiated by MTSI client in terminal.....	268
A.14.1.1	Unknown access technology.....	268
A.14.1.2	EGPRS.....	269
A.14.1.3	NR/E-UTRAN/HSPA.....	270
A.14.1.4	Dual-mono	270
A.14.2	SDP offers initiated by media gateway	271
A.14.2.1	Network between MTSI using fixed access and MTSI modifying SDP offer to configure EVS AMR-WB IO mode.....	272
A.14.3	SDP answers from MTSI client in terminal	273
A.14.3.1	SDP answer from MTSI client in terminal when narrowband speech is negotiated	273
A.14.3.2	SDP answer from MTSI client in terminal when up to wideband speech is negotiated	273
A.14.3.3	SDP answer from MTSI client in terminal when only wideband speech is negotiated	274
A.14.3.4	SDP answer from MTSI client in terminal when up to super-wideband speech is negotiated	274
A.14.3.5	SDP answer from MTSI client in terminal when only super-wideband speech is negotiated	274
A.14.3.6	SDP answer from MTSI client in terminal using WLAN.....	275
A.14.3.7	SDP answer from MTSI client in terminal supporting dual-mono	275
A.14.3.8	SDP answer from MTSI client in terminal supporting dual-mono for send direction	275
A.14.3.9	SDP answer from MTSI client in terminal when SC-VBR is negotiated	276
A.14.4	SDP answers from MTSI client in terminal using fixed access.....	276
A.14.4.1	SDP answer from MTSI client in terminal using fixed access when narrowband speech is negotiated	276
A.14.4.2	SDP answer from MTSI client in terminal using fixed access when only wideband speech is negotiated.....	277
A.14.4.3	SDP answer from MTSI client in terminal using fixed access when only super-wideband speech is negotiated.....	277
Annex B (informative):	Examples of adaptation scenarios	279
B.1	Video bitrate adaptation	279
Annex C (informative):	Example adaptation mechanisms for speech.....	280
C.1	Example of feedback and adaptation for speech and video.....	280
C.1.1	Introduction	280
C.1.2	Signalling state considerations	281
C.1.3	Adaptation state machine implementations	283
C.1.3.1	General.....	283
C.1.3.2	Adaptation state machine with four states	285
C.1.3.3	Adaptation state machine with four states (simplified version without frame aggregation).....	288
C.1.3.4	Adaptation state machine with two states	290
C.1.3.5	Adaptation when using ECN	291
C.2	Example criteria for video bit rate feedback and adaptation.....	293
C.2.1	Introduction	293
C.2.2	Media sender side.....	294
C.2.3	Media receiver side	294
C.2.4	Video encoder bitrate adaptation, down-switch	294
C.2.5	Video encoder bitrate adaptation, receiver-driven up-switch.....	296
C.2.6	Video encoder bitrate adaptation, recovery phase.....	296
Annex D (informative):	Reference delay computation algorithm.....	298
Annex E (informative):	QoS profiles	300
E.1	General	300

E.2	Bi-directional speech (AMR12.2, IPv4, RTCP and MBR=GBR bearer).....	300
E.3	Void.....	301
E.4	Bi-directional real-time text (3 kbps, IPv4 or IPv6, RTCP and MBR=GBR bearer).....	302
E.5	Bi-directional speech (AMR-WB23.85, IPv4, RTCP and MBR=GBR bearer).....	304
E.6	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv4, RTCP and MBR=GBR bearer).....	304
E.7	Bi-directional speech (AMR12.2, IPv6, RTCP and MBR=GBR bearer).....	305
E.8	Bi-directional speech (AMR-WB23.85, IPv6, RTCP and MBR=GBR bearer).....	306
E.9	Void.....	307
E.10	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv6, RTCP and MBR=GBR bearer).....	307
E.11	Bi-directional speech (AMR, IPv4, RTCP and MBR>GBR bearer).....	308
E.12	Bi-directional speech (AMR-WB, IPv4, RTCP and MBR>GBR bearer).....	309
E.13	Void.....	310
E.14	Bi-directional video (H.264 AVC level 1.1, IPv4, RTCP and MBR>GBR bearer).....	310
E.15	Bi-directional speech (AMR, IPv6, RTCP and MBR>GBR bearer).....	311
E.16	Bi-directional speech (AMR-WB, IPv6, RTCP and MBR>GBR bearer).....	312
E.17	Void.....	313
E.18	Bi-directional video (H.264 AVC level 1.1, IPv6, RTCP and MBR>GBR bearer).....	313
E.19	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv4, RTCP and MBR=GBR bearer).....	314
E.20	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv6, RTCP and MBR=GBR bearer).....	315
E.21	Bi-directional video (H.264 AVC level 1.2, IPv4, RTCP and MBR>GBR bearer).....	317
E.22	Bi-directional video (H.264 AVC level 1.2, IPv6, RTCP and MBR>GBR bearer).....	320
E.23	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500 kbps, IPv6, RTCP and MBR=GBR bearer).....	321
E.24	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	322
E.25	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600 kbps, IPv6, RTCP and MBR=GBR bearer).....	323
E.26	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	324
E.27	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650 kbps, IPv6, RTCP and MBR=GBR bearer).....	325
E.28	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	326
E.29	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750 kbps, IPv6, RTCP and MBR=GBR bearer).....	327
E.30	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	328
E.31	Bi-directional speech (EVS 13.2, IPv4, RTCP and MBR=GBR bearer).....	329
E.32	Bi-directional speech (EVS 24.4, IPv4, RTCP and MBR=GBR bearer).....	330
E.33	Bi-directional speech (EVS 13.2, IPv6, RTCP and MBR=GBR bearer).....	331
E.34	Bi-directional speech (EVS 24.4, IPv6, RTCP and MBR=GBR bearer).....	332

Annex F (Normative):	Void	334
Annex G (Normative):	DTMF events	335
G.1	General	335
G.2	Encoding of DTMF events	335
G.3	Session setup	335
G.4	Data transport for DTMF events	337
Annex H (informative):	Network Preference Management Object Device Description Framework	339
Annex I (informative):	QoE Reporting Management Object Device Description Framework ...	340
Annex J (informative):	Media Adaptation Management Object Device Description Framework	341
Annex K (informative):	Computation of b=AS for AMR and AMR-WB	342
K.1	General	342
K.2	Procedure for computing the bandwidth	342
K.3	Computation of RTP payload size.....	342
K.4	Detailed computation	343
Annex L (Normative):	Facsimile transmission	352
L.1	General	352
L.2	FoIP support in MTSI clients	352
L.2.1	FoIP support in MTSI client in terminal 126.114.V15.8.0(2021-05)	352
L.2.2	FoIP support in MTSI MGW 126.114.V15.8.0(2021-05)	352
L.2.3	Recommended configuration 3gpp-standards.itech.ai/catalog/standards/sist/c8290c78-ac87-4d74-a5e0-0028f715943/etsi-ts-126-114-v15-8-0-2021-05	352
L.3	Session setup	353
L.3.1	Session setup for any MTSI client supporting facsimile transmission	353
L.3.2	Session setup when the recommended profile is supported	353
L.4	Data transport using UDP/IP	354
L.5	CS GERAN inter-working	354
L.6	PSTN inter-working	355
L.7	SDP examples	355
L.7.1	Facsimile-only session	355
Annex M (informative):	IANA registration information for SDP attributes.....	357
M.1	Introduction	357
M.2	3gpp_sync_info	357
M.3	3gpp_MaxRecvSDUSize.....	357
M.4	3gpp_mtsi_app_adapt.....	358
M.5	predefined_ROI.....	358
M.6	bw-info	359
M.7	ccc_list.....	360
Annex N (informative):	Computation of b=AS for Video Codec	361
N.1	General	361

N.2	Examples	361
Annex O (informative):	IANA registration information for RTP Header Extensions.....	362
O.1	Introduction	362
O.2	urn:3gpp:video-orientation	362
O.3	urn:3gpp:video-orientation:6.....	362
O.4	urn:3gpp:roi-sent	363
O.5	urn:3gpp:predefined-roi-sent.....	363
Annex P (informative):	Video packet loss handling operation principles and examples	364
P.1	General	364
P.2	Video error recovery	364
P.3	RTP Retransmission.....	366
Annex Q (informative):	Computation of b=AS for EVS.....	368
Q.1	General	368
Q.2	Procedure for computing the bandwidth	368
Q.3	Computation of RTP payload size.....	368
Q.4	Detailed computation	369
Annex R (informative):	IANA registration information for RTCP Feedback Message Types.....	372
R.1	Video Region-of-Interest (ROD).....	372
Annex S (normative):	Multi-party Multimedia Conference Media Handling.....	373
S.1	General	373
S.2	Video	373
S.2.1	Conversational video.....	373
S.2.2	Non-conversational (screenshot) video	373
S.3	Audio.....	373
S.3.1	General	373
S.3.2	De-jitter buffer.....	374
S.4	SIP	374
S.4.1	MSMTSI client in terminal	374
S.4.2	MSMTSI MRF	374
S.5	Media configuration	375
S.5.1	General	375
S.5.2	Main video.....	376
S.5.3	Thumbnail video	376
S.5.4	Screenshot video.....	377
S.5.5	Audio.....	377
S.5.6	BFCP.....	377
S.5.7	Compact Concurrent Codec Negotiation and Capabilities	377
S.5.7.1	General.....	377
S.5.7.2	The Compact CCC SDP Attribute	377
S.5.7.3	Using the Compact CCC SDP Attribute for CCC Exchange.....	378
S.5.7.4	Using the Compact CCC SDP Attribute for Session Initiation.....	379
S.5.7.4.1	General.....	379
S.5.7.4.2	SDP Offer Rules.....	379
S.5.7.4.3	SDP Answer Rules.....	379
S.6	Media transport	379

S.6.1	RTP	379
S.6.2	RTCP	380
S.6.3	RTP Stream Selective Forwarding	380
S.7	BFCP	381
S.7.1	General	381
S.7.2	Floor controlled main video	381
S.7.3	Floor controlled screenshare video	381
S.7.4	Implicit floor control for audio	382
S.7.5	Floor control interworking with DTMF-capable MTSI clients	382
S.8	Rate Adaptation	382
Annex T (informative): SDP examples for Multi-party Multimedia Conference Media Handling		
		383
T.1	General	383
T.1.1	Introduction	383
T.1.2	Quality of Service examples	383
T.2	MSMTSI video offer/answer examples	384
T.2.1	MSMTSI offer/answer towards an MTSI client	384
T.2.2	MSMTSI answer from an MSMTSI MRF	386
T.2.3	MSMTSI answer from an MSMTSI client in terminal	389
T.2.4	MSMTSI simulcast offer using a single payload type	390
T.2.5	MSMTSI simulcast offer using two codecs	391
T.3	MSMTSI audio offer/answer examples	392
T.3.1	MSMTSI offer with multi-stream audio support	392
T.3.2	MSMTSI answer with multi-stream audio support	393
T.3.3	MSMTSI CCCEx SDP offer/answer example	396
T.3.3a	MSMTSI offer/answer examples using the compact CCC SDP attribute	400
T.3.4	SIP OPTIONS request for multi-stream audio support	404
Annex U (informative): IANA registration information for media types		
		405
U.1	Introduction	405
U.2	application/ccce	405
Annex V (informative): Change history		
		406
History	411