

ETSI TS 138 101-1 V16.7.0 (2021-05)



**5G;
NR;
User Equipment (UE) radio transmission and reception;
Part 1: Range 1 Standalone
(3GPP TS 38.101-1 version 16.7.0 Release 16)**



Reference

RTS/TSGR-0438101-1vg70

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITih STANDARD PREVIEW
(standards.itech.ai)

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	16
1 Scope	18
2 References	18
3 Definitions, symbols and abbreviations	18
3.1 Definitions	18
3.2 Symbols.....	19
3.3 Abbreviations	21
4 General	23
4.1 Relationship between minimum requirements and test requirements	23
4.2 Applicability of minimum requirements	23
4.3 Specification suffix information.....	23
5 Operating bands and channel arrangement.....	24
5.1 General	24
5.2 Operating bands.....	24
5.2A Operating bands for CA	26
5.2A.0 General.....	26
5.2A.1 Intra-band CA	26
5.2A.2 Inter-band CA	27
5.2A.2.1 Inter-band CA (two bands).....	27
5.2A.2.2 Inter-band CA (three bands).....	31
5.2A.2.3 Inter-band CA (four bands).....	31
5.2B Operating bands for DC	32
5.2C Operating band combination for SUL	32
5.2D Operating bands for UL MIMO	32
5.2E Operating band for V2X.....	33
5.2E.1 V2X operating bands	33
5.2E.2 V2X operating bands for con-current operation	33
5.3 UE channel bandwidth	34
5.3.1 General.....	34
5.3.2 Maximum transmission bandwidth configuration	34
5.3.3 Minimum guardband and transmission bandwidth configuration.....	34
5.3.4 RB alignment.....	36
5.3.5 UE channel bandwidth per operating band.....	37
5.3.6 Asymmetric channel bandwidths	39
5.3A UE channel bandwidth for CA	40
5.3A.1 General.....	40
5.3A.2 Maximum transmission bandwidth configuration for CA	40
5.3A.3 Minimum guardband and transmission bandwidth configuration for CA	41
5.3A.4 Void	42
5.3A.5 UE channel bandwidth per operating band for CA.....	42
5.3E Channel bandwidth for V2X	43
5.3E.1 General.....	43
5.3E.2 Channel bandwidth for V2X concurrent operation.....	44
5.4 Channel arrangement.....	44
5.4.1 Channel spacing.....	44
5.4.1.1 Channel spacing for adjacent NR carriers	44
5.4.2 Channel raster	44
5.4.2.1 NR-ARFCN and channel raster.....	44
5.4.2.2 Channel raster to resource element mapping.....	45
5.4.2.3 Channel raster entries for each operating band	45

5.4.3	Synchronization raster	47
5.4.3.1	Synchronization raster and numbering.....	47
5.4.3.3	Synchronization raster entries for each operating band.....	48
5.4.4	TX–RX frequency separation	51
5.4A	Channel arrangement for CA.....	51
5.4A.1	Channel spacing for CA.....	51
5.4A.2	Channel raster for CA	52
5.4A.3	Synchronization raster for CA	52
5.4A.4	Tx-Rx frequency separation for CA.....	52
5.4B	Reserved	52
5.4C	Reserved	52
5.4D	Reserved	52
5.4E	Channel arrangement for V2X	52
5.4E.1	Channel spacing.....	52
5.4E.2	Channel raster	53
5.4E.2.1	NR-ARFCN and channel raster.....	53
5.4E.2.2	Channel raster to resource element mapping.....	53
5.4E.2.3	Channel raster entries for each operating band	53
5.4E.3	Synchronization raster for V2X.....	53
5.5	Void.....	53
5.5A	Configurations for CA.....	53
5.5A.0	General.....	53
5.5A.1	Configurations for intra-band contiguous CA.....	54
5.5A.3	Configurations for inter-band CA.....	57
5.5A.3.1	Configurations for inter-band CA (two bands)	57
5.5A.3.2	Configurations for inter-band CA (three bands)	69
5.5A.3.3	Configurations for inter-band CA (four bands)	77
5.5B	Configurations for DC.....	80
5.5C	Configurations for SUL.....	81
6	Transmitter characteristics	83
6.1	General	83
6.1A	General	83
6.2	Transmitter power	83
6.2.1	UE maximum output power	83
6.2.2	UE maximum output power reduction.....	85
6.2.3	UE additional maximum output power reduction.....	88
6.2.3.1	General	88
6.2.3.2	A-MPR for NS_04	93
6.2.3.3	A-MPR for NS_10	94
6.2.3.4	A-MPR for NS_05 and NS_05U.....	94
6.2.3.5	A-MPR for NS_40	97
6.2.3.6	A-MPR for NS_43 and NS_43U.....	97
6.2.3.7	A-MPR for NS_03 and NS_03U.....	98
6.2.3.8	A-MPR for NS_37	99
6.2.3.9	A-MPR for NS_38	99
6.2.3.10	A-MPR for NS_39	100
6.2.3.11	A-MPR for NS_41	100
6.2.3.12	A-MPR for NS_42	101
6.2.3.13	A-MPR for NS_18	101
6.2.3.14	A-MPR for NS_21	102
6.2.3.15	A-MPR for NS_24	102
6.2.3.16	A-MPR for NS_27	103
6.2.3.17	A-MPR for NS_46	104
6.2.3.18	A-MPR for NS_47	105
6.2.3.19	A-MPR for NS_50	106
6.2.3.20	A-MPR for NS_44	106
6.2.3.21	A-MPR for NS_12	107
6.2.3.22	A-MPR for NS_13	107
6.2.3.23	A-MPR for NS_14	108
6.2.3.24	A-MPR for NS_15	109
6.2.3.25	A-MPR for NS_45	109

6.2.3.26	A-MPR for NS_48	110
6.2.3.27	A-MPR for NS_49	110
6.2.3.28	A-MPR for NS_51	111
6.2.4	Configured transmitted power	112
6.2A	Transmitter power for CA	114
6.2A.1	UE maximum output power for CA	114
6.2A.1.1	UE maximum output power for Intra-band contiguous CA	114
6.2A.1.2	UE maximum output power for Intra-band non-contiguous CA	114
6.2A.1.3	UE maximum output power for Inter-band CA	115
6.2A.1.4	Void	118
6.2A.1.5	Void	118
6.2A.2	UE maximum output power reduction for CA	118
6.2A.2.1	UE maximum output power reduction for Intra-band contiguous CA	118
6.2A.2.2	UE maximum output power reduction for Intra-band non-contiguous CA	120
6.2A.2.2.1	MPR _{IM3} to meet -30dBm/MHz	120
6.2A.2.2.2	MPR _{IM3} to meet -13dBm/MHz	121
6.2A.2.3	UE maximum output power reduction for Inter-band CA	121
6.2A.2.4	Void	121
6.2A.3	UE additional maximum output power reduction for CA	121
6.2A.3.1.1	UE additional maximum output power reduction for Intra-band contiguous CA	121
6.2A.3.1.1.1	A-MPR for CA_NS_04	122
6.2A.3.1.2	UE additional maximum output power reduction for Intra-band non-contiguous CA	128
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA	130
6.2A.4	Configured output power for CA	130
6.2A.4.1	Configured transmitted power level	130
6.2A.4.1.1	Configured transmitted power for Intra-band contiguous CA	130
6.2A.4.1.2	Configured transmitted power for Intra-band non-contiguous CA	132
6.2A.4.1.3	Configured transmitted power for Inter-band CA	134
6.2A.4.1.4	Void	136
6.2A.4.2	$\Delta T_{IB,c}$ for CA	136
6.2A.4.2.1	Void	136
6.2A.4.2.2	Void	136
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA (two bands)	136
6.2A.4.2.4	$\Delta T_{IB,c}$ for Inter-band CA (three bands)	141
6.2A.4.2.5	$\Delta T_{IB,c}$ for Inter-band CA (four bands)	144
6.2B	Transmitter power for NR-DC	144
6.2B.0	General	144
6.2B.1	UE maximum output power for NR-DC	144
6.2B.2	UE maximum output power reduction for NR-DC	145
6.2B.3	UE additional maximum output power reduction for NR-DC	145
6.2B.4	Configured output power for NR-DC	145
6.2B.4.1	Configured transmitted power level for NR-DC	145
6.2B.4.2	$\Delta T_{IB,c}$ for NR-DC	148
6.2C	Transmitter power for SUL	148
6.2C.1	Configured transmitted power for SUL	148
6.2C.2	$\Delta T_{IB,c}$	148
6.2D	Transmitter power for UL MIMO	149
6.2D.1	UE maximum output power for UL MIMO	149
6.2D.2	UE maximum output power reduction for UL MIMO	150
6.2D.3	UE additional maximum output power reduction for UL MIMO	151
6.2D.4	Configured transmitted power for UL MIMO	151
6.2E	Transmitter power for V2X	152
6.2E.1	UE maximum output power for V2X	152
6.2E.1.1	General	152
6.2E.1.2	UE maximum output power for V2X con-current operation	152
6.2E.2	UE maximum output power reduction for V2X	153
6.2E.2.1	General	153
6.2E.2.2	MPR for Power class 3 V2X UE	153
6.2E.2.3	MPR for Power class 3 V2X con-current operation	154
6.2E.3	UE additional maximum output power reduction for V2X	154
6.2E.3.1	General	154
6.2E.3.2	A-MPR for Power class 3 V2X UE by NS_33	155

6.2E.3.3	A-MPR for Power class 3 V2X UE by NS_52	157
6.2E.3.4	A-MPR for power class 3 V2X con-current operation.....	158
6.2E.4	Configured transmitted power for V2X.....	158
6.2E.4.1	General.....	158
6.2E.4.2	Configured transmitted power for V2X con-current operation	159
6.2F	Transmitter power for shared spectrum channel access	160
6.2F.1	UE maximum output power.....	160
6.2F.1A	UE maximum output power for CA.....	161
6.2F.1A.1	UE maximum output power for inter-band CA.....	161
6.2F.2	UE maximum output power reduction.....	161
6.2F.2A	UE maximum output power reduction for CA.....	162
6.2F.2A.1	UE maximum output power reduction for inter-band CA.....	162
6.2F.3	UE additional maximum output power reduction.....	162
6.2F.3.1	General.....	162
6.2F.3.2	A-MPR for NS_28	163
6.2F.3.3	A-MPR for NS_29	164
6.2F.3.4	A-MPR for NS_30	164
6.2F.3.5	A-MPR for NS_31	165
6.2F.3.6	A-MPR for NS_53.....	165
6.2F.3.7	A-MPR for NS_54.....	166
6.2F.3A	UE additional maximum output power reduction for CA.....	166
6.2F.3A.1	UE additional maximum output power reduction for inter-band CA.....	166
6.2F.4	Configured transmitted power	167
6.3	Output power dynamics.....	167
6.3.1	Minimum output power	167
6.3.2	Transmit OFF power.....	167
6.3.3	Transmit ON/OFF time mask.....	168
6.3.3.1	General	168
6.3.3.2	General ON/OFF time mask	168
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries.....	168
6.3.3.4	PRACH time mask.....	169
6.3.3.5	Void.....	170
6.3.3.6	SRS time mask.....	170
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks.....	171
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	173
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	173
6.3.4	Power control.....	174
6.3.4.1	General	174
6.3.4.2	Absolute power tolerance.....	174
6.3.4.3	Relative power tolerance.....	174
6.3.4.4	Aggregate power tolerance.....	175
6.3A	Output power dynamics for CA	175
6.3A.1.1	Minimum output power for intra-band contiguous CA.....	175
6.3A.1.2	Minimum output power for intra-band non-contiguous CA	175
6.3A.1.3	Minimum output power for inter-band CA	176
6.3A.1.4	Void.....	176
6.3A.2	Transmit OFF power for CA.....	176
6.3A.2.1	Transmit OFF power for intra-band contiguous CA	176
6.3A.2.2	Transmit OFF power for intra-band non-contiguous CA.....	176
6.3A.2.3	Transmit OFF power for inter-band CA.....	176
6.3A.2.4	Void.....	176
6.3A.3	Transmit ON/OFF time mask for CA	176
6.3A.3.1	Transmit ON/OFF time mask for intra-band contiguous CA.....	176
6.3A.3.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	176
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA	176
6.3A.3.3.1	General	176
6.3A.3.3.2	Time mask for switching between two uplink carriers	176
6.3A.3.4	Void.....	177
6.3A.4	Power control for CA.....	177
6.3A.4.1	Power control for intra-band contiguous CA	177
6.3A.4.1.1	Absolute power tolerance	177

6.3A.4.1.2	Relative power tolerance	178
6.3A.4.1.3	Aggregate power control tolerance.....	178
6.3A.4.2	Power control for intra-band non-contiguous CA	178
6.3A.4.2.1	Absolute power tolerance.....	178
6.3A.4.2.1.1	Minimum requirements	178
6.3A.4.2.2	Relative power tolerance.....	178
6.3A.4.2.2.1	Minimum requirements	178
6.3A.4.2.3	Aggregate power control tolerance	179
6.3A.4.3	Power control for inter-band CA.....	179
6.3A.4.4	Void.....	179
6.3B	Output power dynamics for NR-DC.....	179
6.3C	Output power dynamics for SUL	179
6.3C.1	Void	179
6.3C.2	Void	179
6.3C.3	Transmit ON/OFF time mask for SUL	179
6.3C.3.1	Time mask for switching between two uplink carriers.....	179
6.3D	Output power dynamics for UL MIMO	180
6.3D.1	Minimum output power for UL MIMO	180
6.3D.2	Transmit OFF power for UL MIMO.....	180
6.3D.3	Transmit ON/OFF time mask for UL MIMO	180
6.3D.4	Power control for UL MIMO.....	181
6.3E	Output power dynamics for V2X	181
6.3E.1	Minimum output power for V2X.....	181
6.3E.1.1	General	181
6.3E.1.2	Minimum output power for V2X con-current operation.....	181
6.3E.2	Transmit OFF power for V2X	181
6.3E.2.1	General	181
6.3E.2.2	Transmit OFF power for V2X con-current operation	182
6.3E.3	Transmit ON/OFF time mask for V2X.....	182
6.3E.3.1	General	182
6.3E.3.2	General time mask.....	182
6.3E.3.3	S-SSB time mask	182
6.3E.3.4	Transmit ON/OFF time mask for V2X con-current operation	183
6.3E.4	Power control for V2X.....	183
6.3E.4.1	General	183
6.3E.4.2	Absolute power tolerance.....	183
6.3E.4.3	Power control for V2X con-current operation.....	183
6.3F	Output power dynamics for shared spectrum channel access.....	183
6.3F.1	Minimum output power	183
6.3F.2	Transmit OFF power.....	184
6.3F.3	Transmit ON/OFF time mask	184
6.3F.3.1	General	184
6.3F.3.2	General ON/OFF time mask	184
6.3F.3A	General ON/OFF mask for CA	184
6.3F.3A.1	General ON/OFF mask for inter-band CA	184
6.3F.4	Power control.....	184
6.3F.4.1	General	184
6.3F.4.2	Absolute power tolerance.....	185
6.3F.4.3	Relative power tolerance.....	185
6.3F.4.4	Aggregate power tolerance.....	185
6.4	Transmit signal quality	185
6.4.1	Frequency error.....	185
6.4.2	Transmit modulation quality.....	185
6.4.2.1	Error Vector Magnitude	185
6.4.2.1a	Error Vector Magnitude including symbols with transient period	186
6.4.2.2	Carrier leakage	187
6.4.2.3	In-band emissions	187
6.4.2.4	EVM equalizer spectrum flatness	188
6.4.2.4.1	Requirements for Pi/2 BPSK modulation.....	189
6.4A	Transmit signal quality for CA.....	190
6.4A.1	Frequency error for CA.....	190
6.4A.1.1	Frequency error for intra-band contiguous CA	190

6.4A.1.2	Frequency error for intra-band non-contiguous CA.....	190
6.4A.1.3	Frequency error for inter-band CA.....	190
6.4A.1.4	Void.....	191
6.4A.2	Transmit modulation quality for CA.....	191
6.4A.2.1	Transmit modulation quality for intra-band contiguous CA	191
6.4A.2.1.1	Error Vector Magnitude.....	191
6.4A.2.1.2	In-band emissions	191
6.4A.2.1.3	Carrier leakage.....	194
6.4A.2.2	Transmit modulation quality for intra-band non-contiguous CA	194
6.4A.2.2.1	Error Vector Magnitude	194
6.4A.2.2.2	In-band emissions	194
6.4A.2.3	Transmit modulation quality for inter-band CA.....	195
6.4A.2.4	Void.....	195
6.4B	Transmit signal quality for NR-DC.....	195
6.4D	Transmit signal quality for UL MIMO.....	195
6.4D.1	Frequency error for UL MIMO.....	195
6.4D.2	Transmit modulation quality for UL MIMO.....	195
6.4D.2.1	Error Vector Magnitude	196
6.4D.2.2	Carrier leakage	196
6.4D.2.3	In-band emissions	196
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	196
6.4D.3	Time alignment error for UL MIMO	196
6.4D.4	Requirements for coherent UL MIMO	196
6.4E	Transmit signal quality for V2X.....	197
6.4E.1	Frequency error for V2X	197
6.4E.1.1	General.....	197
6.4E.1.2	Frequency error for V2X con-current operation.....	197
6.4E.2	Transmit modulation quality for V2X	197
6.4E.2.1	General.....	197
6.4E.2.2	Error Vector Magnitude for V2X.....	197
6.4E.2.3	Carrier leakage for V2X.....	197
6.4E.2.4	In-band emissions for V2X.....	197
6.4E.2.5	EVM equalizer spectrum flatness for V2X.....	198
6.4E.2.6	Transmit modulation quality for V2X con-current operation.....	198
6.4F	Transmit signal quality for shared spectrum channel access.....	198
6.4F.1	Frequency error.....	198
6.4F.2	Transmit modulation quality.....	198
6.4F.2.1	Error Vector Magnitude	198
6.4F.2.2	Carrier leakage	198
6.4F.2.3	In-band emissions	198
6.4F.2.4	EVM equalizer spectrum flatness	199
6.4F.2A	Transmit modulation quality for CA.....	199
6.4F.2A.1	Transmit modulation quality for inter-band CA.....	199
6.5	Output RF spectrum emissions.....	200
6.5.1	Occupied bandwidth	200
6.5.2	Out of band emission	200
6.5.2.1	General	200
6.5.2.2	Spectrum emission mask.....	200
6.5.2.3	Additional spectrum emission mask	201
6.5.2.3.1	Requirements for network signalling value "NS_35".....	201
6.5.2.3.2	Requirements for network signalling value "NS_04".....	202
6.5.2.3.3	Requirements for network signalling value "NS_03" and "NS_21".....	202
6.5.2.3.4	Requirements for network signalling value "NS_06".....	203
6.5.2.3.5	Void.....	204
6.5.2.3.6	Void.....	204
6.5.2.3.7	Void.....	204
6.5.2.3.8	Requirements for network signalled value "NS_27"	204
6.5.2.4	Adjacent channel leakage ratio	204
6.5.2.4.1	NR ACLR.....	204
6.5.2.4.2	UTRA ACLR	205
6.5.3	Spurious emissions	205
6.5.3.1	General spurious emissions.....	206

6.5.3.2	Spurious emissions for UE co-existence	206
6.5.3.3	Additional spurious emissions	214
6.5.3.3.1	Requirement for network signalling value "NS_04"	214
6.5.3.3.2	Requirement for network signalling value "NS_17"	215
6.5.3.3.3	Requirement for network signalling value "NS_18"	215
6.5.3.3.4	Requirement for network signalling value "NS_05"	215
6.5.3.3.5	Requirement for network signalling value "NS_43"	215
6.5.3.3.6	Requirement for network signalling value "NS_37"	216
6.5.3.3.7	Requirement for network signalling value "NS_38"	216
6.5.3.3.8	Requirement for network signalling value "NS_39"	216
6.5.3.3.9	Requirement for network signalling value "NS_40"	216
6.5.3.3.10	Requirement for network signalling value "NS_41"	217
6.5.3.3.11	Requirement for network signalling value "NS_42"	217
6.5.3.3.12	Requirement for network signalling value "NS_21"	217
6.5.3.3.13	Requirement for network signalling value "NS_24"	217
6.5.3.3.14	Requirement for network signalling value "NS_27"	218
6.5.3.3.15	Requirement for network signalling value "NS_47"	218
6.5.3.3.16	Requirement for network signalling value "NS_50"	218
6.5.3.3.17	Requirement for network signalled value "NS_12"	219
6.5.3.3.18	Requirement for network signalled value "NS_13"	219
6.5.3.3.19	Requirement for network signalled value "NS_14"	219
6.5.3.3.20	Requirement for network signalled value "NS_15"	219
6.5.3.3.21	Requirement for network signalled value "NS_45"	220
6.5.3.3.22	Requirement for network signalled values "NS_48" and "NS_51"	220
6.5.3.3.23	Requirement for network signalled value "NS_49"	220
6.5.3.3.24	Requirement for network signalled value "NS_44"	221
6.5.3.3.25	Requirement for network signalled value "NS_46"	221
6.5.4	Transmit intermodulation	221
6.5A	Output RF spectrum emissions for CA	222
6.5A.1	Occupied bandwidth for CA	222
6.5A.1.1	Void	222
6.5A.1.1a	Occupied bandwidth for Intra-band contiguous CA	222
6.5A.1.2	Occupied bandwidth for Intra-band non-contiguous CA	222
6.5A.1.3	Occupied bandwidth for Inter-band CA	222
6.5A.2	Out of band emission for CA	222
6.5A.2.1	General	222
6.5A.2.2	Spectrum emission mask	222
6.5A.2.2.1	Spectrum emission mask for intra-band contiguous C	222
6.5A.2.2.2	Spectrum emission mask for intra-band non-contiguous CA	223
6.5A.2.2.3	Spectrum emission mask for Inter-band CA	223
6.5A.2.2.4	Void	223
6.5A.2.3	Additional spectrum emission mask for CA	223
6.5A.2.3.1	Additional spectrum emission mask for intra-band contiguous CA	223
6.5A.2.3.1	Void	224
6.5A.2.3.2	Additional spectrum emission mask for Intra-band non-contiguous CA	224
6.5A.2.3.2.1	Minimum requirement (network signalled value "CA_NC_NS_04")	224
6.5A.2.3.3	Additional spectrum emission mask for Inter-band CA	224
6.5A.2.4	Adjacent channel leakage ratio	224
6.5A.2.4.1	NR ACLR	224
6.5A.2.4.2	UTRA ACLR	226
6.5A.3	Spurious emission for CA	226
6.5A.3.1	General spurious emissions	226
6.5A.3.2	Spurious emissions for UE co-existence	227
6.5A.3.2.1	Spurious emissions for UE co-existence for intra-band contiguous CA	227
6.5A.3.2.2	Spurious emissions for UE co-existence for intra-band non-contiguous CA	228
6.5A.3.2.3	Spurious emissions for UE co-existence for Inter-band CA	228
6.5A.3.2.4	Void	238
6.5A.3.2.5	Void	238
6.5A.3.2.6	Void	238
6.5A.3.3	Additional spurious emissions for CA	238
6.5A.3.3.1	Additional spurious emissions for intra-band contiguous CA	238
6.5A.4	Transmit intermodulation for CA	239

6.5A.4.2.1	Transmit intermodulation for intra-band contiguous CA	239
6.5A.4.2.2	Void.....	239
6.5B	Output RF spectrum emissions for NR-DC.....	239
6.5D	Output RF spectrum emissions for UL MIMO.....	239
6.5D.1	Occupied bandwidth for UL MIMO	239
6.5D.2	Out of band emission for UL MIMO	239
6.5D.3	Spurious emission for UL MIMO.....	240
6.5D.4	Transmit intermodulation for UL MIMO	240
6.5E	Output RF spectrum emissions for V2X	240
6.5E.1	Occupied bandwidth for V2X.....	240
6.5E.1.1	General	240
6.5E.1.2	Occupied bandwidth for V2X con-current operation.....	240
6.5E.2	Out of band emission for V2X.....	241
6.5E.2.1	General	241
6.5E.2.2	Spectrum emission mask.....	241
6.5E.2.2.1	General	241
6.5E.2.2.2	Spectrum emission mask for V2X con-current operation.....	241
6.5E.2.3	Additional Spectrum emission mask.....	241
6.5E.2.3.1	Requirements for network signalled value "NS_33".....	241
6.5E.2.3.2	Requirements for network signalled value "NS_52"	242
6.5E.2.4	Adjacent channel leakage ratio	242
6.5E.2.4.1	General	242
6.5E.2.4.2	ACLR for V2X con-current operation.....	242
6.5E.3	Spurious emissions for V2X.....	242
6.5E.3.1	General spurious emissions.....	242
6.5E.3.2	Spurious emissions for UE co-existence	243
6.5E.3.3	Spurious emissions for UE co-existence for V2X con-current operation	243
6.5E.3.4	Additional spurious emissions requirements for V2X	243
6.5E.3.4.1	General	243
6.5E.3.4.2	Requirements for network signalled value "NS_33"	244
6.5E.3.4.3	Void.....	244
6.5E.4	Transmit intermodulation	244
6.5E.4.1	General	244
6.5E.4.2	Transmit intermodulation for V2X con-current operation	244
6.5F	Output RF spectrum emissions.....	244
6.5F.1	Occupied bandwidth	244
6.5F.2	Out of band emission	245
6.5F.2.1	General	245
6.5F.2.2	Spectrum emission mask for operation with shared spectrum channel access.....	245
6.5F.2.2.1	Spectrum emission mask for non-transmitted channels.....	245
6.5F.2.3	Additional spectrum emission mask	246
6.5F.2.4	Adjacent channel leakage ratio	246
6.5F.2.4.1	Shared spectrum channel access ACLR	246
6.5F.2.4.2	Additional requirement for network signaled value "NS_29"	246
6.5F.3	Spurious emissions	246
6.5F.3.1	General spurious emissions.....	247
6.5F.3.2	Spurious emissions for UE co-existence	247
6.5F.3.3	Additional spurious emissions	247
6.5F.3.3.1	Requirement for network signalled value "NS_28".....	247
6.5F.3.3.2	Requirement for network signalled value "NS_29".....	247
6.5F.3.3.3	Requirement for network signalled value "NS_30".....	249
6.5F.3.3.4	Requirement for network signalled value "NS_31".....	250
6.5F.3.3.5	Requirements for network signalled value "NS_53" or "NS_54"	251
6.5F.4	Transmit intermodulation	251
6.6	Void.....	251
6.6E	Time alignment error.....	251
7	Receiver characteristics	252
7.1	General	252
7.1A	General	252
7.2	Diversity characteristics	253
7.3	Reference sensitivity	253

7.3.1	General.....	253
7.3.2	Reference sensitivity power level	253
7.3.3	$\Delta R_{IB,c}$	261
7.3A	Reference sensitivity for CA	262
7.3A.1	General.....	262
7.3A.2	Reference sensitivity power level for CA	262
7.3A.2.1	Reference sensitivity power level for Intra-band contiguous CA	262
7.3A.2.2	Reference sensitivity power level for Intra-band non-contiguous CA	262
7.3A.2.3	Reference sensitivity power level for Inter-band CA	263
7.3A.2.4	Void.....	263
7.3A.3	$\Delta R_{IB,c}$ for CA	263
7.3A.3.1	General	263
7.3A.3.2	$\Delta R_{IB,c}$ for Inter-band CA.....	263
7.3A.3.2.1	$\Delta R_{IB,c}$ for two bands	265
7.3A.3.2.2	Void.....	268
7.3A.3.2.3	$\Delta R_{IB,c}$ for three bands	268
7.3A.3.2.4	$\Delta R_{IB,c}$ for four bands.....	271
7.3A.4	Reference sensitivity exceptions due to UL harmonic interference for CA.....	271
7.3A.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA	276
7.3A.6	Reference sensitivity exceptions due to cross band isolation for CA	282
7.3B	Reference sensitivity for NR-DC	283
7.3C	Reference sensitivity for SUL	283
7.3C.1	General.....	283
7.3C.2	Reference sensitivity power level for SUL	283
7.3C.3	$\Delta R_{IB,c}$ for SUL	286
7.3C.3.1	General.....	286
7.3C.3.2	SUL band combination	286
7.3C.3.2.1	$\Delta R_{IB,c}$ for two bands	287
7.3D	Reference sensitivity for UL MIMO	287
7.3E	Reference sensitivity for V2X	287
7.3E.1	General.....	287
7.3E.2	Minimum requirements	287
7.3E.3	Reference sensitivity power level for V2X con-current operation.....	288
7.3F	Reference sensitivity for shared spectrum channel access	289
7.3F.1	General.....	289
7.3F.2	Reference sensitivity power level	289
7.3F.3	$\Delta R_{IB,c}$	290
7.3F.4	Intra-band contiguous shared spectrum channel access CA	291
7.3G.5	Inter-band CA with shared spectrum channel access.....	291
7.3G.5.1	Reference sensitivity exceptions due to UL harmonic interference	291
7.3F.5.2	Reference sensitivity exceptions due to cross band isolation.....	291
7.4	Maximum input level	292
7.4A	Maximum input level for CA	292
7.4A.1	Maximum input level for Intra-band contiguous CA.....	292
7.4A.2	Maximum input level for Intra-band non-contiguous CA	293
7.4A.3	Maximum input level for Inter-band CA	293
7.4B	Maximum input level for NR-DC	293
7.4D	Maximum input level for UL MIMO	293
7.4E	Maximum input level for V2X	293
7.4E.1	General.....	293
7.4E.2	Maximum input level for V2X con-current operation	294
7.5	Adjacent channel selectivity.....	294
7.5A	Adjacent channel selectivity for CA.....	298
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	298
7.5A.2	Adjacent channel selectivity Intra-band non-contiguous CA	300
7.5A.3	Adjacent channel selectivity Inter-band CA	301
7.5B	Adjacent channel selectivity for NR-DC.....	301
7.5D	Adjacent channel selectivity for UL MIMO.....	301
7.5E	Adjacent channel selectivity for V2X	301
7.5E.1	General.....	301
7.5E.2	Adjacent channel selectivity for V2X con-current operation.....	302
7.5F	Adjacent channel selectivity.....	302

7.5F.1	General.....	302
7.5F.2	Intra-band contiguous shared spectrum channel access CA	303
7.6	Blocking characteristics	304
7.6.1	General.....	304
7.6.2	In-band blocking.....	304
7.6.3	Out-of-band blocking.....	308
7.6.4	Narrow band blocking	311
7.6A	Blocking characteristics for CA	312
7.6A.1	General.....	312
7.6A.2	In-band blocking for CA.....	312
7.6A.2.1	In-band blocking for Intra-band contiguous CA	312
7.6A.2.2	In-band blocking for Intra-band non-contiguous CA	313
7.6A.2.3	In-band blocking for Inter-band CA.....	313
7.6A.3	Out-of-band blocking for CA.....	314
7.6A.3.1	Out-of-band blocking for Intra-band contiguous CA.....	314
7.6A.3.2	Out-of-band blocking for Intra-band non-contiguous CA.....	315
7.6A.3.3	Out-of-band blocking for Inter-band CA	315
7.6A.4	Narrow band blocking for CA	317
7.6A.4.1	Narrow band blocking for Intra-band contiguous CA.....	317
7.6A.4.2	Narrow band blocking for Intra-band non-contiguous CA	317
7.6A.4.3	Narrow band blocking for Inter-band CA	317
7.6B	Blocking characteristics for NR-DC.....	318
7.6C	Blocking characteristics for SUL	318
7.6C.1	General.....	318
7.6C.2	In-band blocking for SUL.....	318
7.6C.3	Out-of-band blocking for SUL.....	318
7.6C.4	Narrow band blocking for SUL.....	319
7.6D	Blocking characteristics for UL MIMO	319
7.6E	Blocking characteristics for V2X.....	319
7.6E.1	General.....	319
7.6E.2	In-band blocking.....	319
7.6E.2.1	General.....	319
7.6E.2.2	In-band blocking for V2X con-current operation.....	320
7.6E.3	Out-of-band blocking.....	320
7.6E.3.1	General.....	320
7.6E.3.2	Out-of-band blocking for V2X con-current operation	321
7.6F	Blocking characteristics	321
7.6F.1	General.....	321
7.6F.2	In-band blocking.....	321
7.6F.2.1	General.....	321
7.6F.2.2	Intra-band contiguous shared spectrum channel access CA.....	322
7.6F.3	Out-of-band blocking.....	323
7.6F.3.1	General.....	323
7.6F.3.2	Intra-band contiguous shared spectrum channel access CA.....	324
7.7	Spurious response.....	324
7.7A	Spurious response for CA.....	326
7.7A.1	Spurious response for Intra-band contiguous CA	326
7.7A.2	Spurious response for Intra-band non-contiguous CA	326
7.7A.3	Spurious response for Inter-band CA.....	326
7.7B	Spurious response for NR-DC.....	326
7.7D	Spurious response for UL MIMO.....	327
7.7E	Spurious response for V2X	327
7.7E.1	General.....	327
7.7E.2	Spurious response for V2X con-current operation.....	327
7.7F	Spurious response for shared spectrum channel access.....	327
7.7F.1	General.....	327
7.7F.2	Intra-band contiguous shared spectrum channel access CA	328
7.8	Intermodulation characteristics	328
7.8.1	General.....	328
7.8.2	Wide band Intermodulation	328
7.8A	Intermodulation characteristics for CA	331
7.8A.1	General.....	331

7.8A.2	Wide band intermodulation for CA	331
7.8A.2.1	Wide band intermodulation for Intra-band contiguous CA.....	331
7.8A.2.2	Wide band intermodulation for Intra-band non-contiguous CA.....	332
7.8A.2.3	Wide band intermodulation for Inter-band CA	332
7.8B	Intermodulation characteristics for NR-DC	332
7.8D	Intermodulation characteristics for UL MIMO	333
7.8E	Intermodulation characteristics for V2X	333
7.8E.1	General.....	333
7.8E.2	Wide band Intermodulation	333
7.8E.3	Intermodulation for V2X con-current operation	333
7.8F	Intermodulation characteristics for shared spectrum channel access	333
7.8F.1	General.....	333
7.8F.2	Wide band Intermodulation	334
7.9	Spurious emissions	334
7.9A	Spurious emissions for CA.....	335
7.9A.1	Void	335
7.9A.2	Void	335
7.9A.3	Spurious emissions for Inter-band CA.....	335
7.9B	Spurious emissions for NR-DC	335
Annex A (normative):	Measurement channels.....	336
A.1	General	336
A.2	UL reference measurement channels	336
A.2.1	General	336
A.2.2	Reference measurement channels for FDD	337
A.2.2.1	DFT-s-OFDM Pi/2-BPSK	337
A.2.2.2	DFT-s-OFDM QPSK	340
A.2.2.3	DFT-s-OFDM 16QAM	343
A.2.2.4	DFT-s-OFDM 64QAM	346
A.2.2.5	DFT-s-OFDM 256QAM	349
A.2.2.6	CP-OFDM QPSK	352
A.2.2.7	CP-OFDM 16QAM	355
A.2.2.8	CP-OFDM 64QAM	358
A.2.2.9	CP-OFDM 256QAM	361
A.2.3	Reference measurement channels for TDD.....	363
A.2.3.1	DFT-s-OFDM Pi/2-BPSK	364
A.2.3.2	DFT-s-OFDM QPSK	367
A.2.3.3	DFT-s-OFDM 16QAM	371
A.2.3.4	DFT-s-OFDM 64QAM	374
A.2.3.5	DFT-s-OFDM 256QAM	377
A.2.3.6	CP-OFDM QPSK	380
A.2.3.7	CP-OFDM 16QAM	383
A.2.3.8	CP-OFDM 64QAM	386
A.2.3.9	CP-OFDM 256QAM	389
A.3	DL reference measurement channels	392
A.3.1	General	392
A.3.2	DL reference measurement channels for FDD	393
A.3.2.1	General.....	393
A.3.2.2	FRC for receiver requirements for QPSK.....	393
A.3.2.3	FRC for maximum input level for 64QAM	396
A.3.2.4	FRC for maximum input level for 256 QAM	399
A.3.3	DL reference measurement channels for TDD.....	402
A.3.3.1	General.....	402
A.3.3.2	FRC for receiver requirements for QPSK.....	403
A.3.3.3	FRC for maximum input level for 64QAM	406
A.3.3.4	FRC for maximum input level for 256 QAM	409
A.4	CSI reference measurement channels.....	412
A.5	OFDMA Channel Noise Generator (OCNG)	412
A.5.1	OCNG Patterns for FDD	412

A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs.....	412
A.5.2	OCNG Patterns for TDD.....	412
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	412
A.6	Void.....	413
A.7	V2X reference measurement channels.....	413
A.7.1	General	413
A.7.2	FRC for maximum input level for QPSK.....	413
A.7.3	FRC for maximum input level for 64QAM.....	415
A.7.4	FRC for maximum input level for 256QAM.....	416
Annex B (informative):	Void	419
Annex C (informative):	Downlink physical channels.....	420
C.1	General	420
C.2	Setup.....	420
C.3	Connection	420
C.3.1	Measurement of Receiver Characteristics	420
Annex D (normative):	Characteristics of the interfering signal	422
D.1	General.....	422
D.2	Interference signals.....	422
Annex E (normative):	Environmental conditions	424
E.1	General	424
E.2	Environmental	424
E.2.1	Temperature	424
E.2.2	Voltage	424
E.2.3	Vibration.....	425
Annex F (normative):	Transmit modulation.....	426
F.0	General	426
F.1	Measurement Point.....	426
F.2	Basic Error Vector Magnitude measurement	426
F.3	Basic in-band emissions measurement.....	427
F.4	Modified signal under test.....	427
F.5	Window length	430
F.5.1	Timing offset	430
F.5.2	Window length	430
F.5.3	Window length for normal CP	430
F.5.4	Window length for Extended CP.....	431
F.5.5	Window length for PRACH	432
F.6	Averaged EVM	433
F.7	Spectrum Flatness	434
Annex G (informative):	Void	435
Annex H (informative):	Void	435
Annex I (informative):	Void	435
Annex J (informative):	Void	435