

ETSI TS 103 280 V2.6.1 (2021-07)



Lawful Interception (LI); Dictionary for common parameters (standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/662e7405-fb5d-402d-a434-528e04e0df32/etsi-ts-103-280-v2-6-1-2021-07>



Reference

RTS/LI-00210

Keywords

dictionary, lawful interception, security

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	8
3.3 Abbreviations	8
4 Release management	8
5 Parameter requirements.....	9
5.0 Introduction	9
5.1 Parameter attributes.....	9
5.2 Parameter naming conventions.....	9
5.3 Technology conventions.....	10
6 Parameter dictionary.....	10
6.1 LIID.....	10
6.2 UTCDateTime	11
6.3 UTCMicrosecondDateTime	11
6.4 QualifiedDateTime	11
6.5 QualifiedMicrosecondDateTime	11
6.6 InternationalE164	12
6.7 IMSI	12
6.8 IMEI	12
6.9 IMEICheckDigit.....	12
6.10 IMEISV	13
6.11 IPv4Address	13
6.12 IPv4CIDR.....	13
6.13 IPv6Address	13
6.14 IPv6CIDR.....	14
6.15 IPAddress	14
6.16 IPCIDR.....	14
6.17 TCPPort.....	15
6.18 TCPPortRange.....	15
6.19 UDPPort	15
6.20 UDPPortRange	16
6.21 Port	16
6.22 PortRange	16
6.23 IPAddressPort.....	17
6.24 IPAddressPortRange	17
6.25 MACAddress.....	17
6.26 EmailAddress	18
6.27 UUID	18
6.28 ISOCountryCode	18
6.29 ShortString	18
6.30 LongString.....	19
6.31 SIPURI	19
6.32 TELURI.....	19
6.33 WGS84CoordinateDecimal	19
6.34 WGS84LatitudeDecimal	20
6.35 WGS84LongitudeDecimal	20

6.36	WGS84CoordinateAngular	20
6.37	WGS84LatitudeAngular	21
6.38	WGS84LongitudeAngular	21
6.39	SUPIIMSI	21
6.40	SUPINAI	22
6.41	SUCI	22
6.42	PEIIMEI	22
6.43	PEIIMEICheckDigit	22
6.44	PEIIMEISV	23
6.45	GPSIMSISDN	23
6.46	GPSINAI	23
6.47	NAI	23
6.48	LDID	24
6.49	InternationalizedEmailAddress	24
7	Technical implementation	24
7.1	XSD	24
7.2	ASN.1	24
Annex A (normative):	XSD definition	26
Annex B (normative):	ASN.1 definition	30
Annex C (informative):	Change Request history	32
History		33

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ETSI TS 103 280 V2.6.1 \(2021-07\)](#)

<https://standards.iteh.ai/catalog/standards/sist/662e7405-fb5d-402d-a434-528e04e0df32/etsi-ts-103-280-v2-6-1-2021-07>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITih STANDARD PREVIEW
(standards.iteh.ai)

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Lawful Interception (LI).
<https://standards.iteh.ai/catalog/standards/sis/002e7409-1b3d-402a-a154-528e04e0df32/etsi-ts-103-280-v2-6-1-2021-07>

It contains also the XSD technical implementation as attachment to the original document available from the ETSI site.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document defines a dictionary of parameters that are commonly used in multiple TC LI specifications. Aside from defining a dictionary, the present document aims to provide technical means for other specifications to use. It is encouraged to use the present document in the development of new specifications.

It is foreseen that regular maintenance of the present document is required. As such, release management requirements will be defined.

Before accepting any new common parameter, the present document will provide a set of requirements the parameter has to comply to in order to become a common parameter.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 232-1: "Lawful Interception (LI); Handover Interface and Service-Specific Details (SSD) for IP delivery; Part 1: Handover specification for IP delivery"
- [2] W3C® Recommendation 5 April 2012: "W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes".
- [3] Recommendation ITU-T X.680: "Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation".
- [4] Recommendation ITU-T E.164: "The international public telecommunication numbering plan".
- [5] Recommendation ITU-T E.212: "The international identification plan for public networks and subscriptions".
- [6] ETSI TS 123 003: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; 5G; Numbering, addressing and identification (3GPP TS 23.003)".
- [7] ETSI TS 102 657: "Lawful Interception (LI); Retained data handling; Handover interface for the request and delivery of retained data".
- [8] IETF RFC 791: "Internet Protocol".
- [9] IETF RFC 4632: "Classless Inter-domain Routing (CIDR): The Internet Address Assignment and Aggregation Plan".
- [10] IETF RFC 8200: "Internet Protocol, Version 6 (IPv6) Specification".
- [11] IETF RFC 4291: "IP Version 6 Addressing Architecture".
- [12] IETF RFC 793: "Transmission Control Protocol".
- [13] IETF RFC 768: "User Datagram Protocol".

- [14] IEEE 802.3™: "IEEE Standard for Ethernet".
- [15] IETF RFC 5322: "Internet Message Format".
- [16] WHATWG community: "HTML Living standard".
- NOTE: Available at [HTML Standard \(whatwg.org\)](https://html.spec.whatwg.org/).
- [17] IETF RFC 4122: "A Universally Unique Identifier (UUID) URN Namespace".
- [18] ISO 3166-1: "Codes for the representation of names of countries and their subdivisions -- Part 1: Country codes".
- [19] IEEE 1003.1-2017™: "IEEE Standard for Information Technology--Portable Operating System Interface (POSIX(TM)) Base Specifications, Issue 7".
- [20] ISO/IEC 7812-1:2017: "Identification cards -- Identification of issuers -- Part 1: Numbering system".
- [21] IETF RFC 3261: "SIP: Session Initiation Protocol".
- [22] IETF RFC 3966: "The tel URI for Telephone Numbers".
- [23] NIMA Technical Report 8350.2: "Department of Defense World Geodetic System 1984, Its Definition and Relationships With Local Geodetic Systems".
- [24] ETSI TS 123 501: "5G; System architecture for the 5G System (5GS) (3GPP TS 23.501)".
- [25] ETSI TS 133 501: "5G; Security architecture and procedures for 5G System (3GPP TS 33.501)".
- [26] IETF RFC 7542: "The Network Access Identifier".
- [27] ETSI TS 124 501: "5G; Non-Access-Stratum (NAS) protocol for 5G System (5GS); Stage 3 (3GPP TS 24.501)". [ETSI TS 103 280 V2.6.1 \(2021-07\)](https://standards.ietf.ai/catalog/standards/sist/662e7405-fb5d-402d-a434-528e04e0df32/etsi-ts-103-280-v2-6-1-2021-07)
- [28] ETSI TS 103 120: "Lawful Interception (LI); Interface for warrant information". <https://standards.ietf.ai/catalog/standards/sist/662e7405-fb5d-402d-a434-528e04e0df32/etsi-ts-103-280-v2-6-1-2021-07>
- [29] W3C® Recommendation 16 August 2006: "Extensible Markup Language (XML) 1.1 (Second Edition)".
- [30] IETF RFC 6530: "Overview and Framework for Internationalized Email".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

3 Definition of terms, symbols and abbreviations

3.1 Terms

Void.

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

3GPP	3 rd Generation Partnership Project
ASCII	American Standard Code for Information Interchange
ASN.1	Abstract Syntax Notation One
CC	Content of Communication
CIDR	Classless Inter-Domain Routing
CSP	Communications Service Provider
GPSI	Generic Public Subscription Identifier
HEX	HEXadecimal
HI	Handover Interface
HI1	Handover Interface port 1 (for administrative information)
HI2	Handover Interface port 2 (for Intercept Related Information)
HI3	Handover Interface port 3 (for Content of Communication)
IEC	International Electrotechnical Commission
IEEE	Institute of Electrical and Electronics Engineers
IEI	Information Element Identifier
IETF	Internet Engineering Task Force
IMEI	International Mobile station Equipment Identity
IMEISV	International Mobile station Equipment Identity and Software Version number
IMSI	International Mobile Subscriber Identity
IP	Internet Protocol
IPv4	Internet Protocol version 4
IPv6	Internet Protocol version 6
IRI	Intercept Related Information
ISO	International Organization for Standardization
ITU-T	International Telecommunication Union – Telecommunication
LEA	Law Enforcement Agency
LDID	Lawful Disclosure IDentifier
LIID	Lawful Interception Identifier
MAC	Media Access Control
NAI	Network Access Identifier
NIMA	National Imagery and Mapping Agency
PEI	Permanent Equipment Identifier
POSIX	Portable Operating System Interface
RFC	Request For Comments
SIP	Session Initialization Protocol
SUCI	Subscription Concealed Identifier
SUPI	Subscription Permanent Identifier
TCP	Transmission Control Protocol
UDP	User Datagram Protocol
URI	Uniform Resource Identifier
UTC	Coordinated Universal Time
UUID	Universally Unique Identifier
WGS84	World Geodetic System 1984
XML	eXtended Markup Language
XSD	XML Schema Definition

4 Release management

This clause describes the release management requirements. The requirements are:

- The version of the present document is defined as <major>.<minor>.<patch>.

- The major version should be incremented when making a backwards incompatible change.
- The minor version should be incremented when adding backwards compatible functionality.
- The patch version should be incremented when fixing a backwards compatible bug.
- Once a major version has been incremented, the previous major version will be supported for 2 years after publication of the new version. Change requests issued to a version that is no longer supported will need to be issued for the latest supported major version.

5 Parameter requirements

5.0 Introduction

This clause describes the requirements a parameter should comply to in order to be specified as a common parameter.

5.1 Parameter attributes

Name

- The parameter should be assigned a unique name. The naming conventions used are described in clause 5.2.

Description

- A description of the parameter should be provided.

Usage guidance

- If there are circumstances in which additional usage guidance is applicable, use cases may be described in this attribute.

References to other specifications

- If the parameter is specified in another specification (such as an RFC), a reference to that specification shall be provided. If possible, the reference should point to the exact clause in the specification.

EXAMPLE: Specify one or more sample values of the parameter.

Technical means to define and validate the parameter

- If possible, provide a regular expression to specify the value that is accepted by this parameter. Implementations may be required to perform additional validation on the value. The regular expressions follow the IEEE POSIX [19], section 9 regular expression format but shall be limited to the regular expression capabilities supported by XSD [2] patterns, which are matched to the entire value and shall not start with the anchor '^' or end with the anchor '\$'.
- Define the parameter in the XSD [2] in clause 7.1. When converting a regular expression to an XSD [2] pattern, escape any XML [29] markup characters in the regular expression per XML [29] section 2.4 to create a valid XSD [2] pattern.
- Define the parameter in the ASN.1 [3] in clause 7.2.

5.2 Parameter naming conventions

Allowed characters

- The following characters are allowed: A-Z, a-z and 0-9.

Camel casing

- The name of the parameter is to be CamelCased, where the first character is uppercased. Any acronyms should be uppercased.

EXAMPLE:

- IPv4Address.
- SIPURI.
- EmailAddress.

5.3 Technology conventions

The used technologies defined in clause 7 may impose requirements that conflict with the requirements in clauses 5.1 and 5.2. In the case of a conflict and in exceptional cases, it is allowed to deviate from the requirements above.

6 Parameter dictionary

6.1 LIID

Name	LIID
Description	<p>For each target identity related to an interception measure, the authorized CSP operator shall assign a special Lawful Interception Identifier (LIID), which has been agreed between the LEA and the CSP. It is used within parameters of all HI interface ports.</p> <p>Using an indirect identification, pointing to a target identity makes it easier to keep the knowledge about a specific interception target limited within the authorized CSP operators and the handling agents at the LEA.</p> <p>The Lawful Interception Identifier LIID is a component of the CC delivery procedure and of the IRI records. It shall be used within any information exchanged at the Handover Interfaces HI2 and HI3 for identification and correlation purposes.</p> <p>The LIID format shall consist of alphanumeric characters. It might for example, among other information, contain a lawful authorization reference number, and the date, when the lawful authorization was issued.</p> <p>The authorized CSP shall either enter a unique LIID for each target identity of the interception subject or as a national option a single LIID for multiple target identities all pertaining to the same interception subject.</p> <p>EXAMPLE: The interception subject has a telephony service with three telephone numbers. The CSP enters for each telephone number an own LIID, or optionally enters one LIID for all three telephone numbers.</p> <p>If more than one LEA intercepts the same target identity, there shall be unique LIIDs assigned, relating to each LEA.</p>
Usage guidance	The LIID is defined as an OCTET STRING in ASN.1. This means it is possible to use binary octets or ASCII printable characters to express the LIID. To correctly handle this, the parameter accepts both variations.
References	ETSI TS 102 232-1 [1], clause 5.2.2.
Example	ZZZ123 (ASCII printable LIID) 46565527098f6bcd4621d373cade4e832627b4f6ff00ff00ff (Binary LIID, represented in HEX)
Regular expression	([!~]{1,25}) ([0-9a-f]{26,50})
XSD	LIID, simpleType
ASN.1	LIID, OCTET STRING

6.2 UTCDateTime

Name	UTCDateTime
Description	A UTC timestamp with second precision.
Usage guidance	-
References	W3C XML Schema Definition Language [2], section 3.3.7.
Example	2015-12-27T13:37:00Z
Regular expression	[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}Z
XSD	UTCDateTime, simpleType
ASN.1	Not defined

6.3 UTCMicrosecondDateTime

Name	UTCMicrosecondDateTime
Description	A UTC timestamp with microsecond precision.
Usage guidance	-
References	W3C XML Schema Definition Language [2], section 3.3.7.
Example	2015-12-27T13:37:00.012345Z
Regular expression	[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}\.[0-9]{6}Z
XSD	UTCMicrosecondDateTime, simpleType
ASN.1	Not defined

6.4 QualifiedDateTime

Name	QualifiedDateTime
Description	A timestamp with second precision and timezone qualifier.
Usage guidance	-
References	W3C XML Schema Definition Language 1.1 Part 2: Datatypes [2], section 3.3.7.
Example XML	2015-12-27T13:37:00+02:00
Example ASN.1	20151227133700+0200
Regular expression	[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(Z [+-][0-9]{2}:[0-9]{2})
XSD	QualifiedDateTime, simpleType
ASN.1	QualifiedDateTime, GeneralizedTime Timestamps shall be provided with a timezone qualifier. The fractional part of a second shall not be present. Local time format shall not be used.

6.5 QualifiedMicrosecondDateTime

Name	QualifiedMicrosecondDateTime
Description	A timestamp with microsecond precision and timezone qualifier.
Usage guidance	-
References	W3C XML Schema Definition Language 1.1 Part 2: Datatypes [2], section 3.3.7.
Example XML	2015-12-27T13:37:00.012345+02:00
Example ASN.1	20151227133700.012345+0200
Regular expression	[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}\.[0-9]{6}(Z [+-][0-9]{2}:[0-9]{2})
XSD	QualifiedMicrosecondDateTime, simpleType
ASN.1	QualifiedMicrosecondDateTime, GeneralizedTime Timestamps shall be provided with a timezone qualifier. The fractional part of a second with no more than 6 digits shall be present. Local time format shall not be used.

6.6 InternationalE164

Name	InternationalE164
Description	E.164 Number in fully international format, written as decimal digits.
Usage guidance	-
References	Recommendation ITU-T E.164 [4], clause 6.
Example	31612345678
Regular expression	[0-9]{1,15}
XSD	InternationalE164, simpleType
ASN.1	NumericString (SIZE(1..15))

6.7 IMSI

Name	IMSI
Description	International Mobile Subscriber Identity, written as decimal digits.
Usage guidance	-
References	Recommendation ITU-T E.212 [5], clause 6.1 3GPP TS 23.003 [6], clause 2.2 and clause 2.3.
Example	204081234567890
Regular expression	[0-9]{6,15}
XSD	IMSI, simpleType
ASN.1	NumericString (SIZE(6..15))

6.8 IMEI

iTeh STANDARD PREVIEW

Name	IMEI
Description	International Mobile station Equipment Identity, written as decimal digits without the Luhn check digit, annex B of ISO/IEC 7812-1 [20].
Usage guidance	To avoid implementation issues, the IMEI parameter explicitly excludes the Luhn check digit, annex B of ISO/IEC 7812-1 [20]. (See notes 1 and 2).
References	3GPP TS 23.003 [6], clause 6.
Example	35395803121326
Regular expression	[0-9]{14}
XSD	IMEI, simpleType
ASN.1	NumericString (SIZE(14))

NOTE 1: ETSI TS 102 657 [7], clause E.3 identifies potential issues with the inclusion/exclusion of the check digit. As such, the IMEI parameter is explicitly specified without the check digit.

NOTE 2: The IMEICheckDigit parameter can be used when the check digit is explicitly required.

6.9 IMEICheckDigit

Name	IMEICheckDigit
Description	International Mobile station Equipment Identity, written as decimal digits with the Luhn check digit, annex B of ISO/IEC 7812-1 [20].
Usage guidance	-
References	3GPP TS 23.003 [6], clause 6.
Example	35395803121326
Regular expression	[0-9]{15}
XSD	IMEICheckDigit, simpleType
ASN.1	NumericString (SIZE(15))