INTERNATIONAL STANDARD

IEC 60938-1

QC 280000

Edition 2.1

2006-11

Edition 2:1999 consolidated with amendment 1:2006

Fixed inductors for electromagnetic interference suppression –

Part 1:

Generic specification

50**>**38-1:1999

utps://standards.uteh.ai. / a/ \standards.vc/b /4d2/3-b0/c-4a49-830c-851bc2e4eb99/iec-60938-1-1999



Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- IEC Web Site (<u>www.iec.ch</u>)
- Catalogue of IEC publications

The on-line catalogue on the LEC web site (http://www.iec.ch/searchpub/cur_fut.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

• IEC Just Rublished

This summary of recently issued publications (http://www.iec.ch/online_news/ustp.b/jg_entry.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

Customer Service Centre

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: <u>custserv@iec.ch</u> Tel: +41 22 919 02 11 Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 60938-1

QC 280000

Edition 2.1

2006-11

Edition 2:1999 consolidated with amendment 1:2006

Fixed inductors for electromagnetic interference suppression –

Part 1:

Generic specification

12:1/2/12 (17/17) Hellisal

EX60\S8-1:1999

ttps://standards.iteh.ai 💛 a 🔪 stand_rds \c/b /4d2/3-b0/c-4a49-830c-851bc2e4eb99/iec-60938-1-199

© IEC 2006 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale International Electrotechnical Commission Международная Электротехническая Комиссия

CONTENTS

FC		DRD	
1		eral	
	1.1	Scope	
	1.2	Normative references	6
2	Technical data		
	2.1	Units and symbols	8
	2.2	Definitions	8
	2.3	Preferred values	11
	2.4	Marking	11
3	Quality assessment procedures		
	3.1	General	11
	3.2	Primary stage of manufacture	11
	3.3	Structurally similar inductors	11
	3.4	Qualification approval procedures	11
	3.5	Quality conformance inspection	12
	3.6	Alternative test methods	12
	3.7	Unchecked parameters	13
4	Test	and measurement procedure	13
	4.1	General	13
	4.2	Ctandard atmospharia condition	13
	4.3	Drying	14
	4.4		
	4.5	Insulation registance	16
	4.6	Voltage proof	18
	4.7	Inductance 12 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	21
	4.8	Insertion loss	5093821
	4.9	Robustness of terminations	
	4.10	Resistance to soldering hear	
	4.11	Solderability (applicable only for terminations intended to be soldered)	23
	4.12	Rapid change of temperature	
	4.13	Vibration	24
	4.14	Bump	24
	4.15	Shock	
		Container sealing	
	4.17	-	
	4.18	Damp heat, steady state	26
		Temperature rise	
	4.20	Endurance	27
	4.21		
	4.22	Active flammability	
		Solvent resistance of marking	
		Component solvent resistance	

in IEC 60410 for use within the IEC quality assessment system for electronic components (IECQ)29
Annex B (normative) Rules for the preparation of detail specifications for capacitors and resistors for electronic equipment
Annex C (normative) Requirements for earth inductors31
Figure 1 – Voltage proof test circuit19
Table 1 – Reference test: standard atmospheric conditions
Table 2 – Creepage distances and clearances15
Table 3 – Measuring voltage
Table 4 – Measuring points
Table 5 – Force 22
Table 6 – Torque
Table 7 – Number of cycles26
Table 8 – Severities and requirements
Table C.1 – Rated current related to minimum cross-sectional area of copper lead (mm²) of the earth inductor
iTex Sixn(a) (https://stapax.ax.iteh.ai)
Deciment Preview
//standards.iteh.av /a/o/stand_rds.vc/b_74d273-b07c-4a49-830c-851bc2e4eb99/iec-60938-1-1999

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED INDUCTORS FOR ELECTROMAGNETIC INTERFERENCE SUPPRESSION –

Part 1: Generic specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60938-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This consolidated version of IEC 60938-1 consists of the second edition (1999) [documents 40/1110/FDIS and 40/1136/RVD] and its amendment 1 (2006) [documents 40/1602/CDV and 40/1699A/RVC].

The technical content is therefore identical to the base edition and its amendment and has been prepared for user convenience.

It bears the edition number 2.1.

A vertical line in the margin shows where the base publication has been modified by amendment 1.

The QC number that appears on the front cover of this publication is the specification number in the IEC Quality Assessment System for Electronic Components (IECQ).

Annexes A, B and C form an integral part of this standard.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed,
- withdrawn,
- · replaced by a revised edition, or
- amended.



FIXED INDUCTORS FOR ELECTROMAGNETIC INTERFERENCE SUPPRESSION –

Part 1: Generic specification

1 General

1.1 Scope

This International Standard applies to inductors designed for electromagnetic interference suppression intended for use within, or associated with, electronic or electrical equipment and machines. It is restricted to inductors for which safety tests are appropriate.

The combination of two or more inductors within one enclosure is also included.

Inductors within the scope of this standard may also be used to protect apparatus and machines from electrical noise and voltage or current transients coming from either the supply or from other parts of the apparatus.

This standard does not necessarily apply in its entirety to inductors intended for use on motor vehicles, in aircraft or for marine applications.

1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

https://IEC 60027 (all parts), Letter symbols to be used in electrical technology 62e4eb99/jec-60938-1-1999

IEC 60050 (all parts), International Electrotechnical Vocabulary (IEV)

IEC 60062:1992, Marking codes for resistors and capacitors

IEC 60068 1:1988, Environmental testing – Part 1: General and guidance Amendment 1 (1992)

IEC 60068-2-1:1990, Environmental testing - Part 2: Tests - Tests A: Cold

Amendment 1 (1993)

Amendment 2 (1994)

IEC 60068-2-2:1974, Environmental testing - Part 2: Tests - Tests B: Dry Heat

Amendment 1 (1993)

Amendment 2 (1994)

IEC 60068-2-3:1969, Environmental testing – Part 2: Tests – Test Ca: Damp heat, steady state Amendment 1 (1984)

IEC 60068-2-6:1995, Environmental testing – Part 2: Tests – Test Fc: Vibration (sinusoidal)

IEC 60068-2-13:1983, Environmental testing – Part 2: Tests – Test M: Low air pressure

IEC 60068-2-14:1984, Environmental testing – Part 2: Tests – Test N: Change of temperature Amendment 1 (1986)

IEC 60068-2-17:1994, Environmental testing – Part 2: Tests – Test Q: Sealing

IEC 60068-2-20:1979, Environmental testing – Part 2: Tests – Test T: Soldering Amendment 2 (1987)

IEC 60068-2-21:1983, Environmental testing – Part 2: Tests – Test U: Robustness of terminations and integral mounting devices

Amendment 2 (1991)

Amendment 3 (1992)

IEC 60068-2-27:1987, Environmental testing - Part 2: Tests - Test Ea and guidance. Shock

IEC 60068-2-29:1987, Environmental testing - Part 2: Tests - Test Eb and guidance: Bump

IEC 60068-2-30:1980, Environmental testing – Part 2: Tests — Test Db and guidance: Damp heat, cyclic (12 + 12 hour cycle)
Amendment 1 (1985)

IEC 60068-2-45:1980, Environmental testing Rart 2: Tests XA and guidance: Immersion in cleaning solvents
Amendment 1 (1993)

IEC 60294:1969, Measurement of the dimensions of a cylindrical component having two axial terminations

IEC 60335-1:1991, Safety of household and similar electrical appliances – Part 1: General requirements

IEC 60410:1973, Sampling plans and procedures for inspection by attributes 1999/100-60938-1-1999

IEC 60617 (all parts), Graphical symbols for diagrams

IEC 60695-2-2:1991, Fire hazard testing – Section 2: Needle-flame test Amendment 1 (1994)

CISPR 17:1981, Methods of measurement of the suppression characteristics of passive radio interference filters and suppression components

IEC QC 001002-3:1998, Rules of Procedure of the IEC Quality Assessment System for Electronic Components (IECQ) – Part 3: Approval procedures

ISO 1000:1992, SI units and recommendations for the use of their multiples and of certain other units

2 Technical data

2.1 Units and symbols

Units, graphical symbols, letter symbols and terminology shall, whenever possible, be taken from the following publications:

IEC 60027

IEC 60050

IEC 60617

ISO 1000

When further items are required they shall be derived in accordance with the principles of the documents listed above.

2.2 Definitions

For the purpose of this International Standard, the following definitions apply.

2.2.1

type

a group of components having similar design features and the similarity of whose manufacturing techniques enables them to be grouped together either for qualification approval or for quality conformance inspection

They are generally covered by a single detail specification.

NOTE Components described in several detail specifications, may, in some cases, be considered as belonging to the same type.

2.2.2

style

X50**X**58-1:1999

a sub-division of a type, generally based on dimensional factors: 0c-851bc2e4eb99/jec-60938-1-1999

A style may include several variants, generally of a mechanical order

2.2.3

family (of electronic components)

a group of electronic components which predominantly displays a particular physical attribute and/or fulfils a defined function

2.2.4

sub-family (of electronic components)

a group of components within a family manufactured by similar technological methods

2.2.5

rated voltage (U_R)

rated voltage is either the maximum r.m.s. operating voltage of rated frequency or the maximum d.c. operating voltage which may be applied continuously to the terminations of the inductor at any temperature between the lower category temperature and the rated temperature

NOTE For inductors with only one winding, the rated voltage should only be applied between one terminal and any conducting surface with which the case is liable to come into contact in normal use. For inductors having more than one winding, the rated voltage may be applied across two individual windings.

2.2.6

category voltage ($U_{\rm C}$)

maximum voltage which may be applied continuously to an inductor at its upper category temperature

2.2.7

lower category temperature

minimum external surface temperature for which the inductor has been designed to operate continuously

2.2.8

upper category temperature

maximum external surface temperature for which the inductor has been designed to operate continuously

NOTE The external surface temperature can be affected by internal heating due to the lead-through current. The terminations are considered to be part of the external surface.

2.2.9

rated temperature

maximum ambient temperature at which an inductor can carry its rated current

2.2.10

rated current

maximum r.m.s. operating current at rated frequency or maximum d.c. operating current which allows continuous operation of the inductor at the rated temperature. It is assigned by the manufacturer for one or both of the following conditions:

- a) free air (I_{RO}) ;
- b) with a specified heat sink (IRH)

2.2.11

rated inductance (LR)

inductance value for which the inductor has been designed and which is usually indicated upon it

2.2.12

insertion loss

ratio of the voltage before and after the insertion of the suppressor in the circuit as measured at the terminations

- NOTE 1 The insertion loss can be measured either with a symmetrical or an asymmetrical test circuit.
- NOTE 2 When expressed in decibels the insertion loss is 20 times the logarithm of the ratio stated.

2.2.13

asymmetrical test circuit

a test circuit in which the inductor under test is connected with a coaxial cable of which the outer conductor constitutes a return path for high-frequency current

[CISPR 17:1981, 3.5 modified]

2.2.14

symmetrical test circuit

a test circuit in which the inductor under test is connected with screened conductor pairs in which the asymmetrical voltage is small enough to be neglected

[CISPR 17:1981, 3.6 modified]