

INTERNATIONAL STANDARD

NORME INTERNATIONALE

QC 280100

**Fixed inductors for electromagnetic interference suppression –
Part 2: Sectional specification**

**Inductances fixes d'antiparasitage –
Partie 2: Spécification intermédiaire**

IEC 60938-2:1999

<https://standards.iteh.ai/catalog/standards/sist/1e319823-69df-4c69-b5dc-f12b8e55eb05/iec-60938-2-1999>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 1999 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch
Tél.: +41 22 919 02 11
Fax: +41 22 919 03 00



IEC 60938-2

Edition 2.0 1999-11

INTERNATIONAL STANDARD

NORME INTERNATIONALE

QC 280100

Fixed inductors for electromagnetic interference suppression –
Part 2: Sectional specification

Inductances fixes d'antiparasitage –
Partie 2: Spécification intermédiaire

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 29.100.10; 31.020

ISBN 2-8318-9906-0

CONTENTS

FOREWORD.....	4
1 General	6
1.1 Scope.....	6
1.2 Object	6
1.3 Normative references	6
1.4 Information to be given in a detail specification	7
1.4.1 General	7
1.4.2 Outline drawing and dimensions.....	7
1.4.3 Mounting.....	8
1.4.4 Ratings and characteristics	8
1.4.5 Marking	8
1.5 Definitions	8
1.6 Marking	8
2 Preferred ratings and characteristics.....	9
2.1 Climatic categories	9
2.2 Values of ratings.....	9
2.2.1 Rated inductance and tolerance	9
2.2.2 Rated voltage (U_R).....	9
2.2.3 Category voltage (U_C).....	9
2.2.4 Rated temperature.....	9
2.2.5 Rated current.....	9
2.2.6 Passive flammability	9
3 Quality assessment procedures.....	10
3.1 Primary stage of manufacture	10
3.2 Structurally similar inductors	10
3.3 Certified records of released lots	10
3.4 Qualification approval	10
3.4.1 Qualification approval on the basis of the fixed sample size procedures	10
3.5 Quality conformance inspection	13
3.5.1 Formation of inspection lots	13
3.5.2 Test schedule	14
3.5.3 Delayed delivery	14
4 Test and measurement procedures	14
4.1 Visual examination and check of dimensions.....	14
4.1.1 Dimensions (gauging)	14
4.1.2 Dimensions (detail).....	14
4.2 Voltage proof	14
4.3 Insulation resistance.....	15
4.4 Inductance.....	15
4.5 DC line resistance	15
4.6 Robustness of terminations.....	16
4.7 Resistance to soldering heat.....	16
4.7.1 Conditions	16
4.7.2 Final inspection, measurements and requirements	16
4.8 Solderability.....	16
4.9 Rapid change of temperature	16

4.10	Vibration.....	16
4.11	Bump	17
4.12	Shock.....	17
4.13	Container sealing.....	18
4.14	Climatic sequence	18
4.14.1	Initial measurements.....	18
4.14.2	Dry heat.....	18
4.14.3	Damp heat, cyclic, test Db, first cycle	18
4.14.4	Cold.....	18
4.14.5	Low air pressure	18
4.14.6	Damp heat, cyclic, test Db, remaining cycles	18
4.14.7	Final inspection, measurements and requirements	19
4.15	Damp heat, steady state	19
4.15.1	Final inspection, measurements and requirements	19
4.16	Temperature rise (applies only to inductors with a mass > 5 g).....	19
4.16.1	Test method	19
4.16.2	Requirements	20
4.17	Impulse voltage (applies to inductors with more than one winding)	20
4.17.1	Initial measurements.....	20
4.17.2	Requirements	20
4.18	Endurance.....	20
4.18.1	Test conditions – Endurance current test.....	20
4.18.2	Test conditions – Endurance voltage test between terminations (applies to inductors with more than one winding).....	21
4.19	Passive flammability (if applicable).....	21
4.20	Component solvent resistance (if applicable).....	21
4.21	Solvent resistance of marking (if applicable)	21
Annex A	(normative) Test schedule for safety tests only approval	22
Annex B	(normative) Test schedule for safety tests and performance tests for qualification approval, assessment level D.....	25
Annex C	(normative) Example of a suitable circuit for the endurance test voltage.....	30
Annex D	(normative) Declaration of design (confidential to the manufacturer and the certification body).....	31
Annex E	(normative) Test methods for thyristor electromagnetic interference suppression inductors	32
Figure C.1	– Endurance test circuit.....	30
Figure E.1	– Test circuit for temperature rise	32
Figure E.2	– Test circuit for interference voltage attenuation.....	33
Table 1	– Sampling plan for safety tests only.....	12
Table 2	– Sampling plan for safety tests and performance tests, assessment level D	13
Table 3	– Measuring points	15
Table 4	– Acceleration.....	16
Table 5	– Sweep cycles.....	17
Table 6	– Preferred severities	18

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIXED INDUCTORS FOR ELECTROMAGNETIC
INTERFERENCE SUPPRESSION –****Part 2: Sectional specification****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
<https://standards.iteh.ai/catalog/standards/sist/1e319823-69df-4c69-b5dc-f2bdc5893ec/iec-60938-2-1999>
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60938-2 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This second edition cancels and replaces the first edition published in 1988.

This bilingual version, published in 2008-08, corresponds to the English version.

The text of this standard is based on the following documents:

FDIS	Report on voting
40/1111/FDIS	40/1137/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60938 series, under the general title: *Fixed inductors for electromagnetic interference suppression*, can be found on the IEC website.

The QC number that appears on the front cover of this publication is the specification number in the IEC Quality Assessment System for Electronic Components (IECQ).

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW (standards.iteh.ai)

IEC 60938-2:1999

<https://standards.iteh.ai/catalog/standards/sist/1e319823-69df-4c69-b5dc-f12b8e55eb05/iec-60938-2-1999>

FIXED INDUCTORS FOR ELECTROMAGNETIC INTERFERENCE SUPPRESSION –

Part 2: Sectional specification

1 General

1.1 Scope

This International Standard applies to fixed inductors designed for electromagnetic interference suppression and which fall within the scope of the generic specification, IEC 60938-1. It is restricted to fixed inductors for which safety tests are appropriate. This implies that inductors specified according to this specification will either be connected to mains supplies, when compliance with the mandatory tests of Table 1 is necessary, or used in other circuit positions where the equipment specification prescribes that some or all of these safety tests are required.

This standard applies to fixed inductors which will be connected to an a.c. mains or other supply with a nominal voltage not exceeding 1 000 V a.c. (r.m.s.) or d.c. between conductors and with a nominal frequency not exceeding 400 Hz.

1.2 Object

The object of this standard is to prescribe standard requirements for safety tests and standard ratings and characteristics, to select from IEC 60938-1 the appropriate methods of test and to give general performance requirements for suppression inductors. Test severities and performance requirements prescribed in detail specifications referring to this sectional specification shall be of equal or higher performance level. In addition, the minimum requirements for safety tests specified herein always apply.

1.3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60060-1:1989, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60063:1963, *Preferred number series for resistors and capacitors*

Amendment 1 (1967)

Amendment 2 (1977)

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 60085:1984, *Thermal evaluation and classification of electrical insulation*¹⁾

IEC 60279:1969, *Measurement of the winding resistance of an a.c. machine during operation at alternative voltage*²⁾

IEC 60294, *Measurement of the dimensions of a cylindrical component having two axial terminations*

1) A new edition of this publication exists.

2) Withdrawn

IEC 60384-14, *Fixed capacitors for use in electronic equipment – Part 14: Sectional specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains*

IEC 60938-1:1999, *Fixed inductors for electromagnetic interference suppression – Part 1: Generic specification*

IEC 60938-2-1:1999, *Fixed inductors for electromagnetic interference suppression – Part 2-1: Blank detail specification – Inductors for which safety tests are required – Assessment level D*

IEC 60938-2-2:1999, *Fixed inductors for electromagnetic interference suppression – Part 2-2: Blank detail specification – Inductors for which safety tests are required (only)*

CISPR 16-1-1:2003, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus³⁾*

CISPR 16-1-2:2003, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-2: Radio disturbance and immunity measuring apparatus – Ancillary equipment – Conducted disturbances*

ISO 3:1973, *Preferred numbers – Series of preferred numbers*

1.4 Information to be given in a detail specification

1.4.1 General

Detail specifications shall be derived from the relevant blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic or sectional specification. When more severe requirements are included they shall be listed in 1.8 of the detail specification and indicated in the test schedules, for example by an asterisk.

NOTE The information given in 1.4.2 may, for convenience, be presented in tabular form.

The information given in 1.4.2 to 1.4.5 shall be given in each detail specification and the values quoted shall preferably be selected from those given in the appropriate clause of this sectional specification.

1.4.2 Outline drawing and dimensions

There shall be an illustration of the inductor as an aid to easy recognition and for comparison of the inductor with others. Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be indicated upon the drawing. All dimensions shall be stated in millimetres.

Normally the numerical values shall be given for the length of the body, the width and height of the body or for cylindrical types, the body diameter, and the length and diameter of the terminations. When necessary, for example when a number of items (inductance values/voltage ranges) are covered by a detail specification, the dimensions and their associated tolerances shall be placed in a table below the drawing.

When the configuration is other than described above, the detail specification shall state such dimensional information as will adequately describe the inductor. When the inductor is not designed for use on printed boards, this shall be clearly stated in the detail specification.

³⁾ A new edition of this publication exists.

1.4.3 Mounting

The detail specification shall specify the method of mounting to be recommended for normal use and the method which is mandatory for the application of the vibration, bump and shock tests. The design of the inductor may be such that special mounting fixtures are required in its use. In this case, the detail specification shall describe the mounting fixtures and they shall be used in the application of the bump, shock and vibration tests. The specified heat sink shall be used in the application of the endurance test.

1.4.4 Ratings and characteristics

The ratings and characteristics shall be in accordance with the relevant clauses of this specification.

1.4.4.1 Additional characteristics may be listed, when they are considered necessary to specify adequately the inductor for design and application purposes.

1.4.5 Marking

Deviations from 1.6 of this sectional specification, shall be specifically stated in the detail specification.

1.5 Definitions

For the purpose of this International Standard, the definitions in IEC 60938-1 apply.

1.6 Marking

1.6.1 The information given in the marking is normally selected from the following list; the relative importance of each item is indicated by its position in the list:

- a) manufacturer's name (or trade mark);
- b) manufacturer's type designation;
- c) recognized approval mark;
- d) rated inductance and tolerance;
- e) rated voltage;
- f) rated current;
- g) identification of terminations or circuit diagram;
- h) rated temperature;
- i) climatic category;
- j) year and month (or week) of manufacture (this may be in code form);
- k) reference to the detail specification.

1.6.2 Marking of the inductor may be omitted when the manufacturer considers that there is insufficient space, and this fact is recorded in the detail specification. When present, the marking shall be sufficient to provide a clear identification of the inductor. Any duplication of information in the marking on the inductor should be avoided.

1.6.3 The packaging containing the inductor(s) shall be clearly marked with all the information listed in 1.6.1, except g).

1.6.4 Any additional marking shall be so applied that no confusion can arise.

2 Preferred ratings and characteristics

2.1 Climatic categories

Electromagnetic interference suppression inductors covered by this specification are classified into climatic categories according to the general rules given in IEC 60068-1. The lower and upper category temperatures and the duration of the damp heat, steady state test shall be selected from the following:

Lower category temperature: –65 °C, –55 °C, –40 °C, –25 °C and –10 °C.

Upper category temperature: +85 °C, +100 °C, +125 °C and +155 °C.

Duration of the damp heat, steady state test: 21 and 56 days.

The severities for the cold and dry heat tests are the lower and upper category temperatures respectively.

2.2 Values of ratings

2.2.1 Rated inductance and tolerance

Preferred values of rated inductance are values chosen from the E 6 series of preferred values given in IEC 60063.

The preferred tolerances on rated inductance are as follows:

±30 %; –30 %/+50 %.

[IEC 60938-2:1999](https://standards.iteh.ai/catalog/standards/sist/1e319823-69df-4c69-b5dc-f12b8e55eb05/iec-60938-2-1999)

<https://standards.iteh.ai/catalog/standards/sist/1e319823-69df-4c69-b5dc-f12b8e55eb05/iec-60938-2-1999>

2.2.2 Rated voltage (U_R)

Preferred values for rated voltages are:

AC inductors: 50 V, 125 V, 250 V, 400 V, 440 V, 480 V and 760 V.

DC inductors: 50 V, 160 V, 250 V and 500 V.

NOTE Electromagnetic interference suppression inductors are normally chosen to have their rated voltage equal to or greater than the nominal voltage of the supply system to which they are to be connected. It should, however, be borne in mind that the voltage of the system may rise up to 10 % above the nominal voltage.

2.2.3 Category voltage (U_C)

The category voltage is equal to the rated voltage, unless otherwise stated in the detail specification.

2.2.4 Rated temperature

The rated temperature shall not be lower than +40 °C.

2.2.5 Rated current

The preferred values of rated current are selected from the R10 series of ISO 3.

2.2.6 Passive flammability

When specified, the minimum category of passive flammability permitted is category C.

3 Quality assessment procedures

3.1 Primary stage of manufacture

See 3.2 of IEC 60938-1.

3.2 Structurally similar inductors

Inductors are structurally similar when for their range of inductance values they have the following common characteristics:

- a) essentially the same materials;
- b) similar design features and manufacturing techniques;
- c) same rated voltage.

3.3 Certified records of released lots

When certified test records are requested by a purchaser, they shall be specified in the detail specification.

3.4 Qualification approval

The procedures for qualification approval testing for structurally similar inductors are given in 3.4 of IEC 60938-1.

3.4.1 Qualification approval on the basis of the fixed sample size procedures

3.4.1.1 Sampling

This standard covers procedures for qualification approval tests only. Two alternative test procedures are given, namely the full test procedure covering both safety tests and performance requirements, and a restricted test procedure covering safety tests.

Table 1 and Annex A form the schedule limited to tests for safety tests only approval. Prior to the approval testing for safety tests only it is necessary to submit to the certification body a declaration of design (Annex D) registering essential data and basic design details of the inductors for which approval is sought.

Table 2 and Annex B form the full schedule for safety tests and performance approval.

Each rated voltage shall be separately qualified. The total number of inductors of each rated voltage to be tested in each group is given in Table 1 or 2. For each rated voltage, the sample shall contain equal numbers of specimens of the highest and lowest inductance and the highest and lowest rated current in the range to be qualified. Where only one inductance value or rated current value is involved, the total number of inductors as stated in Table 1 or 2 shall be tested.

Spare specimens are permitted as follows:

- a) one per inductance/rated current combination which may be used to replace the permitted non-conforming items in group 0;
- b) one per inductance/rated current combination which may be used as replacements for specimens lost due to incidents not attributable to the manufacturer or the test sequence;
- c) the remainder of the spares may be required if it is necessary to repeat any test according to the provisions of Note 1 to Table 1 or 2;
- d) spares may be kept at the premises of the manufacturer instead of being sent to the testing station.

The number of samples given in group 0 assume that all groups are applicable. If this is not so the numbers may be reduced accordingly.

When additional groups are introduced into the qualification approval test schedule, the number of specimens required for group 0 shall be increased by the same number as that required for the additional groups.

3.4.1.2 Tests

The complete series of tests specified in either Table 1 or 2 is required for the approval of a series of structurally similar inductors of one rated voltage. The tests of each group shall be carried out in the order given.

The whole sample shall be subjected to the tests of group 0 and then divided for the other groups.

Non-conforming items found during the tests of group 0 shall not be used for the other groups.

"One non-conforming item" is counted when an inductor has not satisfied the whole or part of the tests of a group.

The approval is granted when the number of non-conformances does not exceed the specified number of permissible non-conforming items for each group or subgroup and the total number of permissible non-conformances indicated in Table 1 or 2.

NOTE Table 1 and Annex A of Table 2 and Annex B together form the fixed sample size test schedule, for which Table 1 or 2 includes the details for the sampling and permissible non-conforming items for the different tests or groups of tests, whereas Annexes A or B together with the details of test contained in Clause 4 give a complete summary of test conditions and performance requirements and indicate where, for example for the test method or conditions of test, a choice has to be made in the detail specification. The conditions of test and performance requirements for the fixed sample size test schedule shall be identical to those prescribed in the detail specification.

<https://standards.iteh.ai/catalog/standards/sist/1e319823-69df-4c69-b5dc-f12b8e55eb05/iec-60938-2-1999>

Table 1 – Sampling plan for safety tests only

Group	Test	Subclause of this publication	Number of specimens tested per rated voltage and for each mass group (2) n	Number of permissible non-conforming items per rated voltage	
				Per group c	Total c
0	Visual examinations Line resistance Inductance Voltage proof Insulation resistance Spares	4.1 4.5 4.4 4.2 4.3	40/22/10/5 4/2/2/1	1	
1A	Dimensions (detail) Creepage distances and clearances Robustness of terminations Resistance to soldering heat (1) Component solvent resistance (if applicable) (5)	4.1.2 4.1.2 4.6 4.7 4.20	10/6/2/1	0	0
2	Damp heat, steady state	4.15	18/10/4/2	0	
3A	Temperature rise (3) or Endurance current (4)	4.16 or 4.18	12/6/4/2	0	
3B	Impulse voltage (7)(8) Endurance voltage between line terminations (7)	4.17 4.18			
4	Passive flammability (5)	4.19	see 4.19	0	

NOTES to Tables 1 and 2:

NOTE 1 If applicable.

NOTE 2 The number of specimens indicated relate to the mass limits as follows:

≤5 g

>5 g and ≤250 g

>250 g and ≤1 500 g

>1 500 g respectively.

Where a range is qualified which contains inductors within more than one of the mass classifications listed above, the number of specimens selected shall be that for the classification in which the majority of the values in the range fall.

The numbers in group 0 exclude the numbers of specimens required for group 4.

NOTE 3 For inductors with a weight >5 g only.

NOTE 4 For inductors with a weight ≤5 g only.

NOTE 5 If required in the detail specification.

NOTE 6 Whichever is required in the detail specification.

NOTE 7 Applicable to inductors with more than one winding of different polarity.

NOTE 8 Applicable to inductors with earthed metal case, not connected to one of the line terminations.

NOTE 9 If one non-conforming item is obtained, all tests of the group shall be repeated on a new sample and then no further non-conforming items are permitted. The non-conforming item obtained in the first sample shall be counted for the total non-conforming items permitted in the sixth column. Repetition of tests is permitted in one group only.

Table 2 – Sampling plan for safety tests and performance tests, assessment level D

Group	Test	Subclause of this publication	Number of specimens tested per qualification (2) n	Number of permissible non-conforming items per qualification (2)	
				Per group c	Total c
0	Dimensions (gauging) Visual examinations DC line resistance Inductance Voltage proof Insulation resistance Spares	4.1 4.1 4.5 4.4 4.2 4.3	76/48/28/16 24/15/10/5	2/1/1/1	
1A	Dimensions (detail) Creepage distances and clearances Robustness of terminations Resistance to soldering heat (1) Component solvent resistance (5) Solderability (1) Solvent resistance of marking (5)	4.1.2 4.1.2 4.6 4.7 4.20 4.8 4.21	10/6/2/1	0 (9)	1/1/1/0
1B	Rapid change of temperature Vibration Bump or shock (6)	4.9 4.10 4.11 or 4.12	18/12/6/3	0 (9)	
1	Container sealing (5) Climatic sequence	4.13 4.14	28/18/8/4	0 (9)	
2	Damp heat, steady state	4.15	16/10/8/4	0 (9)	
3A	Temperature rise (3) or Endurance current (4)	4.16 or 4.18	12/8/4/4	0 (9)	
3B	Impulse voltage (7)(8) Endurance voltage between line terminations (7)	4.17 4.18	20/12/8/4	0	
4	Passive flammability (5)	4.19	See 4.19	0	
See notes to Tables 1 and 2 at the bottom of Table 1.					

3.5 Quality conformance inspection

3.5.1 Formation of inspection lots

a) Groups A and B inspection

These tests shall be carried out on a lot-by-lot basis using sampling plans appropriate to the given assessment level specified in the relevant blank detail specification.

Manufactured lots of separately identified inductors may be aggregated into inspection lots formed for such tests as are relevant to structural similarities between those manufactured lots.