

ETSI TS 136 101 V15.15.0 (2021-09)



**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 15.15.0 Release 15)**

<https://standards.iteh.ai/catalog/standards/sist/503d00ec-28dc-420e-af69-flc65c49295c/etsi-ts-136-101-v15-15-0-2021-09>



Reference

RTS/TSGR-0436101vff0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITECH STANDARD PREVIEW
(standards.itech.ai)

Legal notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal notice	2
Modal verbs terminology.....	2
Foreword.....	31
1 Scope	32
2 References	32
3 Definitions, symbols and abbreviations	32
3.1 Definitions	32
3.2 Symbols.....	34
3.3 Abbreviations	37
4 General	38
4.1 Relationship between minimum requirements and test requirements	38
4.2 Applicability of minimum requirements	39
4.3 Void.....	39
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category M2, UE category 1bis, UE category NB1 and NB2, V2X Communication, MBMS UE)	39
4.4 RF requirements in later releases	41
5 Operating bands and channel arrangement	41
5.1 General	41
5.2 Void.....	41
5.3 Void.....	41
5.4 Void.....	41
5.5 Operating bands.....	41
5.5A Operating bands for CA	43
5.5B Operating bands for UL-MIMO	57
5.5C Operating bands for Dual Connectivity	57
5.5D Operating bands for ProSe.....	59
5.5E Operating bands for UE category 0, UE category M1 and M2 and UE category 1bis	60
5.5F Operating bands for category NB1 and NB2.....	60
5.5G Operating bands for V2X Communication.....	60
5.6 Channel bandwidth.....	61
5.6.1 Channel bandwidths per operating band.....	62
5.6A Channel bandwidth for CA.....	64
5.6A.1 Channel bandwidths per operating band for CA.....	66
5.6B Channel bandwidth for UL-MIMO	150
5.6B.1 Void	151
5.6C Channel bandwidth for Dual Connectivity	151
5.6C.1 Void	151
5.6D Channel bandwidth for ProSe.....	151
5.6D.1 Channel bandwidths per operating band for ProSe.....	151
5.6F Channel bandwidth for category NB1 and NB2.....	152
5.6G Channel bandwidth for V2X Communication.....	153
5.6G.1 Channel bandwidths per operating band for V2X Communication	153
5.7 Channel arrangement.....	155
5.7.1 Channel spacing.....	155
5.7.1A Channel spacing for CA.....	155
5.7.1F Channel spacing for category NB1 and NB2.....	156
5.7.2 Channel raster	156
5.7.2A Channel raster for CA	156
5.7.2F Channel raster for category NB1 and NB2.....	156
5.7.3 Carrier frequency and EARFCN.....	156
5.7.3F Carrier frequency and EARFCN for category NB1 and NB2.....	158

5.7.4	TX–RX frequency separation	158
5.7.4A	TX–RX frequency separation for CA	159
5.7.4E	TX–RX frequency separation for category M1 and M2	159
5.7.4F	TX–RX frequency separation for category NB1 and NB2	159
6	Transmitter characteristics	160
6.1	General	160
6.2	Transmit power	160
6.2.1	Void	160
6.2.2	UE maximum output power	160
6.2.2A	UE maximum output power for CA	162
6.2.2B	UE maximum output power for UL-MIMO	166
6.2.2C	Void	168
6.2.2D	UE maximum output power for ProSe	168
6.2.2E	UE maximum output power for Category M1 and M2 UE	168
6.2.2F	UE maximum output power for category NB1 and NB2	169
6.2.2G	UE maximum output power for V2X Communication	170
6.2.3	UE maximum output power for modulation / channel bandwidth	172
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	173
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	178
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	178
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2	179
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	181
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	181
6.2.3G.1	MPR for Power class 3 V2X UE	181
6.2.3G.2	MPR for Power class 2 V2X UE	183
6.2.4	UE maximum output power with additional requirements	183
6.2.4A	UE maximum output power with additional requirements for CA	201
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	203
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	204
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	204
6.2.4A.4	A-MPR for CA_NS_04	205
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	207
6.2.4A.6	A-MPR for CA_NS_06	208
6.2.4A.7	A-MPR for CA_NS_07	209
6.2.4A.8	A-MPR for CA_NS_08	210
6.2.4A.9	Void	211
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	211
6.2.4D	UE maximum output power with additional requirements for ProSe	212
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE	212
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE	221
6.2.4G	UE maximum output power with additional requirements for V2X Communication	222
6.2.5	Configured transmitted power	224
6.2.5A	Configured transmitted power for CA	249
6.2.5B	Configured transmitted power for UL-MIMO	253
6.2.5C	Configured transmitted power for Dual Connectivity	254
6.2.5D	Configured transmitted power for ProSe	255
6.2.5F	Configured transmitted Power for category NB1 and NB2	257
6.2.5G	Configured transmitted power for V2X Communication	258
6.3	Output power dynamics	262
6.3.1	(Void)	262
6.3.2	Minimum output power	262
6.3.2.1	Minimum requirement	262
6.3.2A	UE Minimum output power for CA	262
6.3.2A.1	Minimum requirement for CA	262
6.3.2B	UE Minimum output power for UL-MIMO	262
6.3.2B.1	Minimum requirement	263
6.3.2C	Void	263
6.3.2D	UE Minimum output power for ProSe	263
6.3.2F	UE Minimum output power for category NB1 and NB2	263
6.3.2G	UE Minimum output power for V2X Communication	263
6.3.3	Transmit OFF power	264

6.3.3.1.	Minimum requirement	264
6.3.3A	UE Transmit OFF power for CA	264
6.3.3A.1	Minimum requirement for CA	264
6.3.3B	UE Transmit OFF power for UL-MIMO	265
6.3.3B.1	Minimum requirement	265
6.3.3D	Transmit OFF power for ProSe	265
6.3.3F	Transmit OFF power for category NB1 and NB2	265
6.3.3G	Transmit OFF power for V2X Communication	266
6.3.4	ON/OFF time mask	266
6.3.4.1	General ON/OFF time mask	266
6.3.4.2	PRACH and SRS time mask	267
6.3.4.2.1	PRACH time mask	267
6.3.4.2.2	SRS time mask	268
6.3.4.3	Slot / Sub frame boundary time mask for subframe TTI	269
6.3.4.4	PUCCH / PUSCH / SRS time mask for subframe TTI	271
6.3.4.5	Symbol / Subslot boundary time mask for subslot TTI	273
6.3.4.6	Subslot PUCCH / subslot PUSCH / SRS time mask for subslot TTI	275
6.3.4.7	Symbol / Slot boundary time mask for slot TTI	278
6.3.4.8	Slot PUCCH / slot PUSCH / SRS time mask for slot TTI	278
6.3.4.9	Consecutive subslot and slot TTI or consecutive subslot and subframe TTI time mask	279
6.3.4.10	Consecutive subframe and subslot TTI or consecutive slot and subslot TTI time mask	279
6.3.4.11	Consecutive TTI and slot TTI or consecutive slot TTI and TTI time mask	280
6.3.4A	ON/OFF time mask for CA	280
6.3.4B	ON/OFF time mask for UL-MIMO	280
6.3.4D	ON/OFF time mask for ProSe	281
6.3.4D.1	General time mask for ProSe	281
6.3.4D.2	PSSS/SSSS time mask	281
6.3.4D.3	PSSS / SSSS / PSBCH time mask	282
6.3.4D.4	PSSCH / SRS time mask	283
6.3.4F	ON/OFF time mask for category NB1 and NB2	283
6.3.4F.1	General ON/OFF time mask	283
6.3.4F.2	NPRACH time mask	283
6.3.4G	ON/OFF time mask for V2X Communication	284
6.3.4G.1	PSSS / SSSS / PSBCH time mask	284
6.3.5	Power Control	285
6.3.5.1	Absolute power tolerance	285
6.3.5.1.1	Minimum requirements	285
6.3.5.2	Relative Power tolerance	286
6.3.5.2.1	Minimum requirements	286
6.3.5.3	Aggregate power control tolerance	287
6.3.5.3.1	Minimum requirement	287
6.3.5A	Power control for CA	287
6.3.5A.1	Absolute power tolerance	287
6.3.5A.1.1	Minimum requirements	287
6.3.5A.2	Relative power tolerance	288
6.3.5A.2.1	Minimum requirements	288
6.3.5A.3	Aggregate power control tolerance	288
6.3.5A.3.1	Minimum requirements	288
6.3.5B	Power control for UL-MIMO	289
6.3.5D	Power Control for ProSe	289
6.3.5D.1	Absolute power tolerance	289
6.3.5E	Power control for category M1 and M2	289
6.3.5E.1	Absolute power tolerance	289
6.3.5E.2	Relative Power tolerance	289
6.3.5E.3	Aggregate power control tolerance	290
6.3.5E.3.1	Minimum requirement	290
6.3.5F	Power Control for category NB1 and NB2	290
6.3.5F.1	Absolute power tolerance	291
6.3.5F.2	Relative power tolerance	291
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	292
6.3.5F.3.1	Minimum requirement	292
6.3.5G	Power Control for V2X Communication	292

6.3.5G.1	Absolute power tolerance.....	292
6.4	Void.....	293
6.5	Transmit signal quality.....	293
6.5.1	Frequency error.....	293
6.5.1A	Frequency error for CA.....	293
6.5.1B	Frequency error for UL-MIMO.....	293
6.5.1D	Frequency error for ProSe.....	293
6.5.1E	Frequency error for UE category M1 and M2.....	293
6.5.1F	Frequency error for UE category NB1 and NB2.....	294
6.5.1G	Frequency error for V2X Communication.....	294
6.5.2	Transmit modulation quality.....	294
6.5.2.1	Error Vector Magnitude.....	295
6.5.2.1.1	Minimum requirement.....	295
6.5.2.2	Carrier leakage.....	295
6.5.2.2.1	Minimum requirements.....	296
6.5.2.3	In-band emissions.....	296
6.5.2.3.1	Minimum requirements.....	296
6.5.2.4	EVM equalizer spectrum flatness.....	297
6.5.2.4.1	Minimum requirements.....	297
6.5.2A	Transmit modulation quality for CA.....	298
6.5.2A.1	Error Vector Magnitude.....	299
6.5.2A.2	Carrier leakage for CA.....	299
6.5.2A.2.1	Minimum requirements.....	299
6.5.2A.3	In-band emissions.....	299
6.5.2A.3.1	Minimum requirement for CA.....	299
6.5.2B	Transmit modulation quality for UL-MIMO.....	302
6.5.2B.1	Error Vector Magnitude.....	302
6.5.2B.2	Carrier leakage.....	302
6.5.2B.3	In-band emissions.....	302
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO.....	302
6.5.2D	Transmit modulation quality for ProSe.....	302
6.5.2D.1	Error Vector Magnitude.....	302
6.5.2D.2	Carrier leakage.....	303
6.5.2D.3	In-band emissions.....	303
6.5.2D.4	EVM equalizer spectrum flatness for ProSe.....	303
6.5.2E	Transmit modulation quality for category M1 and M2.....	303
6.5.2E.1	Error Vector Magnitude.....	303
The Error Vector Magnitude is defined in section 6.5.2.1.		303
6.5.2E.2	Carrier leakage.....	303
6.5.2E.2.1	Minimum requirements.....	303
6.5.2E.3	In-band emissions.....	303
6.5.2E.3.1	Minimum requirements.....	303
6.5.2F	Transmit modulation quality for Category NB1 and NB2.....	305
6.5.2F.1	Error Vector Magnitude.....	305
6.5.2F.2	Carrier leakage.....	305
6.5.2F.3	In-band emissions.....	305
6.5.2G	Transmit modulation quality for V2X Communication.....	306
6.5.2G.1	Error Vector Magnitude.....	306
6.5.2G.2	Carrier leakage.....	307
6.5.2G.3	In-band emissions.....	307
6.5.2G.4	EVM equalizer spectrum flatness.....	307
6.6	Output RF spectrum emissions.....	307
6.6.1	Occupied bandwidth.....	307
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value “NS_29”).....	308
6.6.1A	Occupied bandwidth for CA.....	308
6.6.1B	Occupied bandwidth for UL-MIMO.....	308
6.6.1F	Occupied bandwidth for category NB1 and NB2.....	309
6.6.1G	Occupied bandwidth for V2X Communication.....	309
6.6.2	Out of band emission.....	309
6.6.2.1	Spectrum emission mask.....	309
6.6.2.1.1	Minimum requirement.....	309
6.6.2.1A	Spectrum emission mask for CA.....	310

6.6.2.2	Additional spectrum emission mask	311
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21") ..	311
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	312
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	312
6.6.2.2.4	Minimum requirement (network signalled value "NS_33" or "NS_34")	313
6.6.2.2.5	Minimum requirement (network signalled value "NS_27" and "NS_43")	313
6.6.2.2.6	Minimum requirement (network signalled value "NS_28")	314
6.6.2.2.7	Minimum requirement (network signalled value "NS_35")	314
6.6.2.2A	Additional Spectrum Emission Mask for CA	315
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04")	315
6.6.2.2A.2	Minimum requirement CA_66B (network signalled value "CA_NS_09")	315
6.6.2.2A.3	Minimum requirement CA_66C (network signalled value "CA_NS_09")	316
6.6.2.3	Adjacent Channel Leakage Ratio	316
6.6.2.3.1	Minimum requirement E-UTRA	317
6.6.2.3.1a	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	318
6.6.2.3.1A	Void	318
6.6.2.3.1Aa	Void	318
6.6.2.3.2	Minimum requirements UTRA	318
6.6.2.3.2A	Minimum requirement UTRA for CA	319
6.6.2.3.3A	Minimum requirements for CA E-UTRA	321
6.6.2.4	Void	322
6.6.2.4.1	Void	322
6.6.2A	Void	322
6.6.2B	Out of band emission for UL-MIMO	322
6.6.2C	Void	322
6.6.2D	Out of band emission for ProSe	323
6.6.2F	Out of band emission for category NB1 and NB2	323
6.6.2F.1	Spectrum emission mask	323
6.6.2F.2	Additional Spectrum Emission Mask for Category NB1 and NB2	323
6.6.2F.2.1	Minimum requirement (network signalled value "NS_02")	323
6.6.2F.2.2	Minimum requirement (network signalled value "NS_03")	324
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1 and NB2	324
6.6.2G	Out of band emission for V2X Communication	324
6.6.3	Spurious emissions	325
6.6.3.1	Minimum requirements	325
6.6.3.1A	Minimum requirements for CA	326
6.6.3.2	Spurious emission band UE co-existence	327
6.6.3.2A	Spurious emission band UE co-existence for CA	334
6.6.3.3	Additional spurious emissions	345
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	345
6.6.3.3.2	Minimum requirement (network signalled value "NS_07")	346
6.6.3.3.3	Minimum requirement (network signalled value "NS_08")	346
6.6.3.3.4	Minimum requirement (network signalled value "NS_09")	346
6.6.3.3.5	Minimum requirement (network signalled value "NS_12")	347
6.6.3.3.6	Minimum requirement (network signalled value "NS_13")	347
6.6.3.3.7	Minimum requirement (network signalled value "NS_14")	347
6.6.3.3.8	Minimum requirement (network signalled value "NS_15")	347
6.6.3.3.9	Minimum requirement (network signalled value "NS_16")	348
6.6.3.3.10	Minimum requirement (network signalled value "NS_17")	348
6.6.3.3.11	Minimum requirement (network signalled value "NS_18")	348
6.6.3.3.12	Minimum requirement (network signalled value "NS_19")	348
6.6.3.3.13	Minimum requirement (network signalled value "NS_11")	349
6.6.3.3.14	Minimum requirement (network signalled value "NS_20")	349
6.6.3.3.15	Minimum requirement (network signalled value "NS_21")	349
6.6.3.3.16	Minimum requirement (network signalled value "NS_22")	350
6.6.3.3.17	Minimum requirement (network signalled value "NS_23")	350
6.6.3.3.18	Void	351
6.6.3.3.19	Minimum requirement (network signalled value "NS_04")	351
6.6.3.3.20	Minimum requirement (network signalled value "NS_24")	351
6.6.3.3.21	Minimum requirement (network signalled value "NS_25")	352
6.6.3.3.22	Minimum requirement (network signalled value "NS_26")	352
6.6.3.3.23	Minimum requirement (network signalled value "NS_27" and "NS_43")	352

6.6.3.3.24	Minimum requirement (network signalled value "NS_28")	352
6.6.3.3.25	Minimum requirement (network signalled value "NS_29")	353
6.6.3.3.26	Minimum requirement (network signalled value "NS_30")	353
6.6.3.3.27	Minimum requirement (network signalled value "NS_31")	354
6.6.3.3.28	Minimum requirement (network signalled value "NS_36")	355
6.6.3.3.29	Minimum requirement (network signalled value "NS_38")	355
6.6.3.3.30	Minimum requirement (network signalled value "NS_39")	355
6.6.3.3.31	Minimum requirement (network signalled value "NS_40" and "NS_41")	356
6.6.3.3.32	Minimum requirement (network signalled value "NS_42")	356
6.6.3.3.33	Minimum requirement (network signalled value "NS_44")	356
6.6.3.3.34	Void	356
6.6.3.3.35	Minimum requirement (network signalled value "NS_56")	356
6.6.3.3A	Additional spurious emissions for CA	357
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01")	357
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02")	357
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03")	358
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05")	358
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06")	358
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07")	359
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08")	359
6.6.3.3A.8	Minimum requirement for CA_41C (network signalled value "CA_NS_04")	360
6.6.3.3A.9	Void	360
6.6.3A	Void	360
6.6.3B	Spurious emission for UL-MIMO	360
6.6.3C	Void	360
6.6.3D	Spurious emission for ProSe	360
6.6.3F	Spurious emission for category NB1 and NB2	360
6.6.3G	Spurious emission for V2X Communication	360
6.6A	Void	364
6.6B	Void	364
6.7	Transmit intermodulation	364
6.7.1	Minimum requirement	364
6.7.1A	Minimum requirement for CA	365
6.7.1B	Minimum requirement for UL-MIMO	365
6.7.1F	Minimum requirement for category NB1 and NB2	365
6.7.1G	Minimum requirement for V2X Communication	366
6.8	Void	366
6.8A	Void	366
6.8B	Time alignment error for UL-MIMO	366
6.8B.1	Minimum Requirements	366
6.8C	Void	367
6.8D	Void	367
6.8E	Void	367
6.8F	Void	367
6.8G	Time alignment error	367
7	Receiver characteristics	367
7.1	General	367
7.2	Diversity characteristics	368
7.3	Reference sensitivity power level	368
7.3.1	Minimum requirements (QPSK)	368
7.3.1A	Minimum requirements (QPSK) for CA	397
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	467
7.3.1D	Minimum requirements (QPSK) for ProSe	467
7.3.1E	Minimum requirements (QPSK) for UE category 0, M1, M2 and 1bis	469
7.3.1F	Minimum requirements for UE category NB1 and NB2	477
7.3.1F.1	Reference sensitivity for UE category NB1 and NB2	477
7.3.1F.2	Void	478
7.3.1G	Minimum requirements (QPSK) for V2X	478
7.3.2	Void	480
7.4	Maximum input level	480

7.4.1	Minimum requirements.....	481
7.4.1A	Minimum requirements for CA	481
7.4.1B	Minimum requirements for UL-MIMO	482
7.4.1D	Minimum requirements for ProSe	482
7.4.1F	Minimum requirements for category NB1 and NB2.....	483
7.4.1G	Minimum requirements for V2X	483
7.4A	Void.....	484
7.4A.1	Void	484
7.5	Adjacent Channel Selectivity (ACS).....	484
7.5.1	Minimum requirements.....	484
7.5.1A	Minimum requirements for CA	485
7.5.1B	Minimum requirements for UL-MIMO	489
7.5.1D	Minimum requirements for ProSe	489
7.5.1F	Minimum requirements for category NB1 and NB2.....	490
7.5.1G	Minimum requirements for V2X	491
7.6	Blocking characteristics	493
7.6.1	In-band blocking.....	493
7.6.1.1	Minimum requirements.....	493
7.6.1.1A	Minimum requirements for CA.....	495
7.6.1.1D	Minimum requirements for ProSe.....	498
7.6.1.1F	Minimum requirements for category NB1 and NB2.....	499
7.6.1.1G	Minimum requirements for V2X.....	499
7.6.2	Out-of-band blocking.....	501
7.6.2.1	Minimum requirements.....	501
7.6.2.1A	Minimum requirements for CA.....	502
7.6.2.1D	Minimum requirements for ProSe.....	506
7.6.2.1F	Minimum requirements for category NB1 and NB2.....	506
7.6.2.1G	Minimum requirements for V2X.....	507
7.6.3	Narrow band blocking	508
7.6.3.1	Minimum requirements.....	508
7.6.3.1A	Minimum requirements for CA.....	509
7.6.3.1D	Minimum requirements for ProSe.....	510
7.6A	Void.....	511
7.6B	Blocking characteristics for UL-MIMO.....	511
7.7	Spurious response.....	511
7.7.1	Minimum requirements.....	511
7.7.1A	Minimum requirements for CA	512
7.7.1B	Minimum requirements for UL-MIMO	513
7.7.1D	Minimum requirements for ProSe	513
7.7.1F	Minimum requirements for UE category NB1 and NB2	514
7.7.1G	Minimum requirements for V2X	514
7.8	Intermodulation characteristics	515
7.8.1	Wide band intermodulation.....	515
7.8.1.1	Minimum requirements.....	515
7.8.1A	Minimum requirements for CA	516
7.8.1B	Minimum requirements for UL-MIMO	519
7.8.1D	Minimum requirements for ProSe	519
7.8.1F	Minimum requirements for category NB1 and NB2.....	520
7.8.1G	Minimum requirements.....	520
7.8.2	Void	521
7.9	Spurious emissions	521
7.9.1	Minimum requirements.....	522
7.9.1A	Minimum requirements.....	522
7.10	Receiver image	523
7.10.1	Void	523
7.10.1A	Minimum requirements for CA	523
7.10.1G	Minimum requirements for V2X Communication.....	523
8	Performance requirement	524
8.1	General	524
8.1.1	Receiver antenna capability	524
8.1.1.1	Simultaneous unicast and MBMS operations.....	525

8.1.1.2	Dual-antenna receiver capability in idle mode	525
8.1.2	Applicability of requirements	525
8.1.2.1	Applicability of requirements for different channel bandwidths.....	525
8.1.2.2	Definition of CA capability	525
8.1.2.2A	Definition of dual connectivity capability	530
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets.....	531
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	533
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets.....	534
8.1.2.3C	Applicability and test rules for SDR tests for 4Rx capable UEs	536
8.1.2.3D	Applicability and test rules for different CA with LAA SCell(s) configurations and bandwidth combination sets.....	536
8.1.2.3E	Applicability and test rules for SDR tests for 8Rx capable UEs	537
8.1.2.4	Test coverage for different number of component carriers	538
8.1.2.5	Applicability of performance requirements for Type B receiver	539
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	539
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	539
8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	541
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	541
8.1.2.6.4	Applicability rule for 256QAM tests	542
8.1.2.6.5	Applicability rule and antenna connection for CA and DC tests with 4Rx	542
8.1.2.6.6	Applicability rule for Type C with 4Rx.....	545
8.1.2.6.7	Applicability rule for 1024QAM tests	545
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	545
8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations.....	547
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	547
8.1.2.9	Applicability of SDR requirements for CA and LAA	548
8.1.2.10	Applicability of performance requirements for Multi-user Superposed Transmission	549
8.1.2.11	Applicability CRS interference mitigation receivers performance requirements.....	549
8.1.2.12	Applicability of performance requirements for 8Rx capable UEs	550
8.1.2.12.1	Applicability rule and antenna connection for single carrier PDSCH tests	550
8.1.2.12.2	Applicability rule and antenna connection for control channel tests	556
8.1.2.12.3	Applicability rule and antenna connection for CA and DC tests	556
8.1.3	UE category and UE DL category	557
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	557
8.2.1	FDD (Fixed Reference Channel)	557
8.2.1.1	Single-antenna port performance	558
8.2.1.1.1	Minimum Requirement	558
8.2.1.1.2	Void	563
8.2.1.1.3	Void	563
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	563
8.2.1.1.4A	Minimum Requirement 1 PRB allocation in presence of FeMBMS Unicast-mixed Cell under CA	564
8.2.1.2	Transmit diversity performance	565
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	565
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	565
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	566
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	568
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	570
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	572
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	573
8.2.1.2.7	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	574
8.2.1.3	Open-loop spatial multiplexing performance.....	574
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	574
8.2.1.3.1A	Soft buffer management test	578

8.2.1.3.1B	Enhanced Performance Requirement Type C – 2Tx Antenna Ports	579
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	580
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	581
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	581
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	585
8.2.1.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	587
8.2.1.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation).....	588
8.2.1.4	Closed-loop spatial multiplexing performance	589
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	589
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	590
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	590
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	592
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	594
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	596
8.2.1.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	597
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	598
8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports.....	599
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	599
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	603
8.2.1.4.4	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	605
8.2.1.5	MU-MIMO.....	606
8.2.1.6	[Control channel performance (D-BCH and PCH)]	606
8.2.1.7	Carrier aggregation with power imbalance	606
8.2.1.7.1	Minimum Requirement	606
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset.....	607
8.2.1.8.1	Minimum Requirement	607
8.2.1.9	HST-SFN performance	608
8.2.1.9.1	Minimum Requirement	608
8.2.1.10	Intra-band contiguous carrier aggregation with minimum channel spacing.....	609
8.2.1.10.1	Minimum Requirement	609
8.2.2	TDD (Fixed Reference Channel)	610
8.2.2.1	Single-antenna port performance	610
8.2.2.1.1	Minimum Requirement	610
8.2.2.1.2	Void	615
8.2.2.1.3	Void	615
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	615
8.2.2.2	Transmit diversity performance	615
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	615
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	616
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	617
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	618
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	620
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	622
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	622
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	624
8.2.2.2.8	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	625

8.2.2.3	Open-loop spatial multiplexing performance.....	626
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	626
8.2.2.3.1A	Soft buffer management test	629
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	629
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	630
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	631
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS)	632
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	636
8.2.2.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	638
8.2.2.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation)	639
8.2.2.4	Closed-loop spatial multiplexing performance	640
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	640
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	641
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	641
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	643
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	645
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	647
8.2.2.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	648
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	650
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	650
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	651
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	655
8.2.2.4.4	Void	656
8.2.2.4.5	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	656
8.2.2.5	MU-MIMO	657
8.2.2.6	[Control channel performance: D-BCH and PCH]	657
8.2.2.7	Carrier aggregation with power imbalance	657
8.2.2.7.1	Minimum Requirement	657
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing	658
8.2.2.8.1	Minimum Requirement	658
8.2.2.9	HST-SFN performance	659
8.2.2.9.1	Minimum Requirement	659
8.2.3	TDD FDD CA (Fixed Reference Channel)	660
8.2.3.1	Single-antenna port performance	661
8.2.3.1.1	Minimum Requirement for FDD PCell	661
8.2.3.1.2	Minimum Requirement for TDD PCell	665
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port	669
8.2.3.2.1	Minimum Requirement for FDD PCell	669
8.2.3.2.1A	Soft buffer management test for FDD PCell	672
8.2.3.2.2	Minimum Requirement for TDD PCell	673
8.2.3.2.2A	Soft buffer management test for TDD PCell	677
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port	678
8.2.3.3.1	Minimum Requirement for FDD PCell	678
8.2.3.3.2	Minimum Requirement for TDD PCell	682
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	686
8.2.4	LAA	687
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port	687
8.2.4.1.1	FDD PCell (FDD single carrier)	687
8.2.4.1.2	TDD PCell (TDD single carrier)	691
8.3	Demodulation of PDSCH (User-Specific Reference Symbols)	695
8.3.1	FDD	695

8.3.1.1	Single-layer Spatial Multiplexing	696
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	698
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	700
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model.....	702
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	704
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model.....	705
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	706
8.3.1.1G	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	708
8.3.1.1H	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured)	710
8.3.1.1I	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH).....	711
8.3.1.2	Dual-Layer Spatial Multiplexing	713
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	714
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	715
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	715
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources)	717
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	719
8.3.1.3.4	Minimum requirement with Different Cell ID and non-colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	721
8.3.1.3.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	723
8.3.1.3.6	Minimum requirements for QCL Type C and 2 Layers Spatial Multiplexing	725
8.3.1.4	Performance Requirements for semiOpenLoop transmission	727
8.3.2	TDD	729
8.3.2.1	Single-layer Spatial Multiplexing	729
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	731
8.3.2.1B	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	733
8.3.2.1C	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	735
8.3.2.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference.....	737
8.3.2.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	739
8.3.2.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference.....	741
8.3.2.1G	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	742
8.3.2.1H	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	744
8.3.2.1I	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured)	746
8.3.2.1J	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH).....	747
8.3.2.2	Dual-Layer Spatial Multiplexing	749
8.3.2.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	749
8.3.2.3	Dual-Layer Spatial Multiplexing (with multiple CSI-RS configurations)	750
8.3.2.4	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	751
8.3.2.4.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	751
8.3.2.4.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources)	753
8.3.2.4.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	755
8.3.2.4.4	Minimum requirement with Different Cell ID and non-Colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	757
8.3.2.4.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	759
8.3.2.4.6	Minimum requirements for QCL Type C and 2 Layers Spatial Multiplexing	761

8.3.2.5	Performance Requirements for semiOpenLoop transmission	763
8.3.3	LAA	765
8.3.3.1	Dual-Layer Spatial Multiplexing with DM-RS	765
8.3.3.1.1	FDD PCell (FDD single carrier)	765
8.3.3.1.2	TDD Pcell (TDD single carrier)	770
8.4	Demodulation of PDCCH/PCFICH	774
8.4.1	FDD	774
8.4.1.1	Single-antenna port performance	775
8.4.1.2	Transmit diversity performance	775
8.4.1.2.1	Minimum Requirement 2 Tx Antenna Port	775
8.4.1.2.2	Minimum Requirement 4 Tx Antenna Port	775
8.4.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	776
8.4.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	780
8.4.1.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port under Asynchronous Network	784
8.4.1.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	785
8.4.1.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer	786
8.4.1.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	787
8.4.1.2.9	Enhanced Downlink Control Channel Performance Requirement Type A - 4 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	788
8.4.2	TDD	789
8.4.2.1	Single-antenna port performance	790
8.4.2.2	Transmit diversity performance	790
8.4.2.2.1	Minimum Requirement 2 Tx Antenna Port	790
8.4.2.2.2	Minimum Requirement 4 Tx Antenna Port	791
8.4.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	791
8.4.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	795
8.4.2.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Colliding CRS Dominant Interferer	799
8.4.2.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	800
8.4.2.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer	801
8.4.2.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	802
8.4.2.2.9	Enhanced Downlink Control Channel Performance Requirement Type A - 4 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	803
8.4.3	LAA	804
8.4.3.1	Transmit diversity performance	804
8.4.3.1.1	FDD Pcell (FDD single carrier)	804
8.4.3.1.2	TDD Pcell (TDD single carrier)	805
8.5	Demodulation of PHICH	806
8.5.1	FDD	807
8.5.1.1	Single-antenna port performance	807
8.5.1.2	Transmit diversity performance	807
8.5.1.2.1	Minimum Requirement 2 Tx Antenna Port	807
8.5.1.2.2	Minimum Requirement 4 Tx Antenna Port	808
8.5.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	808
8.5.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	810
8.5.1.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Ports under Asynchronous Network	812
8.5.1.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Ports with Non-Colliding CRS Dominant Interferer	813