

ETSI TS 138 141-1 v16.8.0 (2021-09)



5G; iTeh STANDARD PREVIEW

Base Station (BS) conformance testing Part 1: Conducted conformance testing (ETSI TS 138 141-1 V16.8.0 (2021-09))

(3GPP TS 38.141-1 version 16.8.0 Release 16) f61151fe6403/etsi-ts-138-141-1-v16-8-0-2021-09



Reference
RTS/TSGR-0438141-1vg80
Keywords
5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

Important notice

[ETSI TS 138 141-1 V16.8.0 \(2021-09\)](#)

<https://standards.iteh.ai/catalog/standards/sist/da9c2bda-4958-4cb5-b599-fb1121fb403cetsi-ts-138-141-1-v16-8-0-2021-09>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

https://standards.iteh.ai/catalog/standards/sist/da9c2bda-4958-4cb5-b599-101151fc0403/etsits_138_141_1_v16_8_0_2021_09

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	15
1 Scope	17
2 References	17
3 Definitions, symbols and abbreviations	19
3.1 Definitions.....	19
3.2 Symbols.....	21
3.3 Abbreviations	23
4 General conducted test conditions and declarations.....	24
4.1 Measurement uncertainties and test requirements	24
4.1.1 General.....	24
4.1.2 Acceptable uncertainty of Test System.....	24
4.1.2.1 General	24
4.1.2.2 Measurement of transmitter	25
4.1.2.3 Measurement of receiver	27
4.1.2.4 Measurement of performance requirements.....	31
4.1.3 Interpretation of measurement results.....	31
4.2 Conducted requirement reference points	31
4.2.1 BS type 1-C	31
4.2.2 BS type 1-H.....	32
4.3 Base station classes	33
4.4 Regional requirements.....	33
4.5 BS configurations https://standards.iteh.ai/catalog/standards/sist/da9c2bda-4958-4cb5-b509-561151fe6403/etsi-ts-138-141-1-v16-8-0-2021-09	34
4.5.1 BS type 1-C	34
4.5.1.1 Transmit configurations	34
4.5.1.1.1 General	34
4.5.1.1.2 Transmission with multiple transmitter antenna connectors.....	35
4.5.1.2 Receive configurations.....	35
4.5.1.2.1 General	35
4.5.1.2.2 Reception with multiple receiver antenna connectors, receiver diversity	35
4.5.1.3 Duplexers	36
4.5.1.4 Power supply options	36
4.5.1.5 Ancillary RF amplifiers.....	36
4.5.2 BS type 1-H.....	37
4.5.2.1 Transmit configurations	37
4.5.2.2 Receive configurations.....	38
4.5.2.3 Power supply options	38
4.5.3 BS with integrated Iuant BS modem	38
4.6 Manufacturer declarations	38
4.7 Test configurations	44
4.7.1 General.....	44
4.7.2 Test signal used to build Test Configurations.....	44
4.7.3 NRTC1: Contiguous spectrum operation.....	44
4.7.3.1 NRTC1 generation	44
4.7.3.2 NRTC1 power allocation	45
4.7.4 NRTC2: Contiguous CA occupied bandwidth.....	45
4.7.4.1 NRTC2 generation	45
4.7.4.2 NRTC2 power allocation	46
4.7.5 NRTC3: Non-contiguous spectrum operation	46
4.7.5.1 NRTC3 generation	46
4.7.5.2 NRTC3 power allocation	46
4.7.6 NRTC4: Multi-band test configuration for full carrier allocation.....	46

4.7.6.1	NRTC4 generation	46
4.7.6.2	NRTC4 power allocation	47
4.7.7	NRTC5: Multi-band test configuration with high PSD per carrier	47
4.7.7.1	NRTC5 generation	47
4.7.7.2	NRTC5 power allocation	48
4.8	Applicability of requirements	48
4.8.1	General	48
4.8.2	Requirement set applicability	48
4.8.3	Applicability of test configurations for single-band operation	48
4.8.4	Applicability of test configurations for multi-band operation	49
4.9	RF channels and test models	50
4.9.1	RF channels	50
4.9.2	Test models	51
4.9.2.1	General	51
4.9.2.2	FR1 test models	51
4.9.2.2.1	FR1 test model 1.1 (NR-FR1-TM1.1)	53
4.9.2.2.2	FR1 test model 1.2 (NR-FR1-TM1.2)	54
4.9.2.2.3	FR1 test model 2 (NR-FR1-TM2)	54
4.9.2.2.4	FR1 test model 2a (NR-FR1-TM2a)	55
4.9.2.2.5	FR1 test model 3.1 (NR-FR1-TM3.1)	55
4.9.2.2.6	FR1 test model 3.1a (NR-FR1-TM3.1a)	55
4.9.2.2.7	FR1 test model 3.2 (NR-FR1-TM3.2)	56
4.9.2.2.8	FR1 test model 3.3 (NR-FR1-TM3.3)	56
4.9.2.2.9	NB-IoT operation in NR in-band test model (NR-N-TM)	57
4.9.2.3	Data content of Physical channels and Signals for NR-FR1-TM	57
4.9.2.3.1	PDCCH	58
4.9.2.3.2	PDSCH	58
4.9.2.4	Data content of Physical channels and Signals for NR-N-TM	59
4.9.3	NB-IoT testing	60
4.10	Requirements for contiguous and non-contiguous spectrum	60
4.11	Requirements for BS capable of multi-band operation	60
4.12	Format and interpretation of tests	61
5	Operating bands and channel arrangement	63
6	Conducted transmitter characteristics	64
6.1	General	64
6.1.1	BS type 1-C	64
6.1.2	BS type 1-H	64
6.2	Base station output power	64
6.2.1	Definition and applicability	64
6.2.2	Minimum requirement	65
6.2.3	Test purpose	65
6.2.4	Method of test	65
6.2.4.1	Initial conditions	65
6.2.4.2	Procedure	66
6.2.5	Test requirement	66
6.3	Output power dynamics	66
6.3.1	General	66
6.3.2	RE power control dynamic range	66
6.3.2.1	Definition and applicability	66
6.3.2.2	Minimum requirement	67
6.3.2.3	Test purpose	67
6.3.3	Total power dynamic range	67
6.3.3.1	Definition and applicability	67
6.3.3.2	Minimum requirement	67
6.3.3.3	Test purpose	67
6.3.3.4	Method of test	67
6.3.3.4.1	Initial conditions	67
6.3.3.4.2	Procedure	67
6.3.3.5	Test requirements	68
6.3.4	NB-IoT RB power dynamic range	68

6.3.4.1	Definition and applicability.....	68
6.3.4.2	Minimum requirement	68
6.3.4.3	Test purpose	69
6.3.4.4	Method of test	69
6.3.4.5	Test requirements	69
6.4	Transmit ON/OFF power	69
6.4.1	Transmitter OFF power	69
6.4.1.1	Definition and applicability.....	69
6.4.1.2	Minimum requirement	69
6.4.1.3	Test purpose	69
6.4.1.4	Method of test	70
6.4.1.5	Test requirements	70
6.4.2	Transmitter transient period.....	70
6.4.2.1	Definition and applicability.....	70
6.4.2.2	Minimum requirement	70
6.4.2.3	Test purpose	70
6.4.2.4	Method of test	70
6.4.2.4.1	Initial conditions.....	70
6.4.2.4.2	Procedure.....	71
6.4.2.5	Test requirements	71
6.5	Transmitted signal quality	72
6.5.1	General.....	72
6.5.2	Frequency error.....	72
6.5.2.1	Definition and applicability.....	72
6.5.2.2	Minimum Requirement	72
6.5.2.3	Test purpose	72
6.5.2.4	Method of test	72
6.5.2.5	Test Requirements.....	72
6.5.3	Modulation quality.....	72
6.5.3.1	Definition and applicability.....	72
6.5.3.2	Minimum Requirement	73
6.5.3.3	Test purpose	73
6.5.3.4	Method of test	73
6.5.3.4.1	Initial conditions.....	73
6.5.3.4.2	Procedure.....	73
6.5.3.5	Test requirements	74
6.5.4	Time alignment error	75
6.5.4.1	Definition and applicability.....	75
6.5.4.2	Minimum requirement	76
6.5.4.3	Test purpose	76
6.5.4.4	Method of test	76
6.5.4.4.1	Initial conditions.....	76
6.5.4.4.2	Procedure.....	76
6.5.4.5	Test requirement	77
6.6	Unwanted emissions	77
6.6.1	General.....	77
6.6.2	Occupied bandwidth	78
6.6.2.1	Definition and applicability.....	78
6.6.2.2	Minimum Requirements.....	78
6.6.2.3	Test purpose	78
6.6.2.4	Method of test	78
6.6.2.4.1	Initial conditions.....	78
6.6.2.4.2	Procedure.....	78
6.6.2.5	Test requirements	79
6.6.3	Adjacent Channel Leakage Power Ratio (ACLR)	79
6.6.3.1	Definition and applicability.....	79
6.6.3.2	Minimum requirement	80
6.6.3.3	Test purpose	80
6.6.3.4	Method of test	80
6.6.3.4.1	Initial conditions.....	80
6.6.3.4.2	Procedure.....	80
6.6.3.5	Test requirements	81

6.6.3.5.1	General requirements.....	81
6.6.3.5.2	Limits and <i>basic limits</i>	81
6.6.3.5.3	<i>BS type 1-C</i>	85
6.6.3.5.4	<i>BS type 1-H</i>	85
6.6.4	Operating band unwanted emissions	86
6.6.4.1	Definition and applicability.....	86
6.6.4.2	Minimum requirement	87
6.6.4.3	Test purpose	87
6.6.4.4	Method of test	87
6.6.4.4.1	Initial conditions.....	87
6.6.4.4.2	Procedure.....	87
6.6.4.5	Test requirements	89
6.6.4.5.1	General requirements.....	89
6.6.4.5.2	Basic limits for Wide Area BS (Category A)	89
6.6.4.5.3	Basic limits for Wide Area BS (Category B)	90
6.6.4.5.3.1	Category B requirements (Option 1).....	90
6.6.4.5.3.2	Category B requirements (Option 2).....	91
6.6.4.5.4	Basic limits for Medium Range BS (Category A and B).....	92
6.6.4.5.5	Basic limits for Local Area BS (Category A and B)	94
6.6.4.5.5A	Basic limits for Local Area and Medium Range BS for band n46 and n96 (Category A and B)	95
6.6.4.5.6	Basic limits for additional requirements.....	98
6.6.4.5.6.1	Limits in FCC Title 47.....	98
6.6.4.5.6.2	Protection of DTT	98
6.6.4.5.6.3	Additional operating band unwanted emissions limits for Band n48.....	98
6.6.4.5.6.4	Additional operating band unwanted emissions limits for Band n53.....	98
6.6.4.5.7	<i>BS type 1-C</i>	99
6.6.4.5.8	<i>BS type 1-H</i>	99
6.6.5	Transmitter spurious emissions.....	99
6.6.5.1	Definition and applicability	99
6.6.5.2	Minimum requirement	100
6.6.5.3	Test purpose	100
6.6.5.4	Method of test	100
6.6.5.4.1	Initial conditions https://standards.iteh.ai/catalog/standards/sist/da9c2bda-4958-4ch5-b599	100
6.6.5.4.2	Procedure	100
6.6.5.5	Test requirements	101
6.6.5.5.1	Basic limits	101
6.6.5.5.1.1	Tx spurious emissions	101
6.6.5.5.1.2	Protection of the BS receiver of own or different BS	102
6.6.5.5.1.3	Additional spurious emissions requirements	102
6.6.5.5.1.4	Co-location with other base stations	111
6.6.5.5.2	(void)	116
6.6.5.5.3	<i>BS type 1-C</i>	116
6.6.5.5.4	<i>BS type 1-H</i>	116
6.7	Transmitter intermodulation.....	117
6.7.1	Definition and applicability	117
6.7.2	Minimum requirement	117
6.7.3	Test purpose.....	117
6.7.4	Method of test	117
6.7.4.1	Initial conditions	117
6.7.4.2	Procedure	118
6.7.5	Test requirements.....	119
6.7.5.1	<i>BS type 1-C</i>	119
6.7.5.1.1	Co-location minimum requirements	119
6.7.5.1.2	Additional requirements	119
6.7.5.2	<i>BS type 1-H</i>	120
6.7.5.2.1	Co-location minimum requirements	120
6.7.5.2.2	Intra-system minimum requirements	120
6.7.5.2.3	Additional requirements	121
7	Conducted receiver characteristics	122
7.1	General	122
7.2	Reference sensitivity level.....	122

7.2.1	Definition and applicability	122
7.2.2	Minimum requirement	122
7.2.3	Test purpose.....	122
7.2.4	Method of test	123
7.2.4.1	Initial conditions	123
7.2.4.2	Procedure	123
7.2.5	Test requirements.....	123
7.3	Dynamic range	128
7.3.1	Definition and applicability	128
7.3.2	Minimum requirement	128
7.3.3	Test purpose.....	128
7.3.4	Method of test	128
7.3.4.1	Initial conditions	128
7.3.4.2	Procedure	129
7.3.5	Test requirements.....	129
7.4	In-band selectivity and blocking	137
7.4.1	Adjacent Channel Selectivity (ACS)	137
7.4.1.1	Definition and applicability.....	137
7.4.1.2	Minimum requirement	137
7.4.1.3	Test purpose	137
7.4.1.4	Method of test	137
7.4.1.4.1	Initial conditions.....	137
7.4.1.4.2	Procedure	138
7.4.1.5	Test requirements.....	138
7.4.2	In-band blocking	140
7.4.2.1	Definition and applicability.....	140
7.4.2.2	Minimum requirement	140
7.4.2.3	Test purpose	140
7.4.2.4	Method of test	140
7.4.2.4.1	Initial conditions	140
7.4.2.4.2	Procedure for general blocking.....	141
7.4.2.4.3	Procedure for narrowband blocking.....	141
7.4.2.5	Test requirements.....	142
7.5	Out-of-band blocking	145
7.5.1	Definition and applicability	145
7.5.2	Minimum requirement	145
7.5.3	Test purpose.....	145
7.5.4	Method of test	146
7.5.4.1	Initial conditions	146
7.5.4.2	Procedure	146
7.5.5	Test requirements.....	146
7.5.5.1	General requirements	146
7.5.5.2	Co-location requirements	147
7.6	Receiver spurious emissions.....	148
7.6.1	Definition and applicability	148
7.6.2	Minimum requirement	149
7.6.3	Test purpose.....	149
7.6.4	Method of test	149
7.6.4.1	Initial conditions	149
7.6.4.2	Procedure	149
7.6.5	Test requirements.....	150
7.6.5.1	Basic limits.....	150
7.6.5.2	BS type 1-C.....	150
7.6.5.3	BS type 1-H.....	150
7.7	Receiver intermodulation	151
7.7.1	Definition and applicability	151
7.7.2	Minimum requirement	151
7.7.3	Test purpose.....	151
7.7.4	Method of test	151
7.7.4.1	Initial conditions	151
7.7.4.2	Procedure	151
7.7.5	Test requirements.....	152

7.8	In-channel selectivity	157
7.8.1	Definition and applicability	157
7.8.2	Minimum requirement	157
7.8.3	Test purpose.....	157
7.8.4	Method of test	157
7.8.4.1	Initial conditions	157
7.8.4.2	Procedure	157
7.8.5	Test requirements.....	157
8	Conducted performance characteristics.....	165
8.1	General	165
8.1.1	Scope and definitions.....	165
8.1.2	Applicability rule	166
8.1.2.0	General	166
8.1.2.1	Applicability of PUSCH performance requirements	166
8.1.2.1.1	Applicability of requirements for different subcarrier spacings	166
8.1.2.1.2	Applicability of requirements for different channel bandwidths	166
8.1.2.1.3	Applicability of requirements for different configurations.....	166
8.1.2.1.7	Applicability of 2-step RA type requirements for different subcarrier spacings	167
8.1.2.2	Applicability of PUCCH performance requirements	167
8.1.2.2.1	Applicability of requirements for different formats.....	167
8.1.2.2.2	Applicability of requirements for different subcarrier spacings	167
8.1.2.2.3	Applicability of requirements for different channel bandwidths	167
8.1.2.2.4	Applicability of requirements for different configurations.....	167
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH.....	167
8.1.2.3	Applicability of PRACH performance requirements	168
8.1.2.3.1	Applicability of requirements for different formats.....	168
8.1.2.3.2	Applicability of requirements for different subcarrier spacings	168
8.1.2.3.3	Applicability of requirements for different channel bandwidths	168
8.1.2.3.4	Applicability of requirements for different restricted set types of long PRACH format 0	168
8.1.2.4	Applicability of PUSCH for high speed train performance requirements.....	168
8.1.2.4.1	Applicability of requirements for different speeds.....	168
8.1.2.4.2	Applicability of requirements for 1T1R.....	168
8.1.2.5	Applicability of interlaced PUSCH performance requirements.....	168
8.1.2.5.1	General applicability of interlaced PUSCH performance requirements	168
8.1.2.5.2	Applicability of requirements for different subcarrier spacings	168
8.1.2.5.3	Applicability of requirements for different channel bandwidths	169
8.1.2.5.4	Applicability of requirements for different configurations.....	169
8.1.2.5.5	Applicability of CG-UCI multiplexed on PUSCH requirements.....	169
8.1.2.6	Applicability of interlaced PUCCH performance requirements.....	169
8.1.2.6.1	General applicability of interlaced PUCCH performance requirements	169
8.1.2.6.2	Applicability of requirements for different formats.....	169
8.1.2.6.3	Applicability of requirements for different subcarrier spacings	169
8.1.2.6.4	Applicability of requirements for different channel bandwidths	169
8.1.2.7	Applicability of performance requirements for PRACH with $L_{RA} = 1151$ and $L_{RA} = 571$	170
8.1.2.7.1	Applicability of requirements for different formats.....	170
8.1.2.7.2	Applicability of requirements for different subcarrier spacings	170
8.1.2.7.3	Applicability of requirements for different channel bandwidths	170
8.2	Performance requirements for PUSCH	170
8.2.1	Performance requirements for PUSCH with transform precoding disabled	170
8.2.1.1	Definition and applicability.....	170
8.2.1.2	Minimum Requirement	170
8.2.1.3	Test Purpose	170
8.2.1.4	Method of test	170
8.2.1.4.1	Initial Conditions	170
8.2.1.4.2	Procedure	170
8.2.1.5	Test Requirement	171
8.2.2	Performance requirements for PUSCH with transform precoding enabled	179
8.2.2.1	Definition and applicability.....	179
8.2.2.2	Minimum Requirement	179
8.2.2.3	Test Purpose	179
8.2.2.4	Method of test	179

8.2.2.4.1	Initial Conditions	179
8.2.2.4.2	Procedure	180
8.2.2.5	Test Requirement	181
8.2.3	Performance requirements for UCI multiplexed on PUSCH	181
8.2.3.1	Definition and applicability	181
8.2.3.2	Minimum Requirements	182
8.2.3.3	Test purpose	182
8.2.3.4	Method of test	182
8.2.3.4.1	Initial conditions	182
8.2.3.4.2	Procedure	182
8.2.3.5	Test Requirement	183
8.2.4	Performance requirements for PUSCH for high speed train	184
8.2.4.1	Definition and applicability	184
8.2.4.2	Minimum Requirement	185
8.2.4.3	Test Purpose	185
8.2.4.4	Method of test	185
8.2.4.4.1	Initial Conditions	185
8.2.4.4.2	Procedure	185
8.2.4.5	Test Requirement	186
8.2.5	Performance requirements for UL timing adjustment	189
8.2.5.1	Definition and applicability	189
8.2.5.2	Minimum Requirement	189
8.2.5.3	Test Purpose	189
8.2.5.4	Method of test	189
8.2.5.4.1	Initial Conditions	189
8.2.5.4.2	Procedure	189
8.2.5.5	Test Requirement for High Speed Train	192
8.2.6	Performance requirements for PUSCH with 0.001% BLER	193
8.2.6.1	Definition and applicability	193
8.2.6.2	Minimum Requirement	193
8.2.6.3	Test Purpose	193
8.2.6.4	Method of test	193
8.2.6.4.1	Initial Conditions	193
8.2.6.4.2	Procedure	193
8.2.6.5	Test Requirement	194
8.2.7	Performance requirements for PUSCH repetition Type A	195
8.2.7.1	Definition and applicability	195
8.2.7.2	Minimum Requirement	196
8.2.7.3	Test Purpose	196
8.2.7.4	Method of test	196
8.2.7.4.1	Initial Conditions	196
8.2.7.4.2	Procedure	196
8.2.7.5	Test Requirement	197
8.2.8	Performance requirements for PUSCH Mapping Type B with non-slot transmission	199
8.2.8.1	Definition and applicability	199
8.2.8.2	Minimum Requirement	199
8.2.8.3	Test Purpose	199
8.2.8.4	Method of test	199
8.2.8.4.1	Initial Conditions	199
8.2.8.4.2	Procedure	199
8.2.8.5	Test Requirement	200
8.2.9	Performance requirements for PUSCH msgA for 2-step RA type	201
8.2.9.1	Definition and applicability	201
8.2.9.2	Minimum Requirement	201
8.2.9.3	Test Purpose	201
8.2.9.4	Method of test	201
8.2.9.4.1	Initial Conditions	201
8.2.9.4.2	Procedure	201
8.2.9.5	Test Requirement	203
8.2.10	Requirements for interlaced PUSCH	204
8.2.10.1	Definition and applicability	204
8.2.10.2	Minimum Requirement	204

8.2.10.3	Test Purpose	204
8.2.10.4	Method of test	204
8.2.10.4.1	Initial Conditions	204
8.2.10.4.2	Procedure	205
8.2.10.5	Test Requirement	206
8.2.11	Performance requirements for CG-UCI multiplexed on interlaced PUSCH.....	206
8.2.11.1	Definition and applicability.....	206
8.2.11.2	Minimum Requirements.....	207
8.2.11.3	Test purpose	207
8.2.11.4	Method of test	207
8.2.11.4.1	Initial conditions.....	207
8.2.11.4.2	Procedure	207
8.2.11.5	Test Requirement	208
8.3	Performance requirements for PUCCH	209
8.3.1	Performance requirements for PUCCH format 0.....	209
8.3.1.1	Definition and applicability.....	209
8.3.1.2	Minimum Requirement	209
8.3.1.3	Test purpose	210
8.3.1.4	Method of test	210
8.3.1.4.1	Initial conditions.....	210
8.3.1.4.2	Procedure	210
8.3.1.5	Test Requirement	211
8.3.2	Performance requirements for PUCCH format 1	212
8.3.2.1	NACK to ACK detection	212
8.3.2.1.1	Definition and applicability.....	212
8.3.2.1.2	Minimum Requirement	212
8.3.2.1.3	Test purpose	212
8.3.2.1.4	Method of test.....	212
8.3.2.1.4.1	Initial Conditions	212
8.3.2.1.4.2	Procedure	212
8.3.2.1.5	Test Requirement.....	213
8.3.2.2	ACK missed detection. ETSI TS 138 141-1, V16.8.0 (2021-09)	214
8.3.2.2.1	Definition and applicability tag/standards/sist/da9c2bda-4958-4cb5-b599-6403/etsi-ts-138-141-1-v16-8-0-2021-09	214
8.3.2.2.2	Minimum Requirement 6403/etsi-ts-138-141-1-v16-8-0-2021-09	214
8.3.2.2.3	Test purpose	214
8.3.2.2.4	Method of test.....	215
8.3.2.2.4.1	Initial Conditions	215
8.3.2.2.4.2	Procedure	215
8.3.2.2.5	Test Requirement.....	216
8.3.3	Performance requirements for PUCCH format 2	216
8.3.3.1	ACK missed detection.....	216
8.3.3.1.1	Definition and applicability	216
8.3.3.1.2	Minimum requirements	217
8.3.3.1.3	Test purpose	217
8.3.3.1.4	Method of test.....	217
8.3.3.1.4.1	Initial Condition	217
8.3.3.1.4.2	Procedure	217
8.3.3.1.5	Test requirements	218
8.3.3.2	UCI BLER performance requirements	218
8.3.3.2.1	Definition and applicability	218
8.3.3.2.2	Minimum Requirement	218
8.3.3.2.3	Test purpose	219
8.3.3.2.4	Method of test.....	219
8.3.3.2.4.1	Initial Condition	219
8.3.3.2.4.2	Procedure	219
8.3.3.2.5	Test requirements	220
8.3.4	Performance requirements for PUCCH format 3	220
8.3.4.1	Definition and applicability.....	220
8.3.4.2	Minimum requirement	220
8.3.4.3	Test purpose	220
8.3.4.4	Method of test	221
8.3.4.4.1	Initial conditions.....	221

8.3.4.4.2	Procedure	221
8.3.4.5	Test requirement	222
8.3.5	Performance requirements for PUCCH format 4	223
8.3.5.1	Definition and applicability	223
8.3.5.2	Minimum requirement	223
8.3.5.3	Test purpose	223
8.3.5.4	Method of test	223
8.3.5.4.1	Initial conditions	223
8.3.5.4.2	Procedure	223
8.3.5.5	Test requirement	224
8.3.6	Performance requirements for multi-slot PUCCH	225
8.3.6.1	Performance requirements for multi-slot PUCCH format 1	225
8.3.6.1.1	NACK to ACK detection	225
8.3.6.1.1.1	Definition and applicability	225
8.3.6.1.1.2	Minimum Requirement	225
8.3.6.1.1.3	Test purpose	225
8.3.6.1.1.4	Method of test	225
8.3.6.1.1.4.1	Initial conditions	225
8.3.6.1.1.4.2	Procedure	226
8.3.6.1.1.5	Test Requirement	226
8.3.6.1.2	ACK missed detection	227
8.3.6.1.2.1	Definition and applicability	227
8.3.6.1.2.2	Minimum Requirement	227
8.3.6.1.2.3	Test purpose	227
8.3.6.1.2.4	Method of test	227
8.3.6.1.2.4.1	Initial conditions	227
8.3.6.1.2.4.2	Procedure	227
8.3.6.1.2.5	Test Requirement	228
8.3.7	Performance requirements for interlaced PUCCH format 0	229
8.3.7.1	Definition and applicability	229
8.3.7.2	Minimum Requirement	229
8.3.7.3	Test purpose	229
8.3.7.4	Method of test	229
8.3.7.4.1	Initial conditions	229
8.3.7.4.2	Procedure	229
8.3.7.5	Test Requirement	230
8.3.8	Performance requirements for interlaced PUCCH format 1	231
8.3.8.1	NACK to ACK detection	231
8.3.8.1.1	Definition and applicability	231
8.3.8.1.2	Minimum Requirement	231
8.3.8.1.3	Test purpose	231
8.3.8.1.4	Method of test	231
8.3.8.1.4.1	Initial Conditions	231
8.3.8.1.4.2	Procedure	231
8.3.8.1.5	Test Requirement	232
8.3.8.2	ACK missed detection	233
8.3.8.2.1	Definition and applicability	233
8.3.8.2.2	Minimum Requirement	233
8.3.8.2.3	Test purpose	233
8.3.8.2.4	Method of test	233
8.3.8.2.4.1	Initial Conditions	233
8.3.8.2.4.2	Procedure	233
8.3.8.2.5	Test Requirement	234
8.3.9	Performance requirements for interlaced PUCCH format 2	234
8.3.9.1	Definition and applicability	234
8.3.9.2	Minimum requirement	235
8.3.9.3	Test purpose	235
8.3.9.4	Method of test	235
8.3.9.4.1	Initial conditions	235
8.3.9.4.2	Procedure	235
8.3.9.5	Test requirement	236
8.3.10	Performance requirements for interlaced PUCCH format 3	236

8.3.10.1	Definition and applicability.....	236
8.3.10.2	Minimum requirement	236
8.3.10.3	Test purpose	237
8.3.10.4	Method of test	237
8.3.10.4.1	Initial conditions.....	237
8.3.10.4.2	Procedure.....	237
8.3.10.5	Test requirement	238
8.4	Performance requirements for PRACH	238
8.4.1	PRACH false alarm probability and missed detection.....	238
8.4.1.1	Definition and applicability.....	238
8.4.1.2	Minimum requirement	239
8.4.1.3	Test purpose	239
8.4.1.4	Method of test	239
8.4.1.4.1	Initial conditions.....	239
8.4.1.4.2	Procedure.....	239
8.4.1.5	Test requirement for Normal Mode.....	241
8.4.1.6	Test requirement for high speed train.....	241
8.4.1.7	Test requirement for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	242

Annex A (normative): Reference measurement channels 244

A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3).....	244
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	245
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	247
A.3A	Fixed Reference Channels for performance requirements (QPSK, R=99/1024)	249
A.3B	Fixed Reference Channels for performance requirements (QPSK, R=308/1024)	250
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	251
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	253
A.6	PRACH test preambles.....	255
A.7	Fixed Reference Channels for performance requirements (QPSK, R=157/1024)	255

Annex B (normative): Environmental requirements for the BS equipment 257

B.1	General	257
B.2	Normal test environment.....	257
B.3	Extreme test environment.....	257
B.3.1	Extreme temperature	257
B.4	Vibration.....	258
B.5	Power supply	258
B.6	Measurement of test environments.....	258

Annex C (informative): Test tolerances and derivation of test requirements..... 259

C.1	Measurement of transmitter.....	259
C.2	Measurement of receiver	261
C.3	Measurement of performance requirements	262

Annex D (informative): Measurement system set-up 265

D.1	BS type I-C transmitter.....	265
D.1.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for BS type I-C	265
D.1.2	Transmitter intermodulation for BS type I-C.....	265

D.1.3	Time alignment error for <i>BS type 1-C</i>	266
D.2	<i>BS type 1-C receiver</i>	266
D.2.1	Reference sensitivity level for <i>BS type 1-C</i>	266
D.2.2	Dynamic range for <i>BS type 1-C</i>	267
D.2.3	In-channel selectivity for <i>BS type 1-C</i>	267
D.2.4	Adjacent Channel Selectivity (ACS) and narrowband blocking for <i>BS type 1-C</i>	268
D.2.5	Blocking characteristics for <i>BS type 1-C</i>	268
D.2.6	Receiver spurious emission for <i>BS type 1-C</i>	269
D.2.7	Intermodulation characteristics for <i>BS type 1-C</i>	269
D.3	<i>BS type 1-H transmitter</i>	270
D.3.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for <i>BS type 1-H</i>	270
D.3.2	Transmitter intermodulation for <i>BS type 1-H</i>	271
D.3.3	Transmitter spurious emissions for <i>BS type 1-H</i>	271
D.3.4	Time alignment error for <i>BS type 1-H</i>	273
D.4	<i>BS type 1-H receiver</i>	273
D.4.1	Reference sensitivity level for <i>BS type 1-H</i>	273
D.4.2	Receiver dynamic range for <i>BS type 1-H</i>	274
D.4.3	Receiver adjacent channel selectivity and narrowband blocking for <i>BS type 1-H</i>	274
D.4.4	Receiver spurious emissions	274
D.4.5	Receiver In-channel selectivity for <i>BS type 1-H</i>	276
D.4.6	Receiver intermodulation for <i>BS type 1-H</i>	277
D.5	<i>BS type 1-C performance requirements</i>	277
D.5.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions and for high speed condition	277
D.5.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..278	
D.5.3	Performance requirements for PUSCH and PRACH in static conditions	278
D.5.4	Performance requirements for UL timing adjustment	279
D.6	<i>BS type 1-H performance requirements</i>	279
D.6.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions and for high speed condition .. https://standards.etsi.org/standards/3gpp/138_141/138_141-1_v16_8_0-2021-09 ..279	
D.6.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..280	
D.6.3	Performance requirements for PUSCH and PRACH in static conditions	280
D.6.4	Performance requirements for UL timing adjustment	281
Annex E (normative):	Characteristics of interfering signals	282
Annex F (normative):	Void	283
Annex G (normative):	Propagation conditions.....	284
G.1	Static propagation condition	284
G.2	Multi-path fading propagation conditions	284
G.2.1	Delay profiles	284
G.2.1.1	Delay profiles for FR1	285
G.2.2	Combinations of channel model parameters	286
G.2.3	MIMO channel correlation matrices	287
G.2.3.1	MIMO correlation matrices using Uniform Linear Array	287
G.2.3.1.1	Definition of MIMO correlation matrices	287
G.2.3.1.2	MIMO correlation matrices at high, medium and low level	288
G.2.3.2	Multi-antenna channel models using cross polarized antennas	290
G.2.3.2.1	Definition of MIMO correlation matrices using cross polarized antennas	291
G.2.3.2.2	Spatial correlation matrices at UE and gNB sides	291
G.2.3.2.2.1	Spatial correlation matrices at UE side	291
G.2.3.2.2.2	Spatial correlation matrices at gNB side	291
G.2.3.2.3	MIMO correlation matrices using cross polarized antennas	292
G.3	High speed train condition	292

G.4	Moving propagation conditions.....	296
Annex H (normative):	In-channel TX tests.....	298
H.1	General	298
H.2	Basic principles	298
H.2.1	Output signal of the TX under test	298
H.2.2	Ideal signal	298
H.2.3	Measurement results.....	299
H.2.4	Measurement points	299
H.3	Pre-FFT minimization process	300
H.4	Timing of the FFT window	300
H.5	Resource element TX power	301
H.6	Post-FFT equalisation.....	302
H.7	EVM	303
H.7.0	General.....	303
H.7.1	Averaged EVM (FDD).....	304
H.7.2	Averaged EVM (TDD).....	304
Annex I (normative):	General rules for statistical testing.....	305
I.1	Testing methodology of PUSCH performance requirements with 0.001% BLER	305
I.1.1	General	305
I.1.2	Numerical definition of the pass-fail limits for testing PUSCH 0.001% BLER	306
I.1.3	Theory to derive the early pass/fail limits in I.4.2 (informative).....	307
I.1.3.1	Numerical definition of the pass-fail limits for testing PUSCH 0.001% BLER	307
I.1.3.2	Simulation to derive the pass-fail limits for testing PUSCH 0.001% BLER	307
Annex J (informative):	Change history TS 38.141-1 V16.8.0 (2021-09)	309
History	https://standards.iteh.ai/catalog/standards/sist/da9c2bda-4958-4cb5-b599-f61151fe6403/etsi-ts-138-141-1-v16-8-0-2021-09	318