

SLOVENSKI STANDARD oSIST prEN ISO 24505:2017

01-julij-2017

Ergonomija - Dostopno načrtovanje - Postopek za izdelavo barvnih kombinacij ob upoštevanju s starostjo povezanih sprememb človeškega zaznavanja barv (ISO 24505:2016)

Ergonomics - Accessible design - Method for creating colour combinations taking account of age-related changes in human colour vision (ISO 24505:2016)

Ergonomie - Barrierefreie Gestaltung - Verfahren für die Gestaltung von Farbkombinationen unter Berücksichtigung altersbedingter Veränderungen der menschlichen Farbwahrnehmung (ISO 24505:2016) 1. 21

Ergonomie - Conception accessible - Méthode de création de combinaisons de couleurs tenant compte des changements liés à l'âge dans la vision en couleurs humaine (ISO 24505:2016)

Ta slovenski standard je istoveten z: prEN ISO 24505

ICS:

13.180 Ergonomija Ergonomics

oSIST prEN ISO 24505:2017 en,fr,de

oSIST prEN ISO 24505:2017

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 24505:2017

INTERNATIONAL STANDARD

ISO 24505

First edition 2016-04-01

Ergonomics — Accessible design — Method for creating colour combinations taking account of agerelated changes in human colour vision

Ergonomie — Conception accessible — Méthode de création de combinaisons de couleurs tenant compte des changements liés à l'âge iTeh ST dans la vision en couleurs humaine

(standards.iteh.ai)



iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 24505:2017 https://standards.iteh.ai/catalog/standards/sist/946b2747-c296-4d7a-aecb-83a45aed0ee0/osist-pren-iso-24505-2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Con	itents	Page
Forev	word	iv
Intro	duction	v
1	Scope	1
2	Normative references	
3	Terms and definitions	1
4	Factors affecting conspicuity of colour combinations 4.1 General 4.2 Luminance level 4.3 Ageing effect 4.4 Viewing mode and condition	2 2
5	 Colour combinations using fundamental colours and their conspicuity 5.1 Fundamental colours and their combinations 5.2 Classification of the conspicuity of colour combinations 5.3 Tables of two-colour combinations of fundamental colours and their conspicuity 5.4 Span 1 of fundamental colours 	3 4 5
6	Procedures to create a colour combination	8
	ex A (normative) Spans of fundamental colours (Span 2)	
Anne	x B (informative) Colouring example: A train network.	22
	ex C (informative) Guidance for transformation of Munsell colour system to CIE XYZ system and to sRGB system in monitor displays	
Biblio	ography <u>osist pren iso 24505 2017</u>	25

https://standards.iteh.ai/catalog/standards/sist/946b2747-c296-4d7a-aecb-83a45aed0ee0/osist-pren-iso-24505-2017

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 159, *Ergonomics*, Subcommittee SC 5, *Ergonomics* of the physical environment.

Introduction

While the social care of older people has widely spread in many countries, the design and production of visual signs and displays do not always take into account the unique needs of older people. This International Standard presents a method for assessing and designing signs and displays in our visual environment so that they are clearly visible to older people. This International Standard includes a method and data for creating conspicuous colour combinations in visual signs and displays seen by people at any age by considering age-related change of human colour vision.

A reasonably large number of people, especially men, have defective colour vision of various types, and some smaller part of the population have suffered from medical disorders of the eye such as low vision. This International Standard is not applicable to colour combinations for people who have deficient colour vision or medical disorders affecting vision. Other International Standards are planned that will provide methods to enable the creation of colour combinations for people with widely varying visual disabilities, including those for people with normal colour vision at any age, people with colour deficiencies and people with low vision, and for general guidance on the use of the colour-combination standard.

In describing colours in this International Standard, the Munsell colour system is used, which is a colour-order system recommended by the Commission Internationale de l'Eclairage. [9]

This International Standard adopts the principles of accessible design given in Reference [3] and amplified in Reference [4].

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 24505:2017

iTeh STANDARD PREVIEW (standards.iteh.ai)

Ergonomics — Accessible design — Method for creating colour combinations taking account of age-related changes in human colour vision

1 Scope

This International Standard provides a method for creating conspicuous colour combinations for use in visual signs and displays taking into account viewer age. It is based on the perceived similarity of colours at photopic and mesopic lighting conditions.

This International Standard applies to the design of visual signs and displays in which multiple colours are used so that the colours are conspicuous to people of any age, including older people who do not have deficient colour vision. The method and data in this International Standard are not applicable to the design of visual signs and displays for people with colour deficiencies or medical disorders affecting vision.

Basically, this International Standard applies to the reflective or object mode colours, but may apply to self-luminous mode colours if the colour coordinates are appropriately transferred to those of the object mode colours.

2 Normative references STANDARD PREVIEW

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

https://standards.iteh.ai/catalog/standards/sist/946b2747-c296-4d7a-aecb-ISO 3864-1, Graphical symbols 33afety-colours, and safety signs — Part 1: Design principles for safety signs and safety markings

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

colour similarity

extent to which some percentage of the population judge a given colour as similar to a fundamental reference colour

 $\mathsf{EXAMPLE}$ Colour similarity of 50 % means that half of the people judge a given colour as similar to the reference colour.

3.2

fundamental colour

set of basic colours perceived by people with normal colour vision, which are red, orange (yellow-red), yellow, green-yellow, green, blue-green, blue, purple-blue, purple, red-purple, black, grey, and white, in accordance with the Munsell colour system

3.3

mesopic vision

vision by the normal eye intermediate between photopic and scotopic vision

[SOURCE: CIE S 017/E:2011]

Note 1 to entry: In mesopic vision, both the cones and the rods are active.

3.4

photopic vision

vision by the normal eye in which cones are the principle active photoreceptors

[SOURCE: CIE S 017/E:2011]

Note 1 to entry: Photopic vision normally occurs when the eye is adapted to levels of luminance of at least 5 cd/m².

Note 2 to entry: Colour perception is typical of photopic vision.

3.5

scotopic vision

vision by the normal eye in which rods are the principle active photoreceptors

[SOURCE: CIE S 017/E:2011]

Note 1 to entry: Scotopic vision normally occurs when the eye is adapted to levels of luminance of less than 10^{-3} cd/m².

Note 2 to entry: In comparison with photopic vision, scotopic vision is characterized by the lack of colour perception and a shift of visual sensitivity towards shorter wavelengths.

span of a fundamental colour

area in a colour space in which colours are perceived as similar to a reference colour in colour appearance

Note 1 to entry: The span is definable differently according to the extent of similarity to the reference fundamental colour, such as "very similar", "moderately similar", or "slightly similar".

Note 2 to entry: The Munsell colour system is used to describe the span in this International Standard.

oSIST prEN ISO 24505:2017

https://standards.iteh.ai/catalog/standards/sist/946b2747-c296-4d7a-aecb-Factors affecting conspicuity of colour combinations

4.1 General

Colour combinations should be conspicuous whenever colours are used for identifying, discriminating, or recognizing information in visual signs and displays. The factors given in 4.2 to 4.4 shall be taken into account in creating and using colour combinations.

For the special use of colour for safety, the selection of colours and colour combinations shall comply with ISO 3864-1.

Conspicuity of a colour combination is the distinctiveness between, and identification of, each colour used in the combination. In colour science, conspicuous colour combination applies to a combination with relatively large colour differences, whereas colour discrimination refers to small colour differences such as a just noticeable difference.

4.2 Luminance level

Colour appearance changes with luminance level. This effect shall be taken into consideration, particularly in choosing colours for use in low-luminance environments such as those in mesopic vision.

EXAMPLE In mesopic vision, reddish colours appear relatively darker and bluish colours appear brighter.

4.3 Ageing effect

Colour appearance changes with age. This effect shall be taken into account, particularly in choosing colours for use by older people.

NOTE Age-related change of colour perception is described in Reference [3]. EXAMPLE A bluish colour on dark background or vice versa is difficult for older people to see.

4.4 Viewing mode and condition

Colour appearance changes with the viewing mode such as the self-luminous mode or the reflective or object mode. This International Standard is based on the Munsell colour system, the colour appearance of which is the object mode. For colours of the self-luminous mode or light sources, such as electronic displays, this International Standard can be applicable when appropriate conversion of colour appearance is assured.

NOTE 1 Transformation of colour coordinates of Munsell colour system to CIE XYZ system has not been formulated yet. There are, however, some conversion methods or data for practical use which can be applied to the self-luminous mode colours (see $\underline{\text{Annex C}}$).

NOTE 2 Some requirements for using colours in electronic visual displays are described in more detail in References [1] and [5].

NOTE 3 The light source of illumination is a factor affecting the appearance of object-mode colours. This International Standard is based on data taken under a daylight fluorescent lamp. When using other light sources, such as incandescent lamps or LEDs, it is noted that the colour appearance is shifted (see Reference [7]).

Colour appearance also changes with visual field size and surrounding colours. This International Standard is based on the field size larger than 20 min of arc of visual angle (2,9 mm from the 50 cm distance) below which colour appearance changes. Care shall be taken to ensure that the visual angle is above 20 min of arc.

This International Standard is based on dark surround where no strong contrast effect occurs. For coloured or lighter surround, the colour appearance also changes more or less with the surround, and care shall be taken not to cause strong change of the appearance.

oSIST prEN ISO 24505:2017

5 Colour combinations using fundamental colours and their conspicuity

83a45aed0ee0/osist-pren-iso-24505-2017


5.1 Fundamental colours and their combinations

Thirteen colours are defined as fundamental colours in this International Standard which are perceived as the most basic in human colour perception for people with normal colour vision. They are red, yellow-red (orange), yellow, green-yellow, green, blue-green, blue, purple-blue, purple, red-purple, white, grey, and black.

Each fundamental colour has a span in a colour space that consists of colours similar in appearance to each reference colour of the fundamentals. Two spans are definable with different extent of similarity: Span 1 consists of colours that are highly similar to the reference, Span 2 are colours that are somewhat or less similar to the reference.

NOTE Span 1 and Span 2, respectively, denote areas in which colours are perceived as similar to the reference fundamental colour with the 50% and 10% colour similarity (see 3.1 and 3.6).

The fundamental colours and their spans are used as components of colour combinations. Exact colours for a combination shall be selected respectively from the Span 1 of each fundamental colour (see Figure 1).



Key	
1	red
2	purple-blue
	Span 1
	Span 2
	reference colour for red fundamental colour
	reference colour for purple-blue fundamental colour

Figure 1 — Examples of Span 1 and Span 2 of fundamental colours in Munsell colour system and an example of colour combination (for value 5 plane only)

5.2 Classification of the conspicuity of colour combinations cape-4d7a-aecb-

The conspicuity of the colour combinations based on fundamental colours is classified into the following three groups depending on the geometrical relations of the Span 1 and Span 2 in a colour space.

a) Highly conspicuous colour combinations

Combinations of fundamental colours for which Span 1 does not mutually overlap in the colour space and neither does Span 2. See Figure 2 c).

b) Conspicuous colour combinations

Combinations of fundamental colours for which Span 1 does not mutually overlap in a colour space, but Span 2 does. See Figure 2 b).

c) Slightly conspicuous colour combination

Combinations of fundamental colours for which Span 1 mutually overlaps in a colour space and Span 2 does as well. See Figure 2 a).