
**Small craft — Reciprocating internal
combustion engines exhaust
emission measurement — Test-
bed measurement of gaseous and
particulate exhaust emissions**

*Petits navires — Moteurs alternatifs à combustion interne mesurage
des émissions de gaz d'échappement — Mesurage des émissions de
gaz et de particules au banc*

(<https://standards.iteh.ai>)
Document Preview

[ISO 18854:2015](https://standards.iteh.ai/catalog/standards/iso/8ce63e01-d442-475e-9589-e996b9403eba/iso-18854-2015)

<https://standards.iteh.ai/catalog/standards/iso/8ce63e01-d442-475e-9589-e996b9403eba/iso-18854-2015>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 18854:2015

<https://standards.iteh.ai/catalog/standards/iso/8ce63e01-d442-475e-9589-e996b9403eba/iso-18854-2015>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vii
Introduction	viii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviations	3
4.1 General symbols.....	3
4.2 Symbols for fuel composition.....	5
4.3 Symbols and abbreviations for the chemical components.....	5
4.4 Abbreviations.....	6
5 Test conditions	7
5.1 Engine test conditions.....	7
5.1.1 Test condition parameter.....	7
5.1.2 Test validity.....	7
5.2 Engines with charge air cooling.....	7
5.3 Power.....	8
5.4 Specific test conditions.....	8
5.4.1 Engine air inlet system.....	8
5.4.2 Engine exhaust system.....	8
5.4.3 Cooling system.....	8
5.4.4 Lubricating oil.....	9
5.4.5 Adjustable carburettors.....	9
5.4.6 Crankcase breather.....	9
6 Test fuels	9
7 Application of the engine family concept and choice of parent engine	9
8 Measurement equipment and data to be measured	10
8.1 General.....	10
8.2 Dynamometer specification.....	10
8.3 Exhaust gas flow.....	10
8.3.1 General.....	10
8.3.2 Direct measurement method.....	10
8.3.3 Air and fuel measurement method.....	11
8.3.4 Fuel flow and carbon balance method.....	11
8.3.5 Tracer measurement method.....	11
8.3.6 Air flow and air-to-fuel ratio measurement method.....	12
8.3.7 Total dilute exhaust gas flow.....	13
8.4 Accuracy.....	13
8.5 Determination of the gaseous components.....	14
8.5.1 General analyser specifications.....	14
8.5.2 Gas drying.....	15
8.5.3 Analysers.....	15
8.5.4 Sampling for gaseous emissions.....	17
8.6 Particulate determination.....	18
8.6.1 General.....	18
8.6.2 Particulate sampling filters.....	19
8.6.3 Weighing chamber and analytical balance specifications.....	20

9	Calibration of the analytical instruments	20
9.1	General requirements	20
9.2	Calibration gases	21
9.2.1	General	21
9.2.2	Pure gas	21
9.2.3	Calibration and span gases	21
9.2.4	Use of gas dividers	21
9.2.5	Oxygen interference gases	22
9.3	Operating procedure for analysers and sampling system	22
9.4	Leakage test	22
9.5	Calibration procedure	22
9.5.1	Instrument assembly	22
9.5.2	Warm-up time	22
9.5.3	NDIR and HFID analyser	22
9.5.4	GC and HPCL	23
9.5.5	Establishment of the calibration curve	23
9.5.6	Alternative calibration methods	23
9.5.7	Verification of the calibration	23
9.6	Calibration of tracer gas analyser for exhaust flow measurement	23
9.7	Efficiency test of the NO _x converter	24
9.7.1	General	24
9.7.2	Test setup	24
9.7.3	Calibration	24
9.7.4	Calculation	25
9.7.5	Adding of oxygen	25
9.7.6	Activation of the ozonator	25
9.7.7	NO _x mode	25
9.7.8	Deactivation of the ozonator	25
9.7.9	NO mode	25
9.7.10	Test interval	25
9.7.11	Efficiency requirement	25
9.8	Adjustment of the FID	26
9.8.1	Optimization of the detector response	26
9.8.2	Hydrocarbon response factors	26
9.8.3	Oxygen interference check	26
9.8.4	Efficiency of the Non-Methane Cutter (NMC)	27
9.8.5	Methanol response factor	28
9.9	Interference effects with CO, CO ₂ , NO _x , O ₂ , NH ₃ , and N ₂ O analysers	28
9.9.1	General	28
9.9.2	CO analyser interference check	29
9.9.3	NO _x analyser quench checks	29
9.9.4	O ₂ analyser interference	30
9.9.5	Cross-interference check compensation for NH ₃ and N ₂ O measurement channels using IR and UV measurement techniques	31
9.10	Calibration intervals	33
10	Calibration of the particulate measuring system	33
10.1	General	33
10.2	Calibration procedure	33
10.2.1	Flow measurement	33
10.2.2	Exhaust gas analysers	33
10.2.3	Carbon flow check	33
10.3	Checking the partial-flow conditions	33
10.4	Calibration intervals	33

11	Calibration of the CVS full-flow dilution system	34
11.1	General	34
11.2	Calibration of the Positive Displacement Pump (PDP)	34
11.2.1	General	34
11.2.2	Data analysis	34
11.3	Calibration of the Critical-Flow Venturi (CFV)	35
11.3.1	General	35
11.3.2	Data analysis	35
11.4	Calibration of the Subsonic Venturi (SSV)	36
11.4.1	General	36
11.4.2	Data analysis	36
11.5	Total system verification	37
11.5.1	General	37
11.5.2	Metering with a critical flow orifice	37
11.5.3	Metering by means of a gravimetric technique	37
12	Test cycles (running conditions)	38
12.1	Requirements	38
12.2	Test cycles	38
12.2.1	Applications	38
12.2.2	Test modes and weighting factors	39
12.2.3	Performing the test	40
13	Test run	40
13.1	Preparation of the sampling filters	40
13.2	Installation of the measuring equipment	40
13.3	Starting the dilution system and the engine	40
13.4	Adjustment of the dilution ratio	40
13.5	Determination of test points	41
13.6	Checking of the analysers	41
13.7	Test cycles	41
13.7.1	Test sequence	41
13.7.2	Analyser response	42
13.7.3	Particulate sampling	42
13.7.4	Engine conditions	42
13.8	Re-checking the analysers	42
13.9	Test report	42
14	Data evaluation for gaseous and particulate emissions	42
14.1	Gaseous emissions	42
14.2	Particulate emissions	43
15	Calculation of the gaseous emissions	43
15.1	General	43
15.2	Determination of the exhaust gas flow	44
15.3	Dry/wet correction	44
15.4	NO _x correction for humidity and temperature	46
15.5	Calculation of the emission mass flow rates	47
15.5.1	Raw exhaust gas	47
15.5.2	Dilute exhaust gas	48
15.5.3	Determination of the NMHC concentration	50
15.6	Calculation of the specific emission	51

16	Calculation of the particulate emission	51
16.1	Particulate correction factor for humidity.....	51
16.2	Partial-flow dilution system.....	52
16.2.1	Isokinetic systems.....	52
16.2.2	Systems with measurement of CO ₂ or NO _x concentration.....	52
16.2.3	Systems with CO ₂ measurement and carbon balance method.....	52
16.2.4	Systems with flow measurement.....	53
16.3	Full-flow dilution system.....	53
16.4	Calculation of the particulate mass flow rate.....	53
16.5	Calculation of the specific emissions.....	54
16.6	Effective weighting factor.....	54
17	Determination of the gaseous emissions	55
17.1	General.....	55
17.2	Main exhaust components CO, CO ₂ , HC, NO _x , O ₂	55
17.3	Ammonia analysis.....	60
17.4	Methane analysis.....	61
17.4.1	Gas chromatographic (GC) method (Figure 6).....	61
17.4.2	Non-methane cutter (NMC) method (Figure 7).....	63
17.5	Methanol analysis.....	64
17.6	Formaldehyde analysis.....	65
18	Determination of the particulates	67
18.1	General.....	67
18.2	Dilution system.....	67
18.2.1	Partial-flow dilution system (Figures 10 to 18).....	67
18.2.2	Full-flow dilution system.....	79
18.3	Particulate sampling system.....	82
Bibliography		86

Document Preview

ISO 18854:2015

<https://standards.iteh.ai/catalog/standards/iso/8ce63e01-d442-475e-9589-e996b9403eba/iso-18854-2015>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 188, *Small craft, SC 2, Engines and propulsion systems*.

Document Preview

[ISO 18854:2015](#)

<https://standards.iteh.ai/catalog/standards/iso/8ce63e01-d442-475e-9589-e996b9403eba/iso-18854-2015>

Introduction

This International Standard is intended for use as a measurement procedure to determine the gaseous and particulate emission levels of reciprocating internal combustion (RIC) engines for marine use in small craft. Its purpose is to provide a map of an engine's emissions characteristics which, through use of the proper weighting factors, can be used as an indication of that engine's emission levels under various applications. The emission results are expressed in units of grams per kilowatt-hour and represent the mass rate of emissions per unit of work accomplished.

Although this International Standard is designed for marine engines, it shares many principles with particulate and gaseous emission measurements that have been in use for many years for on-road engines. One test procedure that shares many of these principles is the process of mixing dilution air with the total exhaust flow prior to separating a fraction of the diluted exhaust stream for analysis (full-flow dilution method) as currently specified for certification of 1985 and later heavy-duty truck engines in the USA. Another is the procedure for direct measurement of the gaseous emissions in the undiluted exhaust gas, as currently specified for the certification of heavy-duty truck engines in Japan and Europe.

NOTE It is common in many full-flow dilution systems to dilute this fraction of pre-diluted exhaust a second time to obtain appropriate sample temperatures at the particulate filter (see [Figure 19](#)).

Many of the procedures described in this International Standard are detailed accounts of laboratory methods, since determining an emissions value requires performing a complex set of individual measurements, rather than obtaining a single measured value. Thus, the results obtained depend as much on the process of performing the measurements as they depend on the engine and test method.

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 18854:2015](#)

<https://standards.iteh.ai/catalog/standards/iso/8ce63e01-d442-475e-9589-e996b9403eba/iso-18854-2015>

Small craft — Reciprocating internal combustion engines exhaust emission measurement — Test-bed measurement of gaseous and particulate exhaust emissions

1 Scope

This International Standard specifies the measurement and evaluation methods for gaseous and particulate exhaust emissions from reciprocating internal combustion (RIC) engines under steady-state conditions on a test bed, necessary for determining one weighted value for each exhaust gas pollutant. Various combinations of engine load and speed reflect different engine applications.

This International Standard is applicable to RIC marine engines intended to be installed in small craft up to 24 m length of hull.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5725-1, *Accuracy (trueness and precision) of measurement methods and results — Part 1: General principles and definitions*

ISO 5725-2, *Accuracy (trueness and precision) of measurement methods and results — Part 2: Basic method for the determination of repeatability and reproducibility of a standard measurement method*

ISO 8178-1:2006, *Reciprocating internal combustion engines — Exhaust emission measurement — Part 1: Test-bed measurement of gaseous and particulate exhaust emissions*

ISO 8178-6:2000, *Reciprocating internal combustion engines — Exhaust emission measurement — Part 6: Report of measuring results and test*

ISO 8666, *Small craft — Principal data*

ISO 14396, *Reciprocating internal combustion engines — Determination and method for the measurement of engine power — Additional requirements for exhaust emission tests in accordance with ISO 8178*

ISO 15550:2002, *Internal combustion engines — Determination and method for the measurement of engine power — General requirements*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8666 and the following apply.

3.1

particulates

material collected on a specified filter medium after diluting exhaust gases with clean, filtered air to a temperature greater than 315 K (42 °C) and less than or equal to 325 K (52 °C), as measured at a point immediately upstream of the primary filter

Note 1 to entry: Particulates consist primarily of carbon, condensed hydrocarbons, and sulfates and associated water.

ISO 18854:2015(E)

Note 2 to entry: Particulates defined in this International Standard are substantially different in composition and weight from particulates or dust sampled directly from the undiluted exhaust gas using a hot filter method. Particulates measurement as described in this International Standard is conclusively proven to be effective for fuel sulfur levels up to 0,8 %.

[SOURCE: ISO 8178-1:2006, 3.1, without Note 3 to entry]

3.2 partial-flow dilution system

system using a process of separating a part of the raw exhaust from the total exhaust flow, then mixing with an appropriate amount of dilution air prior to passing through the particulate sampling filter

Note 1 to entry: See [18.2.1](#), [Figures 10](#) to [18](#).

3.3 full-flow dilution system

system using a process of mixing dilution air with the total exhaust flow prior to separating a fraction of the diluted exhaust stream for analysis

Note 1 to entry: It is common in many full-flow dilution systems to dilute this fraction of pre-diluted exhaust a second time to obtain appropriate sample temperatures at the particulate filter (see [Figure 19](#)).

3.4 isokinetic sampling

process of controlling the flow of the exhaust sample by maintaining the mean sample velocity at the probe equal to the exhaust stream mean velocity

[SOURCE: ISO 8178-1:2006, 3.4]

3.5 multiple-filter method

process of using one filter for each of the individual test cycle modes

Note 1 to entry: The modal weighting factors are accounted for after sampling during the data evaluation phase of the test.

[SOURCE: ISO 8178-1:2006, 3.6]

3.6 single-filter method

process of using one filter for all test cycle modes

Note 1 to entry: Modal weighting factors must be accounted for during the particulate sampling phase of the test cycle by adjusting sample flow rate and/or sampling time. This method dictates that particular attention be given to sampling duration and flow rates.

[SOURCE: ISO 8178-1:2006, 3.7]

3.7 specific emissions

mass emissions expressed in grams per kilowatt-hour

[SOURCE: ISO 8178-1:2006, 3.8—modified]

3.8 span gas

purified gas mixture used to span gas analyzers

Note 1 to entry: Calibration gases and span gases are qualitatively the same, but differ in terms of their primary function. Various performance verification checks for gas analyzers and sample handling components might refer to either calibration gases or span gases.

3.9**zero gas**

gas that yields a zero response in an analyzer

Note 1 to entry: This may either be purified nitrogen, purified air, or a combination of purified air and purified nitrogen.

3.10**calibration**

process of setting a measurement system's response so that its output agrees with a range of reference signals

3.11**verification**

means to evaluate whether or not a measurement system's outputs agree with a range of applied reference signals to within one or more predetermined thresholds for acceptance

4 Symbols and abbreviations**4.1 General symbols**

Symbol	Term	Unit
A/F_{st}	Stoichiometric air-to-fuel ratio	—
A_p	Cross-sectional area of the isokinetic sampling probe	m ²
A_r	Atomic mass	G
A_x	Cross-sectional area of the exhaust pipe	m ²
c_c	Background corrected concentration	ppm % (V/V)
c_d	Concentration in the dilution air	ppm % (V/V)
c_x	Concentration in the exhaust (with suffix of the component nominating)	ppm % (V/V)
D	Dilution factor	—
E_{CO_2}	CO ₂ quench of NO _x analyser	%
E_E	Ethane efficiency	%
E_{H_2O}	Water quench of NO _x analyser	%
E_M	Methane efficiency	%
E_{NO_x}	Efficiency of NO _x converter	%
e_{PT}	Particulate emission	g/kW·h
e_x	Gas emission (with subscript denoting compound)	g/kW·h
λ	Excess air factor ($[(\text{kg dry air})/(\text{kg fuel}) * [A/F_{st}]]$)	—
λ_{Ref}	Excess air factor at reference conditions	—
f_a	Laboratory atmospheric factor	—
f_c	Carbon factor	—
f_{fd}	Fuel specific factor for exhaust flow calculation on dry basis	—
f_{fh}	Fuel specific factor used for the calculations of wet concentrations from dry concentrations	—
f_{fw}	Fuel specific factor for exhaust flow calculation on wet basis	—
H_a	Absolute humidity of the intake air (g water/kg dry air)	g/kg
H_d	Absolute humidity of the dilution air (g water/kg dry air)	g/kg

Symbol	Term	Unit
i	Subscript denoting an individual mode	—
k_f	Fuel specific factor for the carbon balance calculation	—
k_{hd}	Humidity correction factor for NO _x for diesel engines	—
k_{hp}	Humidity correction factor for NO _x for gasoline (petrol) engines	—
k_p	Humidity correction factor for particulates	—
k_{wa}	Dry to wet correction factor for the intake air	—
k_{wd}	Dry to wet correction factor for the dilution air	—
k_{we}	Dry to wet correction factor for the diluted exhaust gas	—
k_{wr}	Dry to wet correction factor for the raw exhaust gas	—
M	Percent torque related to the maximum torque for the test engine speed	%
M_r	Molecular mass	g
m_d	Mass of the dilution air sample passed through the particulate sampling filters	kg
$m_{f,d}$	Particulate sample mass of the dilution air collected	mg
m_f	Particulate sample mass collected	mg
m_{sep}	Mass of the diluted exhaust sample passed through the particulate sampling filters	kg
P_A	Absolute outlet pressure at pump outlet	kPa
p_a	Saturation vapour pressure of the engine intake air	kPa
p_b	Total barometric pressure	kPa
p_d	Saturation vapour pressure of the dilution air	kPa
p_r	Water vapour pressure after cooler	kPa
p_s	Dry atmospheric pressure	kPa
P	Uncorrected brake power	kW
P_{aux}	Declared total power absorbed by auxiliaries fitted for the test and not required by ISO 14396	kW
P_m	Maximum measured or declared power at the test engine speed under test conditions (see 13.5)	kW
q_{mad}	Intake air mass flow rate on dry basis	kg/h
q_{maw}	Intake air mass flow rate on wet basis	kg/h
q_{mdw}	Dilution air mass flow rate on wet basis	kg/h
q_{medf}	Equivalent diluted exhaust gas mass flow rate on wet basis	kg/h
q_{mew}	Exhaust gas mass flow rate on wet basis	kg/h
q_{mf}	Fuel mass flow rate	kg/h
q_{mdew}	Diluted exhaust gas mass flow rate on wet basis	kg/h
q_{mgas}	Emission mass flow rate of individual gas	g/h
q_{mPT}	Particle mass flow rate	g/h
r_d	Dilution ratio	—
r_a	Ratio of cross-sectional areas of isokinetic probe and exhaust pipe	—
R_a	Relative humidity of the intake air	%
R_d	Relative humidity of the dilution air	%
r_h	FID response factor	—
r_m	FID response factor for methanol	—
r_x	Ratio of the SSV throat to inlet absolute, static pressure	—

Symbol	Term	Unit
r_y	Ratio of the SSV throat diameter, d , to the inlet pipe inner diameter	—
ρ	Density	kg/m ³
S	Dynamometer setting	kW
T_a	Absolute temperature of the intake air	K
T_d	Absolute dewpoint temperature	K
T_{ref}	Absolute reference temperature (of combustion air: 298 K)	K
T_c	Absolute temperature of the intercooled air	K
T_{cref}	Absolute intercooled air reference temperature	K
V_m	Molar volume	L
W_f	Weighting factor	—
W_{fe}	Effective weighting factor	—

4.2 Symbols for fuel composition

w_{ALF} H content of fuel, % mass

w_{BET} C content of fuel, % mass

w_{GAM} S content of fuel, % mass

w_{DEL} N content of fuel, % mass

w_{EPS} O content of fuel, % mass

α molar ratio (H/C)

β molar ratio (C/C)

γ molar ratio (S/C)

δ molar ratio (N/C)

ε molar ratio (O/C)

NOTE The conversion between mass content and molar ratio is given in ISO 8178-1:2006, Formulae A.3 to A.12.

4.3 Symbols and abbreviations for the chemical components

ACN acetonitrile

C1 carbon 1 equivalent hydrocarbon

CH₄ methane

C₂H₆ ethane

C₃H₈ propane

CH₃OH methanol

CO carbon monoxide

CO₂ carbon dioxide

ISO 18854:2015(E)

DNPH	dinitrophenyl hydrazine
DOP	dioctyl phthalate
HC	hydrocarbons
HCHO	formaldehyde
H ₂ O	water
NH ₃	ammonia
NMHC	non-methane hydrocarbons
NO	nitric oxide
NO ₂	nitrogen dioxide
NO _x	oxides of nitrogen
N ₂ O	dinitrogen oxide
O ₂	oxygen
RME	rapeseed oil methylester
SO ₂	sulfur dioxide
SO ₃	sulfur trioxide

4.4 Abbreviations

CFV	critical flow venturi
CLD	chemiluminescent detector
CVS	constant volume sample
EP	exhaust pipe
ECS	electrochemical sensor
FID	flame ionization detector
FTIR	Fourier transform infrared analyser
GC	gas chromatograph
HCLD	heated chemiluminescent detector
HFID	heated flame ionization detector
HPLC	high-pressure liquid chromatograph
NDIR	non-dispersive infrared analyser
NMC	non-methane cutter
PDP	positive displacement pump
PMD	paramagnetic detector