

SLOVENSKI STANDARD
oSIST prEN 301 489-17 V3.2.5:2022
01-november-2022

**Standard elektromagnetne združljivosti (EMC) za radijsko opremo in storitve - 17.
del: Posebni pogoji za širokopasovne sisteme za prenos podatkov - Harmonizirani
standard za elektromagnetno združljivost**

ElectroMagnetic Compatibility (EMC) standard for radio equipment and services - Part
17: Specific conditions for Broadband and Wideband Data Transmission Systems -
Harmonised Standard for ElectroMagnetic Compatibility

(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/d123afb4-1d7b-466c-b052-41a60823f1fb/osist-pren-301-489-17-v3-2-5-2022>

Ta slovenski standard je istoveten z: ETSI EN 301 489-17 V3.2.5 (2022-08)

ICS:

| | | |
|-----------|---|--|
| 33.060.01 | Radijske komunikacije na splošno | Radiocommunications in general |
| 33.100.01 | Elektromagnetna združljivost na splošno | Electromagnetic compatibility in general |

oSIST prEN 301 489-17 V3.2.5:2022 **en**

Draft **ETSI EN 301 489-17** V3.2.5 (2022-08)



**ElectroMagnetic Compatibility (EMC)
standard for radio equipment and services;
Part 17: Specific conditions for
Broadband and Wideband Data Transmission Systems;
Harmonised Standard for ElectroMagnetic Compatibility**

<https://standards.iteh.ai/catalog/standards/sist/d123afb4-1d7b-466c-b052-41a60823f1fb/osist-pren-301-489-17-v3-2-5-2022>

Reference

REN/ERM-EMC-409

Keywords

EMC, harmonised standard, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx> 466c-b052-

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.

All rights reserved.

Contents

| | |
|--|-----------|
| Intellectual Property Rights | 4 |
| Foreword..... | 4 |
| Modal verbs terminology..... | 5 |
| 1 Scope | 6 |
| 2 References | 6 |
| 2.1 Normative references | 6 |
| 2.2 Informative references..... | 7 |
| 3 Definition of terms, symbols and abbreviations..... | 7 |
| 3.1 Terms..... | 7 |
| 3.2 Symbols..... | 8 |
| 3.3 Abbreviations | 8 |
| 4 Test conditions | 9 |
| 4.1 General | 9 |
| 4.2 Arrangements for test signals..... | 9 |
| 4.2.1 Arrangements for test signals at the input of transmitters..... | 9 |
| 4.2.2 Arrangements for test signals at the output of transmitters..... | 9 |
| 4.2.3 Arrangements for test signals at the input of receivers | 9 |
| 4.2.4 Arrangements for test signals at the output of receivers | 9 |
| 4.2.5 Arrangements for testing transmitter and receiver together (as a system)..... | 10 |
| 4.2.6 Equipment with an external antenna connector..... | 10 |
| 4.2.7 Equipment without an external antenna connector (integral antenna)..... | 10 |
| 4.2.8 Equipment with more than one antenna..... | 10 |
| 4.3 Exclusion bands..... | 10 |
| 4.3.1 General..... | 10 |
| 4.3.2 Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz band..... | 11 |
| 4.3.3 5 GHz RLAN..... | 11 |
| 4.3.4 Wireless Access Systems (WAS); 5,8 GHz fixed broadband data transmitting systems..... | 11 |
| 4.4 Void..... | 11 |
| 4.5 Normal test modulation | 11 |
| 5 Performance assessment..... | 11 |
| 5.1 General | 11 |
| 5.2 Arrangements for the assessment of host dependent equipment and plug-in cards..... | 12 |
| 5.3 Assessment procedures..... | 12 |
| 6 Performance criteria | 12 |
| 6.1 General performance criteria..... | 12 |
| 6.2 Performance table..... | 13 |
| 6.2.1 Performance criteria overview..... | 13 |
| 6.2.2 Minimum performance level..... | 13 |
| 6.3 Performance criteria for Continuous phenomena | 13 |
| 6.4 Performance criteria for Transient phenomena | 13 |
| 7 Requirements..... | 13 |
| 7.1 Emission | 13 |
| 7.1.1 General..... | 13 |
| 7.2 Immunity | 14 |
| 7.2.1 General..... | 14 |
| Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU | 16 |
| Annex B (informative): Change History | 18 |
| History | 19 |

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.12] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 17 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

| Proposed national transposition dates | |
|--|---------------------------------|
| Date of latest announcement of this EN (doa): | 3 months after ETSI publication |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 6 months after doa |
| Date of withdrawal of any conflicting National Standard (dow): | 18 months after doa |

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN 301 489-17 V3.2.5:2022

<https://standards.iteh.ai/catalog/standards/sist/d123afb4-1d7b-466c-b052-41a60823f1fb/osist-pren-301-489-17-v3-2-5-2022>

1 Scope

The present document specifies technical characteristics and methods of measurements for broadband and wideband data transmission system equipment including the associated ancillary equipment in respect of electromagnetic compatibility, as detailed in table 1.

Technical specifications related to the antenna port and emissions from the enclosure port of the radio equipment are not included in the present document. Such technical specifications are found in the relevant product standards for the effective use of the radio spectrum.

The present document specifies the applicable test conditions, performance assessment and performance criteria for broadband and wideband data transmission systems as detailed in table 1.

NOTE: In the context of the present document, broadband and wideband are interchangeable.

Table 1: Radio Technologies in scope of the present document

| Technology | ETSI Standard |
|---|-----------------------|
| Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz band | ETSI EN 300 328 [i.8] |
| 5 GHz RLAN | ETSI EN 301 893 [i.3] |
| 6 GHz WAS/RLAN | ETSI EN 303 687 [i.2] |
| Wireless Access Systems (WAS); 5,8 GHz fixed broadband data transmitting systems; | ETSI EN 302 502 [i.4] |
| Multi-Gigabit Wireless Systems (MGWS) in the 60 GHz band | ETSI EN 302 567 [i.6] |
| Wideband Data Transmission Systems (WDTs) for Fixed Network Radio Equipment operating in the 57 GHz to 71 GHz band | ETSI EN 303 722 [i.5] |

Emissions requirements in the present document are specified for frequencies above 9 kHz.

The environmental classification and the emission and immunity requirements used in the present document are as stated in ETSI EN 301 489-1 [1], except for any special conditions included in the present document.

NOTE: The relationship between the present document and essential requirements of article 3.1(b) of Directive 2014/53/EU [i.1] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 489-1 (V2.2.3) (11-2019): "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements; Harmonised Standard for ElectroMagnetic Compatibility".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI EN 303 687: "6 GHz WAS/RLAN; Harmonised Standard for access to radio spectrum".
- [i.3] ETSI EN 301 893: "5 GHz WAS/RLAN; Harmonised Standard for access to radio spectrum".
- [i.4] ETSI EN 302 502 (V2.1.3): "Wireless Access Systems (WAS); 5,8 GHz fixed broadband data transmitting systems; Harmonised Standard for access to radio spectrum".
- [i.5] ETSI EN 303 722: "Wideband Data Transmission Systems (WDTS) for Fixed Network Radio Equipment operating in the 57 GHz to 71 GHz band; Harmonised Standard for access to radio spectrum".
- [i.6] ETSI EN 302 567: "Multiple-Gigabit/s radio equipment operating in the 60 GHz band; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU".
- [i.7] Void.
- [i.8] ETSI EN 300 328: "Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz band; Harmonised Standard for access to radio spectrum".
- [i.9] Void.
- [i.10] Void.
- [i.11] Void.
- [i.12] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 301 489-1 [1] and the following apply:

ancillary equipment: electrical or electronic equipment, that is intended to be used with a receiver or transmitter

NOTE 1: It is considered as an ancillary equipment if:

- the equipment is intended for use with a receiver or transmitter to provide additional operational and/or control features to the radio equipment, (e.g. to extend control to another position or location); and
- the ancillary equipment cannot be used without being connected to radio equipment to provide user functions independently of a receiver or transmitter; and

- the receiver or transmitter, to which it is connected, is capable of providing some intended operation such as transmitting and/or receiving without the ancillary equipment (i.e. it is not a sub-unit of the main equipment essential to the main equipment basic functions).

NOTE 2: An example of ancillary equipment would be a docking station for radio equipment whose interface is dedicated to a particular product or range of products.

Equipment Under Test (EUT): equipment subject to the performance requirements of the present document

fixed equipment: equipment intended for use in a fixed location and fitted with one or more antennas

NOTE: The equipment may be fitted with either antenna socket(s) or integral antenna(s) or both.

host: any equipment which has complete user functionality when not connected to the radio equipment part and to which the radio equipment part provides additional functionality and to which connection is necessary for the radio equipment part to offer functionality

plug-in radio device: equipment, including slide-in radio cards, intended to be used with or within a variety of host systems, using their control functions and power supply

portable equipment: radio equipment intended for portable use and powered by integral batteries or battery

NOTE: Devices will typically be handheld.

stand-alone radio equipment: equipment that is intended primarily as communications equipment and that is normally used on a stand-alone basis

vehicular equipment: radio equipment intended for installation and use in a vehicle, and powered by the main battery of the vehicle

3.2 Symbols

For the purposes of the present document, the following symbols apply:

P_{min} minimum power required to establish a communication link

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|------|----------------------------------|
| AC | Alternating Current |
| ACK | ACKnowledgement |
| ARQ | Automatic Retransmission reQuest |
| DC | Direct Current |
| EMC | ElectroMagnetic Compatibility |
| ERM | EMC and Radio Spectrum Matters |
| EUT | Equipment Under Test |
| FER | Frame Error Rate |
| MGWS | Multi-Gigabit Wireless Systems |
| NACK | Not ACKnowledgement |
| PER | Packet Error Rate |
| RF | Radio Frequency |
| RLAN | Radio Local Area Network |

4 Test conditions

4.1 General

For the purposes of the present document, the test conditions of ETSI EN 301 489-1 [1], clause 4, shall apply as appropriate. Further product related test conditions for wideband data communications systems are specified in clauses 4.2 to 4.5.

The radio equipment may take forms which may require special software and/or test fixtures. Equipment which requires connection to a host equipment to function shall use a test configuration representative of the EUT's intended use and shall be recorded in the test report.

4.2 Arrangements for test signals

4.2.1 Arrangements for test signals at the input of transmitters

The provisions of ETSI EN 301 489-1 [1], clause 4.2.1 shall apply with the following modifications.

The wanted signals and/or controls required to establish a communication link and shall be representative of the EUTs intended use.

The transmitter shall be operated at maximum rated power.

4.2.2 Arrangements for test signals at the output of transmitters

The provisions of ETSI EN 301 489-1 [1], clause 4.2.2 shall apply with the following modifications.

A suitable companion receiver shall be used to receive messages or to set up a communication link.

4.2.3 Arrangements for test signals at the input of receivers

The provisions of ETSI EN 301 489-1 [1], clause 4.2.3 shall apply with the following modifications.

For radiated immunity tests, the level of the wanted signal at the input of the receiver or the enclosure port of the EUT, shall be 30 dB (± 6 dB) above the P_{min} for the EUT. For all other tests the level of the wanted signal, required to establish a communication link, shall be representative of the EUT intended use.

NOTE: Simple method to establish the required communication link is establish link, reduce power to point of link failure then increase by 30 dB (± 6 dB).

4.2.4 Arrangements for test signals at the output of receivers

The measuring equipment for the output signal from the receiver under test shall be located outside the test environment.

It shall be possible to assess the performance of the equipment by appropriately monitoring the receiver output.

If the receiver has an output connector or port providing the wanted output signal, then this port shall be used via a cable, consistent with the standard cable used in normal operation, connected to the external measuring equipment outside the test environment.

A suitable companion transmitter shall be used to transmit messages or to set up a communication link.