

DRAFT INTERNATIONAL STANDARD

ISO/DIS 17672

ISO/TC 44

Secretariat: AFNOR

Voting begins on:
2015-03-19

Voting terminates on:
2015-06-19

Brazing — Filler metals

Brasage fort — Métaux d'apport

ICS: 25.160.50

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/adff4e42-9f23-47cf-a703-96642b9f33d6/iso-17672-2016>

ISO/CEN PARALLEL PROCESSING

This draft has been developed within the International Organization for Standardization (ISO), and processed under the **ISO lead** mode of collaboration as defined in the Vienna Agreement.

This draft is hereby submitted to the ISO member bodies and to the CEN member bodies for a parallel five month enquiry.

Should this draft be accepted, a final draft, established on the basis of comments received, will be submitted to a parallel two-month approval vote in ISO and formal vote in CEN.

To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.



Reference number
ISO/DIS 17672:2015(E)

© ISO 2015

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/adff4e42-9f23-47cf-a703-96642b9f33d6/iso-17672-2016>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Composition	1
4 Special vacuum requirement	2
5 Chemical analysis	2
6 Designation	2
7 Technical delivery conditions	3
7.1 Types of product	3
7.2 Dimensions	3
7.2.1 General	3
7.2.2 Foils	4
7.2.3 Rods	4
7.2.4 Wires	5
7.3 Condition	5
7.4 Marking	5
7.5 Packaging	5
7.6 Product certificates	5
8 Metal hazards	5
Annex A (normative) Codification	16
Bibliography	22

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17672 was prepared by Technical Committee ISO/TC 44, *Welding and allied processes*.

This second edition cancels and replaces the first edition (ISO 17672:2010), which has been technically revised.

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/ada1e842-9d23-47cf-a703-96642b9f33d6/iso-17672-2016>

Brazing — Filler metals

1 Scope

This International Standard specifies the compositional ranges of a series of filler metals used for brazing. The filler metals are divided into seven classes, related to their composition, but not necessarily to the major element present.

NOTE 1 For the major element(s) present, see Annex A.

In the case of composite products, such as flux-coated rods, pastes or plastics tapes, this International Standard covers only the filler metal that forms part of such products. The melting temperatures given in the tables are only approximate, as they necessarily vary within the compositional range of the filler metal. Therefore, they are given only for information. Technical delivery conditions are given for brazing filler metals and products containing brazing filler metals with other constituents such as flux and/or binders.

NOTE 2 For some applications, e.g. precious metal jewellery, aerospace and dental, filler metals other than those included in this International Standard are often used and these are covered by other International Standards to which reference can be made.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3677:1992, *Filler metal for soft soldering, brazing and braze welding — Designation*

ISO 80000-1:2009, *Quantities and units — Part 1: General*

3 Composition

The filler metal shall have a composition in accordance with Tables 5 to 13 for the particular type, except as modified for special vacuum requirements (see Clause 4 and Table 1).

For the purposes of determining compliance with composition limits, any value obtained from the analysis shall be rounded to the same number of decimal places as used in this International Standard in expressing the specified limit. The following rules shall be used for rounding.

- a) When the figure immediately after the last figure to be retained is less than five, then the last figure to be retained shall be kept unchanged.
- b) When the figure immediately after the last figure to be retained is either
 - 1) greater than five, or
 - 2) equal to five and followed by at least one figure other than zero,the last figure to be retained shall be increased by one.
- c) When the figure immediately after the last figure to be retained is equal to five, and followed by zeros only, then the last figure to be retained shall be left unchanged if even, and increased by one if odd. For the purposes of determining compliance with the requirements of this International Standard, the actual test values obtained shall be subjected to the rounding-off instructions given in ISO 80000-1:2009, Annex B.

NOTE The chemical analysis is of the bulk material, but the material can be composed of discrete powders with different individual compositions or multiple layers of roll-clad foils where each layer can have a different individual composition.

4 Special vacuum requirement

In a few instances, which are most likely to apply to Ag 272, Pd 287, Pd 387, Pd 388, Pd 481, Pd 483, Pd 484, Pd 587, Pd 647 and Au 295, Au 375, Au 625, Au 752, Au 801 and Au 827, lower impurity limits can be required for brazing in vacuum or service in vacuum and these limits shall be as given in Table 1.

Filler metals complying with Table 1 shall have the letter V added as a suffix to the codification plus the digit 1 or 2 to indicate the grade.

NOTE Grade 1 is intended for the most demanding duties, Grade 2 for less demanding.

Table 1 — Impurity limits for special vacuum requirements

Impurity	Limit (% by mass max.)	
	Grade 1	Grade 2
C ^a	0,005	0,005
Cd	0,001	0,002
P	0,002	0,002 ^b
Pb	0,002	0,002
Zn	0,001	0,002
Mn ^c	0,001	0,002
In ^c	0,002	0,003
All other elements where vapour pressure at 500 °C is $> 1,3 \times 10^{-5}$ Pa ^d	0,001	0,002

^a For filler metal Ag 272 (see Table 6), lower levels may be available by agreement between the purchaser and the supplier.
^b For filler metal Ag 272, 0,02 % maximum.
^c Except where otherwise specified in Tables 5 to 13.
^d Examples of such elements are Ca, Cs, K, Li, Mg, Na, Rb, S, Sb, Se, Sr, Te and Tl. For such elements (including Cd, Pb and Zn), the total is limited to 0,010 %.

5 Chemical analysis

Chemical analyses shall be carried out by any suitable method, but it should be noted that in the case of many brazing alloys, the use of reference standards may be essential, as agreed between the purchaser and the supplier. Analysis is only required to be carried out routinely for those elements for which specific limits are shown. If, however, the presence of other elements is suspected or in the course of routine analysis is indicated to be in excess of the limits laid down for unnamed elements, or would bring the total of impurities above the specified limit, further analyses shall be carried out for such elements.

6 Designation

The filler metal shall be designated by the description “filler metal”, the number of this International Standard, i.e. ISO 17672, and a code. Details of the two options for the code system used are given in Annex A.

As an example, the designations of an aluminium filler metal containing 11 % to 13 % Si, in accordance with this International Standard, can be made in one of the following ways:

EXAMPLE 1 Filler metal ISO 17672-AI 112

where

“Filler metal” is the description;

“ISO 17672” is the number of this International Standard;

“AI 112” is the short code given in Tables 5 to 13.

EXAMPLE 2 Filler metal ISO 17672-B-AI88Si-575/585

where

“Filler metal” is the description;

“ISO 17672” is the number of this International Standard;

“B” denotes brazing;

“AI88Si-575/585” is the code in accordance with ISO 3677.

7 Technical delivery conditions

7.1 Types of product

The form of the material shall be agreed between the purchaser and the manufacturer/supplier at the time of placing the order.

NOTE Brazing filler metals are available as rod, wire, foil (or preforms made from them) or powder, although not all filler metals are necessarily available in every type of product. They are also available as a constituent of brazing pastes or, particularly in the case of aluminium brazing filler metals, clad onto one or both sides of an alloy sheet. Rods can be completely or partially coated with flux.

7.2 Dimensions

7.2.1 General

Dimensions and tolerances for foils (see 7.2.2), rods (see 7.2.3) and, to a lesser extent, wires (see 7.2.4) are defined. For other forms and dimensions not listed in the respective tables, the purchaser and the manufacturer/supplier shall agree on the dimensions and tolerances at the time of placing the order.

7.2.2 Foils

The tolerances for thickness, width and camber are given in Tables 2, 3 and 4.

Table 2 — Thickness tolerance for foils

Thickness nominal size mm		Limits of thickness related to width (nominal size) mm
over	to	over 1 mm
—	0,05	± 10 %
0,05	0,1	± 0,005
0,1	0,2	± 0,010
0,2	0,3	± 0,015
0,3	0,4	± 0,018
0,4	0,5	± 0,020
0,5	0,8	± 0,025
0,8	1,2	± 0,030
1,2	2,0	± 0,035

Table 3 — Width tolerance for foils

Thickness nominal size mm		Limits of width related to width (nominal size) mm		
over	to	to 50 mm	over 50 mm to 100 mm	Over 100 mm
—	0,1	+0,2 0	+0,3 0	+0,4 0
0,1	1,0	+0,2 0	+0,3 0	+0,4 0
1,0	2,0	+0,3 0	+0,4 0	+0,5 0

Table 4 — Camber tolerance for foils

Thickness nominal size mm		Max. camber for width nominal size mm/m				
over	to	3 mm to 10 mm	over 10 mm to 15 mm	over 15 mm to 30 mm	over 30 mm to 50 mm	over 50 mm
—	0,5	10	7	4	3	3
0,5	2,0	15	10	6	4	4

7.2.3 Rods

For rods, the preferred diameters are 1 mm, 1,5 mm, 2 mm, 2,5 mm, 3 mm and 5 mm and the preferred lengths are 500 mm and 1 000 mm. The tolerance on diameter shall be ± 3 % for drawn rods and ± 0,3 mm for other fabrication processes. The tolerance on length shall be ± 5 mm.

7.2.4 Wires

For wires, there are no preferred diameters and the tolerance on diameter shall be $\pm 3\%$.

7.3 Condition

The surface of brazing filler metals shall be free from contamination which could adversely affect brazing. With flux-coated rods, the coating shall firmly adhere to the rod and shall not break off during proper handling and usage. Welds, when present, shall have been made so as not to interfere with uniform, uninterrupted feeding of filler metal on automatic and semiautomatic brazing.

7.4 Marking

Since in many cases the marking of brazing filler metals themselves is impracticable, reliance shall be placed on the marking of packets. The outside of each smallest unit package shall be clearly marked with the following information:

- a) the designation in accordance with Clause 6;
- b) the name of the manufacturer/supplier;
- c) the trade name (if any);
- d) the quantity of material and, if applicable, the dimensions;
- e) the supplier's batch number;
- f) health and safety warnings (as required by national regulations).

7.5 Packaging

Brazing filler metals or products containing them shall be packed to provide sufficient safeguard against damage and deterioration during transportation and storage.

7.6 Product certificates

If certificates (like those specified in ISO 14344) of conformity and/or analysis are required, the purchaser and the manufacturer/supplier shall agree on the details at the time of placing the order.

8 Metal hazards

Although not directly relevant to the requirements of this International Standard, any national requirements for limiting exposure to metal hazards, e.g. fume, should be observed. This is particularly important when using brazing filler metals containing cadmium as an alloying element.

Table 5 — Class Al: aluminium and magnesium brazing filler metals

Code	Composition, % by mass										Melting temperature (approximate)	
	Si	Fe	Cu	Mn	Mg	Zn	Others	Non-defined elements		Al	Solidus °C	Liquidus °C
	min./max.	min./max.	min./max.	min./max.	min./max.	min./max.	min./max.	Each max.	Total max.	min./max.		
Al-Si alloys												
Al 105	4,5/6,0	—/0,6	—/0,30	—/0,15	—/0,20	—/0,10	Ti: —/0,15	0,05	0,15	Remainder	575	630
Al 107	6,8/8,2	—/0,8	—/0,25	—/0,10	—/—	—/0,20	—/—	0,05	0,15	Remainder	575	615
Al 110	9,0/11,0	—/0,8	—/0,30	—/0,05	—/0,05	—/0,10	Ti: —/0,20	0,05	0,15	Remainder	575	590
Al 112	11,0/13,0	—/0,8	—/0,30	—/0,15	—/0,10	—/0,20	—/—	0,05	0,15	Remainder	575	585
Al-Si-Cu alloys												
Al 210	9,3/10,7	—/0,8	3,3/4,7	—/0,15	—/0,15	—/0,20	Cr: —/0,15	0,05	0,15	Remainder	520	585
Al-Si-Mg alloys												
Al 310	9,0/10,5	—/0,8	—/0,25	—/0,10	1,0/2,0	—/0,20	—/—	0,05	0,15	Remainder	555	590
Al 311	9,0/10,5	—/0,8	—/0,25	—/0,10	1,0/2,0	—/0,20	Bi: 0,02/0,20	0,05	0,15	Remainder	555	590
Al 315	9,5/11,0	—/0,8	—/0,25	—/0,10	0,20/1,0	—/0,20	—/—	0,05	0,15	Remainder	559	591
Al 317	11,0/13,0	—/0,8	—/0,25	—/0,10	0,10/0,50	—/0,20	—/—	0,05	0,15	Remainder	562	582
Al 319	10,5/13,0	—/0,8	—/0,25	—/0,10	1,0/2,0	—/0,20	—/—	0,05	0,15	Remainder	559	579
Al-Si-Zn alloys												
Al 410	9,0/11,0	—/0,8	—/0,3	—/0,05	—/0,05	0,50/3,0	—/—	0,05	0,15	Remainder	576	588
Al 415	10,5/13,0	—/0,8	—/0,25	—/0,10	—/—	0,50/3,0	—/—	0,05	0,15	Remainder	576	609
Mg alloys												
Mg 001	—/0,05	—/0,005	—/0,05	0,15/1,5	Remainder	1,7/2,3	Be: 0,0002/0,0008 Ni: —/0,005	0,05	0,30	8,3/9,7	443	599
NOTE Maximum impurity limit applicable to all types are (% by mass) Cd 0,010 and Pb 0,025.												