

ETSI TS 128 404 V16.3.0 (2021-09)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Quality of Experience (QoE) measurement collection;
Concepts, use cases and requirements
(3GPP TS 28.404 version 16.3.0 Release 16)**



ReferenceRTS/TSGS-0528404vg30

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Important notice

<https://standards.iteh.ai/catalog/standards/sist/95ec4409-9d45-49f8-8e7e-462105948656/etsi-ts-128-404-v16-3-0-2021-09>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

<https://standards.iteh.ai/catalog/standards/sist/95ec4409-9d45-49f8-8e7e-4b270059d865/etsi-ts-128-404-v16-3-0-2021-09>

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	5
4 Concepts and background	6
4.1 Concepts	6
4.2 Background	6
5 Business Level Requirements	6
5.1 Requirements.....	6
5.1.1 Collecting QoE information from end user services for UTRAN and LTE.....	6
5.2 Actor roles	7
5.3 Telecommunication resources	7
5.4 High-level use cases	7
5.4.1 Collecting QoE information from a specific end user service type	7
5.4.2 Void	8
5.4.3 Collecting QoE information from end user service type of specific streaming sources	8
5.4.4 Indication of QoE information collection	8
5.4.5 Change collecting QoE information	9
5.4.6 Void	10
6 Specification level requirements	10
6.1 Requirements.....	10
Annex A (informative): Change history	11
History	12

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

iTeh STANDARD PREVIEW

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management, as identified below:

- TS 28.404: "Quality of Experience (QoE) measurement collection; Concepts, use cases and requirements";**
- TS 28.405: "Quality of Experience (QoE) measurement collection; Control and configuration";
- TS 28.406: "Quality of Experience (QoE) measurement collection; Information definition and transport";

One main motivation of mobile network evolution is to improve the user experience why the evaluation of the user experience at the UE side is vital to network operators, especially when the operators provide some real-time services which require for example high data rate and low latency like streaming services (typically video services), where even intermittent quality degradation is very annoying. Many of these streaming services are a significant part of the commercial traffic growth rate, therefore the focus is on the end users' experience.

Quality of Experience (QoE) information collection provides detailed information at call level on a number of UEs.

The capability to log information within a UE, and in particular the QoE of an end user service, initiated by an operator, provides the operator with QoE information. The collected information (specified in 3GPP TS 26.247 [2]) cannot be deduced from performance measurements in the mobile network.

The QoE information is information collected by the end user application in the UE.

The collected QoE information is collected by the management system for analysis and/or KPI calculations.

1 Scope

The present document addresses concepts, business level use cases and requirements for the function Quality of Experience (QoE) measurement collection in UMTS and LTE. The measurements that are collected are DASH [2] and MTSI [3] measurements.

The function includes collecting QoE information from UEs frequenting a specified area .

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 26.247: " Transparent end-to-end Packet-switched Streaming Service (PSS); Progressive Download and Dynamic Adaptive Streaming over HTTP (3GP-DASH)".
- [3] 3GPP TS 26.114: "IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction".
- [4] 3GPP TS 28.307: "Quality of Experience (QoE) measurement collection Integration Reference Point (IRP); Requirements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

QoE	Quality of Experience
-----	-----------------------

4 Concepts and background

4.1 Concepts

A network request session is a session in the mobile network when the network checks for UEs that have the capability to provide requested information.

An UE request session is a session in the network when the network has found an UE that has the capability to provide the requested information and the request is forwarded to the UE.

A recording session is a session in the UE when it initiates recording of the requested end user service/end user service type and record the requested information.

4.2 Background

The collection of QoE information for a specified end user service/end user service type either from UEs in a specified area . The collected information is transported to a collection centre, where it can be analysed and/or KPIs can be calculated.

A collection can be requested by an operator technician via the management system to the traffic network. As the network do not have any knowledge which UEs have the capability to record the requested data, therefore the UEs will report whether they have this capability or not when a session set up. UEs that has this capability that match the request from the management system will be requested to start recording the requested information when the request constraints are met. The UE will make the recorded data available for management system.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

5 Business Level Requirements

5.1 Requirements

<https://standards.iteh.ai/catalog/standards/sist/95ec4409-9d45-49f8-8e7e-46270059d865/etsi-ts-128-404-v16-3-0-2021-09>

5.1.1 Collecting QoE information from end user services for UTRAN and LTE

REQ-EUSPC-CON-1: The operator shall have a capability to request collection of QoE information per end user service/end user service type for a specified area. The request may include an address of a collection centre to which the collected information shall be delivered.

REQ-EUSPC-CON-2: The application providing the end user service performance information should have the capability to provide this information to a collection centre.

REQ-EUSPC-CON-3: It should be possible to restrict the QoE information collection to a subset of the sessions in a UE using an end user service/end user service type.

REQ-EUSPC-CON-4: Void.

REQ-EUSPC-CON-5: The management system shall have a capability to request collection of end user service performance information for a specific service type provided by specific streaming sources. The request may include information of streaming sources for which the information shall be collected.

REQ-EUSPC-CON-6: The 3GPP network shall have a capability to forward an indication to the management system that a recording session has been started.

REQ-EUSPC-CON-7: The operator shall have a capability to stop the collection of QoE information job.

REQ-EUSPC-CON-8: Void.

REQ-EUSPC-CON-9: Void.

REQ-EUSPC-CON-10: Void.

NOTE: The QoE information to be collected are specified in ref. 3GPP TS 26.247 [2] and TS 3GPP TS 26.114 [3].

5.2 Actor roles

See each use case in clause 5.4.

5.3 Telecommunication resources

See each use case in clause 5.4.

5.4 High-level use cases

5.4.1 Collecting QoE information from a specific end user service type

Use case stage	Evolution/Specification	<<Uses>> Related use
Goal	Allow the operator to obtain QoE information for an end user service type based on a 5 % of those sessions in a UE(s) in a specified area using a specific end user service type, in a specified collection centre.	
Actors and roles	The operator which is the requester of the QoE information.	
Telecom resources	The management system, the mobile network and the UE. ETSI TS 128 404 V16.3.0 (2021-09)	
Assumptions	The application providing an end user service type is able to provide QoE information about its end user service performance.	
Pre-conditions	Selected end users are using the specified end user service type.	
Begins when	The management system receives a request from the operator.	
Step 1 (M)	The management system receives a request from the operator and transfers it to the mobile network.	
Step 2 (M)	The mobile network receives the request, starts a network request session and starts to check which connections fulfil the request.	
Step3 (M)	When a connection is found that fulfils the request, the mobile network starts an UE request session and transfers the request to the UE.	
Step 4 (M)	When the requested end user service type is started in the UE, it records the requested information for 5% of sessions of the requested service type and sends the recorded information to the specified collection centre.	
Ends when	The network request session expires.	
Exceptions		
Post-conditions	The collected information is present in the specified collection centre.	
Traceability	REQ-EUSPC-CON-1, REQ-EUSPC-CON-2 and REQ-EUSPC-CON-3	
NOTE Step 2 to 4 is repeated for all UEs that access the network in the specified area during the network request session.		

5.4.2 Void

5.4.3 Collecting QoE information from end user service type of specific streaming sources

Use case stage	Evolution/Specification	<<Uses>> Related use
Goal	Allow the operator to obtain QoE information from end user service type from specific streaming sources.	
Actors and roles	The operator which is the requester of the QoE information.	
Telecom resources	The management system, the mobile network and the UE.	
Assumptions	The application providing streaming video service is able to provide QoE information about its end user performance.	
Pre-conditions	The selected end users are using the specified end user service type from the specified streaming sources.	
Begins when	The operator requests a QoE information collection for a specific service type from specific streaming sources.	
Step 1 (M)	When the management system receives a request from the operator, it transfers the request to the mobile network.	
Step 2 (M)	When the mobile network receives the request it starts a network request session and starts to check which connections fulfil the request.	
Step3 (M)	When a connection is found, the mobile network starts a UE request session and transfers the request to the UE.	
Step 4 (M)	When the specified service type is started in the UE, the UE checks whether the streaming source is consistent with any of the streaming sources set by the request, and if yes, the UE collects relevant QoE information and send to the network.	
Ends when	The network request session expires.	
Exceptions		
Post-conditions	The collected information is present in the specified collection center.	
Traceability	REQ-EUSPC-CON-2, REQ-EUSPC-CON-3 and REQ-EUSPC-CON-5.	

5.4.4 Indication of QoE information collection

Use case stage	Evolution/Specification	<<Uses>> Related use
Goal	Provide the OAM system with an indication that a recording session has started and subsequently allow the OAM system to modify the QoE measurement configuration e.g. the QoE configured area if the number of sessions are too small or too large. The indication may also be used to determine whether or not to terminate the QoE information collection if sufficient number of recording sessions have been started.	
Actors and roles	The operator which is the requester of the QoE information.	
Telecom resources	The management system and the RAN node.	
Assumptions		

Use case stage	Evolution/Specification	<<Uses>> Related use
Pre-conditions	Selected end users have been requested to provide QoE Information when the specified end user service type is used.	
Begins when	The application layer sends AT command including streaming indication to access stratum.	
Step 1 (M)	When the RAN node receives the streaming indication from the UE access stratum, the RAN node sends an indication to the triggering OAM system that a recording session has been started.	
Ends when	The management system has received the indication that a recording session has been started.	
Exceptions		
Post-conditions	The OAM system is able to decide if the ongoing QoE measurement collection needs modification and if sufficient data has been obtained for analysis. The OAM system can use the indications to trigger evaluation of collected data.	
Traceability	REQ-EUSPC-CON-6	

5.4.5 Change collecting QoE information

ITEH STANDARD PREVIEW
(standards.iteh.ai)

Use case stage	ETSI TS 128 404 V16.3.0 (2021-09) https://standards.iteh.ai/catalog/standards/sist/25-c4409-9d45-49f8-8e7e-4b270059d865/etsi-ts-128-404-v16-3-0-2021-09 Evolution/Specification	<<Uses>> Related use
Goal	Allow the operator to change an ongoing QoE information collection job.	
Actors and roles	The operator which is the requester of changing the QoE information collection job.	
Telecom resources	The management system, the mobile network and the UE.	
Assumptions	-	
Pre-conditions	The QoE collection job is active.	
Begins when	The operator has information that QoE information collection job needs to have more information as collected data will not be sufficient or that the collected information is enough.	
Step 1 (M)	The management system receives a request from the operator to terminate the ongoing QoE information collection job.	
Step 2 (M)	For all connections where the UE has been requested to start the QoE job, the mobile network transfer the termination request to the UE, which terminates the specified QoE collection information job.	
Step 3 (M)	When all QoE collections are terminated in the UEs for the specified QoE information collection job, the mobile network finish to terminate the QoE information collection job.	