

ETSI TS 124 501 V16.10.0 (2021-09)



5G;
Non-Access-Stratum (NAS) protocol for 5G System (5GS);
Stage 3
(3GPP TS 24.501 version 16.10.0 Release 16)

<https://standards.iteh.ai/catalog/standards/sist/d5fcd11e-489f-46eb-80f6-84fd214135ab/etsi-ts-124-501-v16-10-0-2021-09>



Reference

RTS/TSGC-0124501vga0

Keywords

5G**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Important notice

<https://standards.iteh.ai/catalog/standards/sist/d5fd11e-489f-46eb-80f6-84d1413389e3/sist-124-501-v16-10-0-2021-09>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

<https://standards.iteh.ai/catalog/standards/sist/d5fcd11e-489f-46eb-80f6-84fd214135ab/etsi-ts-124-501-v16-10-0-2021-09>

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	22
1 Scope	23
2 References	23
3 Definitions and abbreviations.....	27
3.1 Definitions	27
3.2 Abbreviations	34
4 General	37
4.1 Overview	37
4.2 Coordination between the protocols for 5GS mobility management and 5GS session management	37
4.3 UE domain selection	38
4.3.1 UE's usage setting	38
4.3.2 Domain selection for UE originating sessions / calls.....	38
4.3.3 Change of UE's usage setting.....	40
4.3.4 Change or determination of IMS voice availability	40
4.4 NAS security	41
4.4.1 General.....	41
4.4.2 Handling of 5G NAS security contexts.....	41
4.4.2.1 General	41
4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode.....	44
4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover	45
4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode.....	46
4.4.2.5 Establishment of secure exchange of NAS messages	46
4.4.2.6 Change of security keys	48
4.4.3 Handling of NAS COUNT and NAS sequence number	48
4.4.3.1 General	48
4.4.3.2 Replay protection	50
4.4.3.3 Integrity protection and verification.....	50
4.4.3.4 Cipherring and decipherring	50
4.4.3.5 NAS COUNT wrap around.....	51
4.4.4 Integrity protection of NAS signalling messages.....	51
4.4.4.1 General	51
4.4.4.2 Integrity checking of NAS signalling messages in the UE	52
4.4.4.3 Integrity checking of NAS signalling messages in the AMF	52
4.4.5 Cipherring of NAS signalling messages	54
4.4.6 Protection of initial NAS signalling messages.....	54
4.5 Unified access control	56
4.5.1 General.....	56
4.5.2 Determination of the access identities and access category associated with a request for access for UEs not operating in SNPN access mode	58
4.5.2A Determination of the access identities and access category associated with a request for access for UEs operating in SNPN access mode	64
4.5.3 Operator-defined access categories.....	68
4.5.4 Access control and checking.....	70
4.5.4.1 Access control and checking in 5GMM-IDLE mode and in 5GMM-IDLE mode with suspend indication.....	70
4.5.4.2 Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication	72
4.5.5 Exception handling and avoiding double barring	74
4.5.6 Mapping between access categories/access identities and RRC establishment cause	78

4.6	Network slicing	79
4.6.1	General.....	79
4.6.2	Mobility management aspects.....	80
4.6.2.1	General.....	80
4.6.2.2	NSSAI storage.....	81
4.6.2.3	Provision of NSSAI to lower layers in 5GMM-IDLE mode.....	84
4.6.2.4	Network slice-specific authentication and authorization.....	85
4.6.3	Session management aspects	87
4.7	NAS over non-3GPP access	87
4.7.1	General.....	87
4.7.2	5GS mobility management aspects.....	87
4.7.2.1	General.....	87
4.7.2.2	Establishment cause for non-3GPP access.....	88
4.7.3	5GS session management aspects.....	88
4.7.4	Limited service state over non-3GPP access	89
4.7.5	NAS signalling using trusted WLAN access network.....	89
4.8	Interworking with E-UTRAN connected to EPC	90
4.8.1	General.....	90
4.8.2	Single-registration mode.....	90
4.8.2.1	General.....	90
4.8.2.2	Single-registration mode with N26 interface	90
4.8.2.3	Single-registration mode without N26 interface	90
4.8.2.3.1	Interworking between NG-RAN and E-UTRAN	90
4.8.2.3.2	Interworking between TNGF or N3IWF connected to 5GCN and E-UTRAN.....	92
4.8.3	Dual-registration mode	93
4.8.4	Core Network selection for UEs not using ClOT 5GS optimizations	94
4.8.4A	Core Network selection and redirection for UEs using ClOT optimizations.....	94
4.8.4A.1	Core network selection.....	94
4.8.4A.2	Redirection of the UE by the core network.....	95
4.9	Disabling and re-enabling of UE's N1 mode capability	95
4.9.1	General.....	95
4.9.2	Disabling and re-enabling of UE's N1 mode capability for 3GPP access.....	95
4.9.3	Disabling and re-enabling of UE's N1 mode capability for non-3GPP access.....	98
4.10	Interworking with ePDG connected to EPC.....	98
4.11	UE configuration parameter updates	98
4.12	Access traffic steering, switching and splitting (ATSSS).....	99
4.13	Support of NAS signalling using wireline access network.....	99
4.14	Non-public network.....	100
4.14.1	General.....	100
4.14.2	Stand-alone non-public network.....	100
4.14.3	Public network integrated non-public network (PNI-NPN).....	101
4.15	Time sensitive communication.....	101
4.15.1	General.....	101
4.15.2	Integration with TSN network	102
4.15.2.1	General.....	102
4.15.2.2	Time synchronization.....	102
4.15.2.3	TSN bridge management.....	102
4.16	UE radio capability signalling optimisation	102
4.17	5GS mobility management in NB-N1 mode	104
4.18	5GS session management in NB-N1 mode	104
4.19	5GS mobility management in WB-N1 mode for IoT	104
4.20	5GS session management in WB-N1 mode for IoT.....	105
5	Elementary procedures for 5GS mobility management	105
5.1	Overview	105
5.1.1	General.....	105
5.1.2	Types of 5GMM procedures.....	105
5.1.3	5GMM sublayer states	107
5.1.3.1	General	107
5.1.3.2	5GMM sublayer states	107
5.1.3.2.1	5GMM sublayer states in the UE.....	107
5.1.3.2.1.1	General.....	107

5.1.3.2.1.2	Main states	107
5.1.3.2.1.2.1	5GMM-NULL	107
5.1.3.2.1.2.2	5GMM-DEREGISTERED	107
5.1.3.2.1.2.3	5GMM-REGISTERED-INITIATED	108
5.1.3.2.1.2.4	5GMM-REGISTERED	108
5.1.3.2.1.2.5	5GMM-DEREGISTERED-INITIATED	108
5.1.3.2.1.2.6	5GMM-SERVICE-REQUEST-INITIATED	108
5.1.3.2.1.3	Substates of state 5GMM-DEREGISTERED	108
5.1.3.2.1.3.1	General	108
5.1.3.2.1.3.2	5GMM-DEREGISTERED.NORMAL-SERVICE	108
5.1.3.2.1.3.3	5GMM-DEREGISTERED.LIMITED-SERVICE	108
5.1.3.2.1.3.4	5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION	108
5.1.3.2.1.3.5	5GMM-DEREGISTERED.PLMN-SEARCH	108
5.1.3.2.1.3.6	5GMM-DEREGISTERED.NO-SUPI	109
5.1.3.2.1.3.7	5GMM-DEREGISTERED.NO-CELL-AVAILABLE	109
5.1.3.2.1.3.8	5GMM-DEREGISTERED.eCALL-INACTIVE	109
5.1.3.2.1.3.9	5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED	109
5.1.3.2.1.4	Substates of state 5GMM-REGISTERED	109
5.1.3.2.1.4.1	General	109
5.1.3.2.1.4.2	5GMM-REGISTERED.NORMAL-SERVICE	109
5.1.3.2.1.4.3	5GMM-REGISTERED.NON-ALLOWED-SERVICE	110
5.1.3.2.1.4.4	5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE	110
5.1.3.2.1.4.5	5GMM-REGISTERED.LIMITED-SERVICE	110
5.1.3.2.1.4.6	5GMM-REGISTERED.PLMN-SEARCH	110
5.1.3.2.1.4.7	5GMM-REGISTERED.NO-CELL-AVAILABLE	110
5.1.3.2.1.4.8	5GMM-REGISTERED.UPDATE-NEEDED	110
5.1.3.2.2	5GS update status in the UE	111
5.1.3.2.3	5GMM sublayer states in the network side	111
5.1.3.2.3.1	General	111
5.1.3.2.3.2	5GMM-DEREGISTERED	112
5.1.3.2.3.3	5GMM-COMMON-PROCEDURE-INITIATED	112
5.1.3.2.3.4	5GMM-REGISTERED	112
5.1.3.2.3.5	5GMM-DEREGISTERED-INITIATED	112
5.1.4	Coordination between 5GMM and EMM	112
5.1.4.1	General	112
5.1.4.2	Coordination between 5GMM for 3GPP access and EMM with N26 interface	113
5.1.4.3	Coordination between 5GMM for 3GPP access and EMM without N26 interface	113
5.1.5	Coordination between 5GMM and GMM	113
5.2	Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED	114
5.2.1	General	114
5.2.2	UE behaviour in state 5GMM-DEREGISTERED	114
5.2.2.1	General	114
5.2.2.2	Primary substate selection	114
5.2.2.2.1	Selection of the substate after power on	114
5.2.2.3	Detailed description of UE behaviour in state 5GMM-DEREGISTERED	114
5.2.2.3.1	NORMAL-SERVICE	114
5.2.2.3.2	LIMITED-SERVICE	115
5.2.2.3.3	ATTEMPTING-REGISTRATION	115
5.2.2.3.4	PLMN-SEARCH	116
5.2.2.3.5	NO-SUPI	116
5.2.2.3.6	NO-CELL-AVAILABLE	116
5.2.2.3.7	eCALL-INACTIVE	116
5.2.2.3.8	INITIAL-REGISTRATION-NEEDED	116
5.2.2.4	Substate when back to state 5GMM-DEREGISTERED from another 5GMM state	116
5.2.3	UE behaviour in state 5GMM-REGISTERED	117
5.2.3.1	General	117
5.2.3.2	Detailed description of UE behaviour in state 5GMM-REGISTERED	117
5.2.3.2.1	NORMAL-SERVICE	117
5.2.3.2.2	NON-ALLOWED-SERVICE	117
5.2.3.2.3	ATTEMPTING-REGISTRATION-UPDATE	117
5.2.3.2.4	LIMITED-SERVICE	118
5.2.3.2.5	PLMN-SEARCH	119

5.2.3.2.6	NO-CELL-AVAILABLE	119
5.2.3.2.7	UPDATE-NEEDED	119
5.3	General on elementary 5GMM procedures	119
5.3.1	5GMM modes and N1 NAS signalling connection	119
5.3.1.1	Establishment of the N1 NAS signalling connection	119
5.3.1.2	Re-establishment of the N1 NAS signalling connection	121
5.3.1.3	Release of the N1 NAS signalling connection	122
5.3.1.4	5GMM-CONNECTED mode with RRC inactive indication	125
5.3.1.5	Suspend and resume of the N1 NAS signalling connection	127
5.3.2	Permanent identifiers	128
5.3.3	Temporary identities	130
5.3.4	Registration areas	131
5.3.5	Service area restrictions	132
5.3.5.1	General	132
5.3.5.2	3GPP access service area restrictions	132
5.3.5.3	Wireline access service area restrictions	135
5.3.6	Mobile initiated connection only mode	135
5.3.7	Handling of the periodic registration update timer and mobile reachable timer	137
5.3.8	Handling of timer T3502	139
5.3.9	Handling of NAS level mobility management congestion control	139
5.3.10	Handling of DNN based congestion control	140
5.3.11	Handling of S-NSSAI based congestion control	140
5.3.12	Handling of local emergency numbers	140
5.3.12A	Handling of local emergency numbers received via 3GPP access and non-3GPP access	141
5.3.12A.1	General	141
5.3.12A.2	Receiving a REGISTRATION ACCEPT message via non-3GPP access	142
5.3.13	Lists of 5GS forbidden tracking areas	142
5.3.13A	Forbidden PLMN lists	143
5.3.14	List of equivalent PLMNs	143
5.3.15	Transmission failure abnormal case in the UE	143
5.3.16	Extended DRX cycle for UEs in 5GMM-IDLE	143
5.3.17	Service Gap Control	144
5.3.18	Restriction on use of enhanced coverage	146
5.3.19	Handling of congestion control for transport of user data via the control plane	147
5.3.19a	Specific requirements for UE configured to use timer T3245	147
5.3.19a.1	UE not operating in SNPN access operation mode	147
5.3.19a.2	UE operating in SNPN access operation mode	148
5.3.20	Specific requirements for UE when receiving non-integrity protected reject messages	148
5.3.20.1	General	148
5.3.20.2	Requirements for UE in a PLMN	148
5.3.20.3	Requirements for UE in an SNPN	152
5.3.21	CIoT 5GS optimizations	155
5.3.22	Interaction between MICO mode with active time and extended idle mode DRX cycle	158
5.3.23	Forbidden wireline access area	158
5.3.24	WUS assistance	158
5.4	5GMM common procedures	159
5.4.1	Primary authentication and key agreement procedure	159
5.4.1.1	General	159
5.4.1.2	EAP based primary authentication and key agreement procedure	159
5.4.1.2.1	General	159
5.4.1.2.2	EAP-AKA' related procedures	162
5.4.1.2.2.1	General	162
5.4.1.2.2.2	Initiation	162
5.4.1.2.2.3	UE successfully authenticates network	162
5.4.1.2.2.4	Errors when handling EAP-request/AKA'-challenge message	163
5.4.1.2.2.5	Network successfully authenticates UE	163
5.4.1.2.2.6	UE handling EAP-AKA' notification message	163
5.4.1.2.2.6A	EAP based Identification initiation by the network	163
5.4.1.2.2.6B	EAP based Identification response by the UE	164
5.4.1.2.2.7	Network sending EAP-success message	164
5.4.1.2.2.8	UE handling EAP-success message	164
5.4.1.2.2.9	Network not successfully authenticates UE	164

5.4.1.2.2.10	Network sending EAP-failure message	164
5.4.1.2.2.11	UE handling EAP-failure message	165
5.4.1.2.2.12	Abnormal cases in the UE.....	167
5.4.1.2.3	EAP-TLS related procedures.....	167
5.4.1.2.3.1	General.....	167
5.4.1.2.3A	Procedures related to EAP methods other than EAP-AKA' and EAP-TLS.....	170
5.4.1.2.3A.1	General.....	170
5.4.1.2.3B	Procedures related to EAP methods used for primary authentication of an N5GC device.....	172
5.4.1.2.3B.1	General.....	172
5.4.1.2.4	EAP message reliable transport procedure	173
5.4.1.2.4.1	General.....	173
5.4.1.2.4.2	EAP message reliable transport procedure initiation by the network	173
5.4.1.2.4.3	EAP message reliable transport procedure accepted by the UE.....	174
5.4.1.2.4.4	Abnormal cases on the network side.....	174
5.4.1.2.4.5	Abnormal cases in the UE.....	174
5.4.1.2.5	EAP result message transport procedure	176
5.4.1.2.5.1	General.....	176
5.4.1.2.5.2	EAP result message transport procedure initiation by the network	177
5.4.1.3	5G AKA based primary authentication and key agreement procedure	177
5.4.1.3.1	General	177
5.4.1.3.2	Authentication initiation by the network	178
5.4.1.3.3	Authentication response by the UE	178
5.4.1.3.4	Authentication completion by the network.....	179
5.4.1.3.5	Authentication not accepted by the network.....	179
5.4.1.3.6	Authentication not accepted by the UE	181
5.4.1.3.7	Abnormal cases	182
5.4.2	Security mode control procedure.....	186
5.4.2.1	General	186
5.4.2.2	NAS security mode control initiation by the network	186
5.4.2.3	NAS security mode command accepted by the UE.....	189
5.4.2.4	NAS security mode control completion by the network	191
5.4.2.5	NAS security mode command not accepted by the UE.....	192
5.4.2.6	Abnormal cases in the UE.....	192
5.4.2.7	Abnormal cases on the network side.....	192
5.4.3	Identification procedure.....	193
5.4.3.1	General	193
5.4.3.2	Identification initiation by the network	193
5.4.3.3	Identification response by the UE	193
5.4.3.4	Identification completion by the network	193
5.4.3.5	Abnormal cases in the UE.....	194
5.4.3.6	Abnormal cases on the network side.....	194
5.4.4	Generic UE configuration update procedure.....	195
5.4.4.1	General	195
5.4.4.2	Generic UE configuration update procedure initiated by the network	197
5.4.4.3	Generic UE configuration update accepted by the UE.....	199
5.4.4.4	Generic UE configuration update completion by the network	202
5.4.4.5	Abnormal cases in the UE.....	203
5.4.4.6	Abnormal cases on the network side.....	204
5.4.5	NAS transport procedure(s).....	205
5.4.5.1	General	205
5.4.5.2	UE-initiated NAS transport procedure	205
5.4.5.2.1	General	205
5.4.5.2.2	UE-initiated NAS transport procedure initiation	206
5.4.5.2.3	UE-initiated NAS transport of messages accepted by the network	208
5.4.5.2.4	UE-initiated NAS transport of messages not accepted by the network	212
5.4.5.2.5	Abnormal cases on the network side	214
5.4.5.2.6	Abnormal cases in the UE	218
5.4.5.3	Network-initiated NAS transport procedure	220
5.4.5.3.1	General	220
5.4.5.3.2	Network-initiated NAS transport procedure initiation	221
5.4.5.3.3	Network-initiated NAS transport of messages	225
5.4.6	5GMM status procedure	228

5.4.6.1	General	228
5.4.6.2	5GMM status received in the UE	228
5.4.6.3	5GMM status received in the network	228
5.4.7	Network slice-specific authentication and authorization procedure	228
5.4.7.1	General	228
5.4.7.2	Network slice-specific EAP message reliable transport procedure	229
5.4.7.2.1	Network slice-specific EAP message reliable transport procedure initiation	229
5.4.7.2.2	Network slice-specific EAP message reliable transport procedure accepted by the UE	230
5.4.7.2.3	Abnormal cases on the network side	230
5.4.7.2.4	Abnormal cases in the UE	231
5.4.7.3	Network slice-specific EAP result message transport procedure	231
5.4.7.3.1	Network slice-specific EAP result message transport procedure initiation	231
5.5	5GMM specific procedures	232
5.5.1	Registration procedure	232
5.5.1.1	General	232
5.5.1.2	Registration procedure for initial registration	233
5.5.1.2.1	General	233
5.5.1.2.2	Initial registration initiation	233
5.5.1.2.3	5GMM common procedure initiation	238
5.5.1.2.4	Initial registration accepted by the network	238
5.5.1.2.5	Initial registration not accepted by the network	251
5.5.1.2.6	Initial registration for emergency services not accepted by the network	260
5.5.1.2.6A	Initial registration for initiating an emergency PDU session not accepted by the network	261
5.5.1.2.7	Abnormal cases in the UE	262
5.5.1.2.8	Abnormal cases on the network side	264
5.5.1.3	Registration procedure for mobility and periodic registration update	266
5.5.1.3.1	General	266
5.5.1.3.2	Mobility and periodic registration update initiation	266
5.5.1.3.3	5GMM common procedure initiation	275
5.5.1.3.4	Mobility and periodic registration update accepted by the network	276
5.5.1.3.5	Mobility and periodic registration update not accepted by the network	294
5.5.1.3.6	Mobility and periodic registration update for initiating an emergency PDU session not accepted by the network	304
5.5.1.3.7	Abnormal cases in the UE	304
5.5.1.3.8	Abnormal cases on the network side	308
5.5.2	De-registration procedure	310
5.5.2.1	General	310
5.5.2.2	UE-initiated de-registration procedure	311
5.5.2.2.1	UE-initiated de-registration procedure initiation	311
5.5.2.2.2	UE-initiated de-registration procedure completion	312
5.5.2.2.3	UE-initiated de-registration procedure completion for 5GS services over 3GPP access	312
5.5.2.2.4	UE-initiated de-registration procedure completion for 5GS services non-3GPP access	312
5.5.2.2.5	UE-initiated de-registration procedure completion for 5GS services over both 3GPP access and non-3GPP access	313
5.5.2.2.6	Abnormal cases in the UE	313
5.5.2.2.7	Abnormal cases in the network side	315
5.5.2.3	Network-initiated de-registration procedure	315
5.5.2.3.1	Network-initiated de-registration procedure initiation	315
5.5.2.3.2	Network-initiated de-registration procedure completion by the UE	316
5.5.2.3.3	Network-initiated de-registration procedure completion by the network	322
5.5.2.3.4	Abnormal cases in the UE	322
5.5.2.3.5	Abnormal cases in the network side	323
5.5.3	eCall inactivity procedure	324
5.6	5GMM connection management procedures	325
5.6.1	Service request procedure	325
5.6.1.1	General	325
5.6.1.2	Service request procedure initiation	328
5.6.1.2.1	UE is not using 5GS services with control plane CIoT 5GS optimization	328
5.6.1.2.2	UE is using 5GS services with control plane CIoT 5GS optimization	331
5.6.1.3	Common procedure initiation	333
5.6.1.4	Service request procedure accepted by the network	333
5.6.1.4.1	UE is not using 5GS services with control plane CIoT 5GS optimization	333

5.6.1.4.2	UE is using 5GS services with control plane CIoT 5GS optimization	335
5.6.1.5	Service request procedure not accepted by the network.....	338
5.6.1.6	Service request procedure for initiating an emergency PDU session not accepted by the network	347
5.6.1.7	Abnormal cases in the UE.....	348
5.6.1.8	Abnormal cases on the network side.....	351
5.6.2	Paging procedure	353
5.6.2.1	General	353
5.6.2.2	Paging for 5GS services	353
5.6.2.2.1	General	353
5.6.2.2.2	Abnormal cases on the network side	354
5.6.2.2.3	Abnormal cases in the UE	354
5.6.3	Notification procedure	355
5.6.3.1	General	355
5.6.3.2	Notification procedure initiation	355
5.6.3.3	Notification procedure completion.....	356
5.6.3.4	Abnormal cases on the network side.....	357
5.6.3.5	Abnormal cases on the UE side.....	357
6	Elementary procedures for 5GS session management	358
6.1	Overview	358
6.1.1	General.....	358
6.1.2	Types of 5GSM procedures	358
6.1.3	5GSM sublayer states	359
6.1.3.1	General	359
6.1.3.2	5GSM sublayer states in the UE	359
6.1.3.2.1	Overview	359
6.1.3.2.2	PDU SESSION INACTIVE	359
6.1.3.2.3	PDU SESSION ACTIVE PENDING.....	360
6.1.3.2.4	PDU SESSION ACTIVE	360
6.1.3.2.5	PDU SESSION INACTIVE PENDING.....	360
6.1.3.2.6	PDU SESSION MODIFICATION PENDING	360
6.1.3.2.7	PROCEDURE TRANSACTION INACTIVE.....	360
6.1.3.2.8	PROCEDURE TRANSACTION PENDING.....	360
6.1.3.3	5GSM sublayer states in the network side	360
6.1.3.3.1	Overview	360
6.1.3.3.2	PDU SESSION INACTIVE	361
6.1.3.3.3	PDU SESSION ACTIVE	361
6.1.3.3.4	PDU SESSION INACTIVE PENDING.....	361
6.1.3.3.5	PDU SESSION MODIFICATION PENDING	361
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	361
6.1.3.3.7	PROCEDURE TRANSACTION PENDING.....	361
6.1.4	Coordination between 5GSM and ESM.....	362
6.1.4.1	Coordination between 5GSM and ESM with N26 interface	362
6.1.4.2	Coordination between 5GSM and ESM without N26 interface	373
6.1.4a	Coordination between 5GSM and SM.....	376
6.1.5	Coordination for interworking with ePDG connected to EPC.....	376
6.2	General on elementary 5GSM procedures.....	376
6.2.1	Principles of PTI handling for 5GSM procedures.....	376
6.2.2	PDU session types	378
6.2.3	PDU session management	378
6.2.4	IP address allocation	379
6.2.4.1	General	379
6.2.4.2	IP address allocation via NAS signalling	379
6.2.4.3	Additional RG related requirements for IP address allocation.....	380
6.2.5	Quality of service.....	381
6.2.5.1	General	381
6.2.5.1.1	QoS rules	381
6.2.5.1.1.1	General.....	381
6.2.5.1.1.2	Signalled QoS rules	381
6.2.5.1.1.3	Derived QoS rules.....	382
6.2.5.1.1.4	QoS flow descriptions.....	383
6.2.5.1.2	Session-AMBR.....	383

6.2.5.1.2A	Void.....	383
6.2.5.1.3	UL user data packet matching	383
6.2.5.1.4	Reflective QoS.....	384
6.2.5.1.4.1	General.....	384
6.2.5.1.4.2	Derivation of packet filter for UL direction from DL user data packet	384
6.2.5.1.4.3	Creating a derived QoS rule by reflective QoS in the UE.....	386
6.2.5.1.4.4	Updating a derived QoS rule by reflective QoS in the UE	386
6.2.5.1.4.5	Deleting a derived QoS rule in the UE	386
6.2.5.1.4.6	Ignoring RQI in the UE.....	387
6.2.5.2	QoS in MA PDU session.....	387
6.2.6	Local area data network (LADN)	387
6.2.7	Handling of DNN based congestion control	388
6.2.8	Handling of S-NSSAI based congestion control.....	388
6.2.9	Interaction with upper layers	390
6.2.9.1	General	390
6.2.9.2	URSP.....	390
6.2.10	Handling of 3GPP PS data off	390
6.2.11	Multi-homed IPv6 PDU session	391
6.2.12	Handling of network rejection not due to congestion control	392
6.2.13	Handling of Small data rate control	393
6.2.14	Handling of Serving PLMN rate control.....	394
6.2.15	Handling of Reliable Data Service	394
6.2.16	Handling of header compression for control plane CIoT optimizations	394
6.3	Network-requested 5GSM procedures	395
6.3.1	PDU session authentication and authorization procedure.....	395
6.3.1.1	General	395
6.3.1.2	PDU EAP message reliable transport procedure	397
6.3.1.2.1	PDU EAP message reliable transport procedure initiation.....	397
6.3.1.2.2	PDU EAP message reliable transport procedure accepted by the UE	397
6.3.1.2.3	Abnormal cases on the network side	398
6.3.1.2.4	Abnormal cases in the UE	398
6.3.1.3	PDU EAP result message transport procedure	398
6.3.1.3.1	PDU EAP result message transport procedure initiation	398
6.3.2	Network-requested PDU session modification procedure	399
6.3.2.1	General	399
6.3.2.2	Network-requested PDU session modification procedure initiation	399
6.3.2.3	Network-requested PDU session modification procedure accepted by the UE.....	401
6.3.2.4	Network-requested PDU session modification procedure not accepted by the UE.....	407
6.3.2.5	Abnormal cases on the network side.....	411
6.3.2.6	Abnormal cases in the UE.....	412
6.3.3	Network-requested PDU session release procedure	413
6.3.3.1	General	413
6.3.3.2	Network-requested PDU session release procedure initiation	413
6.3.3.3	Network-requested PDU session release procedure accepted by the UE.....	415
6.3.3.4	N1 SM delivery skipped.....	421
6.3.3.5	Abnormal cases on the network side.....	422
6.3.3.6	Abnormal cases in the UE.....	422
6.4	UE-requested 5GSM procedures.....	422
6.4.1	UE-requested PDU session establishment procedure	422
6.4.1.1	General	422
6.4.1.2	UE-requested PDU session establishment procedure initiation	423
6.4.1.3	UE-requested PDU session establishment procedure accepted by the network	430
6.4.1.4	UE requested PDU session establishment procedure not accepted by the network	439
6.4.1.4.1	General	439
6.4.1.4.2	Handling of network rejection due to congestion control.....	442
6.4.1.4.3	Handling of network rejection not due to congestion control.....	447
6.4.1.5	Handling the maximum number of established PDU sessions.....	452
6.4.1.5A	Handling the maximum number of allowed active user-plane resources for PDU sessions of UEs in NB-N1 mode	453
6.4.1.6	Abnormal cases in the UE.....	454
6.4.1.7	Abnormal cases on the network side.....	454
6.4.2	UE-requested PDU session modification procedure.....	455

6.4.2.1	General	455
6.4.2.2	UE-requested PDU session modification procedure initiation	456
6.4.2.3	UE-requested PDU session modification procedure accepted by the network	459
6.4.2.4	UE-requested PDU session modification procedure not accepted by the network	459
6.4.2.4.1	General	459
6.4.2.4.2	Handling of network rejection due to congestion control.....	460
6.4.2.4.3	Handling of network rejection not due to congestion control.....	466
6.4.2.5	Abnormal cases in the UE	469
6.4.2.6	Abnormal cases on the network side	470
6.4.3	UE-requested PDU session release procedure	471
6.4.3.1	General	471
6.4.3.2	UE-requested PDU session release procedure initiation	471
6.4.3.3	UE-requested PDU session release procedure accepted by the network.....	472
6.4.3.4	UE-requested PDU session release procedure not accepted by the network.....	472
6.4.3.5	Abnormal cases in the UE.....	472
6.4.3.6	Abnormal cases on the network side.....	473
6.5	5GSM status procedure	473
6.5.1	General.....	473
6.5.2	5GSM status received in the UE.....	474
6.5.3	5GSM status received in the SMF	474
6.6	Miscellaneous procedures	474
6.6.1	Exchange of extended protocol configuration options.....	474
7	Handling of unknown, unforeseen, and erroneous protocol data	475
7.1	General	475
7.2	Message too short or too long	475
7.2.1	Message too short	475
7.2.2	Message too long	475
7.3	Unknown or unforeseen procedure transaction identity or PDU Session identity.....	475
7.3.1	Procedure transaction identity.....	475
7.3.2	PDU Session identity.....	476
7.4	Unknown or unforeseen message type	477
7.5	Non-semantic mandatory information element errors	477
7.5.1	Common procedures	477
7.5.2	5GS mobility management	478
7.5.3	5GS session management	478
7.6	Unknown and unforeseen IEs in the non-imperative message part.....	479
7.6.1	IEs unknown in the message	479
7.6.2	Out of sequence IEs	479
7.6.3	Repeated IEs	479
7.7	Non-imperative message part errors.....	479
7.7.1	Syntactically incorrect optional IEs	479
7.7.2	Conditional IE errors	479
7.8	Messages with semantically incorrect contents	480
8	Message functional definitions and contents.....	480
8.1	Overview	480
8.2	5GS mobility management messages	480
8.2.1	Authentication request	480
8.2.1.1	Message definition	480
8.2.1.2	Authentication parameter RAND.....	480
8.2.1.3	Authentication parameter AUTN	481
8.2.1.4	Void.....	481
8.2.1.5	EAP message.....	481
8.2.2	Authentication response.....	481
8.2.2.1	Message definition	481
8.2.2.2	Authentication response parameter	481
8.2.2.3	EAP message.....	481
8.2.3	Authentication result.....	481
8.2.3.1	Message definition	481
8.2.3.2	ABBA	482
8.2.4	Authentication failure	482

8.2.4.1	Message definition	482
8.2.4.2	Authentication failure parameter.....	483
8.2.5	Authentication reject.....	483
8.2.5.1	Message definition	483
8.2.5.2	EAP message.....	483
8.2.6	Registration request	483
8.2.6.1	Message definition	483
8.2.6.2	Non-current native NAS key set identifier.....	486
8.2.6.3	5GMM capability	486
8.2.6.4	UE security capability	486
8.2.6.5	Requested NSSAI	486
8.2.6.6	Last visited registered TAI.....	486
8.2.6.7	S1 UE network capability	486
8.2.6.8	Uplink data status.....	486
8.2.6.9	PDU session status	486
8.2.6.10	MICO indication	486
8.2.6.11	UE status	487
8.2.6.12	Additional GUTI.....	487
8.2.6.13	Allowed PDU session status	487
8.2.6.14	UE's usage setting	487
8.2.6.15	Requested DRX parameters	487
8.2.6.16	EPS NAS message container.....	487
8.2.6.17	LADN indication.....	487
8.2.6.17A	Payload container type	487
8.2.6.18	Payload container	487
8.2.6.19	Network slicing indication	488
8.2.6.20	5GS update type	488
8.2.6.21	NAS message container	488
8.2.6.22	Requested extended DRX parameters	488
8.2.6.23	EPS bearer context status	488
8.2.6.24	T3324 value.....	488
8.2.6.25	Mobile station classmark.....	488
8.2.6.26	Supported codecs.....	488
8.2.6.27	UE radio capability.....	488
8.2.6.28	Requested mapped NSSAI.....	488
8.2.6.29	Additional information requested.....	489
8.2.6.30	Requested WUS assistance information.....	489
8.2.6.31	Void.....	489
8.2.6.32	N5GC indication	489
8.2.6.33	Requested NB-N1 mode DRX parameters.....	489
8.2.7	Registration accept.....	489
8.2.7.1	Message definition	489
8.2.7.2	5G-GUTI.....	492
8.2.7.3	Equivalent PLMNs.....	492
8.2.7.4	TAI list	492
8.2.7.5	Allowed NSSAI	492
8.2.7.6	Rejected NSSAI	493
8.2.7.7	Configured NSSAI.....	493
8.2.7.8	5GS network feature support.....	493
8.2.7.9	PDU session status	493
8.2.7.10	PDU session reactivation result.....	493
8.2.7.11	PDU session reactivation result error cause	493
8.2.7.12	LADN information.....	493
8.2.7.13	MICO indication	493
8.2.7.14	Network slicing indication	493
8.2.7.15	Service area list	493
8.2.7.16	T3512 value.....	494
8.2.7.17	Non-3GPP de-registration timer value	494
8.2.7.18	T3502 value.....	494
8.2.7.19	Emergency number list	494
8.2.7.20	Extended emergency number list	494
8.2.7.21	SOR transparent container	494

8.2.7.22	EAP message.....	494
8.2.7.23	NSSAI inclusion mode.....	494
8.2.7.24	Operator-defined access category definitions	494
8.2.7.25	Negotiated DRX parameters	494
8.2.7.26	Non-3GPP NW provided policies	494
8.2.7.27	Negotiated extended DRX parameters	495
8.2.7.28	T3447 value.....	495
8.2.7.29	T3448 value.....	495
8.2.7.30	T3324 value.....	495
8.2.7.31	EPS bearer context status	495
8.2.7.32	UE radio capability ID	495
8.2.7.33	UE radio capability ID deletion indication.....	495
8.2.7.34	Pending NSSAI	495
8.2.7.35	Ciphering key data	495
8.2.7.36	CAG information list.....	495
8.2.7.37	Truncated 5G-S-TMSI configuration.....	496
8.2.7.38	Negotiated NB-N1 mode DRX parameters.....	496
8.2.7.39	Negotiated WUS assistance information.....	496
8.2.8	Registration complete	496
8.2.8.1	Message definition	496
8.2.8.2	SOR transparent container	496
8.2.9	Registration reject.....	497
8.2.9.1	Message definition	497
8.2.9.2	T3346 value.....	497
8.2.9.3	T3502 value.....	497
8.2.9.4	EAP message.....	497
8.2.9.5	Rejected NSSAI	497
8.2.9.6	CAG information list.....	497
8.2.10	UL NAS transport.....	498
8.2.10.1	Message definition	498
8.2.10.2	PDU session ID	498
8.2.10.3	Old PDU session ID	498
8.2.10.4	Request type	499
8.2.10.5	S-NSSAI	499
8.2.10.6	DNN.....	499
8.2.10.7	Additional information.....	499
8.2.10.8	MA PDU session information.....	499
8.2.10.9	Release assistance indication	499
8.2.11	DL NAS transport.....	499
8.2.11.1	Message definition	499
8.2.11.2	PDU session ID.....	500
8.2.11.3	Additional information.....	500
8.2.11.4	5GMM cause.....	500
8.2.11.5	Back-off timer value	500
8.2.12	De-registration request (UE originating de-registration)	500
8.2.12.1	Message definition	500
8.2.13	De-registration accept (UE originating de-registration).....	501
8.2.13.1	Message definition	501
8.2.14	De-registration request (UE terminated de-registration).....	501
8.2.14.1	Message definition	501
8.2.14.2	5GMM cause.....	502
8.2.14.3	T3346 value.....	502
8.2.14.4	Rejected NSSAI	502
8.2.14.5	CAG information list.....	502
8.2.15	De-registration accept (UE terminated de-registration).....	502
8.2.15.1	Message definition	502
8.2.16	Service request.....	503
8.2.16.1	Message definition	503
8.2.16.2	Uplink data status.....	503
8.2.16.3	PDU session status	503
8.2.16.4	Allowed PDU session status	504
8.2.16.5	NAS message container	504

8.2.17	Service accept	504
8.2.17.1	Message definition	504
8.2.17.2	PDU session status	504
8.2.17.3	PDU session reactivation result.....	504
8.2.17.4	PDU session reactivation result error cause	505
8.2.17.5	EAP message.....	505
8.2.17.6	T3448 value.....	505
8.2.18	Service reject	505
8.2.18.1	Message definition	505
8.2.18.2	PDU session status	505
8.2.18.3	T3346 value.....	506
8.2.18.4	EAP message.....	506
8.2.18.5	T3448 value.....	506
8.2.18.6	CAG information list.....	506
8.2.19	Configuration update command.....	506
8.2.19.1	Message definition	506
8.2.19.2	Configuration update indication.....	508
8.2.19.3	5G-GUTI.....	508
8.2.19.4	TAI list	508
8.2.19.5	Allowed NSSAI	508
8.2.19.6	Service area list	508
8.2.19.7	Full name for network	508
8.2.19.8	Short name for network.....	508
8.2.19.9	Local time zone	508
8.2.19.10	Universal time and local time zone	508
8.2.19.11	Network daylight saving time	508
8.2.19.12	LADN information	508
8.2.19.13	MICO indication	508
8.2.19.14	Network slicing indication	508
8.2.19.15	Configured NSSAI.....	508
8.2.19.16	Rejected NSSAI	509
8.2.19.17	Operator-defined access category definitions.....	509
8.2.19.18	SMS indication	509
8.2.19.19	T3447 value.....	509
8.2.19.20	CAG information list.....	509
8.2.19.21	UE radio capability ID	509
8.2.19.22	UE radio capability ID deletion indication.....	509
8.2.19.23	5GS registration result.....	509
8.2.19.24	Truncated 5G-S-TMSI configuration.....	509
8.2.19.25	Additional configuration indication	509
8.2.20	Configuration update complete.....	509
8.2.20.1	Message definition	509
8.2.20.2	Void.....	510
8.2.21	Identity request	510
8.2.21.1	Message definition	510
8.2.22	Identity response	510
8.2.22.1	Message definition	510
8.2.23	Notification	511
8.2.23.1	Message definition	511
8.2.24	Notification response	511
8.2.24.1	Message definition	511
8.2.24.2	PDU session status	512
8.2.25	Security mode command	512
8.2.25.1	Message definition	512
8.2.25.2	IMEISV request	513
8.2.25.3	Void.....	513
8.2.25.4	Selected EPS NAS security algorithms.....	513
8.2.25.5	Additional 5G security information	513
8.2.25.6	EAP message.....	513
8.2.25.7	ABBA	513
8.2.25.8	Replayed S1 UE security capabilities	514
8.2.26	Security mode complete.....	514