SLOVENSKI STANDARD
SIST-TP TR 101 327 V1.1.1:2004

01-april-2004

<Uʹa cb]nU…ˇU hˇY_ca i b]_U… ^]bˇ]bhˇfbYˇfbY[Uˇdfchc_c`Uˇdf Yˇ_ca fYÿ]^fH=D< CBˇ! JcX]ˇcˇnUˇ]nV]fcˇýhˇYj ]ˇˇYbˇUˇnUˇUjbUˇca fYÿˇUˇž_]ˇhˇYa Yˇ¶]^cˇbU…ˇh\bc`c[ ]¶ˇJc=Dˇf[cjcf dfY_`]bhˇYfbY[ Uˇdfchc_c`U…

Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON);
Guide to numbering options for public networks based on VoIP technology

Ta slovenski standard je istoveten z: **TR 101 327 Version 1.1.1**

ICS:

33.020	Telekomunikacije na splošno	Telecommunications in general

SIST-TP TR 101 327 V1.1.1:2004   **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ETSI TR 101 327 V1.1.1 (1999-11)

Technical Report

Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON); Guide to numbering options for public networks based on VoIP technology

iTeh STANDARD PREVIEW

(standards.iteh.ai)

ETSI

Reference
DTR/TIPHON-04004 (cac00ics.PDF)

Keywords
addressing, IP, network, VoIP

ETSI

Postal address
F-06921 Sophia Antipolis Cedex - FRANCE

iTeh STANDARD PREVIEW
Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00   Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet
secretariat@etsi.fr
Individual copies of this ETSI deliverable
can be downloaded from
http://www.etsi.org
If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or
perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).
In case of dispute, the reference should be the printing on ETSI printers of the PDF version kept on a specific network
drive within ETSI Secretariat.

ETSI

Contents

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://www.etsi.org/ipr).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Report (TR) has been produced by ETSI Project Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON).

iTeh STANDARD PREVIEW
(standards.iteh.ai)

1   Scope

The present document provides basic guidance on the range of different numbering options within E.164 that may be used for services provided on public networks using TIPHON compliant technology. The present document identifies:

- the various numbering options;

- the main considerations in selecting an option;

- the advantages and disadvantages of each option;

- issues concerning number portability.

The information and advice in the present document applies primarily to TIPHON Scenarios 0 (all IP) and 2 (SCN to IP) but there are additional comments about Scenario 3 (SCN to IP to SCN).

NOTE: The E.164 number will normally be presented as the calling number in the Calling Line Identity which is relevant to Scenario 1 (IP to SCN) but this is not a major influence on the choice of E.164 number.

2   References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.

- For a specific reference, subsequent revisions do not apply.

- For a non-specific reference, the latest version applies.

- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

[1]   EG 201 367 (V1.1): "Intelligent Network (IN); Number Portability Task Force (NPTF); IN and Intelligence Support for Service Provider Number Portability".

[2]   ITU-T Recommendation E.105: "International telephone service".

[3]   ITU-T Recommendation E.164 (1997): "The international public telecommunication numbering plan".

[4]   TR 101 092: "Network Aspects (NA); Report on Carrier Selection".

[5]   TR 101 118 (V1.1): "Network Aspects (NA); High level network architecture and solutions to support number portability".

[6]   TR 101 119 (V1.1): "Network Aspects (NA); High level description of number portability".

[7]   TR 101 122 (V1.1): "Network Aspects (NA); Numbering and addressing for number portability".

[8]   TR 101 697 (V1.1): "Number Portability Task Force (NPTF); Guidance on choice of network solutions for service provider portability for geographic and non-geographic numbers".

[9]   TR 101 698 (V1.1): "Number Portability Task Force (NPTF); Administrative support of service provider portability for geographic and non-geographic numbers".

3   Abbreviations

For the purposes of the present document, the following abbreviations apply:

VoIP	Voice over IP
IP	Internet Protocol
ISDN	Integrated Services Digital Network
SCN	Switched Circuit network
UPT	Universal Personal Telecommunications

4   General considerations

4.1   Introduction to numbering arrangements

The introduction of VoIP technology in "public" networks is likely to be the second phase of the development of VoIP, use in corporate networks being the first phase. Numbering becomes a significant issue when the network termination point is implemented in IP technology and the transition from the traditional Switched Circuit Network technology occurs within or between public networks.

ITU-T Recommendation E.164 describes the "International Public Telecommunications Numbering Plan".

ITU-T allocates codes to:

- countries and geographical regions;

- global services;

- "Networks" that share a global code.

Numbering within countries and geographical regions (e.g. North America) is managed by the national administration or numbering authority. The numbering space after the country code is subdivided into:

- national destination code;

- subscriber number.

In practice, the national destination code may be used for:

- a geographical area (e.g. a city);

- a service type;

- a network (e.g. a particular mobile network).

The lengths of the national numbers and their constituent parts vary from country to country. Not all service types may be callable from outside the country concerned.

4.2   Basic principles

The approach to numbering varies from country to country and is heavily influenced by historical arrangements, but many numbering authorities follow the following principles:

-    the caller should be able to discern some tariff information from the early part of the number and should be able easily to identify numbers where the tariff is high;

-    numbers should be allocated on the basis of:

   -    service type;

   -    geographical location; and / or

   -    tariff level.

and not on the basis of technology.

Many national regulations are written with reference to services and are designed to be technology independent at least to a first approximation.

With the introduction of competition, many national authorities impose requirements for operator/service provider number portability so that customers' numbers may be transferred between operators and/or service providers when customers change their account. Requirements for number portability between operators are inherently incompatible with identifying a network operator in the initial part of a international or national number. Where numbers ranges have been or are allocated initially to network operators for subsequent sub-allocation of individual numbers to customers and portability is introduced, then the relationship between the number range and the operator is broken and the number range is no longer a precise indicator of the operator.

iTeh STANDARD PREVIEW

The need for callers to be able to discern some tariff information from numbers imposes constraints on the use of numbers and reduces the efficiency of the use of numbers. In the longer term it may not be possible to maintain this information, and it may be desirable to remove this constraint, in which case other adequate forms of tariff transparency for callers may be needed.

4.3   Relationship of numbering to VoIP

VoIP is a technology that may be used to provide various different services. These services include:

-    the international telephony service such as is also provided by the PSTN and ISDN and conforms to ITU-T Recommendation E.105 [2], where there will normally be some location information within the national number;

-    national services that do not indicate location but have special tariff arrangements such as:

   -    freephone;

   -    local tariff;

   -    national tariff;

   -    premium rate.

-    national services with special features such as Universal Personal Telecommunications (UPT);

-    international services such as universal freephone (+800 ….) and UPT.

Since numbering is normally related primarily to services rather than technology, this means that there is no single numbering arrangement for VoIP technology. The numbering options, and the choice from these options, should be determined by the service that is to be provided.