



SLOVENSKI STANDARD
SIST ISO 6336-6:2020

01-oktober-2020

Izračun nosilnosti ravnozobih in poševnozobih zobnikov - 6. del: Izračun dobe trajanja pri spremenljivi obremenitvi

Calculation of load capacity of spur and helical gears - Part 6: Calculation of service life under variable load

iTeh STANDARD PREVIEW

Calcul de la capacité de charge des engrenages cylindriques à dentures droite et hélicoïdale
(standards.iTeh.si)

[SIST ISO 6336-6:2020](#)

Ta slovenski standard je istoveten z: ISO 6336-6:2019
<http://standards.iTeh.si/catalog/stanards/SIST/6336-6:2020/4fde-8aa5-c67d28c0cde2/sist-iso-6336-6-2020>

ICS:

21.200

Gonila

Gears

SIST ISO 6336-6:2020

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 6336-6:2020](https://standards.iteh.ai/catalog/standards/sist/2df45f0f-7d47-4fde-8aa5-c67d28c0cde2/sist-iso-6336-6-2020)

<https://standards.iteh.ai/catalog/standards/sist/2df45f0f-7d47-4fde-8aa5-c67d28c0cde2/sist-iso-6336-6-2020>

INTERNATIONAL
STANDARD

ISO
6336-6

Second edition
2019-11

**Calculation of load capacity of spur
and helical gears —**

**Part 6:
Calculation of service life under
variable load**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Calcul de la capacité de charge des engrenages cylindriques à
dentures droite et hélicoïdale —*

Partie 6: Calcul de la durée de vie en service sous charge variable

SIST ISO 6336-6:2020

<https://standards.iteh.ai/catalog/standards/sist/2df45f0f-7d47-4fde-8aa5-c67d28c0cde2/sist-iso-6336-6-2020>



Reference number
ISO 6336-6:2019(E)

© ISO 2019

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 6336-6:2020

<https://standards.iteh.ai/catalog/standards/sist/2df45f0f-7d47-4fde-8aa5-c67d28c0cde2/sist-iso-6336-6-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms, definitions, symbols and abbreviated terms.....	1
3.1 Terms and definitions.....	1
3.2 Symbols and abbreviated terms.....	1
4 General.....	5
4.1 Determination of load and stress spectra.....	5
4.2 General calculation of service life.....	7
4.3 Palmgren-Miner rule.....	8
5 Calculation of service strength on the basis of single-stage strength according to ISO 6336 series.....	9
5.1 Basic principles.....	9
5.2 Calculation of stress spectra.....	13
5.3 Determination of pitting and bending strength values.....	14
5.4 Determination of safety factors.....	14
Annex A (normative) Determination of application factor, K_A, from given load spectrum using equivalent torque, T_{eq}.....	16
Annex B (informative) Equivalent cumulative damage.....	22
Annex C (informative) Example calculation for safety factor from given load spectrum.....	30
Bibliography.....	37

SIST ISO 6336-6:2020
<https://standards.iteh.ai/catalog/standards/sist/2df45f0f-7d47-4fde-8aa5-c67d28c0cde2/sist-iso-6336-6-2020>

ISO 6336-6:2019(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 2, *Gear capacity calculation*.

This second edition cancels and replaces the first edition (ISO 6336-6:2006), which has been technically revised. It also incorporates the Technical Corrigendum ISO 6336-6:2006/Cor.1:2007.

The main changes compared to the previous edition are as follows:

- in [Annex A](#), examples have been revised;
- integration of [Annex B](#) "Equivalent cumulative damage".

A list of all parts in the ISO 6336 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

ISO 6336 (all parts) consists of International Standards, Technical Specifications (TS) and Technical Reports (TR) under the general title *Calculation of load capacity of spur and helical gears* (see [Table 1](#)).

- International Standards contain calculation methods that are based on widely accepted practices and have been validated.
- Technical Specifications (TS) contain calculation methods that are still subject to further development.
- Technical Reports (TR) contain data that is informative, such as example calculations.

The procedures specified in parts 1 to 19 of the ISO 6336 series cover fatigue analyses for gear rating. The procedures described in parts 20 to 29 of the ISO 6336 series are predominantly related to the tribological behavior of the lubricated flank surface contact. Parts 30 to 39 of the ISO 6336 series include example calculations. The ISO 6336 series allows the addition of new parts under appropriate numbers to reflect knowledge gained in the future.

Requesting standardized calculations according to the ISO 6336 series without referring to specific parts requires the use of only those parts that are currently designated as International Standards (see [Table 1](#) for listing). When requesting further calculations, the relevant part or parts of the ISO 6336 series need to be specified. Use of a Technical Specification as acceptance criteria for a specific design need to be agreed in advance between the manufacturer and the purchaser.

Table 1 — Parts of the ISO 6336 series (STATUS AS OF DATE OF PUBLICATION)
(standards.itech.ai)

Calculation of load capacity of spur and helical gears SIST ISO 6336-6:2020	International Standard	Technical Specification	Technical Report
Part 1: Basic principles, introduction and general influence factors <small>(replaces: ISO/TR 13989-1)</small>	X		
Part 2: Calculation of surface durability (pitting)	X		
Part 3: Calculation of tooth bending strength	X		
Part 4: Calculation of tooth flank fracture load capacity		X	
Part 5: Strength and quality of materials	X		
Part 6: Calculation of service life under variable load	X		
Part 20: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Flash temperature method <small>(replaces: ISO/TR 13989-1)</small>		X	
Part 21: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Integral temperature method <small>(replaces: ISO/TR 13989-2)</small>		X	
Part 22: Calculation of micropitting load capacity <small>(replaces: ISO/TR 15144-1)</small>		X	
Part 30: Calculation examples for the application of ISO 6336-1, 2, 3, 5			X
Part 31: Calculation examples of micropitting load capacity <small>(replaces: ISO/TR 15144-2)</small>			X

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 6336-6:2020](https://standards.iteh.ai/catalog/standards/sist/2df45f0f-7d47-4fde-8aa5-c67d28c0cde2/sist-iso-6336-6-2020)

<https://standards.iteh.ai/catalog/standards/sist/2df45f0f-7d47-4fde-8aa5-c67d28c0cde2/sist-iso-6336-6-2020>

Calculation of load capacity of spur and helical gears —

Part 6:

Calculation of service life under variable load

1 Scope

This document specifies the information and standardized conditions necessary for the calculation of the service life (or safety factors for a required life) of gears subject to variable loading for only pitting and tooth root bending strength.

If this scope does not apply, refer ISO 6336-1:2019, Clause 4.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1122-1:1998, *Vocabulary of gear terms — Part 1: Definitions related to geometry*

ISO 6336-1, *Calculation of load capacity of spur and helical gears — Part 1: Basic principles, introduction and general influence factors*

ISO 6336-2, *Calculation of load capacity of spur and helical gears — Part 2: Calculation of surface durability (pitting)*

ISO 6336-3, *Calculation of load capacity of spur and helical gears — Part 3: Calculation of tooth bending strength*

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 6336-1 and ISO 1122-1:1998 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <http://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.2 Symbols and abbreviated terms

For the purposes of this document, the symbols and abbreviated terms given in ISO 6336-1, ISO 1122-1:1998 and [Table 2](#) apply.

Table 2 — Symbols and abbreviated terms used in this document

Abbreviated terms		
Term	Description	
Eh	material designation for case-hardened wrought steel	
GG	material designation for grey cast iron	
GGG	material designation for nodular cast iron (perlitic, bainitic, ferritic structure)	
GTS	material designation for black malleable cast iron (perlitic structure)	
IF	material designation for flame or induction hardened wrought special steel	
NT	material designation for nitrided wrought steel, nitriding steel	
NV	material designation for through-hardened wrought steel, nitrided, nitrocarburized	
St	material designation for normalized base steel ($\sigma_B < 800 \text{ N/mm}^2$)	
V	material designation for through-hardened wrought special steel, alloy or carbon ($\sigma_B \geq 800 \text{ N/mm}^2$)	
Symbols		
Symbol	Description	Unit
a	centre distance ^a	mm
b	face width	mm
d	diameter (without subscript, reference diameter ^a)	mm
d_a	tip diameter ^a	mm
F	force or load	N
F_t	(nominal) transverse tangential load at reference cylinder per mesh	N
K	constant, factors concerning tooth load	—
K_A	application factor (Annex A shall apply for pitting and tooth root bending)	—
$K_{F\alpha}$	transverse load factor (bending)	—
$K_{F\beta}$	face load factor (bending)	—
$K_{H\alpha}$	transverse load factor (contact stress)	—
$K_{H\beta}$	face load factor (contact stress)	—
K_y	mesh load factor	—
K_v	dynamic factor	—
m_n	normal module	mm
N	number of load cycles	—
N_i	number of load cycles to failure for bin i	—
N_L	number of load cycles of S-N curve	—
N_{LF}	number of load cycles for bending damage	—

^a For external gears a , d , d_a , z_1 and z_2 are positive; for internal gearing, a , d , d_a and z_2 have a negative sign, z_1 has a positive sign. All calculated diameters have a negative sign for internal gearing.

Table 2 (continued)

Symbols		
Symbol	Description	Unit
N_{LH}	number of load cycles for pitting damage	—
$N_{L,ref}$	number of load cycles for endurance limit	—
$n_{D,i}$	number of load cycles for the equivalent damage fatigue curve (Annex B)	—
$n_{D,REF}$	number of load cycles for the equivalent damage fatigue curve (reference) (Annex B)	—
$n_{eq,i}$	equivalent number of load cycles (Annex B)	—
$n_{eq,3REF}$	equivalent number of load cycles (reference) (Annex B)	—
n_i	number of load cycles for bin i	—
n_{Hi}	number of load cycles for contact stress for bin i	—
n_{Fi}	number of load cycles for tooth root stress for bin i	—
$n_{nom,i}$	number of load cycles for nominal stress in bin i (Annex B)	—
p	slope of the S-N curve	—
S	safety factor	—
S_F	safety factor for bending	—
S_H	safety factor for pitting	—
T	torque (pinion torque unless specified otherwise)	N·m
T_{eq}	equivalent torque	N·m
T_i	torque for bin i	N·m
T_n	nominal torque	N·m
U	sum of individual damage parts	—
U_i	individual damage parts for bin i	—
u	gear ratio ($ z_2 / z_1 \geq 1^a$)	—
x	profile shift coefficient	—
Y	factor related to tooth root bending	—
Y_B	rim thickness factor	—
Y_{DT}	deep tooth factor	—
Y_F	tooth form factor, for the influence on nominal tooth root stress with load applied at the outer point of single pair tooth contact	—
Y_{NT}	life factor for tooth root stress for reference test conditions	—
$Y_{Rrel T}$	relative surface factor, the quotient of the gear tooth root surface factor of interest divided by the tooth root surface factor of the reference test gear, $Y_{Rrel T} = Y_R / Y_{RT}$	—
Y_S	stress correction factor, for the conversion of the nominal tooth root stress, determined for application of load at the outer point of single pair tooth contact, to the local tooth root stress	—

^a For external gears a , d , d_a , z_1 and z_2 are positive; for internal gearing, a , d , d_a and z_2 have a negative sign, z_1 has a positive sign. All calculated diameters have a negative sign for internal gearing.

Table 2 (continued)

Symbols		
Symbol	Description	Unit
Y_{ST}	stress correction factor, relevant to the dimensions of the standard reference test gears	—
Y_{β}	helix angle factor (tooth root)	—
$Y_{\delta \text{ rel T}}$	relative notch sensitivity factor, the quotient of the gear notch sensitivity factor of interest divided by the standard reference test gear factor, $Y_{\delta \text{ rel T}} = Y_{\delta} / Y_{\delta T}$	—
Z	factor related to contact stress	—
Z_B, Z_D	single pair tooth contact factors for the pinion, for the wheel	—
Z_E	elasticity factor	$(\text{N/mm}^2)^{0,5}$
Z_H	zone factor	—
Z_L	lubricant factor	—
Z_N	life factor for contact stress	—
Z_{NT}	life factor for contact stress for reference test conditions	—
Z_R	roughness factor affecting surface durability	—
Z_v	velocity factor	—
Z_W	work hardening factor	—
Z_X	size factor (pitting)	—
Z_{β}	helix angle factor (pitting)	—
Z_{ϵ}	contact ratio factor (pitting)	—
z	number of teeth ^a	—
z_n	virtual number of teeth of a helical gear	—
α	pressure angle (without subscript, at reference cylinder)	°
β	helix angle (without subscript, at reference cylinder)	°
σ	normal stress	N/mm^2
σ_D	stress value used to describe the equivalent damage fatigue curve (Annex B)	N/mm^2
σ_F	tooth root stress	N/mm^2
σ_{FG}	tooth root stress limit	N/mm^2
σ_{Fi}	tooth root stress for bin i	N/mm^2
σ_{FP}	permissible bending stress	N/mm^2
$\sigma_{F \text{ lim}}$	nominal stress number (bending)	N/mm^2
σ_G	stress value used to describe the permissible S-N curve	N/mm^2
σ_H	contact stress	N/mm^2
σ_{HG}	pitting stress limit	N/mm^2
σ_{Hi}	contact stress for bin i	N/mm^2

^a For external gears a, d, d_a, z_1 and z_2 are positive; for internal gearing, a, d, d_a and z_2 have a negative sign, z_1 has a positive sign. All calculated diameters have a negative sign for internal gearing.

Table 2 (continued)

Symbols		
Symbol	Description	Unit
σ_{HP}	permissible contact stress	N/mm ²
σ_P	stress value used to describe the S-N curve (Annex B)	N/mm ²
σ_{REF}	reference permissible stress level	N/mm ²
σ_i	stress for bin i	N/mm ²
$\sigma_{nom,i}$	nominal stress for bin i (Annex B)	N/mm ²
^a For external gears a , d , d_a , z_1 and z_2 are positive; for internal gearing, a , d , d_a and z_2 have a negative sign, z_1 has a positive sign. All calculated diameters have a negative sign for internal gearing.		

4 General

4.1 Determination of load and stress spectra

Variable loads resulting from a working process, starting process or from operation at or near a critical speed will cause varying stresses at the gear teeth of a drive system. The magnitude and frequency of these loads depend upon the driven machine(s), the driver(s) or motor(s) and the dynamic mass elastic properties of the system.

These variable loads (stresses) may be determined by such procedures as

- experimental measurement of the operating loads at the machine in question,
- estimation of the spectrum, if this is known, for a similar machine with a similar operating mode, and
- calculation, using known external excitation and a mass elastic simulation of the drive system, preferably followed by experimental testing to validate the calculation.

To obtain the load spectra for fatigue damage calculation, the range of the measured (or calculated) loads is divided into bins or classes. Each bin contains the number of load occurrences recorded in its load range. A widely-used number of bins is 64. These bins can be of an equal size, but it is usually better to use larger bin sizes at the lower loads and smaller bin sizes at the upper loads in the range. In this way, the most damaging loads may be limited to fewer calculated stress cycles and the resulting design is more accurate regarding the effective load. It is recommended that a zero-load bin be included so that the total time used to rate the gears matches the design operating life. For consistency, the usual presentation method is to have the highest torque associated with the lowest numbered bins, such that the most damaging conditions appear towards the top of any table.

The cycle count for the load class corresponding to the load value for the highest loaded tooth is incremented at every load repetition. [Table 3](#) shows as an example of how the torque classes defined in [Table 4](#) can be applied to specific torque levels and correlated numbers of cycles.

Table 3 — Torque classes/numbers of cycles — Example: classes 38 and 39 (see [Table 4](#))

Torque class, T_i N·m	Number of cycles, n_i
$11\,620 \leq T_{38} \leq 12\,619$	$n_{38} = 237$
$10\,565 \leq T_{39} \leq 11\,619$	$n_{39} = 252$

The torques used to evaluate the tooth loading should include the dynamic effects at different rotational speeds.

This spectrum is only valid for the measured or evaluated time period. If the spectrum is extrapolated to represent the required lifetime, the possibility that there might be torque peaks not frequent enough to be evaluated in that measured spectrum shall be considered. These transient peaks can have an