# INTERNATIONAL STANDARD

First edition 2015-09-01

# Microscopes — Minimum requirements for binocular tubes

Microscopes — Exigences minimales pour tubes binoculaires

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 19055:2015</u> https://standards.iteh.ai/catalog/standards/sist/45c64b32-e84e-4b09-8fe2b70dfbed1828/iso-19055-2015



Reference number ISO 19055:2015(E)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 19055:2015</u> https://standards.iteh.ai/catalog/standards/sist/45c64b32-e84e-4b09-8fe2b70dfbed1828/iso-19055-2015



© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Page

# Contents

| Forew | ordi   | V |
|-------|--|---|
| 1     | Scope  | 1 |
| 2     | Normative references                           | 1 |
| 3     | Terms and definitions                          | 1 |
| 4     | Requirements                                   | 2 |
| Annex | A (normative) Test methods for binocular tubes | 4 |

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19055:2015 https://standards.iteh.ai/catalog/standards/sist/45c64b32-e84e-4b09-8fe2b70dfbed1828/iso-19055-2015

# Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="https://www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ASO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 172, *Optics and photonics*, Subcommittee SC 5, *Microscopes and endoscopes*.

<u>ISO 19055:2015</u> https://standards.iteh.ai/catalog/standards/sist/45c64b32-e84e-4b09-8fe2b70dfbed1828/iso-19055-2015

# Microscopes — Minimum requirements for binocular tubes

### 1 Scope

This International Standard specifies the minimum requirements regarding image quality and viewing ergonomics for binocular tubes for compound microscopes when used with eyepieces as specified by the manufacturer. This International Standard makes a distinction between binocular tubes with and without dioptre adjustment.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15227:2000, Optics and optical instruments — Microscopes — Testing of stereomicroscopes

# 3 Terms and definitions TANDARD PREVIEW

For the purposes of this document, the following terms and definitions apply.

#### 3.1

#### interpupillary distance

<u>ISO 19055:2015</u>

IPD https://standards.iteh.ai/catalog/standards/sist/45c64b32-e84e-4b09-8fe2-

distance between the exit pupils of the left and right optical system

#### 3.2

#### optical axis

axis given by the central ray of the pencil exiting the eyepiece for an object point in the centre of the object plane

#### 3.3

#### convergence

describes the situation when the optical axis for the left and right optical systems meet at a position further away from the eye than the eyepiece

Note 1 to entry: Binocular tubes for compound microscopes usually have parallel optical axes for the left and right optical systems.

#### 3.4

#### imaging rotation

orientation of the image with respect to the optical axis as the axis of rotation

#### 3.5

#### relative brightness

brightness of the darker of the two optical systems divided by the brightness of the lighter of the two optical systems

Note 1 to entry: The requirement in <u>Table 3</u> shall be fulfilled for any state of polarization.

Note 2 to entry: It is expressed in percentage (%).

#### **4** Requirements

The requirements specified in <u>Tables 1</u>, <u>2</u>, and <u>3</u> are the minimum requirements for opto-mechanical and radiation specifications of binocular tubes.

Table 1 makes a distinction between tubes for general use and high-performance tubes.

NOTE Tubes for general use fulfil the basic criteria for microscopic applications. High-performance tubes provide increased viewing ergonomics when used over prolonged time periods.

The values shall be met by any individual tube which claims compliance with this International Standard.

For the specified minimum adjustment range for IPD, all requirements shall be met.

Tubes with dioptre adjustment shall meet the requirements in <u>Table 1</u>, <u>2</u>, and <u>3</u>.

Tubes without dioptre adjustment shall meet the requirements in <u>Table 1</u> and <u>Table 3</u>.

| Criterion   |                           |  | Requirement<br>for general<br>use                         | Requirement<br>for high<br>performance<br>tubes | Test<br>method           |  |
|---|---------------------------|--|---|---|--------------------------|--|
| Minimum adjustment range for IPD oh STAND                               |                           |  | A R 55mm to   | 75 mm   | <u>A.1</u>               |  |
| Indication error of IP  | D scale                   |  | ±1 mm   |   | <u>A.2</u>               |  |
| Difference in   | Vertical                  | ertical (standards.iteh. <u>a</u> i <sub>5</sub> ) | 5'  |   |                          |  |
| optical axis<br>between left and  |                           | Convergence  | ≤ 4   | 5'  | ISO 15227:2000,          |  |
| right optical<br>systems  | Horizo <b>ntal</b> ://sta | andards.iteh.ai/catalog/s<br>Divergence/0dfbed1    | tandards/sist/45c64b32<br>828/iso-1 <del>5</del> 095-2015 | -e84e-4b09-8fe2-<br>≤3'                         | 6.3.3.1                  |  |
| Difference in   | Vertical                  | 1  | ≤0,20   | mm  |                          |  |
| centres between   | IIt.a.t.a.l               | Convergence  | ≤0,40 mm  |   | <u>A.3</u>               |  |
| left and right image  | Horizontal                | Divergence   |   |   |                          |  |
| Difference in axial position between left and right image               |                           |  | ±0,3  | mm  | <u>A.4</u>               |  |
| Difference in imaging rotation between left and right image             |                           |  | ≤2  | 0   | ISO 15227:2000,<br>6.3.5 |  |
| Difference in exit pupil position between left and right optical system |                           |  | ≤1 n  | nm  | <u>A.5</u>               |  |

#### Table 1 — Opto-mechanical requirements

| Criterion  | Requirement                | Test method               |
|--|----------------------------|---------------------------|
| Minimum range of dioptre adjustment                              | -5 <i>D</i> to +5 <i>D</i> | ISO 15227:2000,<br>6.3.13 |
| Difference in axial position between left and right image at 0 D | ±0,5 mm                    | <u>A.6</u>                |

#### Table 2 — Additional opto-mechanical requirements for tubes with dioptre adjustment

#### Table 3 — Radiation requirements

| Criterion           | Requirement | Test method |
|---------------------|-------------|-------------|
| Relative brightness | ≥65 %       | <u>A.7</u>  |

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19055:2015 https://standards.iteh.ai/catalog/standards/sist/45c64b32-e84e-4b09-8fe2b70dfbed1828/iso-19055-2015

## Annex A

## (normative)

# Test methods for binocular tubes

## A.1 Minimum adjustment range for IPD

The IPD shall be measured as the distance of the centres of the exit pupils of the two eyepieces.

## A.2 Indication error of IPD scale

The indication error is the difference between the quantity measured in  $\underline{A.1}$  and the marked IPDs on the binocular tube.

## A.3 Difference in centres between left and right image

A reference eyepiece with crosshairs is inserted into the left eyepiece sleeve and a specimen with crosshairs is focused. The specimen is laterally adjusted so the crosshairs of the eyepiece and the specimen are aligned. **The STANDARD PREVIEW** 

The reference eyepiece is then inserted **sinto the right sleeve and the** distance between the eyepiece crosshairs and the specimen crosshairs in vertical and horizontal direction is measured.

#### ISO 19055:2015

#### A.4 Difference in axial position between left and right image 09-8fe2b70dfbed1828/iso-19055-2015

A focusable reference eyepiece set to its nominal focus position is inserted in the left eyepiece sleeve and a specimen is focused.

The reference eyepiece is then inserted into the right sleeve. The eyepiece is axially adjusted until the specimen is focused and the resulting axial adjustment is measured.

## A.5 Difference in exit pupil position between left and right optical system

The exit pupil position shall be measured perpendicular to the surface defined by the eyepiece location flange of the left optical system.

For tubes with dioptre adjustment, this quantity shall be measured at 0 D at the dioptre scale.

## A.6 Difference in axial position between left and right image at 0 D

The eyepiece sleeve with dioptre adjustment is set to 0 D and the same measurement as in <u>A.4</u> is performed.

## A.7 Relative brightness

The brightness shall be measured with a light source of type D65 located in the nominal entrance pupil of the tube. The light source shall be of circular shape and be at least 8 mm in diameter. The measurements shall be carried out in the exit pupils of the eyepieces.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19055:2015 https://standards.iteh.ai/catalog/standards/sist/45c64b32-e84e-4b09-8fe2b70dfbed1828/iso-19055-2015