



**Advanced Surface Movement Guidance and  
Control System (A-SMGCS);  
Part 5: Harmonised Standard for access to  
radio spectrum for Multilateration (MLAT) equipment;  
Sub-part 1: Receivers and Interrogators**

[ETSI EN 303 213-5-1 V2.1.1 \(2023-10\)](#)

<https://standards.iteh.ai/catalog/standards/sist/3f9506e8-5db5-4aab-824f-61090443c784/etsi-en-303-213-5-1-v2-1-1-2023-10>

---

Reference

REN/ERM-TGAERO-100

---

Keywordsaeronautical, harmonised standard,  
interoperability, radio**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:  
<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](https://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our  
<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.  
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.  
All rights reserved.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Modal verbs terminology.....	7
Introduction .....	7
1    Scope .....	8
2    References .....	8
2.1    Normative references .....	8
2.2    Informative references.....	8
3    Definition of terms, symbols and abbreviations.....	9
3.1    Terms.....	9
3.2    Symbols .....	10
3.3    Abbreviations .....	10
4    Technical requirements specifications .....	11
4.1    Environmental profile.....	11
4.2    Conformance Requirements .....	11
4.2.1    Applicability .....	11
4.2.1.1    Equipment with and without integral antenna.....	11
4.2.1.2    Equipment with multiple functions .....	11
4.2.2    Transmitter requirements .....	11
4.2.2.1    Operating frequency and frequency error .....	11
4.2.2.1.1    Definition.....	11
4.2.2.1.2    Limits .....	11
4.2.2.1.3    Conformance .....	11
4.2.2.2    Spectrum mask .....	11
4.2.2.2.1    Definition.....	11
4.2.2.2.2    Limits .....	12
4.2.2.2.3    Conformance .....	12
4.2.2.3    Residual Power Output .....	12
4.2.2.3.1    Definition.....	12
4.2.2.3.2    Limits .....	12
4.2.2.3.3    Conformance .....	13
4.2.2.4    Spurious emissions of transmitter in active mode.....	13
4.2.2.4.1    Definition.....	13
4.2.2.4.2    Limits .....	13
4.2.2.4.3    Conformance .....	13
4.2.2.5    Transmitter Intermodulation attenuation.....	13
4.2.2.5.1    Definition.....	13
4.2.2.5.2    Limits .....	13
4.2.2.5.3    Conformance .....	14
4.2.2.6    Transmitter time domain characteristics .....	14
4.2.2.6.1    Definition.....	14
4.2.2.6.2    Limits .....	14
4.2.2.6.3    Conformance .....	14
4.2.3    Receiver requirements .....	15
4.2.3.1    Sensitivity variation over the operating frequency range .....	15
4.2.3.1.1    Definition.....	15
4.2.3.1.2    Limits .....	15
4.2.3.1.3    Conformance .....	15
4.2.3.2    RF selectivity and spurious response rejection .....	15
4.2.3.2.1    Definition.....	15
4.2.3.2.2    Limits .....	15
4.2.3.2.3    Conformance .....	15
4.2.3.3    Inter-modulation response rejection.....	16
4.2.3.3.1    Definition.....	16

4.2.3.3.2	Limits .....	16
4.2.3.3.3	Conformance .....	16
4.2.3.4	Co-channel rejection .....	16
4.2.3.4.1	Definition.....	16
4.2.3.4.2	Limits .....	16
4.2.3.4.3	Conformance .....	16
4.2.3.5	Blocking.....	16
4.2.3.5.1	Definition.....	16
4.2.3.5.2	Limits .....	16
4.2.3.5.3	Conformance .....	16
4.2.3.6	Sensitivity .....	17
4.2.3.6.1	Definition.....	17
4.2.3.6.2	Limits .....	17
4.2.3.6.3	Conformance .....	17
4.2.3.7	Receiver spurious emissions .....	17
4.2.3.7.1	Definition.....	17
4.2.3.7.2	Limits .....	17
4.2.3.7.3	Conformance .....	17
4.2.3.8	Receiver dynamic range .....	17
4.2.3.8.1	Definition.....	17
4.2.3.8.2	Limits .....	17
4.2.3.8.3	Conformance .....	18
<b>5</b>	<b>Testing for compliance with technical requirements.....</b>	<b>18</b>
5.1	Environmental conditions for testing .....	18
5.1.1	General requirements .....	18
5.1.2	Test Conditions .....	18
5.1.2.1	Thermal Balance .....	18
5.1.2.2	Normal Test Conditions .....	18
5.1.2.2.1	Temperature and humidity.....	18
5.1.2.2.2	Power supply .....	18
5.1.2.3	Extreme Test Conditions.....	19
5.1.2.3.1	Temperature and humidity.....	19
5.1.2.3.2	Power supply .....	19
5.2	Test and General Conditions .....	19
5.2.1	Transmitter test signals .....	19
5.2.1.1	General Considerations .....	19
5.2.1.2	Test signal 1 .....	19
5.2.1.3	Test signal 2 .....	20
5.2.2	Simulated received signals.....	20
5.2.2.1	General Considerations .....	20
5.2.2.2	Test signal 3 .....	20
5.2.2.3	Test signal 4 .....	21
5.2.2.4	Test signal 5 .....	21
5.3	Transmitter tests .....	21
5.3.1	Operating frequency and frequency error .....	21
5.3.1.1	Description .....	21
5.3.1.2	Test conditions .....	21
5.3.1.3	Method of measurement.....	21
5.3.1.4	Measurement procedure .....	22
5.3.2	Spectrum mask.....	22
5.3.2.1	Description .....	22
5.3.2.2	Test conditions .....	22
5.3.2.3	Method of measurement.....	22
5.3.2.4	Measurement procedure .....	23
5.3.3	Residual Power Output .....	23
5.3.3.1	Description .....	23
5.3.3.2	Test conditions .....	23
5.3.3.3	Method of measurement.....	23
5.3.3.4	Measurement procedure .....	23
5.3.4	Spurious emissions of transmitter in active mode.....	24
5.3.4.1	Description .....	24

5.3.4.2	Test conditions .....	24
5.3.4.3	Method of measurement.....	24
5.3.4.4	Measurement Procedure.....	24
5.3.4.4.1	Part 1: Measurement of PEP and determination of spurious emission limit.....	24
5.3.4.4.2	Part 2: Spurious emission measurement procedure .....	25
5.3.5	Transmitter intermodulation attenuation.....	25
5.3.5.1	Description .....	25
5.3.5.2	Test Conditions .....	25
5.3.5.3	Method of Measurement .....	26
5.3.5.4	Measurement Procedure.....	26
5.3.6	Transmitter time domain characteristics .....	27
5.3.6.1	Description .....	27
5.3.6.2	Test Conditions .....	27
5.3.6.3	Method of measurement.....	27
5.3.6.4	Measurement procedure .....	27
5.4	Receiver Tests .....	28
5.4.1	Sensitivity and Sensitivity variation over the operating frequency range.....	28
5.4.1.1	Description .....	28
5.4.1.2	Test conditions .....	28
5.4.1.3	Method of measurement.....	28
5.4.1.4	Measurement procedure .....	28
5.4.2	RF selectivity and spurious response rejection .....	29
5.4.2.1	Description .....	29
5.4.2.2	Test conditions .....	29
5.4.2.3	Method of measurement.....	29
5.4.2.4	Measurement procedure .....	29
5.4.3	Inter-modulation response rejection .....	30
5.4.3.1	Description .....	30
5.4.3.2	Test conditions .....	30
5.4.3.3	Method of measurement.....	30
5.4.3.4	Measurement procedure .....	31
5.4.4	Co-channel rejection .....	31
5.4.4.1	Description .....	31
5.4.4.2	Test conditions .....	31
5.4.4.3	Method of measurement.....	31
5.4.4.4	Measurement procedure .....	32
5.4.5	Blocking.....	32
5.4.5.1	Description .....	32
5.4.5.2	Test conditions .....	32
5.4.5.3	Method of measurement.....	32
5.4.5.4	Measurement procedure .....	33
5.4.6	Receiver spurious emissions .....	33
5.4.6.1	Description .....	33
5.4.6.2	Test conditions .....	33
5.4.6.3	Method of measurement.....	33
5.4.6.4	Measurement Procedure.....	34
5.4.7	Receiver Dynamic Range .....	34
5.4.7.1	Description .....	34
5.4.7.2	Test Conditions .....	34
5.4.7.3	Method of measurement.....	34
5.4.7.4	Measurement procedure .....	35
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>36</b>
<b>Annex B (informative):</b>	<b>Maximum measurement uncertainty .....</b>	<b>38</b>
<b>Annex C (informative):</b>	<b>Checklist .....</b>	<b>39</b>
<b>Annex D (informative):</b>	<b>Bibliography .....</b>	<b>40</b>
<b>Annex E (informative):</b>	<b>Change history .....</b>	<b>41</b>
History .....	42	

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 5, sub-part 1, of a multi-part deliverable covering Advanced Surface Movement Guidance and Control System (A-SMGCS), as identified below.

- Part 1: "Community Specification for A-SMGCS surveillance service including external interfaces";
- Part 2: "Community Specification for A-SMGCS airport safety support service";
- Part 3: "Community Specification for a deployed cooperative sensor including its interfaces";
- Part 4: "Community Specification for a deployed non-cooperative sensor including its interfaces";

**Part 5: "Harmonised Standard for access to radio spectrum for Multilateration (MLAT) equipment":**

**Sub-part 1: "Receivers and Interrogators";**

Sub-part 2: "Reference and vehicle transmitters";

Part 6: "Harmonised Standard for access to radio spectrum for deployed surface movement radar sensors";

Part 7: "Community Specification for A-SMGCS routing service";

Part 8: "Community Specification for A-SMGCS guidance service".

<b>National transposition dates</b>	
Date of adoption of this EN:	3 October 2023
Date of latest announcement of this EN (doa):	31 January 2024
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2024
Date of withdrawal of any conflicting National Standard (dow):	31 July 2025

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are NOT allowed in ETSI deliverables except when used in direct citation.

## Introduction

A-SMGCS are systems providing routing, guidance, surveillance and control to aircraft and affected vehicles in order to maintain movement rate under all local weather conditions within the Aerodrome Visibility Operational Level (AVOL) whilst maintaining the required level of safety.

# 1 Scope

The present document specifies technical characteristics and methods of measurements for the following equipment:

- 1) Interrogators transmitting in the 1 030 MHz band, used in Mode S multilateration equipment in an Advanced Surface Movement Guidance and Control System (A-SMGCS).
- 2) Receivers, receiving in the 1 090 MHz band, used in Mode S multilateration equipment in an Advanced Surface Movement Guidance and Control System (A-SMGCS).

Antennas for this equipment are passive without an additional amplifier.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in Annex A.

# 2 References

## 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ICAO Annex 10, Volume IV](#): "Surveillance Radar and Collision Avoidance Systems", 5<sup>th</sup> edition, July 2014, including amendments up to amendment 91 dated 18-07-2022.
- [2] Void. 10
- [3] [ETSI EN 300 019-1-3 \(V2.4.1\) \(04-2014\)](#): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weatherprotected locations".
- [4] [ETSI EN 300 019-1-4 \(V2.2.1\) \(04-2014\)](#): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weatherprotected locations".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] [Directive 2014/53/EU](#) of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

- [i.2] ITU Radio Regulations (2020).
- [i.3] [Commission Implementing Decision C\(2015\) 5376 final of 4.8.2015](#) on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.4] [ECC/Recommendation \(02\)05 \(2012\)](#): "Unwanted emissions".
- [i.5] ETSI EG 203 336 (V1.2.1): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.6] [ERC/Recommendation 74-01 \(2019\)](#): "Unwanted emissions in the spurious domain".
- [i.7] EUROCAE ED-117A (September 2016): "MOPS for Mode S Multilateration Systems for Use in Advanced Surface Movement Guidance and Control Systems (A-SMGCS)".

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the following terms apply:

**conducted measurements:** measurements which are made using a wired connection to the EUT

**duty cycle:** ratio expressed as a percentage, of the cumulative duration of transmissions within an observation interval and the interval itself, as measured in an observation bandwidth

**equipment under test:** system of constituents provided by the manufacturer for qualification under the present document

**ground based multilateration equipment or ground station:** aeronautical station equipment intended for use in an A-SMGCS multilateration component

**interrogator:** aeronautical station equipment including at least one transmitter designed to produce aeronautical mobile service signals at 1 030 MHz

10

**Mode S:** particular type of uplink or downlink message defined in ICAO Annex 10, Volume IV [1]

**multilateration:** surveillance technique which provides position derived from the Secondary Surveillance Radar (SSR) transponder signals (replies or squitters) primarily using Time Difference Of Arrival (TDOA) techniques

NOTE: Additional information, including identification, can be extracted from the received signals.

**Operating Channel (OC):** frequency range in which the transmission from the EUT occurs, or in which the EUT is intended to receive transmissions

**operating frequency:** centre of the OC

**out of band emissions:** power transmitted at frequencies outside the OC but within the specified spectral mask

**probability of detection:** rate of correctly received and decoded squitter messages

**receiver:** EUT which includes the capability to convert RF signals into binary content

**resolution bandwidth:** bandwidth that is used for spectral measurements

**transmission:** radio emission consisting of one uplink or downlink Mode S message

**transmitter:** EUT which includes the capability to convert binary content into RF signals

**transponder:** aeronautical station equipment including at least one transmitter designed to produce aeronautical mobile radionavigation service signals at 1 090 MHz and zero or more receivers designed to receive aeronautical mobile radionavigation service signals at 1 030 MHz

**unwanted signal:** any signal other than the wanted signal or as described in a specific test case

**wanted signal:** in-band signal modulated according to the Mode specification

NOTE: Some manufacturers may also accept Mode 3A/C and other modulations which is beyond the scope of the present document.

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

dB	decibel
dBc	dB relative to carrier
dBm	power in dB relative to 1 milliwatt
dBpp	dB below PEP
f	measurement frequency
μs	Microsecond
Ω	Ohm

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
ADS-B	Automatic Dependant Surveillance Broadcast
A-SMGCS	Advanced Surface Movement Guidance and Control System
AVOL	Aerodrome Visibility Operational Level
CRC	Cyclic Redundancy Check
CW	Continuous Wave
DC	Direct Current
DF	Downlink Format
DME	Distance Measuring Equipment
EUT	Equipment Under Test
ICAO	International Civil Aviation Organization
MLAT	Multilateration
MOPS	Minimum Operational Performance Specification
NA	Not Applicable
NA	Not Applicable
OC	Operating Channel
OOB	Out Of Band
PD	Probability of Detection
PEP	Peak Envelope Power
RBW	Reference BandWidth
RF	Radio Frequency
RX	Receive
SSR	Secondary Surveillance Radar
TX	Transmit
VBW	Video BandWidth

## 4 Technical requirements specifications

### 4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be in accordance with its intended use but, as a minimum, shall be that specified in the test conditions contained in the present document. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the operational environmental profile defined by its intended use.

### 4.2 Conformance Requirements

#### 4.2.1 Applicability

##### 4.2.1.1 Equipment with and without integral antenna

For the purposes of conducted measurements on an EUT, a  $50 \Omega$  connection point shall be provided for test purposes.

For EUT with integral antenna, the connection point shall correspond to the input of the integral antenna.

##### 4.2.1.2 Equipment with multiple functions

Any ground station which includes the interrogator function shall comply with the requirements in clause 4.2.2.

Any ground station which includes the receiver function shall comply with the requirements in clause 4.2.3.

#### 4.2.2 Transmitter requirements

##### 4.2.2.1 Operating frequency and frequency error

###### 4.2.2.1.1 Definition

10

The operating frequency is the nominal value of the carrier frequency.

The frequency error is the difference between the actual carrier frequency and its nominal value of 1 030 MHz.

###### 4.2.2.1.2 Limits

The nominal value of carrier frequency of the interrogation and control transmissions shall be 1 030 MHz.

The absolute value of the frequency error shall not exceed 0,01 MHz.

NOTE: This limit is specified in ICAO Annex 10, Volume IV [1], clause 3.1.2.1.1 and is stricter than the requirement defined in the ITU Radio Regulations [1.2], Appendix 2.

###### 4.2.2.1.3 Conformance

The conformance tests for this requirement are defined in clause 5.3.1.

##### 4.2.2.2 Spectrum mask


###### 4.2.2.2.1 Definition

A spectrum mask is a set of limit lines applied to a plot of a transmitter spectrum.

The Out of Band domain extends to  $\pm 125$  MHz from the actual carrier frequency of 1 030 MHz. The frequencies outside the Out of Band domain are defined as the spurious domain.

#### 4.2.2.2.2 Limits

The measured spectrum shall be below the limit lines shown in Figure 1.



**Figure 1: Spectrum mask for an interrogator transmitter**

NOTE: The spectrum mask specified in ICAO Annex 10, Volume 4 [1], Figure 3-2 has been modified in order to be consistent with the ITU Radio Regulations [i.2], Appendix 3. The ICAO mask was extrapolated from the last three steps to determine when the mask would intercept the -60 dB point. A value of approximately 125 MHz was reached. 125 MHz is also the point reached when extrapolating the mask from the -40 dB (i.e. 40 MHz) by -40 dB per decade, which is the design objective for the 60 dB<sub>pp</sub> systems reflected in ECC/Recommendation (02)05 [i.4], Table 3 until the spurious limit is reached. This is also reflected in ECC/Recommendation (02)05 [i.4], Figure A2.1, item a), the Emission Mask for radars.

#### 4.2.2.2.3 Conformance

The conformance tests for this requirement are defined in clause 5.3.2.

#### 4.2.2.3 Residual Power Output

##### 4.2.2.3.1 Definition

The residual power output is the power output when not in the active state.

##### 4.2.2.3.2 Limits

The residual power output shall not exceed the limits specified in Table 1.