
**Rough-terrain trucks — Safety
requirements and verification —**

**Part 6:
Tilting operator's cabs**

Chariots tout-terrain — Exigences de sécurité et vérification —

Partie 6: Postes de l'opérateur/inclinables

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[ISO 10896-6:2015](https://standards.iteh.ai/catalog/standards/sist/3a5cd8fd-9114-43fb-a3d5-8afd7791996/iso-10896-6-2015)

<https://standards.iteh.ai/catalog/standards/sist/3a5cd8fd-9114-43fb-a3d5-8afd7791996/iso-10896-6-2015>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 10896-6:2015

<https://standards.iteh.ai/catalog/standards/sist/3a5cd8fd-9114-43fb-a3d5-8afd7791996/iso-10896-6-2015>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Safety requirements and/or protective measures	2
4.1 General	2
4.1.1 Access	2
4.1.2 Operator's seat	2
4.1.3 Tilting operator's cab	2
4.1.4 Travel restrictions	3
4.1.5 Maintenance	3
4.2 Tilting control	3
4.3 Stability	3
4.4 Crushing hazard	3
4.5 Roll over protective structure (ROPS) for tilting operator's cabs	3
4.6 Falling object protective structure (FOPS)	3
5 Verification of the safety requirements and/or protective measures	3
6 Information for use	4
Bibliography	5

iTech STANDARD PREVIEW
(standards.iteh.ai)

[ISO 10896-6:2015](https://standards.iteh.ai/catalog/standards/sist/3a5cd8fd-9114-43fb-a3d5-8af1d7791996/iso-10896-6-2015)

<https://standards.iteh.ai/catalog/standards/sist/3a5cd8fd-9114-43fb-a3d5-8af1d7791996/iso-10896-6-2015>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 110, *Industrial trucks*, Subcommittee SC 4, *Rough-terrain trucks*.

ISO 10896 consists of the following parts, under the general title *Rough-terrain trucks — Safety requirements and verification*:

- *Part 1: Variable-reach trucks*
- *Part 2: Slewing trucks*
- *Part 4: Additional requirements for variable reach trucks handling freely suspended loads*
- *Part 5: Interface between rough-terrain truck and integrated personnel work platform*
- *Part 6: Tilting operator's cabs*
- *Part 7: Longitudinal load moment systems*

Safety requirements and verification for lorry-mounted trucks are dealt with by ISO 20297-1.

Introduction

This part of ISO 10896 is one of a set of standards produced by ISO/TC 110/SC 4 as part of its program of work regarding standardization of terminology, general safety, performance and user requirements for rough-terrain trucks (hereafter also referred to as trucks).

This part of ISO 10896 is a type-C standard as stated in ISO 12100.

This part of ISO 10896 is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organizations, market surveillance, etc.).

Others can be affected by the level of machinery safety achieved with the means of this part of ISO 10896 by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e.g. for maintenance (small, medium and large enterprises);
- consumers (in the case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this part of ISO 10896:

The machinery and systems concerned and the extent to which hazards, hazardous situations or hazardous events are covered are indicated in the scope of this part of ISO 10896.

When requirements of this type-C standard are different from those which are stated in type-A or type-B standards, the requirements of this type-C standard take precedence over the requirements of the other standards for machines that have been designed and built according to the requirements of this type-C standard.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 10896-6:2015

<https://standards.iteh.ai/catalog/standards/sist/3a5cd8fd-9114-43fb-a3d5-8af1d7791996/iso-10896-6-2015>


Rough-terrain trucks — Safety requirements and verification —

Part 6: Tilting operator's cabs

1 Scope

This part of ISO 10896 specifies safety requirements and means of verification for tilting operator's cabs of trucks covered by ISO 10896-1 and ISO 10896-2, where the seat index point height (SIP) is lifted not more than 400 mm when the cab is fully tilted. See [Figure 1](#).

Dimension in millimetres



Key

- A SIP in tilted position
- B SIP in non-tilted position

Figure 1 — Tilting operator's cab

This part of ISO 10896 only deals with significant hazards, hazardous situations or hazardous events relevant to the tilting cab affixed to trucks.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3449, *Earth-moving machinery — Falling-object protective structures — Laboratory tests and performance requirements*

ISO 3471:2008, *Earth-moving machinery — Roll-over protective structures — Laboratory tests and performance requirements*

ISO 5053, *Powered industrial trucks — Terminology*

ISO 10896-1:2012, *Rough-terrain trucks — Safety requirements and verification — Part 1: Variable-reach trucks*

ISO 10896-2:—¹⁾, *Rough-terrain trucks, safety requirements and verification — Part 2: Slewing variable-reach trucks*

ISO 12100, *Safety of machinery — General principles for design — Risk assessment and risk reduction*

ISO 22915-14, *Industrial trucks — Verification of stability — Part 14: Rough-terrain variable-reach trucks*

ISO 22915-24, *Industrial trucks — Verification of stability — Part 24: Slewing variable-reach rough-terrain trucks*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5053, ISO 10896-1, ISO 10896-2 and the following apply.

3.1

tilting operator's cab

operator station where the seat index point (SIP) height can be lifted vertically 400 mm or less when the cab is fully tilted, intended to provide the operator with increased visibility during operation, but can also be used for cab or truck maintenance

Note 1 to entry: For the definition of seat index point (SIP), see ISO 5353:1995, 3.1.

iteh STANDARD PREVIEW

4 Safety requirements and/or protective measures

4.1 General

ISO 10896-6:2015

<https://standards.iteh.ai/catalog/standards/sist/3a5cd8fd-9114-43fb-a3d5->

Tilting operator's cabs shall comply with the safety requirements and/or protective/risk reduction measures of this clause. In addition, the tilting operator's cab shall be designed according to the principles of ISO 12100 for relevant but not significant hazards which are not dealt with by this part of ISO 10896.

4.1.1 Access

With the tilting operator's cab in the lowest position, the access to the normal operating position shall comply with the following:

- ISO 10896-1:2012, 4.11 for variable reach trucks;
- ISO 10896-2:—, 4.11 for slewing trucks.

4.1.2 Operator's seat

The seat shall be designed to maintain the operator in the tilted position.

4.1.3 Tilting operator's cab

The maximum tilting angle should not exceed 20° from the horizontal axis of the truck chassis.

The tilting speed shall not exceed 5°/s under normal working conditions.

Means shall be provided to prevent uncontrolled movement in case of hydraulic line rupture or interruption of the power supply.

1) To be published.

4.1.4 Travel restrictions

Provisions shall be made to prevent travel of the truck when the tilting operator's cab is not in the travel position as defined by the manufacturer.

4.1.5 Maintenance

If service or maintenance operation has to be done with a tilting operator's cab in the tilted position, the tilting operator's cab support device complying with ISO 10896-1:2012, 4.8.2 or ISO 10896-2:—, 4.8.2 shall be fitted to the truck. The support device shall withstand a force of twice the mass ($\times g$) of the tilting operator's cab.

4.2 Tilting control

The tilting control shall be clearly marked, separated from the other controls and protected against inadvertent activation. It shall be of a hold to run type.

4.3 Stability

The stability tests as given in ISO 22915-14 or ISO 22915-24 (except tests T2 and T4) shall be performed with the tilting operator's cab in the most unfavourable tilted positions.

4.4 Crushing hazard

The hazardous area between the truck main frame and the bottom of the tilting operator's cab shall be marked with warning signs.

4.5 Roll over protective structure (ROPS) for tilting operator's cabs

ROPS shall comply with ISO 3471 with the following specifications:

- the operator's station shall be regarded as a separate independent ROPS (ROPS not connected to the machine frame);
- only vertical load test of ISO 3471:2008, 6.3, shall be applied in all planes of the cab (i.e. lateral, vertical and longitudinal);
- ISO 3471:2008, 8 h) does not apply.

The test shall be carried out with the tilting operator's cab in the lowest position.

4.6 Falling object protective structure (FOPS)

FOPS shall comply with ISO 3449. The tests shall be carried out with the tilting operator's cab in lower position, and in maximum tilting position.

5 Verification of the safety requirements and/or protective measures

Methods of testing of safety requirements stated in [Clause 4](#) are either one or a combination of the following:

- measurement;
- visual examination;
- testing means only referred to in [4.5](#).