
Nespremenljivi kondenzatorji za elektronsko opremo - 24. del: Področna specifikacija - Nespremenljivi tantalovi elektrolitski kondenzatorji s prevodnim polimernim trdim elektrolitom za površinsko montažo (IEC 60384-24:2015/COR1:2016) - Popravek AC

Fixed capacitors for use in electronic equipment - Part 24: Sectional specification - Fixed tantalum electrolytic surface mount capacitors with conductive polymer solid electrolyte (IEC 60384-24:2015/COR1:2016)

iTeh STANDARD PREVIEW

Festkondensatoren zur Verwendung in Geräten der Elektronik - Teil 24: Rahmenspezifikation - Oberflächenmontierbare Tantal-Elektrolyt-Kondensatoren mit leitfähigem Polymerfestkörper-Elektrolyten

<https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7cfb/sist-en-60384-24-2015-ac-2017>

Condensateurs fixes utilisés dans les équipements électroniques - Partie 24: Spécification intermédiaire – Condensateurs fixes électrolytiques au tantale pour montage en surface à électrolyte solide en polymère conducteur (IEC 60384-24:2015/COR1:2016)

Ta slovenski standard je istoveten z: EN 60384-24:2015/AC:2017-01

ICS:

31.060.40	Tantalski elektrolitni kondenzatorji	Tantalum electrolytic capacitors
-----------	--------------------------------------	----------------------------------

SIST EN 60384-24:2015/AC:2017 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 60384-24:2015/AC:2017](https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7cfb/sist-en-60384-24-2015-ac-2017)

<https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7cfb/sist-en-60384-24-2015-ac-2017>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

**EN 60384-24:2015/AC:2017-
01**

January 2017

ICS 31.060.40; 31.060.50

English Version

**Fixed capacitors for use in electronic equipment - Part 24:
Sectional specification - Fixed tantalum electrolytic surface
mount capacitors with conductive polymer solid electrolyte
(IEC 60384-24:2015/COR1:2016)**

Condensateurs fixes utilisés dans les équipements
électroniques - Partie 24: Spécification intermédiaire -
Condensateurs fixes électrolytiques au tantale pour
montage en surface à électrolyte solide en polymère
conducteur
(IEC 60384-24:2015/COR1:2016)

Festkondensatoren zur Verwendung in Geräten der
Elektronik -Teil 24: Rahmenspezifikation -
Oberflächenmontierbare Tantal-Elektrolyt-Kondensatoren
mit leitfähigem Polymerfestkörper-Elektrolyten
(IEC 60384-24:2015/COR1:2016)

This corrigendum becomes effective on 20 January 2017 for incorporation in the English language version of the EN.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 60384-24:2015/AC:2017](https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7cfb/sist-en-60384-24-2015-ac-2017)

<https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7cfb/sist-en-60384-24-2015-ac-2017>



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Endorsement notice

The text of the corrigendum IEC 60384-24:2015/COR1:2016 was approved by CENELEC as EN 60384-24:2015/AC:2017-01 without any modification.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 60384-24:2015/AC:2017](https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7cfb/sist-en-60384-24-2015-ac-2017)

<https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7cfb/sist-en-60384-24-2015-ac-2017>

INTERNATIONAL ELECTROTECHNICAL COMMISSION
COMMISSION ÉLECTROTECHNIQUE INTERNATIONALEIEC 60384-24
Edition 2.0 2015-07IEC 60384-24
Édition 2.0 2015-07FIXED CAPACITORS FOR USE IN ELECTRONIC
EQUIPMENTCONDENSATEURS FIXES UTILISÉS DANS LES
EQUIPEMENTS ELECTRONIQUESPart 24: Sectional specification – Fixed tantalum
electrolytic surface mount capacitors with
conductive polymer solid electrolytePartie 24: Spécification intermédiaire –
Condensateurs fixes électrolytiques au tantale
pour montage en surface à électrolyte solide en
polymère conducteur

CORRIGENDUM 1

Corrections to the French version appear after the English text.

Les corrections à la version française sont données après le texte anglais.

[SIST EN 60384-24:2015/AC:2017](https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7c7b/sist-en-60384-24-2015-ac-2017)[https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-](https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7c7b/sist-en-60384-24-2015-ac-2017)[bb2c42ed7c7b/sist-en-60384-24-2015-ac-2017](https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7c7b/sist-en-60384-24-2015-ac-2017)**Table 3 – Sampling plan for qualification approval, assessment level EZ**

Replace with the following new Table 3:

Group no.	Test	Subclause	Number of specimens n^d	Permissible number of non-conforming items c
0	High surge current ^c	4.18	120+12 ^f	0
	Visual examination	4.4		
	Dimensions	4.4		
	Leakage current	4.5.1		
	Capacitance	4.5.2		
	Tangent of loss angle	4.5.3		
	Equivalent series resistance ^c	4.5.4		
	Spare specimens			
1A	Resistance to soldering heat	4.6	12	0
	Component solvent resistance ^c	4.16		
1B	Solderability	4.7	12	0
	Solvent resistance of marking ^c	4.17		
2	Substrate bending test ^e	4.9	12	0
3 ^a	Mounting	4.3	84	0 ^b
	Visual examination	4.4.2		

		Leakage current	4.5.1		
		Capacitance	4.5.2		
		Tangent of loss angle	4.5.3		
		Equivalent series resistance ^c	4.5.4		
	3.1	Shear test	4.8	12	0
		Rapid change of temperature	4.10		
		Climatic sequence	4.11		
	3.2	Damp heat, steady state	4.12	12	0
	3.3	Characteristics at high and low temperature	4.13	12	0
		Surge voltage	4.14		
	3.4	Endurance	4.15	36	0
	3.5	Storage at high temperature	4.19	12	0

a The values of these inspections serve as initial inspections for the tests of Group 3.

b The capacitors found non-conforming after mounting shall not be taken into account when calculating the non-conforming items for the following tests. They shall be replaced by spare capacitors.

c If required.

d For case size/voltage combinations, see 3.4.2.

e Not applicable to capacitors, which shall be mounted on alumina substrates only, according to their detail specification.

f Spare specimens.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Table 4 – Test schedule for qualification approval

Replace the row concerning **GROUP 3** with the following new row:

GROUP 3	D		See Table 3	
4.3 Mounting		See 4.3.3		
4.3.2 Initial inspections				
Capacitance		See 4.5.2.2		
4.3.4 Final inspections				
Visual examination		See 4.4.2		No visible damage
Leakage current		See 4.5.1.2		See detail specification
Capacitance		See 4.5.2.2		$ \Delta C/C < 8\%$ of value measured in 4.3.2
Tangent of loss angle		See 4.5.3.2		See detail specification
Equivalent series resistance ^e		See 4.5.4.2		See detail specification

4.3 Mounting

Replace with this new subclause 4.3:

4.3 Mounting

4.3.1 General

See IEC 60384-1:2008, 4.33, with the details in 4.3.2, 4.3.3 and 4.3.4.

IEC 60384-24:2015/COR1:2016

– 3 –

© IEC 2016

4.3.2 Initial inspections

See Table 4.

4.3.3 Test conditions

The test method shall be the reflow method and reflow temperature profile specified in the detail specification.

4.3.4 Final inspections and requirements

See Table 4.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 60384-24:2015/AC:2017](https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7cfb/sist-en-60384-24-2015-ac-2017)

<https://standards.iteh.ai/catalog/standards/sist/27558fd3-b88a-4abe-b4ad-bb2c42ed7cfb/sist-en-60384-24-2015-ac-2017>