



**Digital cellular telecommunications system (Phase 2+) (GSM);  
Universal Mobile Telecommunications System (UMTS);  
LTE;  
5G;  
NR, E-UTRA, UTRA and GSM/EDGE;  
Multi-Standard Radio (MSR) Base Station (BS)  
conformance testing  
(3GPP TS 37.141 version 14.14.0 Release 14)**



---

**Reference**RTS/TSGR-0437141vee0

---

**Keywords**5G,GSM,LTE,UMTS

---

**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

---

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx><https://standards.iteh.ai/catalog/standards/sist/fa179fc6-5656-4ec0-b011-702203>**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Legal Notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope .....	12
2 References .....	12
3 Definitions, symbols and abbreviations .....	13
3.1 Definitions .....	13
3.2 Symbols.....	16
3.3 Abbreviations .....	18
4 General test conditions and declarations .....	20
4.1 Measurement uncertainties and test requirements .....	20
4.1.1 General.....	20
4.1.2 Acceptable uncertainty of Test System.....	20
4.1.2.1 Measurement of transmitter .....	21
4.1.2.2 Measurement of receiver .....	22
4.1.3 Interpretation of measurement results .....	24
4.2 Base Station classes.....	25
4.3 Regional requirements.....	25
4.4 Operating bands and band categories .....	27
4.4.1 Band category 1 aspects (BC1).....	30
4.4.2 Band category 2 aspects (BC2).....	31
4.4.3 Band category 3 aspects (BC3).....	31
4.5 Channel arrangement.....	31
4.5.1 Channel spacing.....	31
4.5.1A CA Channel spacing .....	32
4.5.2 Channel raster .....	32
4.5.3 Carrier frequencies and numbering.....	32
4.6 Manufacturer's declarations of regional and optional requirements .....	32
4.6.1 Operating band and frequency range .....	32
4.6.2 Spurious emissions category.....	33
4.6.3 Additional operating band unwanted emissions .....	33
4.6.4 Co-existence with other systems.....	33
4.6.5 Co-location with other Base Stations.....	34
4.6.6 NB-IoT sub-carrier spacing .....	34
4.6.7 NB-IoT power dynamic range .....	34
4.7 Capability set definition and manufacturer's declarations of supported RF configurations .....	34
4.7.1 Definition of Capability Sets (CS).....	34
4.7.2 Manufacturer's declarations of supported RF configurations .....	37
4.8 MSR test configurations .....	40
4.8.1 TC1: UTRA multicarrier operation .....	40
4.8.1.1 TC1a generation.....	40
4.8.1.2 TC1b generation.....	40
4.8.1.3 TC1 power allocation.....	40
4.8.1a NTC1: UTRA multicarrier non-contiguous operation .....	40
4.8.1a.1 NTC1a generation.....	41
4.8.1a.2 NTC1 power allocation .....	41
4.8.2 TC2: E-UTRA multicarrier operation.....	41
4.8.2.1 TC2 generation.....	41
4.8.2.2 TC2 power allocation.....	41
4.8.2a NTC2: E-UTRA multicarrier non-contiguous operation .....	41
4.8.2a.1 NTC2 generation.....	42
4.8.2a.2 NTC2 power allocation.....	42
4.8.3 TC3: UTRA and E-UTRA multi RAT operation.....	42

4.8.3.1	TC3a generation.....	42
4.8.3.2	TC3b generation.....	43
4.8.3.3	TC3 power allocation.....	43
4.8.3a	NTC3: UTRA and E-UTRA multi RAT non-contiguous operation.....	43
4.8.3a.1	NTC3a generation.....	43
4.8.3a.2	NTC3 power allocation.....	44
4.8.4	TC4: BC2 transmitter operation.....	44
4.8.4.1	TC4a generation.....	44
4.8.4.2	TC4b generation.....	44
4.8.4.3	TC4c generation.....	45
4.8.4.4	TC4d generation.....	45
4.8.4.5	TC4e generation.....	45
4.8.4.6	TC4 power allocation.....	46
4.8.4a	NTC4: Non-contiguous multi RAT operations with GSM for the transmitter.....	46
4.8.4a.1	NTC4a generation.....	46
4.8.4a.2	NTC4b generation.....	47
4.8.4a.3	NTC4c generation.....	47
4.8.4a.4	NTC4 power allocation.....	48
4.8.5	TC5: BC2 receiver operation.....	48
4.8.5.1	TC5a generation.....	48
4.8.5.2	TC5b generation.....	49
4.8.5a	NTC5: Non-contiguous multi RAT operations with GSM for the receiver.....	49
4.8.5a.1	NTC5a generation.....	49
4.8.5a.2	NTC5b generation.....	49
4.8.5a.3	NTC5c generation.....	49
4.8.6	TC6: Single carrier for receiver tests.....	50
4.8.6.1	TC6a generation.....	50
4.8.6.2	TC6b generation.....	50
4.8.6.3	TC6c generation.....	50
4.8.7	Generation of MB-MSR test configurations.....	50
4.8.7.1	TC7a: MB-MSR test configuration for full carrier allocation.....	50
4.8.7.1.1	TC7a generation.....	50
4.8.7.1.2	TC7a power allocation.....	51
4.8.7.2	TC7b: MB-MSR test configuration with high PSD per carrier.....	51
4.8.7.2.1	TC7b generation.....	51
4.8.7.2.2	TC7b power allocation.....	52
4.8.7.3	TC7c: MB-MSR test configuration with GSM/EDGE single RAT operation in one band.....	52
4.8.7.3.1	TC7c generation.....	52
4.8.7.3.2	TC7c power allocation.....	53
4.8.8	TC8: NB-IoT standalone multi-carrier operation.....	53
4.8.8.1	TC8 generation.....	53
4.8.8.2	TC8 power allocation.....	53
4.8.9	TC9: GSM and NB-IoT standalone multi-carrier operation.....	53
4.8.9.1	TC9 generation.....	54
4.8.9.2	TC9 power allocation.....	54
4.8.10	TC10: UTRA and NB-IoT standalone multi-carrier operation.....	54
4.8.10.1	TC10 generation.....	54
4.8.10.2	TC10 power allocation.....	54
4.8.11	TC11: E-UTRA and NB-IoT standalone multi-carrier operation.....	54
4.8.11.1	TC11 generation.....	55
4.8.11.2	TC11 power allocation.....	55
4.8.12	TC12: GSM and UTRA and NB-IoT standalone multi-carrier operation.....	55
4.8.12.1	TC12 generation.....	55
4.8.12.2	TC12 power allocation.....	56
4.8.13	TC13: GSM and E-UTRA and NB-IoT standalone multi-carrier operation.....	56
4.8.13.1	TC13 generation.....	56
4.8.13.2	TC13 power allocation.....	56
4.8.14	TC14: UTRA and E-UTRA and NB-IoT standalone multi-carrier operation.....	56
4.8.14.1	TC14 generation.....	56
4.8.14.2	TC14 power allocation.....	57
4.8.15	TC15: GSM and E-UTRA with NB-IoT in-band multi-carrier operation.....	57
4.8.15.1	TC15 generation.....	57

4.8.15.2	TC15 power allocation .....	57
4.8.16	TC16: UTRA and E-UTRA with NB-IoT in-band multi-carrier operation .....	57
4.8.16.1	TC16 generation.....	57
4.8.16.2	TC16 power allocation.....	58
4.8.17	TC17: E-UTRA and E-UTRA with NB-IoT in-band multi-carrier operation .....	58
4.8.17.1	TC17 generation.....	58
4.8.17.2	TC17 power allocation.....	58
4.8.18	TC18: GSM and E-UTRA with NB-IoT guard-band multi-carrier operation .....	58
4.8.18.1	TC18 generation.....	58
4.8.18.2	TC18 power allocation.....	59
4.8.19	TC19: UTRA and E-UTRA with NB-IoT guard-band multi-carrier operation .....	59
4.8.19.1	TC19 generation.....	59
4.8.19.2	TC19 power allocation.....	59
4.8.20	TC20: E-UTRA and E-UTRA with NB-IoT guard-band multi-carrier operation .....	59
4.8.20.1	TC20 generation.....	59
4.8.20.2	TC20 power allocation.....	60
4.9	RF channels and test models .....	60
4.9.1	RF channels .....	60
4.9.2	Test models .....	61
4.10	BS configurations .....	62
4.10.1	Transmit configurations .....	62
4.10.1.1	Transmission with multiple transmitter antenna connectors .....	62
4.10.2	Receive configurations .....	62
4.10.2.1	Reception with multiple receiver antenna connectors, receiver diversity .....	62
4.10.3	Duplexers.....	63
4.10.4	Power supply options.....	63
4.10.5	Ancillary RF amplifiers .....	63
4.10.6	BS with integrated Iuant BS modem .....	64
4.10.7	BS using antenna arrays.....	64
4.10.7.1	Receiver tests .....	64
4.10.7.2	Transmitter tests.....	65
4.11	Format and interpretation of tests.....	65
4.12	Requirements for BS capable of multi-band operation .....	66
4.13	Tests for BS capable of multi-band operation with three or more bands .....	66
5	Applicability of requirements and test configurations .....	67
5.1	Multi-RAT capable Base Stations .....	69
5.2	Single-RAT Multi-carrier capable Base Stations .....	86
5.3	Multi-band capable Base Stations .....	95
6	Transmitter characteristics .....	98
6.1	General .....	98
6.2	Base Station output power.....	98
6.2.1	Base Station maximum output power .....	98
6.2.1.1	Definition and applicability.....	98
6.2.1.2	Minimum requirement .....	98
6.2.1.3	Test purpose .....	99
6.2.1.4	Method of test .....	99
6.2.1.4.1	Initial conditions .....	99
6.2.1.4.2	Procedure.....	99
6.2.1.5	Test requirements .....	99
6.2.2	E-UTRA DL RS power.....	99
6.2.2.1	Definition and applicability.....	99
6.2.2.2	Minimum requirement .....	100
6.2.2.3	Test purpose .....	100
6.2.2.4	Method of test .....	100
6.2.2.5	Test requirements.....	100
6.2.3	UTRA FDD primary CPICH power .....	100
6.2.3.1	Definition and applicability.....	100
6.2.3.2	Minimum requirement .....	100
6.2.3.3	Test purpose .....	100
6.2.3.4	Method of test .....	100

6.2.3.5	Test requirements .....	100
6.2.3A	UTRA FDD secondary CPICH power.....	101
6.2.3A.1	Definition and applicability.....	101
6.2.3A.2	Minimum requirement .....	101
6.2.3A.3	Test purpose .....	101
6.2.3A.4	Method of test .....	101
6.2.3A.5	Test requirements.....	101
6.2.4	UTRA TDD primary CCPCH power.....	101
6.2.4.1	Definition and applicability.....	101
6.2.4.2	Minimum requirement .....	101
6.2.4.3	Test purpose .....	101
6.2.4.4	Method of test .....	101
6.2.4.5	Test requirements.....	102
6.2.5	NB-IoT DL NRS power.....	102
6.2.5.1	Definition and applicability.....	102
6.2.5.2	Minimum requirement .....	102
6.2.5.3	Test purpose .....	102
6.2.5.4	Method of test .....	102
6.2.5.5	Test requirements.....	102
6.3	Output power dynamics.....	102
6.3.1	Definition and applicability .....	102
6.3.2	Minimum Requirement.....	102
6.3.3	Test purpose.....	102
6.3.4	Method of test .....	103
6.3.4.1	Initial conditions for GSM/EDGE output power dynamics for CS7 .....	103
6.3.4.2	Procedure for GSM/EDGE output power dynamics .....	103
6.3.5	Test Requirement.....	103
6.4	Transmit ON/OFF power .....	103
6.4.1	Definition and applicability .....	104
6.4.2	Minimum Requirement.....	104
6.4.3	Test purpose.....	104
6.4.4	Method of test .....	104
6.4.4.1	Initial conditions .....	104
6.4.4.2	Procedure .....	104
6.4.5	Test requirement .....	105
6.5	Transmitted signal quality .....	105
6.5.1	Modulation quality.....	105
6.5.1.1	Definition and applicability.....	105
6.5.1.2	Minimum Requirement .....	105
6.5.1.3	Test purpose .....	105
6.5.1.4	Method of test .....	105
6.5.1.4.1	Initial conditions .....	105
6.5.1.4.2	Procedure.....	105
6.5.1.5	Test Requirements.....	106
6.5.1.5.1	E-UTRA test requirement.....	106
6.5.1.5.2	UTRA FDD test requirement .....	106
6.5.1.5.3	UTRA TDD test requirement .....	106
6.5.1.5.4	GSM/EDGE test requirement.....	106
6.5.1.5.5	NB-IoT test requirement.....	106
6.5.2	Frequency error.....	106
6.5.2.1	Definition and applicability.....	106
6.5.2.2	Minimum Requirement .....	107
6.5.2.3	Test purpose .....	107
6.5.2.4	Method of test .....	107
6.5.2.5	Test Requirements.....	107
6.5.2.5.1	E-UTRA test requirement.....	107
6.5.2.5.2	UTRA FDD test requirement .....	107
6.5.2.5.3	UTRA TDD test requirement .....	107
6.5.2.5.4	GSM/EDGE test requirement.....	107
6.5.2.5.5	NB-IoT test requirement.....	107
6.5.3	Time alignment error .....	107
6.5.3.1	Definition and applicability.....	107

6.5.3.2	Minimum requirement .....	107
6.5.3.3	Test purpose .....	108
6.5.3.4	Method of test .....	108
6.5.3.5	Test requirement .....	108
6.6	Unwanted emissions.....	108
6.6.1	Transmitter spurious emissions.....	108
6.6.1.1	Definition and applicability.....	108
6.6.1.2	Minimum requirement .....	109
6.6.1.3	Test purpose .....	109
6.6.1.4	Method of test .....	109
6.6.1.4.1	Initial conditions.....	109
6.6.1.4.2	Procedure.....	109
6.6.1.5	Test requirements.....	109
6.6.1.5.1	Spurious emissions (Category A).....	110
6.6.1.5.2	Spurious emissions (Category B).....	110
6.6.1.5.3	Additional test requirement for BC2 (category B).....	110
6.6.1.5.4	Protection of the BS receiver of own or different BS.....	111
6.6.1.5.5	Additional spurious emission requirements.....	111
6.6.1.5.6	Co-location with other Base Stations .....	119
6.6.2	Operating band unwanted emissions .....	124
6.6.2.1	Definition and applicability.....	124
6.6.2.2	Minimum requirement .....	124
6.6.2.3	Test purpose .....	124
6.6.2.4	Method of test .....	124
6.6.2.4.1	Initial conditions.....	124
6.6.2.4.2	Procedure.....	125
6.6.2.5	Test requirement .....	125
6.6.2.5.1	Test requirements for Band Categories 1 and 3.....	125
6.6.2.5.2	Test requirements for Band Category 2.....	131
6.6.2.5.3	Test requirements for GSM/EDGE single-RAT requirements.....	136
6.6.2.5.4	Test requirements for additional requirements .....	137
6.6.2.5.4.1	Limits in FCC Title 47.....	137
6.6.2.5.4.2	Unsynchronized operation for BC3.....	137
6.6.2.5.4.3	Protection of DTT.....	137
6.6.2.5.4.4	Co-existence with services in adjacent frequency bands.....	137
6.6.2.5.4.7	Additional requirements for band 48.....	139
6.6.3	Occupied bandwidth .....	139
6.6.3.1	Definition and applicability.....	139
6.6.3.2	Minimum requirements.....	139
6.6.3.3	Test purpose .....	139
6.6.3.4	Method of test .....	139
6.6.3.5	Test requirement .....	140
6.6.4	Adjacent Channel Leakage power Ratio (ACLR) .....	140
6.6.4.1	Definition and applicability.....	140
6.6.4.2	Minimum requirement .....	140
6.6.4.3	Test purpose .....	140
6.6.4.4	Method of test .....	140
6.6.4.4.1	Initial conditions.....	140
6.6.4.4.2	Procedure.....	141
6.6.4.5	Test requirements.....	141
6.6.4.5.1	E-UTRA test requirement.....	141
6.6.4.5.2	UTRA FDD test requirement .....	143
6.6.4.5.3	UTRA TDD test requirement .....	143
6.6.4.5.4	Cumulative ACLR requirement in non-contiguous spectrum .....	143
6.6.4.5.5	NB-IoT test requirement.....	144
6.7	Transmitter intermodulation.....	145
6.7.1	Definition and applicability .....	145
6.7.2	Minimum requirement .....	145
6.7.2A	Additional requirement for Band 41 .....	145
6.7.3	Test purpose.....	145
6.7.4	Method of test.....	145
6.7.4.1	Initial conditions .....	145

6.7.4.2	Procedure .....	145
6.7.4.2.1	General minimum requirement test procedure .....	145
6.7.4.2.2	Additional minimum requirement (BC1 and BC2) test procedure .....	146
6.7.4.2.3	Additional minimum requirement (BC3) test procedure .....	147
6.7.5	Test requirements.....	148
6.7.5.1	General test requirement .....	148
6.7.5.2	Additional test requirement (BC1 and BC2).....	148
6.7.5.3	Additional test requirement (BC3).....	148
6.7.5.4	Additional test requirement for Band 41 .....	149
7	Receiver characteristics.....	149
7.1	General .....	149
7.2	Reference sensitivity level.....	149
7.2.1	Definition and applicability .....	149
7.2.2	Minimum requirement .....	149
7.2.3	Test purpose.....	149
7.2.4	Method of test .....	149
7.2.4.1	Initial conditions for GSM/EDGE reference sensitivity level for CS7 and CS15.....	150
7.2.4.2	Procedure for GSM/EDGE reference sensitivity level for CS7 and CS15.....	150
7.2.5	Test requirements.....	150
7.3	Dynamic range .....	150
7.3.1	Definition and applicability .....	150
7.3.2	Minimum requirement .....	150
7.3.3	Test purpose.....	150
7.3.4	Method of test .....	151
7.3.4.1	Initial conditions for GSM/EDGE dynamic range for CS7 and CS15 .....	151
7.3.4.2	Procedure for GSM/EDGE dynamic range for CS7 and CS15 .....	151
7.3.5	Test requirements.....	151
7.4	In-band selectivity and blocking .....	152
7.4.1	Definition and applicability .....	152
7.4.2	Minimum requirement .....	152
7.4.3	Test purpose.....	152
7.4.4	Method of test .....	152
7.4.4.1	Initial conditions .....	152
7.4.4.2	Procedure for general blocking .....	152
7.4.4.3	Procedure for narrowband blocking .....	153
7.4.4.4	Procedure for additional narrowband blocking for GSM/EDGE .....	153
7.4.4.4.1	Initial conditions for additional narrowband blocking for GSM/EDGE for CS7 and CS15.....	153
7.4.4.4.2	Procedure for additional narrowband blocking for GSM/EDGE for CS7 and CS15.....	153
7.4.4.5	Procedure for GSM/EDGE AM suppression .....	154
7.4.4.5.1	Initial conditions for GSM/EDGE AM suppression for CS7 and CS15.....	154
7.4.4.5.2	Procedure for GSM/EDGE AM suppression for CS7 and CS15.....	154
7.4.4.6	Procedure for additional BC3 blocking requirement.....	154
7.4.5	Test requirements.....	155
7.4.5.1	General blocking test requirement .....	155
7.4.5.2	General narrowband blocking test requirement .....	156
7.4.5.3	Additional narrowband blocking test requirement for GSM/EDGE .....	158
7.4.5.4	GSM/EDGE test requirements for AM suppression .....	158
7.4.5.5	Additional BC3 blocking test requirement.....	158
7.5	Out-of-band blocking .....	159
7.5.1	Definition and applicability .....	159
7.5.2	Minimum requirement .....	159
7.5.3	Test purpose.....	159
7.5.4	Method of test .....	159
7.5.4.1	Initial conditions .....	159
7.5.4.2	Procedure .....	160
7.5.5	Test requirements.....	160
7.5.5.1	General out-of-band blocking test requirements .....	160
7.5.5.2	Co-location test requirements.....	161
7.6	Receiver spurious emissions.....	165
7.6.1	Definition and applicability .....	165
7.6.2	Minimum requirements.....	165

7.6.3	Test purpose.....	165
7.6.4	Method of test.....	165
7.6.4.1	Initial conditions.....	165
7.6.4.2	Procedure.....	166
7.6.5	Test requirements.....	166
7.6.5.1	General test requirements.....	166
7.6.5.2	Additional test requirement for BC2 (Category B).....	166
7.7	Receiver intermodulation.....	167
7.7.1	Definition and applicability.....	167
7.7.2	Minimum requirement.....	167
7.7.3	Test purpose.....	167
7.7.4	Method of test.....	167
7.7.4.1	Initial conditions.....	167
7.7.4.2	Procedure for general and narrowband intermodulation.....	168
7.7.4.3	Procedure for additional narrowband intermodulation for GSM/EDGE.....	168
7.7.4.3.1	Initial conditions for additional narrowband intermodulation for GSM/EDGE for CS7 and CS15.....	168
7.7.4.3.2	Procedure for additional narrowband intermodulation for GSM/EDGE for CS7 and CS15.....	168
7.7.5	Test requirements.....	169
7.7.5.1	General intermodulation test requirement.....	169
7.7.5.2	General narrowband intermodulation test requirement.....	170
7.7.5.3	Additional narrowband intermodulation test requirement for GSM/EDGE.....	172
7.8	In-channel selectivity.....	173
7.8.1	Definition and applicability.....	173
7.8.2	Minimum requirement.....	173
7.8.3	Test purpose.....	173
7.8.4	Method of testing.....	173
7.8.5	Test requirements.....	173
8	Performance requirements.....	173
<b>Annex A (normative): Characteristics of interfering signals.....</b>		<b>174</b>
A.1	UTRA FDD interfering signal.....	174
A.2	UTRA TDD interfering signal.....	174
A.3	E-UTRA interfering signal.....	174
<b>Annex B (normative): Environmental requirements for the BS equipment.....</b>		<b>175</b>
B.1	General.....	175
B.2	Normal test environment.....	175
B.3	Extreme test environment.....	175
B.3.1	Extreme temperature.....	175
B.4	Vibration.....	176
B.5	Power supply.....	176
B.6	Measurement of test environments.....	176
<b>Annex C (informative): Test Tolerances and Derivation of test requirements.....</b>		<b>177</b>
C.1	Measurement of transmitter.....	178
C.2	Measurement of receiver.....	182
<b>Annex D (informative): Measurement system set-up.....</b>		<b>185</b>
D.1	Transmitter.....	185
D.1.1	Base station output power, transmitter ON/OFF power, modulation quality, transmitter spurious emissions and operating band unwanted emissions.....	185
D.1.2	Transmitter intermodulation.....	185

D.2	Receiver.....	186
D.2.1	Blocking characteristics .....	186
D.2.2	Receiver spurious emissions.....	186
D.2.3	Receiver intermodulation .....	186
<b>Annex E (normative):</b>	<b>E-UTRA Test model for BC3 CS3 BS.....</b>	<b>187</b>
E.0	BC3 CS3 Test model description .....	187
E.1	E-UTRA Test Model 1.1 (E-TM1.1_BC3CS3) .....	188
E.2	E-UTRA Test Model 1.2 (E-TM1.2_BC3CS3) .....	188
E.3	E-UTRA Test Model 2 (E-TM2_BC3CS3) .....	188
E.4	E-UTRA Test Model 3.1 (E-TM3.1_BC3CS3) .....	188
E.5	E-UTRA Test Model 3.2 (E-TM3.2_BC3CS3) .....	188
E.6	E-UTRA Test Model 3.3 (E-TM3.3_BC3CS3) .....	188
<b>Annex F (informative):</b>	<b>Change history .....</b>	<b>189</b>
History .....		196

**iTeh STANDARD  
PREVIEW  
(standards.iteh.ai)**

[ETSI TS 137 141 V14.14.0 \(2022-03\)](https://standards.iteh.ai/catalog/standards/sist/fa179fc6-5656-4edc-afbc-a4f4de494c4f/etsi-ts-137-141-v14-14-0-2022-03)  
<https://standards.iteh.ai/catalog/standards/sist/fa179fc6-5656-4edc-afbc-a4f4de494c4f/etsi-ts-137-141-v14-14-0-2022-03>

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ETSI TS 137 141 V14.14.0 \(2022-03\)](https://standards.iteh.ai/catalog/standards/sist/fa179fc6-5656-4edc-afbc-a4f4de494c4f/etsi-ts-137-141-v14-14-0-2022-03)  
<https://standards.iteh.ai/catalog/standards/sist/fa179fc6-5656-4edc-afbc-a4f4de494c4f/etsi-ts-137-141-v14-14-0-2022-03>



- [19] ETSI EN 300 019-1-3, *European Standard (Telecommunications series)*, "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weather protected locations"
- [20] ETSI EN 300 019-1-4, *European Standard (Telecommunications series)*, "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weather protected locations".
- [21] IEC 60068-2-1 (2007): "Environmental testing - Part 2: Tests. Tests A: Cold".
- [22] IEC 60068-2-2 (2007): "Environmental testing - Part 2: Tests. Tests B: Dry heat".
- [23] IEC 60068-2-6 (2007): "Environmental testing - Part 2: Tests - Test Fc: Vibration (sinusoidal)".
- [24] CEPT ECC Decision (13)03, "The harmonised use of the frequency band 1452-1492 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

**Band category:** group of operating bands for which the same MSR scenarios apply.

**Base Station RF Bandwidth:** RF bandwidth in which a base station transmits and/or receives single or multiple carrier(s) and/or RATs simultaneously within a supported operating band.

NOTE: In single carrier operation, the Base Station RF Bandwidth is equal to the channel bandwidth.

**Base Station RF Bandwidth edge:** frequency of one of the edges of the Base Station RF Bandwidth.

**Carrier:** modulated waveform conveying the E-UTRA, UTRA or GSM/EDGE physical channels.

**Carrier aggregation:** aggregation of two or more E-UTRA component carriers in order to support wider transmission bandwidths.

**Carrier aggregation band:** set of one or more operating bands across which multiple E-UTRA carriers are aggregated with a specific set of technical requirements.

NOTE: Carrier aggregation band(s) for an E-UTRA BS is declared by the manufacturer according to the designations in Tables 5.5-2 to 5.5-4 of TS 36.104 [5].

**Channel bandwidth:** RF bandwidth supporting a single E-UTRA, UTRA or GSM/EDGE RF carrier with the transmission bandwidth configured in the uplink or downlink of a cell.

NOTE: The channel bandwidth is measured in MHz and is used as a reference for transmitter and receiver RF requirements.

**Contiguous carriers:** set of two or more carriers configured in a spectrum block where there are no RF requirements based on co-existence for un-coordinated operation within the spectrum block.

**Carrier power:** power at the antenna connector in the channel bandwidth of the carrier averaged over at least one subframe for E-UTRA, at least one slot for UTRA and the useful part of the burst for GSM/EDGE.

**Contiguous spectrum:** spectrum consisting of a contiguous block of spectrum with no sub-block gap(s).

**Downlink operating band:** part of the operating band designated for downlink.

**Highest Carrier:** carrier with the highest carrier centre frequency transmitted/received in the specified operating band(s).

**Inter RF Bandwidth gap:** frequency gap between two consecutive Base Station RF Bandwidths that are placed within two supported operating bands.

**Inter-band carrier aggregation:** carrier aggregation of E-UTRA component carriers in different operating bands.

NOTE: Carriers aggregated in each band can be contiguous or non-contiguous.

**Inter-band gap:** The frequency gap between two supported consecutive operating bands.

**Intra-band contiguous carrier aggregation:** contiguous E-UTRA carriers aggregated in the same operating band.

**Intra-band non-contiguous carrier aggregation:** non-contiguous E-UTRA carriers aggregated in the same operating band.

**Lowest Carrier:** carrier with the lowest carrier centre frequency transmitted/received in the specified operating band(s).

**Lower Base Station RF Bandwidth edge:** frequency of the lower Base Station RF Bandwidth edge, used as a frequency reference point for transmitter and receiver requirements.

**Lower sub-block edge:** frequency at the lower edge of one sub-block.

NOTE: It is used as a frequency reference point for both transmitter and receiver requirements.

**Maximum Base Station RF Bandwidth:** maximum RF bandwidth supported by a BS within each supported operating band.

NOTE: The maximum Base Station RF Bandwidth for BS configured for contiguous and non-contiguous operation within each supported operating band is declared separately.

**Maximum carrier output power:** carrier power available at the antenna connector for a specified reference condition.

**Maximum Radio Bandwidth:** maximum frequency difference between the upper edge of the highest used carrier and the lower edge of the lowest used carrier.

**Maximum RAT output power:** sum of the power of all carriers of the same RAT available at the antenna connector for a specified reference condition.

**Maximum throughput:** maximum achievable throughput for a reference measurement channel.

**Maximum total output power:** sum of the power of all carriers available at the antenna connector for a specified reference condition.

**MB-MSR Base Station:** MSR base station characterized by the ability of its transmitter and/or receiver to process two or more carriers in common active RF components simultaneously, where at least one carrier is configured at a different operating band (which is not a sub-band or superseding-band of another supported operating band) than the other carrier(s).

**Mean power:** power measured in the bandwidth and period of measurement applicable for each RAT

NOTE: Mean power for an E-UTRA carrier is defined in TS 36.141 [9] and mean power for a UTRA carrier is defined in TS 25.141 [10]. In case of multiple carriers, the mean power is the sum of the mean power of all carriers.

**Measurement bandwidth:** RF bandwidth in which an emission level is specified.

**MSR Base Station:** base station characterized by the ability of its receiver and transmitter to process two or more carriers in common active RF components simultaneously in a declared Base Station RF Bandwidth, where at least one carrier is of a different RAT than the other carrier(s).

**Multi-band transmitter:** transmitter characterized by the ability to process two or more carriers in common active RF components simultaneously, where at least one carrier is configured at a different operating band (which is not a sub-band or superseding-band of another supported operating band) than the other carrier(s).