



ISO/IEC 14543-5-102

Edition 1.0 2020-02

INTERNATIONAL STANDARD



**Information technology – Home electronic system (hes) architecture –
Part 5-102: Intelligent grouping and resource sharing for HES Class 2 and
Class 3 – Remote universal management profile**

ISO/IEC 14543-5-102:2020

<https://standards.iteh.ai/catalog/standards/sist/a365a095-684f-472c-8799-217bc1a0476e/iso-iec-14543-5-102-2020>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and definitions clause of IEC publications issued between 2002 and 2015. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

[ISO/IEC 14543-5-102:2020](https://standards.iteh.ai/catalog/standards/sist/a365a095-684f-472c-8799-217bc1a0476e/iso-iec-14543-5-102-2020)

<https://standards.iteh.ai/catalog/standards/sist/a365a095-684f-472c-8799-217bc1a0476e/iso-iec-14543-5-102-2020>



ISO/IEC 14543-5-102

Edition 1.0 2020-02

INTERNATIONAL STANDARD



**Information technology – Home electronic system (hes) architecture –
Part 5-102: Intelligent grouping and resource sharing for HES Class 2 and
Class 3 – Remote universal management profile**

ISO/IEC 14543-5-102:2020

<https://standards.iteh.ai/catalog/standards/sist/a365a095-684f-472c-8799-217bc1a0476e/iso-iec-14543-5-102-2020>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.020

ISBN 978-2-8322-7521-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	5
1 Scope.....	7
2 Normative references	7
3 Terms, definitions and abbreviated terms	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	10
4 Conformance.....	10
5 IGRS RUMP overview.....	10
6 IGRS RA and RUMP system architecture and message exchange model overview	11
6.1 IGRS RA system structure	11
6.2 RUMP protocol layer hierarchy.....	12
6.3 Server types	13
6.3.1 IGRS RA message exchange model in the IRSP.....	13
6.3.2 Account server	14
6.3.3 Message server	14
6.3.4 Application server.....	15
6.3.5 IRSP external application server.....	15
6.4 Message exchange between user or controlled device and message server.....	15
6.4.1 Device registration management.....	15
6.4.2 User/controller ↔ controlled device message exchange that needs response (control message).....	16
6.4.3 Controlled device ↔ user/controller message exchange that does not need response (status update).....	17
6.4.4 Controlled device ↔ user/controller message exchange that does not need response (alarm message).....	18
6.4.5 Controlled device ↔ user/controller message exchange that that needs response (firmware version query).....	18
6.5 Workflow.....	19
6.5.1 LAN control	19
6.5.2 WAN control	20
7 RUMP.....	21
7.1 Protocol overview	21
7.2 Applications	21
7.3 Logical components	21
7.4 Device ID.....	21
7.5 RUMP message format	22
7.6 RUMP response and status message format.....	23
7.7 RUMP water heater.....	23
7.7.1 Water heater control message format	23
7.7.2 Water heater response and status message format	24
7.7.3 Water heater alarm message format	25
7.8 RUMP air conditioner.....	26
7.8.1 Air conditioner control message format.....	26
7.8.2 Air conditioner response and status message format	27
7.8.3 Air conditioner alarm message format.....	27
7.9 RUMP refrigerator.....	28

7.9.1	Refrigerator control message format	28
7.9.2	Refrigerator response and status message format	29
7.9.3	Refrigerator alarm message format	29
7.10	RUMP microwave oven	30
7.10.1	Microwave oven control message format	30
7.10.2	Microwave oven response and status message format	31
7.10.3	Microwave oven alarm message format	31
7.11	Device status query message	32
7.12	Device version query message	32
	Bibliography	34
	Figure 1 – IGRS RA system structure	11
	Figure 2 – RUMP protocol layer	12
	Figure 3 – RUMP message interaction flow	13
	Figure 4 – Message exchange models in IGRS RA system	14
	Figure 5 – Flow of message exchange between user/controller and controlled device that needs response	16
	Figure 6 – Flow of message exchange between controlled device and user/controller that does not need response	17
	Figure 7 – LAN control flow diagram	20
	Figure 8 – Controller–IRSP–device WAN interaction process	21
	Table 1 – Device ID definitions	22
	Table 2 – RUMP message format	22
	Table 3 – RUMP message identifier	23
	Table 4 – Control message body	23
	Table 5 – Water heater control message format	24
	Table 6 – Water heater response and status message format	25
	Table 7 – Water heater alarm message format	26
	Table 8 – Air conditioner control message format	26
	Table 9 – Air conditioner response and status message format	27
	Table 10 – Air conditioner alarm message format	28
	Table 11 – Refrigerator control message format	28
	Table 12 – Refrigerator response and status information format	29
	Table 13 – Refrigerator alarm message format	30
	Table 14 – Microwave oven control message format	30
	Table 15 – Microwave oven response and status message format	31
	Table 16 – Microwave oven alarm message format	32
	Table 17 – Device status query request message format	32
	Table 18 – Device version query request message format	32
	Table 19 – Device version query response message format	33

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE – Part 5-102: Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Remote universal management profile

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14543-5-102 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 14543 series, under the general title *Information technology – Home electronic system (HES) architecture*, can be found on the IEC website and ISO website.

The text of this standard is based on the following documents:

FDIS	Report on voting
JTC1-SC25/2898/FDIS	JTC1-SC25/2908/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

ISO/IEC 14543-5 (all parts) specifies the services and protocol of the application layer for intelligent grouping and resource sharing (IGRS) devices and services in the home electronic system. Some parts reference Classes 1, 2 and 3, which are HES designations specified in the HES architecture standard, ISO/IEC 14543-2-1.

ISO/IEC 14543-5 (all parts) includes the following parts.

- ISO/IEC 14543-5-1: Core protocol
 - Specifies the TCP/IP protocol stack as the basis and the HTTP protocol as the message-exchange framework among devices.
 - Specifies a series of device and service interaction/invocation standards, including device and service discovery protocol, device and service description, service invocation, security mechanisms, etc.
 - Specifies core protocols for a type of home network that supports streaming media and other high-speed data transports within a home.
- ISO/IEC 14543-5-2#: Application profile
 - Based on the IGRS core protocol.
 - Specifies a device and service interaction mechanism, as well as application interfaces used in IGRS basic applications.
 - Multiple application profiles are specified, including:
 - i) ISO/IEC 14543-5-21: AV profile
 - ii) ISO/IEC 14543-5-22: File profile
- ISO/IEC 14543-5-3: Basic application
 - Includes an IGRS basic application list.
 - Specifies a basic application framework.
 - Specifies operation details (device grouping, service description template, etc.), function definitions and service invocation interfaces.
- ISO/IEC 14543-5-4: Device validation
 - Defines a standard method to validate an IGRS-compliant device.
- ISO/IEC 14543-5-5: Device type
 - Specifies IGRS device types used in IGRS applications.
- ISO/IEC 14543-5-6: Service type
 - Specifies basic service types used in IGRS applications.
- ISO/IEC 14543-5-7: Remote access system architecture
 - Specifies the architecture and framework for the remote access of IGRS devices and services in the home electronic system. The remote access communications protocol and application profiles are specified in the following parts of ISO/IEC 14543-5:
 - i) ISO/IEC 14543-5-8: Remote access core protocol
 - ii) ISO/IEC 14543-5-9: Remote access service platform
 - iii) ISO/IEC 14543-5-101: Remote media access profile
 - iv) ISO/IEC 14543-5-102: Remote universal management profile
 - v) ISO/IEC 14543-5-11: Remote user interface
 - vi) ISO/IEC 14543-5-12: Remote access test and verification
 - The relationships among these parts are specified in Part 5-7.

- ISO/IEC 14543-5-8: Remote access core protocol
 - Provides detailed system components, system function modules, basic concepts of IGRS remote access elements and their relationships, message exchange mechanisms and security related specifications.
 - Specifies interfaces between IGRS remote access (RA) client and service platforms. Defines co-operative procedures among IGRS RA clients.
- ISO/IEC 14543-5-9: Remote access service platform
 - Specifies the IGRS RA service platform (IRSP) architectures and interfaces among servers in the service platforms.
 - Based on ISO/IEC 14543-5-8: Remote access core protocol.
- ISO/IEC 14543-5-101 and ISO/IEC 14543-5-102: Remote access application profiles
 - Defines a device and service interaction mechanism for various applications.
 - Based on ISO/IEC 14543-5-8: Remote access core protocol.
 - Two profiles have been developed:
 - i) ISO/IEC 14543-5-101: Remote media access profile. This part defines the common requirements for IGRS RA media users and devices in IGRS networks.
 - ii) ISO/IEC 14543-5-102: Remote universal management profile. This part specifies a mechanism for integrating devices with both relatively high and low processing capabilities into IGRS networks. It also specifies universal remote device discovery and a management framework.
 - Additional application profiles will be specified in the future.
- ISO/IEC 14543-5-11: Remote user interface
 - Specifies adaptive user interface generation and remote device control mechanisms suitable for different remote access applications and devices.
- ISO/IEC 14543-5-12: Remote access test and verification
 - Defines a standard method to test and verify IGRS-RA compliant device and service interfaces.

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE –

Part 5-102: Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Remote universal management profile

1 Scope

This part of ISO/IEC 14543 specifies the system architecture and communication protocols of remote universal management profile to achieve intelligent grouping, resource sharing and service collaboration among different devices and controllers. The protocol features are:

- a) remote universal device discovery and management framework that includes connection methods and network architecture, device configuration interfaces, management message formats and message exchange flows;
- b) request/response message formats for four remote universal management profile device types: water heater, refrigerator, air conditioner, microwave.

This document is applicable to remote access of water heaters, refrigerators, air conditioners, microwave ovens at home, office or other remote environments, to achieve universal management and interactions among these controllers and devices.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 14543-5-1, *Information technology – Home electronic system (HES) architecture – Part 5-1: Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Core protocol*

ISO/IEC 14543-5-7, *Information technology – Home electronic system (HES) architecture – Part 5-7: Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Remote access system architecture*

ISO/IEC 14543-5-8, *Information technology – Home electronic system (HES) architecture – Part 5-8: Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Remote access core protocol*

ISO/IEC 14543-5-9, *Information technology – Home electronic system (HES) architecture – Part 5-9: Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Remote access service platform*

ISO/IEC 15045 (all parts), *Information technology – Home electronic system (HES) gateway*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1.1

account server

IGRS RA server that processes services related to user and device account information

3.1.2

application server

IGRS RA server or third-party server located outside of an IGRS RA system that processes application service-related logical functions

Note 1 to entry: The application server provides the approach to access application service logical functions (also called logics). By using the application server, IGRS RA user or device or other server can access the application service logics.

3.1.3

controlled device **device**

physical device that is accessible to the controller

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14543-5-102:2020](https://standards.iteh.ai/catalog/standards/sist/a365a095-684f-472c-8799-217bc1a0476e/iso-iec-14543-5-102-2020)

3.1.4

controller

physical device that can access a controlled device in the IGRS RA system

<https://standards.iteh.ai/catalog/standards/sist/a365a095-684f-472c-8799-217bc1a0476e/iso-iec-14543-5-102-2020>

Note 1 to entry: Controller is typically a mobile device or application such as a smart phone or smart pad, which is handled by an IGRS RA user.

3.1.5

device ID

unique identification of an IGRS RA device

EXAMPLE If the local part of a device ID is “#igrsdevice” and the domain name part of the user ID is “igrs.com”, the device ID is “#igrsdevice@igrs.com”.

Note 1 to entry: A device ID consists of a local part and a domain name part. A “@” is used to separate the two parts. Each device ID starts with a “#”.

3.1.6

device verification code

string used to examine if the user has the authority to bind a device

Note 1 to entry: For a device without a user interface, the device verification code is used to bind a device to a user. The device owner guarantees the safety of the device verification code.

3.1.7

IGRS AS

basic service unit composed of one or multiple IGRS servers

Note 1 to entry: Each IGRS AS provides services for a dedicated user and/or device group and constructs an IGRS RA domain. This document defines all of the necessary requirements that allow different IGRS ASs to exchange messages with each other.

© ISO/IEC 2020

3.1.8**IGRS RA agent**

functional entity which can provide the IGRS RA service to IGRS LAN devices

Note 1 to entry: The main functionalities of the IGRS RA agent are sending instructions to and receiving instructions from the IGRS RA service platform, and translating the instructions of local IGRS networks to and from those of the IGRS RA networks. The IGRS RA agent provides compatibility of the local IGRS devices to the IGRS RA devices.

3.1.9**IGRS RA device**

physical device that is accessible to the IGRS RA user in the IGRS RA system

3.1.10**IGRS RA server**

instantiation of a service provider that may be included in an IRSP

Note 1 to entry: An IGRS RA server is deployed on the internet. It maintains relationships among IGRS RA user and IGRS devices. It also provides re-transmission of collaborative messages. The IGRS RA user and IGRS device can start a data connection to the IRSP and support interconnections using the data connection and re-transmission functions of the IRSP.

3.1.11**IGRS RA service platform****IRSP**

collection of multiple IGRS RA servers that are deployed on the internet to maintain the relationships among IGRS RA user and IGRS RA device and to exchange collaborative messages

Note 1 to entry: IGRS RA user and device can establish connections to the IRSP, can send collaborative messages over these connections and can exchange messages in the servers of the IRSP.

3.1.12**IGRS RA user**

entity that uses the IGRS RA devices and application services

Note 1 to entry: Generally, an IGRS RA user is a human being. Each IGRS RA user has a unique user ID (identification). A bundle relationship can be established between one IGRS RA user and another. A binding relationship can be established between one IGRS RA user and one IGRS device.

3.1.13**message server**

IGRS RA server that processes message exchanging logics (transmitting, receiving, forwarding and blocking, etc.)

3.1.14**server address**

ID to identify the network location of a server in IGRS RA system

EXAMPLE One IGRS RA server address could be: "www.igrslab.com:8080".

Note 1 to entry: Server address format in IGRS RA system is "domain name of server:port".

3.2 Abbreviated terms

AS	autonomous system
HTTP	hypertext transfer protocol
ID	identification
IGRS	intelligent grouping and resource sharing
IRSP	IGRS RA service platform
LAN	local area network
RA	remote access
RUMP	remote universal management profile
TCP/IP	transmission control protocol/ internet protocol
UI	user interface
XMPP	extensible messaging and presence protocol
WAN	wide area network

4 Conformance

A system that conforms to this document shall be implemented according to Clauses 5 through 7, where the IGRS remote access capabilities including system architecture, message exchange mechanism and work flow shall conform to Clause 6, and the RUMP application protocol for specific device types shall conform to Clause 7.

5 IGRS RUMP overview

[ISO/IEC 14543-5-102:2020](https://standards.iteh.ai/catalog/standards/sist/a365a095-684f-472c-8799-877b6b145f0e/iec-14543-5-102-2020)

[https://standards.iteh.ai/catalog/standards/sist/a365a095-684f-472c-8799-](https://standards.iteh.ai/catalog/standards/sist/a365a095-684f-472c-8799-877b6b145f0e/iec-14543-5-102-2020)

RUMP (remote universal management profile) protocol provides specific IGRS remote access application scenarios based on the remote management of all devices at home, office and other remote locations, which is applicable to not only devices with strong processing capability such as TV, PC, set-top box, etc., but also devices with weak processing capability such as refrigerator, microwave oven, washing machine, dishwasher, etc.

RUMP defines the configuration and interface of IP and non-IP devices, the overall system architecture of comprehensive remote control and management of a variety of home devices. It also defines the communication interface, message flow and message format for universal management of devices, as well as the type of connection and network structure between non-IP devices and IP devices.

RUMP offers an efficient solution for IP or non-IP devices to access IGRS network, as it resolves the requirements of defining common system structure, port, message format and message flow to enable remote access of different RUMP devices (with strong or weak processing capabilities).

The specific protocol contents are as follows.

a) Remote universal device discovery and management framework:

- connection methods and network architecture;
- device configuration interfaces;
- management message formats;
- message exchange flows.