

**SLOVENSKI STANDARD**  
**oSIST prEN ISO 15118-2:2018**

**01-november-2018**

---

**Cestna vozila - Komunikacijski vmesnik med vozilom in omrežjem - 2. del: Zahteve za protokol omrežja in uporabe (ISO/DIS 15118-2:2018)**

Road vehicles - Vehicle to grid communication interface - Part 2: Network and application protocol requirements (ISO/DIS 15118-2:2018)

Straßenfahrzeuge - Kommunikationsschnittstelle zwischen Fahrzeug und Ladestation - Teil 2: Anforderungen an das Netzwerk- und Anwendungsprotokoll (ISO/DIS 15118-2:2018)

**ITEN STANDARD PREVIEW**

**(standards.iteh.ai)**

Véhicules routiers - Interface de communication entre véhicule et réseau électrique - Partie 2 : Exigences du protocole d'application et du réseau (ISO/DIS 15118-2:2018)  
<https://standards.iteh.ai/iteng-standard/standards/sist-pr-en-iso-15118-2-2018-ed18e05e7161/osit-pren-iso-15118-2-2018>

**Ta slovenski standard je istoveten z:** **prEN ISO 15118-2**

---

**ICS:**

35.100.05	Večslojne uporabniške rešitve	Multilayer applications
43.040.15	Avtomobilska informatika. Vgrajeni računalniški sistemi	Car informatics. On board computer systems

**oSIST prEN ISO 15118-2:2018** **en,fr,de**

## iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 15118-2:2018  
<https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d-ed18e05e7161/osist-pren-iso-15118-2-2018>

# DRAFT INTERNATIONAL STANDARD

## ISO/DIS 15118-2

ISO/TC 22/SC 31

Secretariat: DIN

Voting begins on:  
2018-09-10Voting terminates on:  
2018-12-03

## Road vehicles — Vehicle to grid communication interface —

### Part 2: Network and application protocol requirements

*Véhicules routiers — Interface de communication entre véhicule et réseau électrique —  
Partie 2: Exigences du protocole d'application et du réseau*

ICS: 43.120

### iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 15118-2:2018](https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d-ed18e05e7161/osist-pren-iso-15118-2-2018)  
<https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d-ed18e05e7161/osist-pren-iso-15118-2-2018>

Member bodies are requested to consult relevant national interests in IEC/TC 69 before casting their ballot to the e-Ballotting application.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

### ISO/CEN PARALLEL PROCESSING



Reference number  
ISO/DIS 15118-2:2018(E)

© ISO 2018

**ISO/DIS 15118-2:2018(E)**

**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

[oSIST prEN ISO 15118-2:2018](#)  
<https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d-ed18e05e7161/osist-pr-en-15118-2-2018>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

Page

1	Scope .....	9
2	Normative references .....	9
3	Terms and definitions .....	12
4	Symbols and abbreviated terms .....	16
5	Conventions .....	18
5.1	Definition of OSI based services .....	18
5.2	Requirement structure .....	18
5.3	Usage of RFC references .....	19
5.4	Notation used for XML schema diagrams .....	19
6	Document overview .....	19
7	Basic requirements for V2G communication .....	21
7.1	General information .....	21
7.2	Service primitive concept of OSI layered architecture .....	21
7.2.1	Overview .....	21
7.2.2	Syntax of service primitives .....	21
7.3	Security concept .....	22
7.3.1	General .....	22
7.3.2	Certificate and key management .....	26
7.3.3	Number of root certificates and root validity, certificate depth and size .....	28
7.3.4	Support and application of TLS .....	29
7.3.5	Firewall .....	30
7.4	V2G communication states and data link handling .....	31
7.5	Data link layer ( <a href="https://standards.ieee.org/catalog/standards/sist/1dfe34f459e-4038-9c8d-ed18e05e7161/osiit-pren-iso-15118-2-2018">https://standards.ieee.org/catalog/standards/sist/1dfe34f459e-4038-9c8d-ed18e05e7161/osiit-pren-iso-15118-2-2018</a> ) .....	37
7.6	Network layer .....	37
7.6.1	General .....	37
7.6.2	Applicable RFCs and limitations and protocol parameter settings .....	37
7.6.3	IP addressing .....	39
7.7	Transport layer .....	39
7.7.1	Transmission control protocol (TCP) .....	39
7.7.2	User datagram protocol (UDP) .....	40
7.7.3	Transport layer security (TLS) .....	40
7.8	V2G transfer protocol .....	44
7.8.1	General information .....	44
7.8.2	Supported ports .....	44
7.8.3	Protocol data unit .....	45
7.9	Presentation layer .....	49
7.9.1	XML and efficient XML interchange (EXI) .....	49
7.9.2	Message security .....	51
7.10	Application layer .....	58
7.10.1	SECC discovery protocol .....	58
7.10.2	Vehicle to grid application layer messages .....	65
7.10.3	Application layer service primitives .....	66
8	Application layer messages .....	69
8.1	General information and definitions .....	69
8.2	Protocol handshake definition .....	70
8.2.1	Handshake sequence .....	70
8.2.2	Message definition supportedAppProtocolReq and supportedAppProtocolRes .....	71
8.2.3	Semantics description supportedAppProtocol messages .....	71
8.2.4	Message examples .....	74
8.3	V2G message definition .....	75

8.3.1	Overview .....	75
8.3.2	Message definition .....	75
8.3.3	Message header definition.....	77
8.3.4	Message body definition.....	80
8.3.5	V2G request definition .....	81
8.3.6	V2G response definition .....	81
8.4	V2G communication session and body element definitions .....	81
8.4.1	General.....	81
8.4.2	Session handling .....	83
8.4.3	Common messages.....	89
8.4.4	AC messages .....	138
8.4.5	DC messages .....	143
8.4.6	WPT messages .....	154
8.4.7	ACD messages.....	181
8.4.8	BPT messages .....	193
8.5	Complex data types.....	205
8.5.1	Overview .....	205
8.5.2	Common .....	205
8.5.3	AC .....	262
8.5.4	DC .....	270
8.5.5	WPT .....	281
8.5.6	BPT .....	320
8.5.7	ACD .....	347
8.6	Service and message set selection .....	348
8.6.1	General.....	348
8.6.2	Selection of service and service parameters.....	349
8.6.3	Selection of message sets.....	361
8.6.4	Supported messages and parameters of message sets .....	365
8.7	V2G communication timing .....	368
8.7.1	Overview .....	368
8.7.2	Message sequence and communication session .....	370
8.7.3	Session setup and ready to charge .....	376
8.7.4	V2G message synchronization with IEC 61851-1 signalling .....	381
8.7.5	V2G message synchronization with IEC 61980-2 signalling .....	387
8.8	Message sequencing and error handling.....	388
8.8.1	Overview .....	388
8.8.2	Basic Definitions for Error Handling .....	388
8.8.3	ResponseCode handling.....	389
8.8.4	Request-response message sequence requirements .....	393
8.9	request-response message sequence examples .....	445
8.9.1	AC .....	445
8.9.2	DC .....	448
8.9.3	WPT .....	453
8.9.4	ACD .....	457
8.9.5	BPT .....	461
	Annex A (normative) Schema definition .....	470
A.1	Overview .....	470
A.2	V2G_CI_AppProtocol.xsd .....	471
A.3	V2G_CI_MsgDef.xsd .....	472
A.4	V2G_CI_MsgHeader.xsd .....	472
A.5	V2G_CI_MsgBody.xsd .....	472
A.6	V2G_CI_MsgDataTypes.xsd .....	484
A.7	xmldsig-core-schema.xsd.....	504
	Annex B (normative) Certificate profiles .....	508
	Annex C (normative) Specification of identifiers .....	516
C.1	e-Mobility Authentication Identifier (EMAID) .....	516
C.1.1	EMAID Syntax .....	516
C.1.2	EMAID Semantics .....	517

C.1.3	Calculation of the check digit .....	517
C.1.4	Usage of country codes.....	517
C.1.5	PCID structure .....	517
C.1.6	SECCID structure .....	518
C.2	Electric Vehicle Supply Equipment ID (EVSEID).....	518
C.2.1	EVSEID Syntax.....	518
C.2.2	EVSEID Semantics .....	519
C.2.3	Usage of country codes.....	520
Annex D (informative)	Message sequencing for renegotiation .....	521
D.1	Overview.....	521
D.2	Renegotiation after resuming a V2G communication session .....	523
Annex E (informative)	Overview on XML signatures.....	525
E.1	Overview.....	525
E.2	Signature generation.....	525
E.3	Signature generation for secondary actors .....	528
E.4	Signature validation .....	528
Annex F (informative)	WPT message examples .....	530
F.1	Example of WPT message sequence .....	530
F.2	XML view of PairingReq for LPE.....	531
F.3	XML view of PairingRes for LPE .....	532
F.4	XML view of PairingReq for P2PS.....	533
F.5	XML view of PairingRes for P2PS.....	534
F.6	XML view of FinePositioningReq.....	535
F.7	XML view of FinePositioningRes.....	536
Annex G (informative)	ACD message examples .....	538
G.1	Enable SystemStatus messaging via a value added service selection .....	538
Annex H (informative)	Summary of requirements .....	543
Annex I (Informativ)	<a href="https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d-ed18e05e7167/osit-pr-en-15118-2-2018">oSIST prEN ISO 15118-2:2018 https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d- ed18e05e7167/osit-pr-en-15118-2-2018</a> .....	562
Annex J (Informativ)	<a href="https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d-ed18e05e7167/osit-pr-en-15118-2-2018">cd18e05e7167/osit-pr-en-15118-2-2018</a> .....	563
Annex K (informative)	Mapping of Part 1 use case elements.....	564
K.1	Relation of Identification Modes and Use Case Elements .....	564
Annex L (informative)	Mapping of ISO 15118 message element names to SAE J2847/2 terms .....	601
L.1	SAE J2847/2 status codes .....	601
L.2	SAE J2847/2 Energy Transfer Types .....	602
L.3	SAE J2847/2 signals.....	603
Annex M (informative)	Message examples .....	604
M.1	Value Added Service selection .....	604
M.2	EXI encoded message examples .....	606
M.2.1	SessionSetupRes message.....	606
M.2.2	ChargeParameterDiscoveryReq message (AC-based).....	606
M.2.3	CurrentDemandReq message .....	607
M.3	Schedules and tariff information .....	608
M.3.1	Overview.....	608
M.3.2	Dynamic GridSchedule w/o SalesTariff over ISO 15118 V2G CI.....	608
M.3.3	“Time Of Use”-based SalesTariff with constant value for GridSchedule .....	610
M.3.4	“Time Of Use”-based SalesTariff with dynamic GridSchedule .....	611
M.3.5	“Consumption”-based SalesTariff with constant value for GridSchedule .....	613
M.3.6	Multiple SalesTariffs with different Demand Limits in GridSchedule .....	614
M.3.7	Time of Use-based SalesTariffs including relativePricePercentage.....	616
Annex N (informative)	Application of certificates .....	627
N.1	General information .....	627
N.1.1	Overview.....	627
N.1.2	Demands of the OEM .....	628
N.1.3	Demands of the Secondary Actors.....	628

N.1.4	Rationale for Decisions in this Standard .....	629
N.1.5	Overview of the resulting certificate structure .....	630
N.2	Simplified certificate management in private environment .....	632
N.2.1	Overview (motivation) .....	632
N.2.2	Solution for private environments .....	632
N.2.3	Solution for emergency and disaster situations .....	635
N.3	Use of OEM provisioning certificates .....	636
N.3.1	Introduction .....	636
N.3.2	Processes .....	637
N.4	Security appliances and their associated certificates .....	639
<b>Annex O (informative) Encryption for the distribution of secret keys .....</b>		<b>642</b>
O.1	Overview .....	642
O.2	Ephemeral-static Diffie-Hellman key agreement .....	642
O.3	Key pairs .....	643

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 15118-2:2018](#)  
<https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d-ed18e05e7161/osist-pr-en-iso-15118-2-2018>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

## iTeh STANDARD PREVIEW (standard.iteh.ai)

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/foreword.html](http://www.iso.org/foreword.html).

[oSIST prEN ISO 15118-2:2018](#)

This document was prepared by Technical Committee ISO/TC 22, Road vehicles; Subcommittee SC 31, Data communication. <https://standards.iteh.ai/standard/is/15118-21&450-4038-0-81-ed18e05e7161/osist-pren-iso-15118-2-2018>

This second edition cancels and replaces the first edition (ISO 15118-2:2014), which has been technically revised.

The main changes compared to the previous edition are as follows:

- Includes corrections of errors and inconsistencies;
- Missing parts added;
- Applied changes to achieve a Unified XML Scheme supporting all charging modes and needs;
- Communication requirements on reserve power transfer added;
- Includes requirements in regard to wireless power transfer (included from ISO 15118-7).

A list of all parts in the ISO 15118 series can be found on the ISO website.

## Introduction

The pending energy crisis and necessity to reduce greenhouse gas emissions started in the former century has led the vehicle manufacturers to a very significant effort to reduce the energy consumption of their vehicles up to the present. As countermeasures to this continuous problem, they developed vehicles partly or completely propelled by electricity power and launched them into the market. Those vehicles will reduce the dependency on oil, improve the global energy efficiency and reduce the total CO<sub>2</sub> emissions for road transportation if the electricity is produced from renewable sources. To charge electricity to the batteries of such vehicles, specific charging infrastructure was required.

Much of the standardization work on dimensional and electrical specifications of the charging infrastructure for electric vehicles and the vehicle interface were treated in the relevant ISO or IEC groups. However, the standardization work about direct information transfer between the electric vehicle and the charging infrastructure was not enough, but it was assigned to ISO 15118 series came to be treated sufficiently.

Such communication is necessary for the optimization of energy resources and energy production systems. With it electric vehicles can be connected to the supply network and communicate the most economic or most energy efficient way for charging/discharging. It is also required to develop efficient and convenient billing systems in order to cover the resulting payments. The necessary communication channel may serve in the future to contribute to the stabilization of the supply network as well as to support additional information services required to operate electric vehicles efficiently and economically.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

It includes:

[oSIST prEN ISO 15118-2:2018](#)

- \* Improved charge methods that reduces efforts and agonies of the charging operation,  
<https://standards.iteh.ai/standards/iso/14634s450c4038.0e8d-ed18e05e7161/ositpr-en-iso-15118-2-2018>
- \* Extended functions for the electric vehicles to be utilized as distributed energy resources (enables smoothing of the electricity load of the supply network for higher energy efficiency, and also provide power back to the grid (e.g. for grid services or acting as a standalone power supply as an emergency lifeline),
- \* Information services for the user with higher added value and new convenience.

As for the communication system, the next evolution will be expected to realize these new applications.

# Road vehicles — Vehicle to grid communication interface — Part 2: Network and application protocol requirements

## 1 Scope

This international standard specifies the communication between the electric vehicle (EV), including battery electric vehicle (BEV) and plug-in hybrid electric vehicle (PHEV), and the EV supply equipment. The application layer message sets defined in this revision of ISO 15118-2 are designed to support the electricity power transfer between an EV and an EV supply equipment.

The bidirectional electricity power transfer, use case of that was already included in edition 1.0 of part 1 but not included in part 2, was officially added to the scope of this standard. Herein edition 2.0 of part 2 defines the communication messages and sequence requirements for bidirectional power transfer.

Also the scope is widely extended in this revision, requirements of wireless communication for both conductive charging and wireless charging are defined. Additionally, requirements of communication for automatic connection device and information services about charging and control status are defined in this revision.

The purpose of this part 2 of ISO 15118 is to detail the communication between an electric vehicle communication controller (EVCC) and supply equipment communication controller (SECC). Aspects are specified to detect a vehicle in a communication network and enable an Internet Protocol (IP) based communication between EVCC and SECC.



### Key

- 1 Scope of ISO 15118-2
- 2 Message definition considers use cases defined for communication between SECC to SA

**Figure 1 — Communication relationship among EVCC, SECC and secondary actor**

This part 2 defines messages, data model, XML/EXI based data representation format, usage of V2GTP, TLS, TCP and IPv6. These requirements belong to the area of from 3rd to 7th OSI layer model. In addition the document describes main service sequences of conductive charging, wireless power transfer and bidirectional power transfer, and how data link layer services can be accessed from a layer 3 perspective. The data link layer and physical layer functionality for wired communication is described in part 3 of this standard, and those of wireless communication are described in part 8 of this standard.

## 2 Normative references

The following referenced documents are required for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3166-1, *Codes for the representation of names of countries and their subdivisions — Part 1: Country codes*

ISO 15118-1, *Road vehicles — Vehicle to grid communication interface — Part 1: General information and use-case definition*

ISO 15118-3, *Road Vehicles — Vehicle to grid communication interface — Part 3: Physical and data link layer requirements*

**ISO/DIS 15118-2:2018(E)  
ISO/DIS 15118-2 ED2**

*ISO 15118-8, Road Vehicles — Vehicle to grid communication interface — Part 8: Physical and data link layer requirements for wireless communication*

IEC 61851-1, *Electric vehicle conductive charging system — Part 1: General requirements(Ed 2.0 2010)*

IEC 61851-22, *Electric vehicle conductive charging system - Part 22: AC electric vehicle charging station*

IEC CDV 61851-23, *Electric vehicle conductive charging system - Part 23: D.C. electric vehicle charging station (Ed 1.0 2012)*

IEC 62196, *Plugs, socket-outlets, vehicle connectors and vehicle inlets - Conductive charging of electric vehicles*

IEC 61980-1, *Electric vehicle wireless power transfer (WPT) systems - Part 1 General Requirements*

IEC 61980-2, *Electric vehicle wireless power transfer (WPT) systems - Part 2 specific requirements for communication between electric road vehicle (EV) and infrastructure with respect to wireless power transfer (WPT) systems*

IEC61980-3, Electric vehicle wireless power transfer (WPT) systems – Part 3: Specific requirements for the magnetic field wireless power transfer systemsISO 19363, *Electrically propelled vehicles—Magnetic field wireless power transfer—Safety and interoperability requirements*

SAE J2847-2 V4, *Communication Between Plug-In Vehicles and Off-Board DC Chargers*

W3C EXI 1.0, *Efficient XML Interchange (EXI) Format 1.0 W3C Recommendation (March 2011)*

W3C XML Signature Syntax and Processing Version 1.1, *W3C Recommendation (April 2013)*

ISO 4130 Road vehicles -- Three-dimensional reference system and fiducial marks -- Definitions

IETF RFC 768, *User Datagram Protocol (August 1980)*

IETF RFC 793, *Transmission Control Protocol - DARPA Internet Program - Protocol Specification (September 1981)*

IETF RFC 1981, *Path MTU Discovery for IP version 6 (August 1996)*

IETF RFC 2460, *Internet Protocol, Version 6 (IPv6) Specification (December 1998)*

IETF RFC 6960, *X.509 Internet Public Key Infrastructure Online Certificate Status Protocol - OCSP (June 2013)*

IETF RFC 3122, *Extensions to IPv6 Neighbor Discovery for Inverse Discovery Specification (June 2001)*

IETF RFC 3315, *Dynamic Host Configuration Protocol for IPv6 (DHCPv6) (July 2003)*

IETF RFC 3484, *Default Address Selection for Internet Protocol version 6 (IPv6) (February 2003)*

IETF RFC 6582, *The NewReno Modification to TCP's Fast Recovery Algorithm (April 2012)*

IETF RFC 4050, *Using the Elliptic Curve Signature Algorithm (ECDSA) for XML Digital Signatures (April 2005)*

IETF RFC 4291, *IP Version 6 Addressing Architecture (February 2006)*

IETF RFC 4429, *Optimistic Duplicate Address Detection (DAD) for IPv6 (April 2006)*

IETF RFC 4443, *Internet Control Message Protocol (ICMP v6) for the Internet Protocol version 6 (IPv6) specification (March 2006)*

IETF RFC 4514, *Lightweight Directory Access Protocol (LDAP): String Representation of Distinguished Names (June 2006)*

IETF RFC 4861, *Neighbor Discovery for IP version 6 (IPv6) (September 2007)*

IETF RFC 4862, *IPv6 Stateless Address Autoconfiguration (September 2007)*

IETF RFC 5095, *Deprecation of Type 0 Routing Headers in IPv6 (December 2007)*

IETF RFC 5116, *An Interface and Algorithms for Authenticated Encryption (January 2008)*

IETF RFC 5234, *Augmented BNF for Syntax Specifications: ABNF (January 2008)*

IETF RFC 5246, *The Transport Layer Security (TLS) Protocol Version 1.2 (August 2008)*

IETF RFC 5280, *Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile (May 2008)*

IETF RFC 5289, *TLS Elliptic Curve Cipher Suites with SHA-256/384 and AES Galois Counter Mode (GCM) (August 2008)*

## iTeh STANDARD PREVIEW

IETF RFC 5480, *Elliptic Curve Cryptography Subject Public Key Information (March 2009)*

**(standards.iteh.ai)**

IETF RFC 5722, *Handling of Overlapping IPv6 Fragments (December 2009)*

[oSIST prEN ISO 15118-2:2018](#)

IETF RFC 6066, *Transport Layer Security (TLS) Extensions: Extension Definitions (January 2011)*

<https://standards.iteh.ai/catalog/standards/iso/iso-15118-2-2018-ed18e05e7161/osist-pren-iso-15118-2-2018>

IETF RFC 6106, *IPv6 Router Advertisement Options for DNS Configuration (November 2010)*

IETF RFC 6961, *The Transport Layer Security (TLS) Multiple Certificate Status Request Extension (June 2013)*

IANA Service&PortRegistry, *Service Name and Transport Protocol Port Number Registry [viewed 2011-01-16], Available from: <http://www.iana.org/assignments/service-names-port-numbers/service-names-port-numbers.xml>*

NIST FIPS PUB 180-4: *Secure Hash Standard (SHS) (March 2012)*

NIST Special Publication 800-56A: *Recommendation for Pair-Wise Key Establishment Schemes Using Discrete Logarithm Cryptography (Revised) (March 2007)*

NIST Special Publication 800-38A: *Recommendation for Block Cipher Modes of Operation - Methods and Techniques (2001)*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

#### 3.1

##### **automatic connection device**

###### **ACD**

components supporting the automatic connection and disconnection process for conductive energy transfer between an EV and EV supply equipment

#### 3.2

##### **basic charging**

###### **BC**

charging phase during a charging session controlled by IEC 61851-1 Annex A only

#### 3.3

##### **BCB Toogle**

a switching sequence of the PWM Signal from State B to C and back to State B

### iTeh STANDARD PREVIEW (standards.iteh.ai)

#### 3.4

##### **charging limits**

a set of physical constraints (e.g. voltage, current, energy, power) that is negotiated during a service session

#### 3.5

##### **charging session**

<https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d-41f0f5743333/sist-pr-en-iso-15118-2-2018>

a kind of service session applied to charging services

#### 3.6

##### **communication setup timer**

a timer monitoring the time D-LINK\_READY.indication(DLINKSTATUS=LinkEstablished) until the Session Setup message

#### 3.7

##### **contract certificate**

certificate issued for EVCC by a MO Sub-CA, which is used in XML signatures in application layer so that SECC or secondary actor can verify the contract issued to the EVCC and signatures issued by the EVCC

#### 3.8

##### **control pilot state**

###### **CP state**

control pilot state according to control pilot function defined in IEC 61851-1 Annex A

#### 3.9

##### **credentials**

piece of information attesting an entity's identity

EXAMPLE The combination of an account number and a password is a widely used example of credentials.

**3.10****distinguished encoding rules****DER**

method for encoding a data object, such as an X.509 certificate, to be digitally signed or to have its signature verified

**3.11****dynamic control mode**

Control Mode for the Communication further Information can be found in ISO 15118-1 ED2NOTE The SECC controls the power flow and gives the EVCC Set Points it has to follow

**3.12****elliptic curve cryptography****ECC**

mechanism for implementing public-key cryptography based on the discrete logarithms by algebraic structure of elliptic curves

**3.13****flexible schedule mode**

Control Mode for the Communication further Information can be found in ISO 15118-1 ED2

Note 1 to entry: EVCC and SECC negotiate a power profile for Charging or Discharging purposes

**3.14****global address**

IP address with unlimited scope

## ITEH STANDARD PREVIEW (standards.iteh.ai)

**3.15****high level communication charging****HLC-C**

charging phase during a service session controlled by ISO 15118-2:2018

<https://standards.iteh.ai/catalog/standards/sist/1df6e34f-459e-4038-9c8d-ed18e05e7161/osist-pren-iso-15118-2-2018>

**3.16****link-local address**

IP address with link-only scope that can be used to reach neighboring interfaces attached to the same link

**3.17****identification mode**

authenticate and authorize the user account

Note 1 to entry: An identification mode is used for identification selection. Multiple identification modes cover same service sequence.

Note 2 to entry: Identification mode refers to EIM and PnC

**3.18****IP address****address**

IP-layer identifier for an interface or a set of interfaces

**3.19****maximum transfer unit****MTU**

maximum size (in bytes) of the largest protocol data unit that the data link layer can pass onwards

**3.20****message set**

set of V2G messages and parameters for the EVCC or SECC covering one or multiple use case elements