



iTeh STANDARD
Universal Mobile Telecommunications System (UMTS);
LTE; PREVIEW
5G;
(standards.iteh.ai)
Non-Access-Stratum (NAS)
protocol for Evolved Packet System (EPS);
Stage 3
ETSI TS 124 301 V17.6.0 (2022-05)
https://standards.iteh.ai/standards/sist/ee2abf04-
b3f2-45e8-afbc-893079cfaf5/etsi-ts-124-301-v17-6-0-
2022-05
(3GPP TS 24.301 version 17.6.0 Release 17)



Reference

RTS/TSGC-0124301vh60

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:
<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

[ETSI TS 124 301 V17.6.0 \(2022-05\)](#)

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

[3GPP TS 24.301 V17.6.0 \(2022-05\)](#)

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

2022-05

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	20
1 Scope	22
2 References	22
3 Definitions and abbreviations.....	25
3.1 Definitions	25
3.2 Abbreviations	32
4 General	34
4.1 Overview	34
4.2 Linkage between the protocols for EPS mobility management and EPS session management	34
4.2A Handling of NAS signalling low priority indication	35
4.3 UE mode of operation	35
4.3.1 General.....	35
4.3.2 Change of UE mode of operation	36
4.3.2.1 General	36
4.3.2.2 Change of UE's usage setting	38
4.3.2.3 Change of voice domain preference for E-UTRAN	39
4.3.2.4 Change or determination of IMS registration status.....	40
4.3.2.5 Change of configuration regarding the use of SMS	42
4.4 NAS security	43
4.4.1 General.....	43
4.4.2 Handling of EPS security contexts	43
4.4.2.1 General	43
4.4.2.2 Establishment of a mapped EPS security context during intersystem handover	44
4.4.2.3 Establishment of secure exchange of NAS messages	45
4.4.2.4 Change of security keys	47
4.4.2.5 Derivation of keys at CS to PS SRVCC handover from A/Gb mode to S1 mode or from Iu mode to S1 mode	48
4.4.3 Handling of NAS COUNT and NAS sequence number	49
4.4.3.1 General	49
4.4.3.2 Replay protection	50
4.4.3.3 Integrity protection and verification	50
4.4.3.4 Ciphering and deciphering	50
4.4.3.5 NAS COUNT wrap around	50
4.4.4 Integrity protection of NAS signalling messages.....	51
4.4.4.1 General	51
4.4.4.2 Integrity checking of NAS signalling messages in the UE	51
4.4.4.3 Integrity checking of NAS signalling messages in the MME	52
4.4.5 Ciphering of NAS signalling messages	54
4.5 Disabling and re-enabling of UE's E-UTRA capability	54
4.6 Applicability of procedures	57
4.6.1 Relay nodes.....	57
4.7 EPS mobility management and EPS session management in NB-S1 mode	57
4.8 EPS mobility management and EPS session management in WB-S1 mode for IoT	58
4.8.1 UE not using satellite E-UTRAN access	58
4.8.2 UE using satellite E-UTRAN access	59
4.9 Disabling and re-enabling of UE's NB-IoT capability	59
4.10 Support of MUSIM features	60
5 Elementary procedures for EPS mobility management.....	60
5.1 Overview	60
5.1.1 General.....	60

5.1.2	Types of EMM procedures	60
5.1.3	EMM sublayer states	62
5.1.3.1	General	62
5.1.3.2	EMM sublayer states in the UE	62
5.1.3.2.1	General	62
5.1.3.2.2	Main states	62
5.1.3.2.2.1	EMM-NUL.....	62
5.1.3.2.2.2	EMM-DEREGISTERED	62
5.1.3.2.2.3	EMM-REGISTERED-INITIATED	62
5.1.3.2.2.4	EMM-REGISTERED	62
5.1.3.2.2.5	EMM-DEREGISTERED-INITIATED	63
5.1.3.2.2.6	EMM-TRACKING-AREA-UPDATING-INITIATED	63
5.1.3.2.2.7	EMM-SERVICE-REQUEST-INITIATED	63
5.1.3.2.3	Substates of state EMM-DEREGISTERED	63
5.1.3.2.3.1	General	63
5.1.3.2.3.2	EMM-DEREGISTERED.NORMAL-SERVICE	64
5.1.3.2.3.3	EMM-DEREGISTERED.LIMITED-SERVICE	64
5.1.3.2.3.4	EMM-DEREGISTERED.ATTEMPTING-TO-ATTACH	64
5.1.3.2.3.5	EMM-DEREGISTERED.PLMN-SEARCH	64
5.1.3.2.3.6	EMM-DEREGISTERED.NO-IMSI	64
5.1.3.2.3.7	EMM-DEREGISTERED.ATTACH-NEEDED	64
5.1.3.2.3.8	EMM-DEREGISTERED.NO-CELL-AVAILABLE	64
5.1.3.2.3.9	EMM-DEREGISTERED.eCALL-INACTIVE	64
5.1.3.2.4	Substates of state EMM-REGISTERED	65
5.1.3.2.4.1	General	65
5.1.3.2.4.2	EMM-REGISTERED.NORMAL-SERVICE	65
5.1.3.2.4.3	EMM-REGISTERED.ATTEMPTING-TO-UPDATE	65
5.1.3.2.4.4	EMM-REGISTERED.LIMITED-SERVICE	65
5.1.3.2.4.5	EMM-REGISTERED.PLMN-SEARCH	65
5.1.3.2.4.6	EMM-REGISTERED.UPDATE-NEEDED	65
5.1.3.2.4.7	EMM-REGISTERED.NO-CELL-AVAILABLE	65
5.1.3.2.4.8	EMM-REGISTERED.ATTEMPTING-TO-UPDATE-MM	65
5.1.3.2.4.9	EMM-REGISTERED.IMSI-DETACH-INITIATED	65
5.1.3.3	EPS update status	66
5.1.3.4	EMM sublayer states in the MME	66
5.1.3.4.1	EMM-DEREGISTERED	66
5.1.3.4.2	EMM-COMMON-PROCEDURE-INITIATED	66
5.1.3.4.3	EMM-REGISTERED	66
5.1.3.4.4	EMM-DEREGISTERED-INITIATED	66
5.1.4	Coordination between EMM and GMM	67
5.1.5	Coordination between EMM and MM	68
5.2	Behaviour of the UE in state EMM-DEREGISTERED and state EMM-REGISTERED	68
5.2.1	General	68
5.2.2	UE behaviour in state EMM-DEREGISTERED	68
5.2.2.1	General	68
5.2.2.2	Primary substate selection	69
5.2.2.2.1	Selection of the substate after power on	69
5.2.2.3	Detailed description of UE behaviour in state EMM-DEREGISTERED	69
5.2.2.3.1	NORMAL-SERVICE	69
5.2.2.3.2	LIMITED-SERVICE	69
5.2.2.3.3	ATTEMPTING-TO-ATTACH	69
5.2.2.3.4	PLMN-SEARCH	70
5.2.2.3.5	NO-IMSI	70
5.2.2.3.6	ATTACH-NEEDED	70
5.2.2.3.7	NO-CELL-AVAILABLE	70
5.2.2.3.8	eCALL-INACTIVE	71
5.2.2.4	Substate when back to state EMM-DEREGISTERED from another EMM state	71
5.2.3	UE behaviour in state EMM-REGISTERED	71
5.2.3.1	General	71
5.2.3.2	Detailed description of UE behaviour in state EMM-REGISTERED	72
5.2.3.2.1	NORMAL-SERVICE	72
5.2.3.2.2	ATTEMPTING-TO-UPDATE	72

5.2.3.2.3	LIMITED-SERVICE.....	73
5.2.3.2.4	PLMN-SEARCH.....	73
5.2.3.2.5	UPDATE-NEEDED	73
5.2.3.2.6	NO-CELL-AVAILABLE	74
5.2.3.2.7	ATTEMPTING-TO-UPDATE-MM.....	74
5.2.3.2.8	IMSI-DETACH-INITIATED	74
5.3	General on elementary EMM procedures.....	74
5.3.1	EMM modes and NAS signalling connection.....	74
5.3.1.1	Establishment of the NAS signalling connection.....	74
5.3.1.2	Release of the NAS signalling connection	76
5.3.1.2.1	General	76
5.3.1.2.2	UE is using EPS services with control plane CIoT EPS optimization.....	79
5.3.1.3	Suspend and resume of the NAS signalling connection.....	79
5.3.2	Lists of forbidden tracking areas.....	80
5.3.3	List of forbidden PLMNs for attach in S101 mode.....	80
5.3.3a	Forbidden PLMNs for EPS services	80
5.3.4	Equivalent PLMNs list.....	80
5.3.5	Handling of the periodic tracking area update timer and mobile reachable timer (S1 mode only).....	81
5.3.6	Handling of timer T3402	82
5.3.7	Handling of the Local Emergency Numbers List and the Extended Local Emergency Numbers List	83
5.3.7a	Specific requirements for UE configured to use timer T3245	84
5.3.7b	Specific requirements for UE when receiving non-integrity protected reject messages	84
5.3.8	Abnormal cases in the UE	87
5.3.9	Handling of NAS level mobility management congestion control	88
5.3.9A	Handling of congestion control for transport of user data via the control plane	89
5.3.10	Access class control.....	89
5.3.11	Power saving mode.....	89
5.3.12	Extended idle-mode DRX cycle.....	90
5.3.13	Interaction between power saving mode and extended idle mode DRX cycle	91
5.3.14	Dedicated core network	91
5.3.15	CIoT EPS optimizations	91
5.3.16	Restriction on use of enhanced coverage	93
5.3.17	Service Gap Control.....	93
5.3.18	Restricted local operator services	95
5.3.19	Core Network selection and redirection for UEs using CIoT optimizations.....	95
5.3.19.1	Core network selection.....	95
5.3.19.2	Redirection of the UE by the core network	95
5.3.20	UE radio capability signalling optimisation.....	96
5.3.21	Wake-up signal assistance	97
5.4	EMM common procedures	98
5.4.1	GUTI reallocation procedure	98
5.4.1.1	General	98
5.4.1.2	GUTI reallocation initiation by the network	98
5.4.1.3	GUTI reallocation completion by the UE	99
5.4.1.4	GUTI reallocation completion by the network	99
5.4.1.5	Abnormal cases in the UE.....	99
5.4.1.6	Abnormal cases on the network side.....	100
5.4.2	Authentication procedure.....	101
5.4.2.1	General	101
5.4.2.2	Authentication initiation by the network.....	101
5.4.2.3	Authentication response by the UE.....	102
5.4.2.4	Authentication completion by the network	103
5.4.2.5	Authentication not accepted by the network	103
5.4.2.6	Authentication not accepted by the UE.....	104
5.4.2.7	Abnormal cases	105
5.4.3	Security mode control procedure	109
5.4.3.1	General	109
5.4.3.2	NAS security mode control initiation by the network	110
5.4.3.3	NAS security mode command accepted by the UE.....	112
5.4.3.4	NAS security mode control completion by the network	114
5.4.3.5	NAS security mode command not accepted by the UE.....	114
5.4.3.6	Abnormal cases in the UE.....	114

5.4.3.7	Abnormal cases on the network side.....	115
5.4.4	Identification procedure.....	115
5.4.4.1	General	115
5.4.4.2	Identification initiation by the network	116
5.4.4.3	Identification response by the UE	116
5.4.4.4	Identification completion by the network	116
5.4.4.5	Abnormal cases in the UE.....	116
5.4.4.6	Abnormal cases on the network side.....	117
5.4.5	EMM information procedure	118
5.4.5.1	General	118
5.4.5.2	EMM information procedure initiation by the network	118
5.4.5.3	EMM information procedure in the UE	118
5.4.5.4	Abnormal cases on the network side.....	118
5.5	EMM specific procedures	118
5.5.1	Attach procedure.....	118
5.5.1.1	General	118
5.5.1.2	Attach procedure for EPS services.....	120
5.5.1.2.1	General	120
5.5.1.2.2	Attach procedure initiation	120
5.5.1.2.3	EMM common procedure initiation	125
5.5.1.2.4	Attach accepted by the network.....	125
5.5.1.2.4A	Attach successful for EPS services and not accepted for SMS services.....	131
5.5.1.2.5	Attach not accepted by the network.....	132
5.5.1.2.5A	Attach for emergency bearer services not accepted by the network.....	138
5.5.1.2.5B	Attach for initiating a PDN connection for emergency bearer services not accepted by the network.....	140
5.5.1.2.5B1	Attach by a UE transferring an emergency PDU session using a standalone PDN CONNECTIVITY REQUEST message	141
5.5.1.2.5C	Attach for access to RLOS not accepted by the network.....	141
5.5.1.2.6	Abnormal cases in the UE	142
5.5.1.2.6A	Abnormal cases in the UE, SMS services not accepted.....	145
5.5.1.2.7	Abnormal cases on the network side	146
5.5.1.3	Combined attach procedure for EPS services and non-EPS services (S1 mode only)	147
5.5.1.3.1	General	147
5.5.1.3.2	Combined attach procedure initiation	148
5.5.1.3.3	EMM common procedure initiation	148
5.5.1.3.4	Combined attach accepted by the network	148
5.5.1.3.4.1	General.....	148
5.5.1.3.4.2	Combined attach successful	148
5.5.1.3.4.3	Combined attach successful for EPS services only.....	149
5.5.1.3.5	Combined attach not accepted by the network	151
5.5.1.3.6	Abnormal cases in the UE	156
5.5.1.3.7	Abnormal cases on the network side	157
5.5.2	Detach procedure	157
5.5.2.1	General	157
5.5.2.2	UE initiated detach procedure	158
5.5.2.2.1	UE initiated detach procedure initiation	158
5.5.2.2.2	UE initiated detach procedure completion for EPS services only	159
5.5.2.2.3	UE initiated combined detach procedure completion.....	160
5.5.2.2.4	Abnormal cases in the UE	160
5.5.2.2.5	Abnormal cases on the network side	162
5.5.2.3	Network initiated detach procedure	162
5.5.2.3.1	Network initiated detach procedure initiation	162
5.5.2.3.2	Network initiated detach procedure completion by the UE.....	163
5.5.2.3.3	Network initiated detach procedure completion by the network	168
5.5.2.3.4	Abnormal cases in the UE	168
5.5.2.3.5	Abnormal cases on the network side	169
5.5.3	Tracking area updating procedure (S1 mode only).....	170
5.5.3.1	General	170
5.5.3.2	Normal and periodic tracking area updating procedure	171
5.5.3.2.1	General	171
5.5.3.2.2	Normal and periodic tracking area updating procedure initiation	172

5.5.3.2.3	EMM common procedure initiation	179
5.5.3.2.4	Normal and periodic tracking area updating procedure accepted by the network	180
5.5.3.2.4A	Tracking area updating successful for EPS services and not accepted for SMS services.....	190
5.5.3.2.5	Normal and periodic tracking area updating procedure not accepted by the network	191
5.5.3.2.5A	Tracking area updating procedure for initiating a PDN connection for emergency bearer services not accepted by the network	199
5.5.3.2.5B	Tracking area updating for access to RLOS not accepted by the network	199
5.5.3.2.6	Abnormal cases in the UE	200
5.5.3.2.6A	Abnormal cases in the UE, SMS services not accepted.....	206
5.5.3.2.7	Abnormal cases on the network side	206
5.5.3.3	Combined tracking area updating procedure.....	208
5.5.3.3.1	General	208
5.5.3.3.2	Combined tracking area updating procedure initiation.....	208
5.5.3.3.3	EMM common procedure initiation	211
5.5.3.3.4	Combined tracking area updating procedure accepted by the network	211
5.5.3.3.4.1	General.....	211
5.5.3.3.4.2	Combined tracking area updating successful.....	211
5.5.3.3.4.3	Combined tracking area updating successful for EPS services only.....	213
5.5.3.3.5	Combined tracking area updating procedure not accepted by the network	215
5.5.3.3.6	Abnormal cases in the UE	222
5.5.3.3.7	Abnormal cases on the network side	223
5.5.4	eCall inactivity procedure	223
5.5.5	Tracking area update request message (for N1 mode only).....	224
5.5.6	Attach request message (for N1 mode only).....	224
5.6	EMM connection management procedures (S1 mode only).....	225
5.6.1	Service request procedure	225
5.6.1.1	General	225
5.6.1.2	Service request procedure initiation.....	229
5.6.1.2.1	UE is not using EPS services with control plane CIoT EPS optimization.....	229
5.6.1.2.2	UE is using EPS services with control plane CIoT EPS optimization.....	230
5.6.1.3	EMM common procedure initiation	230
5.6.1.4	Service request procedure accepted by the network	231
5.6.1.4.1	UE is not using EPS services with control plane CIoT EPS optimization.....	231
5.6.1.4.2	UE is using EPS services with control plane CIoT EPS optimization.....	233
5.6.1.5	Service request procedure not accepted by the network.....	237
5.6.1.5A	Service request procedure for initiating a PDN connection for emergency bearer services not accepted by the network.....	246
5.6.1.5B	Service request procedure for UE attached for access to RLOS not accepted by the network.....	247
5.6.1.6	Abnormal cases in the UE.....	247
5.6.1.7	Abnormal cases on the network side	254
5.6.2	Paging procedure	256
5.6.2.1	General	256
5.6.2.2	Paging for EPS services	256
5.6.2.2.1	Paging for EPS services through E-UTRAN using S-TMSI	256
5.6.2.2.1.1	General	256
5.6.2.2.1.2	Abnormal cases on the network side	259
5.6.2.2.1.3	Abnormal cases in the UE	259
5.6.2.2.2	Paging for EPS services through E-UTRAN using IMSI.....	259
5.6.2.3	Paging for CS fallback to A/Gb or Iu mode	260
5.6.2.3.1	General	260
5.6.2.3.2	Abnormal cases in the UE	261
5.6.2.3.3	Abnormal cases on the network side	261
5.6.2.4	Paging for SMS	261
5.6.3	Transport of NAS messages procedure.....	262
5.6.3.1	General	262
5.6.3.2	UE initiated transport of NAS messages	262
5.6.3.3	Network initiated transport of NAS messages	262
5.6.3.4	Abnormal cases in the UE	262
5.6.3.5	Abnormal cases on the network side	263
5.6.4	Generic transport of NAS messages procedure	263
5.6.4.1	General	263
5.6.4.2	UE initiated generic transport of NAS messages	263

5.6.4.3	Network initiated transport of NAS messages	263
5.6.4.4	Abnormal cases in the UE.....	264
5.6.4.5	Abnormal cases on the network side.....	264
5.7	Reception of an EMM STATUS message by an EMM entity	264
6	Elementary procedures for EPS session management.....	265
6.1	Overview	265
6.1.1	General.....	265
6.1.2	Types of ESM procedures.....	265
6.1.3	ESM sublayer states.....	267
6.1.3.1	General.....	267
6.1.3.2	ESM sublayer states in the UE.....	267
6.1.3.2.1	BEARER CONTEXT INACTIVE	267
6.1.3.2.2	BEARER CONTEXT ACTIVE	267
6.1.3.2.3	PROCEDURE TRANSACTION INACTIVE.....	267
6.1.3.2.4	PROCEDURE TRANSACTION PENDING	267
6.1.3.3	ESM sublayer states in the MME.....	268
6.1.3.3.1	BEARER CONTEXT INACTIVE	268
6.1.3.3.2	BEARER CONTEXT ACTIVE PENDING.....	268
6.1.3.3.3	BEARER CONTEXT ACTIVE	268
6.1.3.3.4	BEARER CONTEXT INACTIVE PENDING.....	268
6.1.3.3.5	BEARER CONTEXT MODIFY PENDING.....	268
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	268
6.1.3.3.7	PROCEDURE TRANSACTION PENDING	268
6.1.4	Coordination between ESM and SM	269
6.1.4A	Coordination between ESM and 5GSM	270
6.1.5	Coordination between ESM and EMM for supporting ISR	270
6.2	IP address allocation.....	270
6.2.1	General.....	270
6.2.2	IP address allocation via NAS signalling.....	270
6.2A	IP header compression.....	272
6.3	General on elementary ESM procedures	272
6.3.1	Services provided by lower layers	272
6.3.2	Principles of address handling for ESM procedures	272
6.3.3	Abnormal cases in the UE	275
6.3.4	Abnormal cases in the network	275
6.3.5	Handling of APN based congestion control	276
6.3.5A	Handling of group specific session management congestion control	276
6.3.6	Handling of network rejection not due to APN based congestion control	276
6.3.7	Handling of WLAN offload control	277
6.3.8	Handling of serving PLMN rate control	277
6.3.9	Handling of APN rate control	277
6.3.10	Handling of 3GPP PS data off	278
6.3.11	Handling of Reliable Data Service	279
6.3.12	Handling of Ethernet PDN type	279
6.3.13	Handling of Uncrewed aerial vehicle identification, authentication, and authorization	279
6.3.13.1	General	279
6.3.13.2	Authentication and authorization of UAV	279
6.3.13.3	Authorization of C2 communication.....	280
6.3.13.4	Authorization of UAV flight	280
6.4	Network initiated ESM procedures	280
6.4.1	Default EPS bearer context activation procedure	280
6.4.1.1	General	280
6.4.1.2	Default EPS bearer context activation initiated by the network.....	280
6.4.1.3	Default EPS bearer context activation accepted by the UE.....	281
6.4.1.4	Default EPS bearer context activation not accepted by the UE.....	282
6.4.1.5	Abnormal cases in the UE	283
6.4.1.6	Abnormal cases on the network side.....	283
6.4.2	Dedicated EPS bearer context activation procedure	283
6.4.2.1	General	283
6.4.2.2	Dedicated EPS bearer context activation initiated by the network.....	284
6.4.2.3	Dedicated EPS bearer context activation accepted by the UE	284

6.4.2.4	Dedicated EPS bearer context activation not accepted by the UE	286
6.4.2.5	Abnormal cases in the UE.....	287
6.4.2.6	Abnormal cases on the network side.....	287
6.4.3	EPS bearer context modification procedure.....	288
6.4.3.1	General	288
6.4.3.2	EPS bearer context modification initiated by the network	288
6.4.3.3	EPS bearer context modification accepted by the UE	289
6.4.3.4	EPS bearer context modification not accepted by the UE.....	291
6.4.3.5	Abnormal cases in the UE.....	293
6.4.3.6	Abnormal cases on the network side.....	293
6.4.4	EPS bearer context deactivation procedure.....	294
6.4.4.1	General	294
6.4.4.2	EPS bearer context deactivation initiated by the network	294
6.4.4.3	EPS bearer context deactivation accepted by the UE.....	295
6.4.4.4	Abnormal cases in the UE.....	297
6.4.4.5	Abnormal cases on the network side.....	297
6.4.4.6	Local EPS bearer context deactivation without NAS signalling	298
6.5	UE requested ESM procedures.....	299
6.5.0	General.....	299
6.5.1	UE requested PDN connectivity procedure	300
6.5.1.1	General	300
6.5.1.2	UE requested PDN connectivity procedure initiation	301
6.5.1.3	UE requested PDN connectivity procedure accepted by the network	304
6.5.1.4	UE requested PDN connectivity procedure not accepted by the network.....	306
6.5.1.4.1	General	306
6.5.1.4.2	Handling of network rejection due to ESM cause #26	308
6.5.1.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	310
6.5.1.4A	Handling the maximum number of active EPS bearer contexts	316
6.5.1.4B	Void.....	316
6.5.1.4C	Handling the maximum number of active user plane radio bearers in NB-S1 mode	316
6.5.1.5	Abnormal cases in the UE.....	317
6.5.1.6	Abnormal cases on the network side.....	317
6.5.1.7	Handling PDN connectivity request for UE configured for dual priority	318
6.5.2	UE requested PDN disconnect procedure.....	319
6.5.2.1	General	319
6.5.2.2	UE requested PDN disconnection procedure initiation	319
6.5.2.3	UE requested PDN disconnection procedure accepted by the network.....	319
6.5.2.4	UE requested PDN disconnection procedure not accepted by the network	320
6.5.2.5	Abnormal cases in the UE.....	320
6.5.2.6	Abnormal cases on the network side.....	320
6.5.3	UE requested bearer resource allocation procedure	321
6.5.3.1	General	321
6.5.3.2	UE requested bearer resource allocation procedure initiation	321
6.5.3.3	UE requested bearer resource allocation procedure accepted by the network	322
6.5.3.4	UE requested bearer resource allocation procedure not accepted by the network	322
6.5.3.4.1	General	322
6.5.3.4.2	Handling of network rejection due to ESM cause #26	324
6.5.3.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	325
6.5.3.4A	Handling the maximum number of active EPS bearer contexts	327
6.5.3.5	Abnormal cases in the UE.....	328
6.5.3.6	Abnormal cases on the network side.....	328
6.5.4	UE requested bearer resource modification procedure	328
6.5.4.1	General	328
6.5.4.2	UE requested bearer resource modification procedure initiation	329
6.5.4.3	UE requested bearer resource modification procedure accepted by the network	332
6.5.4.4	UE requested bearer resource modification procedure not accepted by the network	332
6.5.4.4.1	General	332
6.5.4.4.2	Handling of network rejection due to ESM cause #26	335
6.5.4.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	336
6.5.4.5	Abnormal cases in the UE.....	338
6.5.4.6	Abnormal cases on the network side.....	339
6.5.5	Handling session management request for UE configured for dual priority	340

6.6	Miscellaneous procedures	340
6.6.1	Exchange of protocol configuration options	340
6.6.1.1	General	340
6.6.1.2	ESM information request procedure	341
6.6.1.2.1	General	341
6.6.1.2.2	ESM information request initiated by the network	341
6.6.1.2.3	ESM information request completion by the UE	342
6.6.1.2.4	ESM information request completion by the network	342
6.6.1.2.5	Abnormal cases in the UE	342
6.6.1.2.6	Abnormal cases on the network side	342
6.6.1.3	Exchange of protocol configuration options in other messages	342
6.6.2	Notification procedure	343
6.6.2.1	General	343
6.6.2.2	Notification procedure initiation by the network	343
6.6.2.3	Notification procedure in the UE	343
6.6.2.4	Abnormal cases on the network side	343
6.6.3	Remote UE Report procedure	343
6.6.3.1	General	343
6.6.3.2	Remote UE Report initiated by the UE	343
6.6.3.3	Remote UE Report completion by the network	344
6.6.3.4	Remote UE Report completion by the UE	344
6.6.3.5	Abnormal cases in the UE	344
6.6.3.6	Abnormal cases on the network side	344
6.6.4	Transport of user data via the control plane procedure	344
6.6.4.1	General	344
6.6.4.2	UE initiated transport of user data via the control plane	345
6.6.4.3	Network initiated transport of user data via the control plane	345
6.6.4.4	Abnormal cases in the UE	346
6.6.4.5	Abnormal cases on the network side	346
6.7	Reception of an ESM STATUS message by an ESM entity	346
7	Handling of unknown, unforeseen, and erroneous protocol data	347
7.1	General	347
7.2	Message too short	348
7.3	Unknown or unforeseen procedure transaction identity or EPS bearer identity	348
7.3.1	Procedure transaction identity	348
7.3.2	EPS bearer identity	349
7.4	Unknown or unforeseen message type	351
7.5	Non-semantical mandatory information element errors	351
7.5.1	Common procedures	351
7.5.2	EPS mobility management	352
7.5.3	EPS session management	352
7.6	Unknown and unforeseen IEs in the non-imperative message part	352
7.6.1	IEIs unknown in the message	352
7.6.2	Out of sequence IEs	352
7.6.3	Repeated IEs	353
7.7	Non-imperative message part errors	353
7.7.1	Syntactically incorrect optional IEs	353
7.7.2	Conditional IE errors	353
7.8	Messages with semantically incorrect contents	353
8	Message functional definitions and contents	354
8.1	Overview	354
8.2	EPS mobility management messages	355
8.2.1	Attach accept	355
8.2.1.1	Message definition	355
8.2.1.2	GUTI	358
8.2.1.3	Location area identification	358
8.2.1.4	MS identity	358
8.2.1.5	EMM cause	358
8.2.1.6	T3402 value	358
8.2.1.7	T3423 value	358

8.2.1.8	Equivalent PLMNs.....	358
8.2.1.9	Emergency number list	358
8.2.1.9A	Extended emergency number list	358
8.2.1.10	EPS network feature support.....	358
8.2.1.11	Additional update result	358
8.2.1.12	T3412 extended value	359
8.2.1.13	T3324 value.....	359
8.2.1.14	Extended DRX parameters.....	359
8.2.1.15	DCN-ID.....	359
8.2.1.16	SMS services status.....	359
8.2.1.17	Non-3GPP NW provided policies	359
8.2.1.18	T3448 value.....	359
8.2.1.19	Network policy.....	359
8.2.1.20	T3447 value.....	359
8.2.1.21	Ciphering key data	360
8.2.1.22	UE radio capability ID	360
8.2.1.23	UE radio capability ID deletion indication.....	360
8.2.1.24	Negotiated WUS assistance information.....	360
8.2.1.25	Negotiated DRX parameter in NB-S1 mode	360
8.2.1.26	Negotiated IMSI offset.....	360
8.2.2	Attach complete	360
8.2.3	Attach reject.....	361
8.2.3.1	Message definition	361
8.2.3.2	ESM message container	361
8.2.3.3	T3346 value.....	361
8.2.3.4	T3402 value.....	361
8.2.3.5	Extended EMM cause	361
8.2.4	Attach request	361
8.2.4.1	Message definition	361
8.2.4.2	Old P-TMSI signature.....	364
8.2.4.3	Additional GUTI.....	364
8.2.4.4	Last visited registered TAI.....	364
8.2.4.5	DRX parameter	364
8.2.4.6	MS network capability.....	364
8.2.4.7	Old location area identification.....	364
8.2.4.8	TMSI status.....	364
8.2.4.9	Mobile station classmark 2.....	364
8.2.4.10	Mobile station classmark 3.....	364
8.2.4.11	Supported Codecs	364
8.2.4.12	Additional update type	364
8.2.4.13	Voice domain preference and UE's usage setting.....	365
8.2.4.14	Device properties	365
8.2.4.15	Old GUTI type	365
8.2.4.16	MS network feature support.....	365
8.2.4.17	TMSI based NRI container	365
8.2.4.18	T3324 value.....	365
8.2.4.19	T3412 extended value	365
8.2.4.20	Extended DRX parameters.....	365
8.2.4.21	UE additional security capability	365
8.2.4.22	UE status	365
8.2.4.23	Additional information requested.....	365
8.2.4.24	N1 UE network capability.....	365
8.2.4.25	UE radio capability ID availability IE.....	365
8.2.4.26	Requested WUS assistance information.....	366
8.2.4.27	DRX parameter in NB-S1 mode	366
8.2.4.28	Requested IMSI offset.....	366
8.2.5	Authentication failure	366
8.2.5.1	Message definition	366
8.2.5.2	Authentication failure parameter.....	366
8.2.6	Authentication reject.....	366
8.2.7	Authentication request	367
8.2.8	Authentication response.....	367

8.2.9	CS service notification.....	368
8.2.9.1	Message definition	368
8.2.9.2	CLI	368
8.2.9.3	SS Code.....	368
8.2.9.4	LCS indicator	368
8.2.9.5	LCS client identity	368
8.2.10	Detach accept.....	368
8.2.10.1	Detach accept (UE originating detach)	368
8.2.10.2	Detach accept (UE terminated detach).....	369
8.2.11	Detach request	369
8.2.11.1	Detach request (UE originating detach)	369
8.2.11.2	Detach request (UE terminated detach).....	370
8.2.11.2.1	Message definition.....	370
8.2.11.2.2	EMM cause.....	370
8.2.12	Downlink NAS Transport.....	370
8.2.13	EMM information.....	370
8.2.13.1	Message definition	370
8.2.13.2	Full name for network.....	371
8.2.13.3	Short name for network.....	371
8.2.13.4	Local time zone	371
8.2.13.5	Universal time and local time zone	371
8.2.13.6	Network daylight saving time	372
8.2.14	EMM status.....	372
8.2.15	Extended service request	372
8.2.15.1	Message definition	372
8.2.15.2	CSFB response	373
8.2.15.3	EPS bearer context status.....	373
8.2.15.4	Device properties	373
8.2.15.5	UE request type	373
8.2.15.6	Paging restriction	373
8.2.16	GUTI reallocation command	373
8.2.16.1	Message definition	373
8.2.16.2	TAI list	374
8.2.16.3	DCN-ID.....	374
8.2.16.4	UE radio capability ID	374
8.2.16.5	UE radio capability ID deletion indication.....	374
8.2.17	GUTI reallocation complete	374
8.2.18	Identity request	375
8.2.19	Identity response	375
8.2.20	Security mode command	376
8.2.20.1	Message definition	376
8.2.20.2	IMEISV request	376
8.2.20.3	Replayed nonce _{UE}	376
8.2.20.4	Nonce _{MME}	376
8.2.20.5	Hash _{MME}	376
8.2.20.6	Replayed UE additional security capability	377
8.2.20.7	UE radio capability ID request.....	377
8.2.21	Security mode complete.....	377
8.2.21.1	Message definition	377
8.2.21.2	IMEISV	377
8.2.21.3	Replayed NAS message container	377
8.2.21.4	UE radio capability ID	377
8.2.22	Security mode reject	377
8.2.23	Security protected NAS message.....	378
8.2.24	Service reject	378
8.2.24.1	Message definition	378
8.2.24.2	T3442 value.....	379
8.2.24.3	T3346 value.....	379
8.2.24.4	T3448 value.....	379
8.2.25	Service request.....	379
8.2.26	Tracking area update accept.....	379
8.2.26.1	Message definition	379

iTeh STANDARD
PREVIEW
(standards.itech.ai)

8.2.26.2	T3412 value.....	383
8.2.26.3	GUTI.....	383
8.2.26.4	TAI list	383
8.2.26.5	EPS bearer context status	383
8.2.26.6	Location area identification.....	383
8.2.26.7	MS identity.....	383
8.2.26.8	EMM cause	383
8.2.26.9	T3402 value.....	383
8.2.26.10	T3423 value.....	383
8.2.26.11	Equivalent PLMN.....	383
8.2.26.12	Emergency number list	384
8.2.26.12A	Extended emergency number list	384
8.2.26.13	EPS network feature support.....	384
8.2.26.14	Additional update result	384
8.2.26.15	T3412 extended value	384
8.2.26.16	T3324 value.....	384
8.2.26.17	Extended DRX parameters.....	384
8.2.26.18	DCN-ID.....	384
8.2.26.19	SMS services status.....	384
8.2.26.20	Non-3GPP NW provided policies.....	385
8.2.26.21	T3448 value.....	385
8.2.26.22	Network policy.....	385
8.2.26.23	T3447 value.....	385
8.2.26.24	Ciphering key data	385
8.2.26.25	UE radio capability ID	385
8.2.26.26	UE radio capability ID deletion indication.....	385
8.2.26.27	Negotiated WUS assistance information	385
8.2.26.28	Negotiated DRX parameter in NB-SI mode	385
8.2.26.29	Negotiated IMSI offset.....	385
8.2.26.30	EPS additional request result	386
8.2.27	Tracking area update complete	386
8.2.28	Tracking area update reject	386
8.2.28.1	Message definition	386
8.2.28.2	T3346 value.....	386
8.2.28.3	Extended EMM cause	387
8.2.29	Tracking area update request	387
8.2.29.1	Message definition	387
8.2.29.2	Non-current native NAS key set identifier	390
8.2.29.3	GPRS ciphering key sequence number	390
8.2.29.4	Old P-TMSI signature	390
8.2.29.5	Additional GUTI	390
8.2.29.6	Nonce _{UE}	390
8.2.29.7	UE network capability	390
8.2.29.8	Last visited registered TAI	390
8.2.29.9	DRX parameter	391
8.2.29.10	UE radio capability information update needed	391
8.2.29.11	EPS bearer context status	391
8.2.29.12	MS network capability	391
8.2.29.13	Old location area identification	391
8.2.29.14	TMSI status	391
8.2.29.15	Mobile station classmark 2	391
8.2.29.16	Mobile station classmark 3	391
8.2.29.17	Supported Codecs	391
8.2.29.18	Additional update type	391
8.2.29.19	Voice domain preference and UE's usage setting	391
8.2.29.20	Old GUTI type	391
8.2.29.21	Device properties	392
8.2.29.22	MS network feature support	392
8.2.29.23	TMSI based NRI container	392
8.2.29.24	T3324 value.....	392
8.2.29.25	T3412 extended value	392
8.2.29.26	Extended DRX parameters	392

8.2.29.27	UE additional security capability	392
8.2.29.28	UE status	392
8.2.29.29	Additional information requested.....	392
8.2.29.30	N1 UE network capability.....	392
8.2.29.31	UE radio capability ID availability IE.....	392
8.2.29.32	DRX parameter in NB-S1 mode	392
8.2.29.33	Requested WUS assistance information.....	392
8.2.29.34	Requested IMSI offset.....	393
8.2.29.35	UE request type	393
8.2.29.36	Paging restriction	393
8.2.30	Uplink NAS Transport.....	393
8.2.31	Downlink generic NAS transport.....	393
8.2.31.1	Message definition	393
8.2.31.2	Additional information.....	394
8.2.32	Uplink generic NAS transport	394
8.2.32.1	Message definition	394
8.2.32.2	Additional information.....	394
8.2.33	CONTROL PLANE SERVICE REQUEST	394
8.2.33.1	Message definition	394
8.2.33.2	ESM message container	395
8.2.33.3	NAS message container	395
8.2.33.4	EPS bearer context status	395
8.2.33.5	Device properties	395
8.2.33.6	UE request type	395
8.2.33.7	Paging restriction	395
8.2.34	Service Accept	396
8.2.34.1	Message definition	396
8.2.34.2	EPS bearer context status	396
8.2.34.3	T3448 value.....	396
8.2.34.4	EPS additional request result	396
8.3	EPS session management messages	396
8.3.1	Activate dedicated EPS bearer context accept	396
8.3.1.1	Message definition	396
8.3.1.2	Protocol configuration options	397
8.3.1.3	NBIFOM container	397
8.3.1.4	Extended protocol configuration options	397
8.3.2	Activate dedicated EPS bearer context reject	397
8.3.2.1	Message definition	397
8.3.2.2	Protocol configuration options	398
8.3.2.3	NBIFOM container	398
8.3.2.4	Extended protocol configuration options	398
8.3.3	Activate dedicated EPS bearer context request	398
8.3.3.1	Message definition	398
8.3.3.2	Transaction identifier	399
8.3.3.3	Negotiated QoS	399
8.3.3.4	Negotiated LLC SAPI	399
8.3.3.5	Radio priority	399
8.3.3.6	Packet flow identifier	400
8.3.3.7	Protocol configuration options	400
8.3.3.8	WLAN offload indication	400
8.3.3.9	NBIFOM container	400
8.3.3.10	Extended protocol configuration options	400
8.3.3.11	Extended EPS QoS.....	400
8.3.4	Activate default EPS bearer context accept	400
8.3.4.1	Message definition	400
8.3.4.2	Protocol configuration options	401
8.3.4.3	Extended protocol configuration options	401
8.3.5	Activate default EPS bearer context reject	401
8.3.5.1	Message definition	401
8.3.5.2	Protocol configuration options	402
8.3.5.3	Extended protocol configuration options	402
8.3.6	Activate default EPS bearer context request	402