

FINAL
DRAFT

INTERNATIONAL
STANDARD

ISO/IEC
FDIS
7816-6

ISO/IEC JTC 1/SC 17

Secretariat: BSI

Voting begins on:
2015-11-25

Voting terminates on:
2016-01-25

Identification cards — Integrated circuit cards —

Part 6: Interindustry data elements for interchange

Cartes d'identification — Cartes à circuit intégré —

Partie 6: Éléments de données intersectoriels pour les échanges

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/IEC FDIS 7816-6:2015(E)

© ISO/IEC 2015

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/dc4720e0-0e8d-4576-951f-951f07a4d834/iso-iec-7816-6-2016>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword.....	iv
Introduction.....	vi
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Abbreviated terms and notation.....	2
5 Maintenance of interindustry data objects.....	3
6 Specific interindustry data elements.....	3
6.1 Name of an individual.....	3
6.2 Proprietary login data.....	3
6.3 Magnetic stripe data.....	3
6.4 PIN usage policy.....	3
6.5 Login template.....	4
6.6 Qualified name template.....	5
6.7 Cardholder image template.....	5
6.8 Application image template.....	6
6.9 Display control template.....	6
7 Identification of integrated circuit manufacturers.....	6
7.1 General.....	6
7.2 Identifier.....	6
7.3 Rules for assignment.....	7
8 Interchange profile.....	7
9 Interindustry data elements in alphabetic order.....	7
10 Interindustry tags in numeric order.....	14
11 Interindustry templates.....	27
11.1 Interindustry data objects within interindustry templates.....	27
11.2 Interindustry templates defining a context.....	29
Annex A (normative) Application for integrated circuit manufacturers number.....	31
Bibliography.....	32

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.

This third edition cancels and replaces the second edition (ISO/IEC 7816-6:2004), which has been technically revised. It also incorporates the Technical Corrigendum ISO/IEC 7816-6:2004/Cor. 1:2006.

ISO/IEC 7816 consists of the following parts, under the general title *Identification cards — Integrated circuit cards*:

- *Part 1: Cards with contacts — Physical characteristics*
- *Part 2: Cards with contacts — Dimensions and location of the contacts*
- *Part 3: Cards with contacts — Electrical interface and transmission protocols*
- *Part 4: Organization, security and commands for interchange*
- *Part 5: Registration of application providers*
- *Part 6: Interindustry data elements for interchange*
- *Part 7: Interindustry commands for Structured Card Query Language (SCQL)*
- *Part 8: Commands and mechanisms for security operations*
- *Part 9: Commands for card management*
- *Part 10: Electronic signals and answer to reset for synchronous cards*
- *Part 11: Personal verification through biometric methods*
- *Part 12: Cards with contacts — USB electrical interface and operating procedures*
- *Part 13: Commands for application management in a multi-application environment*

— Part 15: Cryptographic information application

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/dc4720e0-0e8d-4576-951f-951f07a4d834/iso-iec-7816-6-2016>

Introduction

ISO/IEC 7816 is a series of International Standards specifying integrated circuit cards and the use of such cards for interchange. These cards are identification cards intended for information exchange negotiated between the outside world and the integrated circuit in the card. As a result of an information exchange, the card delivers information (computation result, stored data) and/or modifies its content (data storage, event memorization).

- Five parts are specific to cards with galvanic contacts and three of them specify electrical interfaces.
 - ISO/IEC 7816-1 specifies physical characteristics for cards with contacts.
 - ISO/IEC 7816-2 specifies dimensions and location of the contacts.
 - ISO/IEC 7816-3 specifies electrical interface and transmission protocols for asynchronous cards.
 - ISO/IEC 7816-10 specifies electrical interface and answer to reset for synchronous cards.
 - ISO/IEC 7816-12 specifies electrical interface and operating procedures for USB cards.
- All the other parts are independent from the physical interface technology. They apply to cards accessed by contacts and/or by radio frequency.
 - ISO/IEC 7816-4 specifies organization, security and commands for interchange.
 - ISO/IEC 7816-5 specifies registration of application providers.
 - ISO/IEC 7816-6 specifies interindustry data elements for interchange.
 - ISO/IEC 7816-7 specifies commands for structured card query language.
 - ISO/IEC 7816-8 specifies commands for security operations.
 - ISO/IEC 7816-9 specifies commands for card management.
 - ISO/IEC 7816-11 specifies personal verification through biometric methods.
 - ISO/IEC 7816-13 specifies commands for handling the life cycle of applications.
 - ISO/IEC 7816-15 specifies cryptographic information application.

ISO/IEC 10536 specifies access by close coupling. ISO/IEC 14443 and ISO/IEC 15693 specify access by radio frequency. Such cards are also known as contactless cards.

Identification cards — Integrated circuit cards —

Part 6: Interindustry data elements for interchange

1 Scope

This part of ISO/IEC 7816 specifies directly or by reference, data elements, including composite data elements, that may be used in interindustry interchange.

It identifies the following characteristics of each data element:

- identifier;
- name;
- description and reference;
- format and coding (if not available in other ISO standards or parts of ISO/IEC 7816).

The layout of each data element is described as seen at the interface between the interface device and the card.

This part of ISO/IEC 7816 provides the definition of data elements without consideration of any restrictions on the usage of the data elements.

It does not cover the internal implementation within the card and/or the outside world. With the exception of login data objects (see 6.5), only application class tags are eligible in this part of ISO/IEC 7816.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 4909, *Identification cards — Financial transaction cards — Magnetic stripe data content for track 3*

ISO/IEC 7813, *Information technology — Identification cards — Financial transaction cards*

ISO/IEC 7816 (all parts), *Identification cards — Integrated circuit cards*

ISO/IEC 10918-1, *Information technology — Digital compression and coding of continuous-tone still images: Requirements and guidelines — Part 1*

ISO/IEC 11544, *Information technology — Coded representation of picture and audio information — Progressive bi-level image compression*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

**3.1
data element**

item of information seen at the interface for which are defined a name, a description of logical content, a format and a coding

[SOURCE: ISO/IEC 7816-4:2013, 3.16, modified]

**3.2
data object**

information seen at the interface consisting of the concatenation of a mandatory tag field, a mandatory length field and a conditional value field

[SOURCE: ISO/IEC 7816-4:2013, 3.17]

**3.3
template**

concatenation of BER-TLV data objects forming the value field of a constructed BER-TLV data object

[SOURCE: ISO/IEC 7816-4:2013, 3.58]

4 Abbreviated terms and notation

For the purposes of this part of ISO/IEC 7816, the following abbreviated terms and notations apply.

- a alphabetic character
- n numeric (binary-coded decimal format)
- s special character
- an alphanumeric character
- ans alphanumeric and special characters
- .. denotes a range of values between two numbers
- BCD Binary Coded Decimal

Any number following the notation denotes the number of digits or characters.

EXAMPLE

- a3 means three alphabetic characters;
- n..3 means one, two or three binary-coded decimal digits;
- n2..4 means two, three or four binary-coded decimal digits.

If the number of bits representing a data element is not a multiple of eight, then the mapping into a byte string should be defined in the context of the respective data element. If not specified otherwise, the appropriate number of bits shall be set to one in the last byte starting from bit 1.

- YYMMDD 6 BCD-encoded digits
- YYYYMMDD 8 BCD-encoded digits
- YDDDDHHMMSS 10 BCD-encoded digits

5 Maintenance of interindustry data objects

It is the intention that every interindustry data object, specified at the time of publication, should be listed in this part of ISO/IEC 7816. To allow the introduction, deletion or amendment of any data object, the following procedures shall be adopted.

- **Interindustry data objects from ISO/IEC 7816** — if any part of ISO/IEC 7816 introduces new data objects, then the normal ballot process shall approve them. Following publication of that part of ISO/IEC 7816, these data objects will be incorporated into this part of ISO/IEC 7816 at the next revision.
- **Interindustry data objects from other standards** — for such data objects, an amendment to this part of ISO/IEC 7816 will be required and this will be subject to the normal ISO/IEC JTC 1 voting procedures. Following successful ballot the data objects will be incorporated into this part of ISO/IEC 7816.
- **Allocation authority** — once an application class tag is allocated to a norm as described above, this norm becomes the allocation authority for all context-specific Data Objects it endorses and encapsulates under the aforementioned tag.

6 Specific interindustry data elements

According to its needs, any application may use the following interindustry data elements and templates.

6.1 Name of an individual

Referenced by tag '5B', this interindustry data element consists of up to 39 bytes; each byte is a character as defined in ISO/IEC 7501-1. The data element consists of surname, i.e. family name, given name(s), i.e. forename(s), name suffix, e.g. Jr., number, and filler(s), all coded according to ISO/IEC 8859-1.

National languages with non-Latin characters shall be transliterated or transcribed into the Latin alphabet using the appropriate ISO standard. In cases where names cannot be shown in full or a special alphabet is needed or the transliteration or transcription is not sufficient, the qualified name template should be used.

6.2 Proprietary login data

Referenced by tag '5E', this interindustry data element consists of login data with proprietary structures not specified in ISO/IEC 7816.

6.3 Magnetic stripe data

The coding of the magnetic stripe data is as follows:

- referenced respectively by tags '5F21', '5F22' and '5F23', these interindustry data elements shall code card tracks 1, 2 and 3. Such a tag shall be used when the data element is identical to the data coded on the corresponding track on the magnetic stripe of the card (see ISO/IEC 7813 and ISO/IEC 4909);
- referenced respectively by tags '56', '57' and '58', these interindustry data elements shall code application tracks 1, 2 and 3. Such a tag shall be used when, while formatted according to ISO/IEC 7813 and ISO/IEC 4909, the data element may differ from the data coded on the corresponding track of the magnetic stripe of the card.

6.4 PIN usage policy

Referenced by tag '5F2F', this interindustry data element shall consist of two bytes. It lists the tests the terminal shall perform in order to determine whether a personal identification number (PIN) is applicable to the current transaction, and, therefore, whether the terminal should prompt for the PIN. If

set to one, bit 8 of the first byte specifies that a PIN applies to this application and the terminal should prompt for the PIN. The meaning of the other fifteen bits is application-dependent. If all bits are set to zero, then the terminal should not prompt for the PIN. If bit 8 of the first byte is set to one or if any test implies a PIN, but the PIN cannot be presented, then the action to take is application-dependent.

6.5 Login template

Referenced by tag '6A', this interindustry template shall consist of one or more primitive data objects. Within the login template, the context-specific class (first byte in the range '80' to 'BF') is reserved for login data objects such as qualifiers, numbers, texts and delay indicators, as listed in [Table 1](#) and specified hereafter.

Table 1 — Login data objects

Tag (hex)	Meaning
6A	Interindustry template for nesting login data objects with the following tags
80	Qualifier
81	Number
82	Text
83, 84	Delay indicators

In this context, ISO/IEC JTC 1/SC17 reserves any other data object of the context-specific class (first byte from '80' to 'BF')

- **Qualifier** — referenced by tag '80' in a login template, this data element shall consist of one to nine bytes: a mandatory first byte coding a rank, followed by up to eight optional bytes coding a mnemonic. It shall qualify the subsequent objects in the template until the next qualifier, if any.
 - The rank is a number from 0 to 255. If two or more qualifiers have the same rank within the same context, then only the set of objects qualified by the most recent one is valid.
 - The mnemonic is a string of up to eight bytes consisting of 7-bit characters (bit 8 set to 0; see ISO/IEC 646) to display at the man-machine interface.
- **Number** — Referenced by tag '81' in a login template, this data element shall consist of an even number of quartets where each quartet codes one character for representing a telephone number according to [Table 2](#).

Table 2 — Telephone number

Quartet	Character	Meaning
'0' to '9'	0 to 9	Decimal digits
'A'	(Opening bracket
'B')	Closing bracket
'C'	C	Requirement for connecting to the line before continuing
'D'	+	Introduction to an international telephone number
'E'	-	If first, introduction of a number to use without prefix If not first, requirement for a delay (two seconds) before continuing
'F'		Reserved for padding

- **Text** — referenced by tag '82' in a login template, this data element shall consist of one or more bytes where each byte codes one character. Bit 8 sets the difference between data characters (bit 8 set to zero) and control characters (bit 8 set to one). The byte string consists of one or more strings

of data characters (7-bit character, see ISO/IEC 646) separated by strings of control characters. The following control characters are defined.

- ‘80’ — a message has to be received before sending the next character.
- ‘C0’ — a modulation has to be present before sending the next character.
- ‘8X’ — x characters have to be received in echo before waiting for a message.
- **Delay indicators** — referenced by tag ‘83’ or ‘84’ in a login template, this data element shall consist of one byte as specified in [Table 3](#).
 - When present, a delay indicator data object with tag ‘83’ fixes the time for detecting an end of message. The default value shall be two seconds.
 - When present, a delay indicator data object with tag ‘84’ fixes the time for detecting an absence of response. The default value shall be 60 seconds.

Table 3 — Delay indicator byte

b8	b7	b6	b5	b4	b3	b2	b1	Meaning
0	0							Any other value is reserved for future use by ISO/IEC JTC 1/SC 17.
-	-	x	x	-	-	-	-	The time unit is
-	-	0	0	-	-	-	-	— 100 ms
-	-	0	1	-	-	-	-	— 1 s
-	-	1	0	-	-	-	-	— 10 s
-	-	1	1	-	-	-	-	— 100 s
				x	x	x	x	Number of time units from 0 to 15

6.6 Qualified name template

Referenced by tag ‘6B’, this interindustry template shall consist of

- one or more object identifiers (tag ‘06’) referring to the standards defining the qualified name presentation,
- a name (tag ‘80’ or ‘A0’), the value and coding of which are defined by the aforementioned standards,
- other related optional information (e.g. sex, nationality, place of birth).

6.7 Cardholder image template

Referenced by tag ‘6C’, this interindustry template shall contain at least one data object as defined hereafter, possibly preceded by an tag allocation authority indicator [see ISO/IEC 7816 (all parts)] for identifying the authority responsible for the data object format.

- **Cardholder biometric data** — referenced by tag ‘5F2E’, this interindustry data element contains biometric data for verifying the claimed identity of the person presenting the card. Examples of biometric data are fingerprints, palm prints, voiceprints, dynamic signatures, etc.
- **Cardholder portrait image** — referenced by tag ‘5F40’, this interindustry data element shall be formatted as defined in ISO/IEC 10918-1, unless otherwise specified and/or requested by an authority.
- **Cardholder handwritten signature image** — referenced by tag ‘5F43’, this interindustry data element shall be formatted as defined in ISO/IEC 11544 unless otherwise specified and/or requested by an authority.

The use of this interindustry data object should be associated with appropriate security measures.

Further information on personal verification through biometric methods may be found in ISO/IEC 7816 (all parts).

6.8 Application image template

Referenced by tag '6D', this interindustry template shall contain at least an application image (tag '5F44'), i.e. an icon or a logo related to the application. It may also contain an authority indicator [see ISO/IEC 7816 (all parts)] identifying the authority responsible for the data format of the application image. In the absence of authority indicator, the format shall be as defined in ISO/IEC 10918-1.

6.9 Display control template

Referenced by tag '7F20', this interindustry template may contain one or more data objects, the value of which, either directly or indirectly through templates, is not intended to be displayed and should only be used, when relevant, for processing of transmission.

7 Identification of integrated circuit manufacturers

7.1 General

This Clause specifies

- a numbering system for integrated circuit manufacturer identifiers, and
- rules for registration of integrated circuit manufacturers and rules for assignment of identifiers

to identify manufacturers of integrated circuits to be embedded in contact and/or contactless integrated circuits cards. The assigned values of the integrated circuit manufacturer identifiers will form the register, published as SC 17 Standing Document 5.

Applications for a number may be made using the form in Annex A.

7.2 Identifier

The identifier is referenced by tag '5F4D'. It may be present in pre-issuing data (compact header '6Y' in the historical bytes and interindustry tag '46' in EF.ATR/INFO) on a proprietary basis.

NOTE In amendment 1 to the first edition of this part of ISO/IEC 7816, tag '5F4B' references an integrated circuit manufacturer identifier (a data element of one byte). In the first edition of ISO/IEC 7816-9, tag '5F4B' references a certificate holder authorization (a data element of five or more bytes). Consequently, tag '5F4B' is now deprecated in ISO/IEC 7816 (all parts).

The identifier consists of one byte where the bits are not all set to one; the value 'FF' is reserved for future extension. Longer identifiers are reserved for future use by ISO/IEC JTC 1/SC 17.

The identifier byte shall be used according to [Table 4](#).

Table 4 — Identifier byte

Value	Meaning
'00'	Reserved for future use by ISO/IEC JTC 1/SC 17
'01' - '7E'	Reserved for the register
'7F', '80'	Reserved for future use by ISO/IEC JTC 1/SC 17
'81' - 'FE'	Proprietary
'FF'	Reserved for future extension by ISO/IEC JTC 1/SC 17