

ETSI TS 123 501 V17.4.0 (2022-05)



iTeh STANDARD
5G;
System architecture for the 5G System (5GS)
(3GPP TS 23.501 version 17.4.0 Release 17)
(standards.iteh.ai)

[ETSI TS 123 501 V17.4.0 \(2022-05\)](https://standards.iteh.ai/catalog/standards/sist/84eb229e-1a0f-4f4a-93a5-ac02a10960c0/etsi-ts-123-501-v17-4-0-2022-05)
<https://standards.iteh.ai/catalog/standards/sist/84eb229e-1a0f-4f4a-93a5-ac02a10960c0/etsi-ts-123-501-v17-4-0-2022-05>



ReferenceRTS/TSGS-0223501vh40

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.

All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	19
1 Scope	20
2 References	20
3 Definitions and abbreviations.....	25
3.1 Definitions	25
3.2 Abbreviations	31
4 Architecture model and concepts	34
4.1 General concepts	34
4.2 Architecture reference model	34
4.2.1 General.....	34
4.2.2 Network Functions and entities	35
4.2.3 Non-roaming reference architecture	36
4.2.4 Roaming reference architectures.....	40
4.2.5 Data Storage architectures.....	44
4.2.5a Radio Capabilities Signalling optimisation.....	46
4.2.6 Service-based interfaces	46
4.2.7 Reference points	47
4.2.8 Support of non-3GPP access.....	50
4.2.8.0 General	50
4.2.8.1 General Concepts to Support Trusted and Untrusted Non-3GPP Access	50
4.2.8.1A General Concepts to support Wireline Access	51
4.2.8.2 Architecture Reference Model for Trusted and Untrusted Non-3GPP Accesses	52
4.2.8.2.1 Non-roaming Architecture.....	52
4.2.8.2.2 LBO Roaming Architecture.....	53
4.2.8.2.3 Home-routed Roaming Architecture.....	55
4.2.8.3 Reference Points for Non-3GPP Access.....	57
4.2.8.3.1 Overview	57
4.2.8.3.2 Requirements on Ta.....	58
4.2.8.4 Architecture Reference Model for Wireline Access network.....	58
4.2.8.5 Access to 5GC from devices that do not support 5GC NAS over WLAN access.....	59
4.2.8.5.1 General	59
4.2.8.5.2 Reference Architecture.....	60
4.2.8.5.3 Network Functions	60
4.2.8.5.4 Reference Points.....	60
4.2.9 Network Analytics architecture	61
4.2.10 Architecture Reference Model for ATSSS Support.....	61
4.2.11 Architecture for 5G multicast-broadcast services	62
4.2.12 Architecture for Proximity based Services (ProSe) in 5GS	62
4.2.13 Architecture enhancements for Edge Computing	62
4.2.14 Architecture for Support of Uncrewed Aerial Systems connectivity, identification and tracking	63
4.2.15 Architecture to support WLAN connection using 5G credentials without 5GS registration	63
4.3 Interworking with EPC.....	63
4.3.1 Non-roaming architecture	63
4.3.2 Roaming architecture.....	64
4.3.3 Interworking between 5GC via non-3GPP access and E-UTRAN connected to EPC.....	66
4.3.3.1 Non-roaming architecture	66
4.3.3.2 Roaming architecture	67
4.3.4 Interworking between ePDG connected to EPC and 5GS	69
4.3.4.1 Non-roaming architecture	69
4.3.4.2 Roaming architectures.....	70
4.3.5 Service Exposure in Interworking Scenarios	72

4.3.5.1	Non-roaming architecture	72
4.3.5.2	Roaming architectures.....	73
4.4	Specific services	74
4.4.1	Public Warning System	74
4.4.2	SMS over NAS	74
4.4.2.1	Architecture to support SMS over NAS.....	74
4.4.2.2	Reference point to support SMS over NAS	76
4.4.2.3	Service based interface to support SMS over NAS	76
4.4.3	IMS support	76
4.4.4	Location services	76
4.4.4.1	Architecture to support Location Services	76
4.4.4.2	Reference point to support Location Services.....	76
4.4.4.3	Service Based Interfaces to support Location Services.....	76
4.4.5	Application Triggering Services	77
4.4.6	5G LAN-type Services.....	77
4.4.6.1	User plane architecture to support 5G LAN-type service	77
4.4.6.2	Reference points to support 5G LAN-type service	77
4.4.7	MSISDN-less MO SMS Service.....	77
4.4.8	Architecture to enable Time Sensitive Communication and Time Synchronization	78
4.4.8.1	General	78
4.4.8.2	Architecture to support IEEE Time Sensitive Networking	78
4.4.8.3	Architecture for AF requested support of Time Sensitive Communication and Time Synchronization	79
5	High level features.....	80
5.1	General	80
5.2	Network Access Control	80
5.2.1	General.....	80
5.2.2	Network selection	81
5.2.2a	Void	81
5.2.3	Identification and authentication.....	81
5.2.4	Authorisation	81
5.2.5	Access control and barring	81
5.2.6	Policy control.....	82
5.2.7	Lawful Interception.....	82
5.3	Registration and Connection Management.....	82
5.3.1	General.....	82
5.3.2	Registration Management	82
5.3.2.1	General	82
5.3.2.2	5GS Registration Management states.....	82
5.3.2.2.1	General	82
5.3.2.2.2	RM-DEREGISTERED state.....	83
5.3.2.2.3	RM-REGISTERED state	83
5.3.2.2.4	5GS Registration Management State models	84
5.3.2.3	Registration Area management.....	84
5.3.2.4	Support of a UE registered over both 3GPP and Non-3GPP access	86
5.3.3	Connection Management	87
5.3.3.1	General	87
5.3.3.2	5GS Connection Management states.....	87
5.3.3.2.1	General	87
5.3.3.2.2	CM-IDLE state	88
5.3.3.2.3	CM-CONNECTED state	88
5.3.3.2.4	5GS Connection Management State models	89
5.3.3.2.5	CM-CONNECTED with RRC Inactive state	89
5.3.3.3	NAS signalling connection management	91
5.3.3.3.1	General	91
5.3.3.3.2	NAS signalling connection establishment	91
5.3.3.3.3	NAS signalling connection Release.....	92
5.3.3.4	Support of a UE connected over both 3GPP and Non-3GPP access	92
5.3.4	UE Mobility	92
5.3.4.1	Mobility Restrictions.....	92
5.3.4.1.1	General	92

5.3.4.1.2	Management of Service Area Restrictions	95
5.3.4.2	Mobility Pattern	96
5.3.4.3	Radio Resource Management functions	96
5.3.4.3.1	General	96
5.3.4.3.2	Preferred band(s) per data radio bearer(s)	97
5.3.4.3.3	Redirection to dedicated frequency band(s) for an S-NSSAI	97
5.3.4.4	UE mobility event notification	98
5.3.5	Triggers for network analytics	99
5.4	3GPP access specific aspects	99
5.4.1	UE reachability in CM-IDLE	99
5.4.1.1	General	99
5.4.1.2	UE reachability allowing mobile terminated data while the UE is CM-IDLE	100
5.4.1.3	Mobile Initiated Connection Only (MICO) mode	100
5.4.2	UE reachability in CM-CONNECTED	101
5.4.3	Paging strategy handling	102
5.4.3.1	General	102
5.4.3.2	Paging Policy Differentiation	102
5.4.3.3	Paging Priority	103
5.4.4	UE Radio Capability handling	103
5.4.4.1	UE radio capability information storage in the AMF	103
5.4.4.1a	UE radio capability signalling optimisation (RACS)	104
5.4.4.2	Void	108
5.4.4.2a	UE Radio Capability Match Request	108
5.4.4.3	Paging assistance information	108
5.4.4a	UE MM Core Network Capability handling	109
5.4.4b	UE 5GSM Core Network Capability handling	110
5.4.5	DRX (Discontinuous Reception) framework	110
5.4.6	Core Network assistance information for RAN optimization	111
5.4.6.1	General	111
5.4.6.2	Core Network assisted RAN parameters tuning	111
5.4.6.3	Core Network assisted RAN paging information	112
5.4.7	NG-RAN location reporting	112
5.4.8	Support for identification and restriction of using unlicensed spectrum	112
5.4.9	Wake Up Signal Assistance	113
5.4.9.1	General	113
5.4.9.2	Group Wake Up Signal	114
5.4.10	Support for identification and restriction of using NR satellite access	114
5.4.11	Support for integrating NR satellite access into 5GS	115
5.4.11.1	General	115
5.4.11.2	Support of RAT types defined in 5GC for satellite access	115
5.4.11.3	Void	115
5.4.11.4	Verification of UE location	115
5.4.11.5	Network selection for NR satellite access	115
5.4.11.6	Support of Mobility Registration Update	115
5.4.11.7	Tracking Area handling for NR satellite access	116
5.4.11.8	Support for mobility Forbidden Area and Service Area Restrictions for NR satellite access	116
5.4.12	Paging Early Indication with Paging Subgrouping Assistance	116
5.4.12.1	General	116
5.4.12.2	Core Network Assistance for PEIPS	117
5.5	Non-3GPP access specific aspects	117
5.5.0	General	117
5.5.1	Registration Management	118
5.5.2	Connection Management	118
5.5.3	UE Reachability	119
5.5.3.1	UE reachability in CM-IDLE	119
5.5.3.2	UE reachability in CM-CONNECTED	120
5.6	Session Management	120
5.6.1	Overview	120
5.6.2	Interaction between AMF and SMF	123
5.6.3	Roaming	125
5.6.4	Single PDU Session with multiple PDU Session Anchors	126
5.6.4.1	General	126

5.6.4.2	Usage of an UL Classifier for a PDU Session.....	127
5.6.4.3	Usage of IPv6 multi-homing for a PDU Session.....	128
5.6.5	Support for Local Area Data Network.....	130
5.6.6	Secondary authentication/authorization by a DN-AAA server during the establishment of a PDU Session	132
5.6.7	Application Function influence on traffic routing	134
5.6.7.1	General	134
5.6.7.2	Enhancement of UP path management based on the coordination with AFs	141
5.6.8	Selective activation and deactivation of UP connection of existing PDU Session	142
5.6.9	Session and Service Continuity	143
5.6.9.1	General	143
5.6.9.2	SSC mode.....	143
5.6.9.2.1	SSC Mode 1.....	143
5.6.9.2.2	SSC Mode 2.....	144
5.6.9.2.3	SSC Mode 3.....	144
5.6.9.3	SSC mode selection.....	144
5.6.10	Specific aspects of different PDU Session types	145
5.6.10.1	Support of IP PDU Session type	145
5.6.10.2	Support of Ethernet PDU Session type	146
5.6.10.3	Support of Unstructured PDU Session type	147
5.6.10.4	Maximum Transfer Unit size considerations	148
5.6.11	UE presence in Area of Interest reporting usage by SMF.....	149
5.6.12	Use of Network Instance.....	150
5.6.13	Always-on PDU session	151
5.6.14	Support of Framed Routing	151
5.6.15	Triggers for network analytics.....	152
5.7	QoS model.....	152
5.7.1	General Overview.....	152
5.7.1.1	QoS Flow	152
5.7.1.2	QoS Profile.....	153
5.7.1.2a	Alternative QoS Profile.....	153
5.7.1.3	Control of QoS Flows	153
5.7.1.4	QoS Rules	154
5.7.1.5	QoS Flow mapping	154
5.7.1.6	DL traffic	156
5.7.1.7	UL Traffic	157
5.7.1.8	AMBR/MFBR enforcement and rate limitation.....	157
5.7.1.9	Precedence Value.....	158
5.7.1.10	UE-Slice-MBR enforcement and rate limitation.....	158
5.7.1.11	QoS aspects of home-routed roaming	158
5.7.2	5G QoS Parameters.....	158
5.7.2.1	5QI	158
5.7.2.2	ARP	159
5.7.2.3	RQA	159
5.7.2.4	Notification control	159
5.7.2.4.1	General	159
5.7.2.4.1a	Notification Control without Alternative QoS Profiles	159
5.7.2.4.1b	Notification control with Alternative QoS Profiles	160
5.7.2.4.2	Usage of Notification control with Alternative QoS Profiles at handover	161
5.7.2.4.3	Usage of Notification control with Alternative QoS Profiles during QoS Flow establishment and modification.....	162
5.7.2.5	Flow Bit Rates.....	162
5.7.2.6	Aggregate Bit Rates	162
5.7.2.7	Default values	163
5.7.2.8	Maximum Packet Loss Rate.....	164
5.7.2.9	Wireline access network specific 5G QoS parameters.....	164
5.7.3	5G QoS characteristics.....	164
5.7.3.1	General	164
5.7.3.2	Resource Type.....	164
5.7.3.3	Priority Level	164
5.7.3.4	Packet Delay Budget.....	165
5.7.3.5	Packet Error Rate	166

5.7.3.6	Averaging Window	166
5.7.3.7	Maximum Data Burst Volume	166
5.7.4	Standardized 5QI to QoS characteristics mapping.....	166
5.7.5	Reflective QoS.....	172
5.7.5.1	General	172
5.7.5.2	UE Derived QoS Rule.....	172
5.7.5.3	Reflective QoS Control	173
5.7.6	Packet Filter Set	174
5.7.6.1	General	174
5.7.6.2	IP Packet Filter Set.....	174
5.7.6.3	Ethernet Packet Filter Set.....	175
5.8	User Plane Management.....	175
5.8.1	General.....	175
5.8.2	Functional Description.....	176
5.8.2.1	General	176
5.8.2.2	UE IP Address Management	176
5.8.2.2.1	General	176
5.8.2.2.2	Routing rules configuration	178
5.8.2.2.3	The procedure of Stateless IPv6 Address Autoconfiguration	178
5.8.2.3	Management of CN Tunnel Info	179
5.8.2.3.1	General	179
5.8.2.3.2	Void	179
5.8.2.3.3	Management of CN Tunnel Info in the UPF	179
5.8.2.4	Traffic Detection	179
5.8.2.4.1	General	179
5.8.2.4.2	Traffic Detection Information	179
5.8.2.5	Control of User Plane Forwarding	180
5.8.2.5.1	General	180
5.8.2.5.2	Data forwarding between the SMF and UPF	180
5.8.2.5.3	Support of Ethernet PDU Session type.....	181
5.8.2.6	Charging and Usage Monitoring Handling	182
5.8.2.6.1	General	182
5.8.2.6.2	Activation of Usage Reporting in UPF	182
5.8.2.6.3	Reporting of Usage Information towards SMF	183
5.8.2.7	PDU Session and QoS Flow Policing	183
5.8.2.8	PCC Related Functions	183
5.8.2.8.1	Activation/Deactivation of predefined PCC rules	183
5.8.2.8.2	Enforcement of Dynamic PCC Rules	184
5.8.2.8.3	Redirection	184
5.8.2.8.4	Support of PFD Management	185
5.8.2.9	Functionality of Sending of "End marker".....	185
5.8.2.9.0	Introduction	185
5.8.2.9.1	UPF Constructing the "End marker" Packets	185
5.8.2.9.2	SMF Constructing the "End marker" Packets.....	186
5.8.2.10	UP Tunnel Management	186
5.8.2.11	Parameters for N4 session management.....	186
5.8.2.11.1	General	186
5.8.2.11.2	N4 Session Context	188
5.8.2.11.3	Packet Detection Rule	188
5.8.2.11.4	QoS Enforcement Rule.....	191
5.8.2.11.5	Usage Reporting Rule.....	194
5.8.2.11.6	Forwarding Action Rule	197
5.8.2.11.7	Usage Report generated by UPF	200
5.8.2.11.8	Multi-Access Rule	201
5.8.2.11.9	Bridge Information	202
5.8.2.11.10	Void	202
5.8.2.11.11	Session Reporting Rule	202
5.8.2.11.12	Session reporting generated by UPF.....	203
5.8.2.11.13	Void	203
5.8.2.11.14	TSC Management Information.....	203
5.8.2.11.15	Downlink Data Report generated by UPF	204
5.8.2.12	Reporting of the UE MAC addresses used in a PDU Session.....	204

5.8.2.13	Support for 5G VN group communication.....	204
5.8.2.13.0	General	204
5.8.2.13.1	Support for unicast traffic forwarding of a 5G VN.....	205
5.8.2.13.2	Support for unicast traffic forwarding update due to UE mobility	206
5.8.2.13.3	Support for user plane traffic replication in a 5G VN	207
5.8.2.14	Inter PLMN User Plane Security functionality	209
5.8.2.15	Reporting of satellite backhaul to SMF.....	209
5.8.2.16	Support for L2TP tunnelling on N6	209
5.8.3	Explicit Buffer Management.....	210
5.8.3.1	General	210
5.8.3.2	Buffering at UPF	210
5.8.3.3	Buffering at SMF	211
5.8.4	SMF Pause of Charging.....	211
5.9	Identifiers	211
5.9.1	General.....	211
5.9.2	Subscription Permanent Identifier	211
5.9.2a	Subscription Concealed Identifier.....	212
5.9.3	Permanent Equipment Identifier	212
5.9.4	5G Globally Unique Temporary Identifier	212
5.9.5	AMF Name	213
5.9.6	Data Network Name (DNN)	213
5.9.7	Internal-Group Identifier.....	213
5.9.8	Generic Public Subscription Identifier.....	214
5.9.9	AMF UE NGAP ID	214
5.9.10	UE Radio Capability ID	214
5.10	Security aspects.....	214
5.10.1	General.....	214
5.10.2	Security Model for non-3GPP access	215
5.10.2.1	Signalling Security	215
5.10.3	PDU Session User Plane Security.....	215
5.11	Support for Dual Connectivity, Multi-Connectivity.....	217
5.11.1	Support for Dual Connectivity.....	217
5.12	Charging.....	218
5.12.1	General.....	218
5.12.2	Usage Data Reporting for Secondary RAT.....	218
5.12.3	Secondary RAT Periodic Usage Data Reporting Procedure.....	219
5.13	Support for Edge Computing.....	219
5.14	Policy Control	220
5.15	Network slicing	220
5.15.1	General.....	220
5.15.2	Identification and selection of a Network Slice: the S-NSSAI and the NSSAI	221
5.15.2.1	General	221
5.15.2.2	Standardised SST values	222
5.15.3	Subscription aspects.....	223
5.15.4	UE NSSAI configuration and NSSAI storage aspects	223
5.15.4.1	General	223
5.15.4.1.1	UE Network Slice configuration	223
5.15.4.1.2	Mapping of S-NSSAIs values in the Allowed NSSAI and in the Requested NSSAI to the S-NSSAIs values used in the HPLMN.....	226
5.15.4.2	Update of UE Network Slice configuration	226
5.15.5	Detailed Operation Overview	227
5.15.5.1	General	227
5.15.5.2	Selection of a Serving AMF supporting the Network Slices.....	227
5.15.5.2.1	Registration to a set of Network Slices.....	227
5.15.5.2.2	Modification of the Set of Network Slice(s) for a UE	232
5.15.5.2.3	AMF Re-allocation due to Network Slice(s) Support.....	233
5.15.5.3	Establishing a PDU Session in a Network Slice	234
5.15.6	Network Slicing Support for Roaming	235
5.15.7	Network slicing and Interworking with EPS	235
5.15.7.1	General	235
5.15.7.2	Idle mode aspects	236
5.15.7.3	Connected mode aspects	236

5.15.8	Configuration of Network Slice availability in a PLMN	237
5.15.9	Operator-controlled inclusion of NSSAI in Access Stratum Connection Establishment	237
5.15.10	Network Slice-Specific Authentication and Authorization	238
5.15.11	Network Slice Admission Control	240
5.15.11.0	General	240
5.15.11.1	Network Slice Admission Control for maximum number of UEs	240
5.15.11.2	Network Slice Admission Control for maximum number of PDU sessions	241
5.15.11.3	Network Slice Admission Control for Roaming	241
5.15.11.4	Network Slice status notifications and reports to a consumer NF	242
5.15.11.5	Support of Network Slice Admission Control and Interworking with EPC	242
5.15.12	Support of subscription-based restrictions to simultaneous registration of network slices	244
5.15.12.1	General	244
5.15.12.2	UE and UE configuration aspects	244
5.15.13	Support of data rate limitation per Network Slice for a UE	245
5.16	Support for specific services	246
5.16.1	Public Warning System	246
5.16.2	SMS over NAS	246
5.16.2.1	General	246
5.16.2.2	SMS over NAS transport	246
5.16.3	IMS support	246
5.16.3.1	General	246
5.16.3.2	IMS voice over PS Session Supported Indication over 3GPP access	247
5.16.3.2a	IMS voice over PS Session Supported Indication over non-3GPP access	248
5.16.3.3	Homogeneous support for IMS voice over PS Session supported indication	248
5.16.3.4	P-CSCF address delivery	248
5.16.3.5	Domain selection for UE originating sessions / calls	248
5.16.3.6	Terminating domain selection for IMS voice	249
5.16.3.7	UE's usage setting	249
5.16.3.8	Domain and Access Selection for UE originating SMS	250
5.16.3.8.1	UE originating SMS for IMS Capable UEs supporting SMS over IP	250
5.16.3.8.2	Access Selection for SMS over NAS	250
5.16.3.9	SMF support for P-CSCF restoration procedure	250
5.16.3.10	IMS Voice Service via EPS Fallback or RAT fallback in 5GS	250
5.16.3.11	P-CSCF discovery and selection	251
5.16.3.12	HSS discovery and selection	251
5.16.4	Emergency Services	251
5.16.4.1	Introduction	251
5.16.4.2	Architecture Reference Model for Emergency Services	254
5.16.4.3	Mobility Restrictions and Access Restrictions for Emergency Services	254
5.16.4.4	Reachability Management	255
5.16.4.5	SMF and UPF selection function for Emergency Services	255
5.16.4.6	QoS for Emergency Services	255
5.16.4.7	PCC for Emergency Services	255
5.16.4.8	IP Address Allocation	255
5.16.4.9	Handling of PDU Sessions for Emergency Services	256
5.16.4.9a	Handling of PDU Sessions for normal services for Emergency Registered UEs	256
5.16.4.10	Support of eCall Only Mode	256
5.16.4.11	Emergency Services Fallback	256
5.16.5	Multimedia Priority Services	257
5.16.6	Mission Critical Services	259
5.17	Interworking and Migration	260
5.17.1	Support for Migration from EPC to 5GC	260
5.17.1.1	General	260
5.17.1.2	User Plane management to support interworking with EPS	261
5.17.1.3	QoS handling for home routed roaming	262
5.17.2	Interworking with EPC	262
5.17.2.1	General	262
5.17.2.2	Interworking Procedures with N26 interface	265
5.17.2.2.1	General	265
5.17.2.2.2	Mobility for UEs in single-registration mode	266
5.17.2.3	Interworking Procedures without N26 interface	267
5.17.2.3.1	General	267

5.17.2.3.2	Mobility for UEs in single-registration mode	268
5.17.2.3.3	Mobility for UEs in dual-registration mode	269
5.17.2.3.4	Redirection for UEs in connected state	270
5.17.2.4	Mobility between 5GS and GERAN/UTRAN	270
5.17.3	Interworking with EPC in presence of Non-3GPP PDU Sessions	271
5.17.4	Network sharing support and interworking between EPS and 5GS	271
5.17.5	Service Exposure in Interworking Scenarios	271
5.17.5.1	General	271
5.17.5.2	Support of interworking for Monitoring Events	272
5.17.5.2.1	Interworking with N26 interface	272
5.17.5.2.2	Interworking without N26 interface	273
5.17.5.3	Availability or expected level of a service API	273
5.17.6	Void	274
5.17.7	Configuration Transfer Procedure between NG-RAN and E-UTRAN	274
5.17.7.1	Architecture Principles for Configuration Transfer between NG-RAN and E-UTRAN	274
5.17.7.2	Addressing, routing and relaying	275
5.17.7.2.1	Addressing	275
5.17.7.2.2	Routing	275
5.17.7.2.3	Relaying	275
5.18	Network Sharing	275
5.18.1	General concepts	275
5.18.2	Broadcast system information for network sharing	276
5.18.2a	PLMN list handling for network sharing	276
5.18.3	Network selection by the UE	277
5.18.4	Network selection by the network	277
5.18.5	Network Sharing and Network Slicing	277
5.19	Control Plane Load Control, Congestion and Overload Control	278
5.19.1	General	278
5.19.2	TNLA Load Balancing and TNLA Load Re-Balancing	278
5.19.3	AMF Load Balancing	278
5.19.4	AMF Load Re-Balancing	278
5.19.5	AMF Control Of Overload	279
5.19.5.1	General	279
5.19.5.2	AMF Overload Control	279
5.19.6	SMF Overload Control	280
5.19.7	NAS level congestion control	280
5.19.7.1	General	280
5.19.7.2	General NAS level congestion control	280
5.19.7.3	DNN based congestion control	282
5.19.7.4	S-NSSAI based congestion control	283
5.19.7.5	Group specific NAS level congestion control	285
5.19.7.6	Control Plane data specific NAS level congestion control	285
5.20	External Exposure of Network Capability	286
5.20a	Data Collection from an AF	287
5.21	Architectural support for virtualized deployments	287
5.21.0	General	287
5.21.1	Architectural support for N2	288
5.21.1.1	TNL associations	288
5.21.1.2	NGAP UE-TNLA-binding	288
5.21.1.3	N2 TNL association selection	288
5.21.2	AMF Management	288
5.21.2.1	AMF Addition/Update	288
5.21.2.2	AMF planned removal procedure	289
5.21.2.2.1	AMF planned removal procedure with UDSF deployed	289
5.21.2.2.2	AMF planned removal procedure without UDSF	290
5.21.2.3	Procedure for AMF Auto-recovery	292
5.21.3	Network Reliability support with Sets	294
5.21.3.1	General	294
5.21.3.2	NF Set and NF Service Set	294
5.21.3.3	Reliability of NF instances within the same NF Set	294
5.21.3.4	Reliability of NF Services	294
5.21.4	Network Function/NF Service Context Transfer	295

5.21.4.1	General	295
5.22	System Enablers for priority mechanism.....	295
5.22.1	General.....	295
5.22.2	Subscription-related Priority Mechanisms.....	295
5.22.3	Invocation-related Priority Mechanisms.....	296
5.22.4	QoS Mechanisms applied to established QoS Flows.....	297
5.23	Supporting for Asynchronous Type Communication.....	298
5.24	3GPP PS Data Off.....	298
5.25	Support of OAM Features	299
5.25.1	Support of Tracing: Signalling Based Activation/Deactivation of Tracing	299
5.25.2	Support of OAM-based 5G VN group management.....	299
5.26	Configuration Transfer Procedure.....	300
5.26.1	Architecture Principles for Configuration Transfer	300
5.26.2	Addressing, routing and relaying.....	301
5.26.2.1	Addressing	301
5.26.2.2	Routing.....	301
5.26.2.3	Relaying	301
5.27	Enablers for Time Sensitive Communications and Time Synchronization	301
5.27.0	General.....	301
5.27.1	Time Synchronization.....	302
5.27.1.1	General	302
5.27.1.2	Distribution of timing information.....	303
5.27.1.2.1	Distribution of 5G internal system clock.....	303
5.27.1.2.2	Distribution of grandmaster clock and time-stamping.....	303
5.27.1.3	Support for multiple (g)PTP domains	306
5.27.1.4	DS-TT and NW-TT Time Synchronization functionality	307
5.27.1.5	Detection of (g)PTP Sync and Announce timeouts.....	307
5.27.1.6	Distribution of Announce messages and best master clock selection	308
5.27.1.7	Support for PTP grandmaster function in 5GS.....	309
5.27.1.8	Exposure of Time Synchronization	309
5.27.1.9	Support for control of time distribution methods	310
5.27.1a	Periodic deterministic communication.....	311
5.27.2	TSC Assistance Information (TSCAI) and TSC Assistance Container (TSCAC).....	311
5.27.2.1	General	311
5.27.2.2	TSC Assistance Container determination based on PSFP	312
5.27.2.3	TSC Assistance Container determination by TSCTSP	312
5.27.2.4	TSCAI determination based on TSC Assistance Container	313
5.27.3	Support for TSC QoS Flows	314
5.27.4	Hold and Forward Buffering mechanism.....	314
5.27.5	5G System Bridge delay	315
5.28	Support of integration with TSN	315
5.28.1	5GS bridge management.....	315
5.28.2	5GS Bridge configuration.....	318
5.28.3	Port and user plane node management information exchange in 5GS	319
5.28.3.1	General	319
5.28.3.2	Transfer of port or user plane node management information	336
5.28.3.3	VLAN Configuration Information	336
5.28.4	QoS mapping tables.....	337
5.29	Support for 5G LAN-type service	338
5.29.1	General.....	338
5.29.2	5G VN group management	338
5.29.3	PDU Session management.....	339
5.29.4	User Plane handling.....	340
5.30	Support for non-public networks.....	341
5.30.1	General.....	341
5.30.2	Stand-alone non-public networks	341
5.30.2.0	General	341
5.30.2.1	Identifiers	342
5.30.2.2	Broadcast system information.....	342
5.30.2.3	UE configuration and subscription aspects	343
5.30.2.4	Network selection in SNPN access mode	344
5.30.2.4.1	General	344

5.30.2.4.2	Automatic network selection	344
5.30.2.4.3	Manual network selection.....	345
5.30.2.5	Network access control	345
5.30.2.6	Cell (re-)selection in SNPN access mode.....	346
5.30.2.7	Access to PLMN services via stand-alone non-public networks.....	346
5.30.2.8	Access to stand-alone non-public network services via PLMN	346
5.30.2.9	SNPN connectivity for UEs with credentials owned by Credentials Holder	347
5.30.2.9.1	General	347
5.30.2.9.2	Credentials Holder using AAA Server for primary authentication and authorization	347
5.30.2.9.3	Credentials Holder using AUSF and UDM for primary authentication and authorization.....	348
5.30.2.10	Onboarding of UEs for SNPNs	349
5.30.2.10.1	General	349
5.30.2.10.2	Onboarding Network is an SNPN	349
5.30.2.10.3	Onboarding Network is a PLMN.....	354
5.30.2.10.4	Remote Provisioning of UEs in Onboarding Network	354
5.30.2.11	UE Mobility support for SNPN.....	356
5.30.3	Public Network Integrated NPN	356
5.30.3.1	General	356
5.30.3.2	Identifiers	357
5.30.3.3	UE configuration, subscription aspects and storage.....	357
5.30.3.4	Network and cell (re-)selection, and access control.....	358
5.30.3.5	Support of emergency services in CAG cells.....	359
5.31	Support for Cellular IoT	359
5.31.1	General.....	359
5.31.2	Preferred and Supported Network Behaviour.....	360
5.31.3	Selection, steering and redirection between EPS and 5GS	361
5.31.4	Control Plane CIoT 5GS Optimisation	361
5.31.4.1	General	361
5.31.4.2	Establishment of N3 data transfer during Data Transport in Control Plane CIoT 5GS Optimisation.....	363
5.31.4.3	Control Plane Relocation Indication procedure	363
5.31.5	Non-IP Data Delivery (NIDD).....	363
5.31.6	Reliable Data Service.....	364
5.31.7	Power Saving Enhancements.....	364
5.31.7.1	General	364
5.31.7.2	Extended Discontinuous Reception (DRX) for CM-IDLE and CM-CONNECTED with RRC-INACTIVE.....	365
5.31.7.2.1	Overview	365
5.31.7.2.2	Paging for extended idle mode DRX in E-UTRA and NR connected to 5GC	366
5.31.7.2.3	Paging for a UE registered in a tracking area with heterogeneous support of extended idle mode DRX.....	367
5.31.7.3	MICO mode with Extended Connected Time	367
5.31.7.4	MICO mode with Active Time	368
5.31.7.5	MICO mode and Periodic Registration Timer Control	368
5.31.8	High latency communication	368
5.31.9	Support for Monitoring Events	369
5.31.10	NB-IoT UE Radio Capability Handling.....	370
5.31.11	Inter-RAT idle mode mobility to and from NB-IoT	370
5.31.12	Restriction of use of Enhanced Coverage	370
5.31.13	Paging for Enhanced Coverage.....	371
5.31.14	Support of rate control of user data.....	372
5.31.14.1	General	372
5.31.14.2	Serving PLMN Rate Control.....	372
5.31.14.3	Small Data Rate Control	373
5.31.15	Control Plane Data Transfer Congestion Control	374
5.31.16	Service Gap Control.....	374
5.31.17	Inter-UE QoS for NB-IoT.....	375
5.31.18	User Plane CIoT 5GS Optimisation.....	376
5.31.19	QoS model for NB-IoT	377
5.31.20	Category M UEs differentiation.....	377
5.32	Support for ATSSS.....	377
5.32.1	General.....	377

5.32.2	Multi Access PDU Sessions	379
5.32.3	Policy for ATSSS Control	381
5.32.4	QoS Support.....	382
5.32.5	Access Network Performance Measurements.....	383
5.32.5.1	General principles	383
5.32.5.1a	Address of PMF messages	385
5.32.5.2	Round Trip Time Measurements.....	386
5.32.5.2a	Packet Loss Rate Measurements	387
5.32.5.3	Access Availability/Unavailability Report.....	387
5.32.5.4	Protocol stack for user plane measurements and measurement reports.....	388
5.32.5.5	UE Assistance Operation	389
5.32.6	Support of Steering Functionalities	389
5.32.6.1	General	389
5.32.6.2	High-Layer Steering Functionalities	391
5.32.6.2.1	MPTCP Functionality.....	391
5.32.6.3	Low-Layer Steering Functionalities.....	392
5.32.6.3.1	ATSSS-LL Functionality.....	392
5.32.7	Interworking with EPS.....	393
5.32.7.1	General	393
5.32.7.2	Interworking with N26 Interface.....	393
5.32.7.3	Interworking without N26 Interface.....	394
5.32.8	ATSSS Rules	394
5.33	Support for Ultra Reliable Low Latency Communication.....	397
5.33.1	General.....	397
5.33.2	Redundant transmission for high reliability communication	398
5.33.2.1	Dual Connectivity based end to end Redundant User Plane Paths.....	398
5.33.2.2	Support of redundant transmission on N3/N9 interfaces	400
5.33.2.3	Support for redundant transmission at transport layer	402
5.33.3	QoS Monitoring to Assist URLLC Service	402
5.33.3.1	General	402
5.33.3.2	Per QoS Flow per UE QoS Monitoring.....	402
5.33.3.3	GTP-U Path Monitoring.....	403
5.34	Support of deployments topologies with specific SMF Service Areas.....	404
5.34.1	General.....	404
5.34.2	Architecture	405
5.34.2.1	SBA architecture	405
5.34.2.2	Non-roaming architecture	405
5.34.2.3	Roaming architecture	406
5.34.3	I-SMF selection, V-SMF reselection	407
5.34.4	Usage of an UL Classifier for a PDU Session controlled by I-SMF.....	408
5.34.5	Usage of IPv6 multi-homing for a PDU Session controlled by I-SMF.....	409
5.34.6	Interaction between I-SMF and SMF for the support of traffic offload by UPF controlled by the I-SMF	409
5.34.6.1	General	409
5.34.6.2	N4 information sent from SMF to I-SMF for local traffic offload.....	410
5.34.7	Event Management	411
5.34.7.1	UE's Mobility Event Management.....	411
5.34.7.2	SMF event exposure service	411
5.34.7.3	AMF implicit subscription about events related with the PDU Session	411
5.34.8	Support for Cellular IoT	412
5.34.9	Support of the Deployment Topologies with specific SMF Service Areas feature within and between PLMN(s).....	412
5.34.10	Support for 5G LAN-type service.....	412
5.35	Support for Integrated access and backhaul (IAB).....	412
5.35.1	IAB architecture and functional entities	412
5.35.2	5G System enhancements to support IAB	414
5.35.3	Data handling and QoS support with IAB	414
5.35.4	Mobility support with IAB	414
5.35.5	Charging support with IAB.....	415
5.35.6	IAB operation involving EPC.....	415
5.36	RIM Information Transfer.....	415
5.37	Support for high data rate low latency services.....	415

5.38	Support for Multi-USIM UE	415
5.38.1	General.....	415
5.38.2	Connection Release.....	416
5.38.3	Paging Cause Indication for Voice Service	416
5.38.4	Reject Paging Request	417
5.38.5	Paging Restriction.....	417
5.38.6	Paging Timing Collision Control.....	418
5.39	Remote provisioning of credentials for NSSAA or secondary authentication/authorization	418
5.39.1	General.....	418
5.39.2	Configuration for the UE	418
5.40	Support of Disaster Roaming with Minimization of Service Interruption.....	419
5.40.1	General.....	419
5.40.2	UE configuration and provisioning for Disaster Roaming.....	419
5.40.3	Disaster Condition Notification and Determination	420
5.40.4	Registration for Disaster Roaming service	420
5.40.5	Handling when a Disaster Condition is no longer applicable	420
5.40.6	Prevention of signalling overload related to Disaster Condition and Disaster Roaming service	421
5.41	NR RedCap UEs differentiation	421
5.42	Support of Non-seamless WLAN offload	422
6	Network Functions	422
6.1	General	422
6.2	Network Function Functional description	423
6.2.1	AMF.....	423
6.2.2	SMF.....	424
6.2.3	UPF.....	426
6.2.4	PCF.....	427
6.2.5	NEF.....	427
6.2.5.0	NEF functionality.....	427
6.2.5.1	Support for CAPIF.....	428
6.2.5a	Void	428
6.2.6	NRF	428
6.2.6.1	General	428
6.2.6.2	NF profile.....	429
6.2.6.3	SCP profile.....	431
6.2.7	UDM.....	431
6.2.8	AUSF	432
6.2.9	N3IWF	432
6.2.9A	TNGF.....	433
6.2.10	AF	433
6.2.11	UDR.....	433
6.2.12	UDSF	434
6.2.13	SMSF	434
6.2.14	NSSF.....	434
6.2.15	5G-EIR.....	434
6.2.16	LMF.....	434
6.2.16A	GMLC.....	434
6.2.17	SEPP	435
6.2.18	Network Data Analytics Function (NWDAF)	435
6.2.19	SCP	435
6.2.20	W-AGF	436
6.2.21	UE radio Capability Management Function (UCMF).....	436
6.2.22	TWIF	436
6.2.23	NSSAAF.....	436
6.2.24	DCCF.....	437
6.2.25	MFAF	437
6.2.26	ADRF.....	437
6.2.27	MB-SMF.....	437
6.2.27a	MB-UPF	438
6.2.27b	MBSF.....	438
6.2.27c	MBSTF	438
6.2.28	NSACF	438

iTEH STANDARD
PREVIEW
(standards.iteh.ai)

ETSI TS 123 501 V17.4.0 (2022-05)

file:ps://standards.iteh.ai/catalog/standards/sist/84eh229e-1a0f-4f4a-93a5-ac02a10960e0/etsi-ts-123-501-v17-4-0-2022-05