
**Heavy commercial vehicles and
buses — Emergency braking on a
defined path — Test method for
trajectory measurement**

*Véhicules utilitaires lourds et autobus — Freinage d'urgence sur un
passage défini — Méthodes d'essai pour la mesure de trajectoire*

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ISO 19377:2017](https://standards.iteh.ai/catalog/standards/iso/886bacde-4056-4823-9a90-5a48684543bb/iso-19377-2017)

<https://standards.iteh.ai/catalog/standards/iso/886bacde-4056-4823-9a90-5a48684543bb/iso-19377-2017>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 19377:2017](https://standards.iteh.ai/catalog/standards/iso/886bacde-4056-4823-9a90-5a48684543bb/iso-19377-2017)

<https://standards.iteh.ai/catalog/standards/iso/886bacde-4056-4823-9a90-5a48684543bb/iso-19377-2017>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Variables	2
6 Measuring equipment	3
7 Test conditions	3
7.1 General.....	3
7.2 Test track and ambient conditions.....	4
7.3 Test vehicle.....	4
7.3.1 General vehicle condition.....	4
7.3.2 Loading condition.....	4
7.3.3 Number of test runs.....	4
8 Test methods	4
8.1 Test method for braking straight ahead.....	4
8.1.1 Initial driving condition.....	4
8.1.2 Definition of the desired path and track.....	4
8.1.3 System intervention.....	5
8.2 Test method for braking in a constant radius curve.....	5
8.2.1 Initial driving condition.....	5
8.2.2 Definition of the desired path and track.....	5
8.2.3 System intervention.....	6
9 Data evaluation and presentation of results	6
9.1 General.....	6
9.2 Characteristic values.....	7
9.2.1 Maximum path deviation, $D_{P,max}$	7
9.2.2 Maximum rear axle path deviation, $D_{PR,max}$	7
9.2.3 Maximum trailer path deviation, $D_{PT,max}$	8
9.2.4 Deceleration at full braking.....	8
9.2.5 Maximum articulation angle(s) (optional).....	8
9.2.6 Corrective steering action, $\delta_{H,C}$ (for closed-loop test).....	8
9.2.7 Indication of leaving the desired track (optional).....	8
Annex A (normative) Test report — General data and test conditions	9
Annex B (informative) Example of test reports	10
Bibliography	12

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by ISO/TC 22, *Road vehicles*, Subcommittee SC 33, *Vehicle dynamics and chassis components*.

ISO 19377:2017

<https://standards.iteh.ai/catalog/standards/iso/886bacde-4056-4823-9a90-5a48684543bb/iso-19377-2017>

Introduction

The main purpose of this document is to provide repeatable and discriminatory test results.

The dynamic behaviour of a road vehicle is a very important aspect of active vehicle safety. Any given vehicle, together with its driver and the prevailing environment, constitutes a closed-loop system that is unique. The task of evaluating the dynamic behaviour is, therefore, very difficult since the significant interaction of these driver-vehicle-environment elements are each complex in themselves. A complete and accurate description of the behaviour of the road vehicle requires information obtained from a number of different tests.

Since this test method quantifies only one small part of the complete vehicle handling characteristics, the results of these tests can only be considered significant for a correspondingly small part of the overall dynamic behaviour.

Moreover, insufficient knowledge is available concerning the relationship between overall vehicle dynamic properties and accident avoidance. A substantial amount of work is necessary to acquire sufficient and reliable data on the correlation between accident avoidance and vehicle dynamic properties in general and the results of these tests in particular. Consequently, any application of this test method for regulation purposes will require proven correlation between test results and accident statistics.

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO 19377:2017](#)

<https://standards.iteh.ai/catalog/standards/iso/886bacde-4056-4823-9a90-5a48684543bb/iso-19377-2017>

Heavy commercial vehicles and buses — Emergency braking on a defined path — Test method for trajectory measurement

1 Scope

This document describes test methods for determining the deviation of the path travelled by a vehicle during a braking manoeuvre induced by an emergency braking system from a pre-defined desired path. The purpose of this document is the evaluation of the vehicle path during and following the system intervention. The corrective steering actions for keeping the vehicle on the desired path can be applied either by the driver or by a steering machine or by a driver assistance system. By making this document open for either open-loop or closed-loop testing, it is possible to apply the test method for evaluating how well the vehicle can be kept within user-defined lane markings after the system intervention, and also for evaluating the precision of the interaction between the emergency braking system and an active lane keeping system.

This document applies to heavy vehicles equipped with an advanced emergency braking system (AEBS), including commercial vehicles, commercial vehicle combinations, buses and articulated buses as defined in ISO 3833 (trucks and trailers with maximum weight above 3,5 tonnes and buses and articulated buses with maximum weight above 5 tonnes, according to ECE and EC vehicle classification, categories M3, N₂, N₃, O₃ and O₄).

NOTE The test method is intended to evaluate the entire vehicle behaviour, not for defining system requirements for the AEBS, which is done in the respective standards created by ISO/TC 204.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8855:2011, *Road vehicles — Vehicle dynamics and road-holding ability — Vocabulary*

ISO 15037-2:2002, *Road vehicles — Vehicle dynamics test methods — Part 2: General conditions for heavy vehicles and buses*

ISO 16552:2015, *Heavy commercial vehicles and buses — Stopping distance at straight-line braking with ABS — Open-loop and closed-loop test methods*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8855 and ISO 15037-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1
vehicle reference point
point fixed in the vehicle

Note 1 to entry: For use with this document, the vehicle reference point of the first vehicle unit shall be set to the following:

- $X_V = 0$ at the wheel centre of the first axle;
- $Y_V = 0$ at the centre of the connection line between the tyre contact centres of the first axle;
- $Z_V = 0$ on ground level.

3.2
activation time

t_0
point in time of intervention of the AEBS, given by a trigger signal

3.3
vehicle reference position

X_0, Y_0
lateral and longitudinal position of the reference point of the first vehicle unit at the *activation time* (3.2)

3.4
path deviation

D_{Pn}
shortest distance between the desired vehicle path and the position of the reference point of vehicle unit, n , at a certain point in time, t

4 Principle

This document specifies a method to determine the deviation of the vehicle from a defined path. The driving situation represents an intervention of an advanced emergency braking system during straight-ahead driving or in a curve on an even road surface with a uniform coefficient of friction as specified in ISO 15037-2. It is necessary that the emergency braking system of the test vehicle allows an external input for triggering the system intervention. After the triggering, the AEBS shall remain active until vehicle standstill. The test may be conducted as open-loop or as a closed-loop test. In case of an open-loop test, the steering wheel angle is kept to its initial value. In case of a closed-loop test, the driver (or a steering robot) or a lane keeping assistance system or both attempt to keep the vehicle on the desired path.

If the test is conducted with corrective steering actions by the driver, the results will strongly depend on the driver activities. This should be considered when comparing closed-loop test results. For excluding the driver influence during a closed-loop test, it is recommended to conduct the test with a steering robot which has the capability to be programmed for a desired path via GPS feedback.

NOTE By leaving the test method open for interventions of driver assistance systems other than the emergency braking system, the interactions of the systems can be investigated, e.g. the steering interventions of an active lane keeping assistance system acting during the emergency braking can be compared with the steering actions of a steering robot or a driver.

5 Variables

The variables of motion used to describe the behaviour of the vehicle shall be related to the *reference axis system* (X, Y, Z) of the first vehicle unit (see ISO 8855) with the *reference point* as described in 3.1. The variables that shall be determined for compliance with this document are the following:

- longitudinal velocity, v_x ;
- steering-wheel angle, δ_H ;

- activation time (t_0);
- longitudinal and lateral distance travelled by the vehicle reference point of the first unit (X_{V1} , Y_{V1});
- longitudinal and lateral distance travelled by the centre of the last axle i of the first unit (X_{V1Ai} , Y_{V1Ai});
- longitudinal and lateral distance travelled by the centre of the last axle ($i = i_{\max}$) of the vehicle combination (X_{VnAi} , Y_{VnAi});
- longitudinal and lateral acceleration at the vehicle reference point, a_x and a_y .

It is recommended that the following variables are also determined:

- yaw velocity of the first vehicle unit, $\dot{\psi}$;
- yaw angle of the first vehicle unit, ψ ;
- articulation angles between the vehicle units, $\psi_{Vn-Vn+1}$;
- sideslip angle of the first vehicle unit, β_{V1} ;
- wheel brake pressures.

6 Measuring equipment

The measuring equipment, transducer installation and data processing shall be in accordance with ISO 15037-2. Typical operating ranges of the variables to be determined for this document are shown in [Table 1](#) and in ISO 15037-2.

It is recommended to use a position measurement system (e.g. a differential GPS device) to measure the path travelled by the vehicle before and after the activation time. Only the relative position between the desired path and the path travelled by the vehicle shall be determined, see [Table 1](#) for the accuracy. Furthermore, it is recommended to use a photoelectric barrier for triggering the system intervention at the same place on the test track for each measurement.

Table 1 — Variables, typical operating ranges and recommended maximum errors of variables not listed in ISO 15037-2

Variable	Typical operating range	Recommended maximum errors of the combined transducer and recorder system
Longitudinal and lateral distance (for position measurement systems)	0 m to 200 m	$\pm 0,05$ m
Yaw angle	$\pm 360^\circ$	$\pm 1^\circ$

7 Test conditions

7.1 General

The test conditions described in ISO 15037-2 shall apply to this document. General data of the test vehicle shall be recorded as specified in ISO 15037-2. See [Annex A](#).

7.2 Test track and ambient conditions

All tests shall be carried out on an even road surface with a uniform coefficient of friction. An estimation of the friction level shall be reported.

NOTE The test method can be used for investigation of the differences in vehicle behaviour on different road friction conditions.

7.3 Test vehicle

7.3.1 General vehicle condition

The reference condition of the test vehicle shall be in accordance with the vehicle manufacturer's specifications, particularly with respect to the brake system, the suspension, power train configuration (e.g. differentials and locks) and shall be in accordance with ISO 15037-2. Deviations from this reference condition shall be reported in the test results.

The brake system shall be in a well-maintained condition. Any newly installed wheel brakes shall be burnished in accordance with vehicle manufacturer specifications. If the vehicle is equipped with additional drive train braking devices (e.g. retarder) or functions other than ABS that influence braking performance (e.g. cross-axle braking difference compensation), the actual condition shall be reported.

7.3.2 Loading condition

The loading condition of the vehicle shall be in accordance with ISO 15037-2 and shall be reported in the test results.

7.3.3 Number of test runs

One test sequence consists of at least three valid test runs, i.e. test runs performed while observing all conditions specified.

8 Test methods

8.1 Test method for braking straight ahead

8.1.1 Initial driving condition

The initial driving condition for the test shall be driving straight ahead as specified in ISO 15037-2. The standard nominal initial vehicle velocity at the beginning of braking is 80 km/h. Other initial velocities may be used, especially for tests conducted on road surfaces with a low coefficient of friction.

8.1.2 Definition of the desired path and track

The desired path for braking straight ahead is a straight line in the lane centre with a length of at least 50 m before the trigger point and at least 100 m after this point. The track shall be marked with pylons as shown in [Figure 1](#). An entrance lane with a recommended width of 3,0 m and a recommended length of 25 m is set up to help ensure precise straight-ahead driving before the intervention of the emergency braking system. The following lane width may also be marked by pylons for an indication if the vehicle is leaving a desired lane width during the system intervention. For this purpose, a standard lane width of 4,0 m and a longitudinal distance of 10 m between the pylons are recommended. Alternatively, especially when the vehicle is equipped with an active lane keeping system, existing lane markings may be used.