

SLOVENSKI STANDARD oSIST prEN 14178-2:2017

01-september-2017

Steklo v gradbeništvu - Osnovni izdelki iz zemljoalkalijskega silikatnega stekla - 2. del: Standard za proizvod

Glass in building - Basic alkaline earth silicate glass products - Part 2: Product standard

Glas im Bauwesen - Basiserzeugnisse aus Erdalkali-Silicatglas - Teil 2: Produktnorm

Verre dans la construction - Verre de silicate alcalino-terreux de base - Partie 2 : Norme de produit (standards.iteh.ai)

Ta slovenski standard je istoveten 2: 05 pr EN 14178-2

0936436a2e80/osist-pren-14178-2-2017

ICS:

81.040.20 Steklo v gradbeništvu Glass in building

oSIST prEN 14178-2:2017 en,fr,de

oSIST prEN 14178-2:2017

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN 14178-2:2017 https://standards.iteh.ai/catalog/standards/sist/a49e69a0-5d8f-4d3e-8f05-0936436a2e80/osist-pren-14178-2-2017

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

DRAFT prEN 14178-2

July 2017

ICS 81.040.20

Will supersede EN 14178-2:2004

English Version

Glass in building - Basic alkaline earth silicate glass products - Part 2: Product standard

Verre dans la construction - Verre de silicate alcalinoterreux de base - Partie 2 : Norme de produit Glas im Bauwesen - Basiserzeugnisse aus Erdalkali-Silicatglas - Teil 2: Produktnorm

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 129.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.//standards.itch.ai/catalog/standards/sist/a49e69a0-5d8f-4d3e-8f05-

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning: This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Cont	ents	Page
Europ	ean foreword	4
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Requirements	7
4.1	Product description	
4.2	Determination of the characteristic's performances	
4.2.1	Characteristics of basic alkaline earth silicate glasses	
4.2.2	Determination of characteristics of basic alkaline earth silicate glass products	
4.3	Characteristics other than listed in 4.2	
4.4	Dangerous substances	
4.5	General	
4.6	Determination of the product type (see 5.1, 1))	
4.6.1	General	
4.6.2	Type testing of characteristic's performances	
4.6.3	Test reports	12
4.6.4	Multiple lines/sites.	13
4.7	Factory Production Control (FPC) and ards. itch. ai	13
4.7.1	General	
4.7.2	Inspection of samples in accordance with a prescribed test plan (see 5.1, 2a))	
4.8	Initial inspection of factory and of factory production control (see 5.1, 2b))	
4.9	Continuous surveillance and assessment of the factory production control (see 5.1, 2c))	15
4.10	Procedure for modifications	
4.10 4.11	Pre-production products (e.g. prototypes)	
5	Marking and labelling	
5.1	General	
5.2	Product marking	16
Annex	A (normative) Factory Production Control	17
A.1	Factory Production Control requirements	17
A.1.1	General	17
A.1.2	Organization	17
A.1.2.1	Responsibility and authority	17
A.1.2.2	Management representative for factory production control	17
	Management review	
A.1.3	Control system	17
A.1.3.1	General	17
	Personnel	
	Documentation	
	Equipment	
7.I.T		то

	Testing	
A.1.4.2	Manufacturing	18
A.1.5	Inspection and testing	18
A.1.6	Non-complying materials / products	18
A.2	Inspection and testing tables of basic alkaline earth silicate glass production	18
A.2.1	Information on Table A.1	18
A.2.2	Use of proxy testing	19
Annex	B (normative) Type testing of spectrophotometric and energy characteristics	23
B.1	Sampling	23
B.2	Measurement of spectrophotometric characteristics	23
B.3	Tolerances on spectrophotometric characteristics	23
Annex	C (informative) Provisions for voluntary involvement of third party(ies)	25
C.1	General	25
C.2	Voluntary tasks for third parties	25
C.3	Marking and labelling	25
Annex	ZA (informative) Relationship of this European Standard with Regulation (EU) No.305/2011	26
ZA.1	Scope and relevant characteristics.r.ds.iteh.ai	26
ZA.2	System of Assessment and Verification of Constancy of Performance (AVCP)oSIST prEN 14178-2:2017	27
ZA.3	OSIST prEN 14178-2:2017 Assignment of AVCP tasks nicotalog/standarda/gist/a40e69a0-5d8f-4d3e-8f05	28
Riblio	0936436a2e80/osist-pren-14178-2-2017	31

European foreword

This document (prEN 14178-2:2017) has been prepared by Technical Committee CEN/TC 129 "Glass in building", the secretariat of which is held by NBN.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 14178-2:2004.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports basic work requirements of EU Regulation and essential requirements of EU Directive(s).

For relationship with EU Regulation/Directive(s), see informative Annex ZA which is an integral part of this document.

This European standard differs from EN 14178-2:2004 as follows:

- a) the standard has been revised to fulfil the requirements of the Regulation (EU) No 305/2011 (Construction Product Regulation), modified by Regulations (EU) No 157/2014, (EU) No 568/2014 and (EU) No 574/2014;
- b) the solar factor, g, is listed within the spectrophotometric characteristics to be declared in the Declaration of Performances (DoP); (standards.iteh.ai)
- c) the durability/conformity assessment is listed within the characteristics to be declared in the DoP;
- d) the mechanical resistance shall be given in the DoP by the characteristic bending strength.

This part of the European standard does not stand alone; it is a part of one document:

- prEN 14178-1: Glass in building Basic alkaline earth silicate glass products Part 1: Float glass;
- prEN 14178-2: Glass in building Basic alkaline earth silicate glass products Part 2: Product standard.

This document contains other aspects of importance for trade.

1 Scope

This European standard covers the evaluation of conformity and the factory production control of basic alkaline earth silicate glass for use in buildings.

For glass products with electrical wiring or connections for, e.g. alarm or heating purposes, other directives, e.g. Low Voltage Directive, may apply.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 356, Glass in building — Security glazing — Testing and classification of resistance against manual attack

EN 410, Glass in building — Determination of luminous and solar characteristics of glazing

EN 673, Glass in building — Determination of thermal transmittance (U value) — Calculation method

EN 1063, Glass in building — Security glazing — Testing and classification of resistance against bullet attack

EN 12600, Glass in building — Pendulum test — Impact test method and classification for flat glass

EN 12758, Glass in building — Glazing and airborne sound insulation — Product descriptions and determination of properties

oSIST prEN 14178-2:2017

EN 13501-1, Fire classification of construction products and building elements — Part 1: Classification using data from reaction to fire tests 436a2e80/osist-pren-14178-2-2017

EN 13501-2, Fire classification of construction products and building elements — Part 2: Classification using data from fire resistance tests, excluding ventilation services

EN 13501-5, Fire classification of construction products and building elements — Part 5: Classification using data from external fire exposure to roofs tests

EN 13541, Glass in building — Security glazing — Testing and classification of resistance against explosion pressure

prEN 14178-1:2017, Glass in building — Basic alkaline earth silicate glass products — Part 1: Float glass

EN 15998, Glass in building — Safety in case of fire, fire resistance — Glass testing methodology for the purpose of classification

prEN 16612:2017, Glass in building — Determination of the lateral load resistance of glass panes by calculation

ISO 9385, Glass and glass-ceramics — Knoop hardness test

3 Terms and definitions

For the purposes of this document, the terms and definitions given in prEN 14178-1:2017 and the following apply.

3.1

factory production control

FPC

documented, permanent and internal control of production in a factory, in accordance with this standard

Note 1 to entry: See also Annex A.

3.2

product-type

set of representative performance levels or classes of a construction product, in relation to its essential characteristics, produced using a given combination of raw materials or other elements in a specific production process

3.3

essential characteristic

characteristic of the construction product which relate to the basic requirements for construction works

Note 1 to entry: Basic requirements for construction work are given in the regulation (EU) No 305/2011, Annex I. (standards.iteh.ai)

3.4

performance of a construction product

oSIST prEN 14178-2:2017

performance related to the relevant essential characteristics, expressed by level or class, or in a description

3.5

level

result of the assessment of the performance of a construction product in relation to its essential characteristics, expressed as a numerical value

3.6

class

range of levels, delimited by a minimum and a maximum value, of performance of a construction product

3.7

type testing

ТТ

determination of the performance of a product (characteristic, durability), on the basis of either actual tests or other procedures (such as conventional, standardised, tabulated or generally accepted values, standardised or recognised calculation methods, test reports when made available, ...), in accordance with this European standard and that demonstrates compliance with this European standard

3.8

test report

document that covers the results of tests undertaken on a representative sample of the product from production or on a prototype design of the product

3.9

product description

document that details the relevant parameters, e.g. process conditions, structure, etc., for defining a product that complies with the standard and that includes specific reference(s) to characteristics that are modified by the production process

3.10

product family

group of products determined by the manufacturer, which is made with similar components and processes and which is tested for FPC using the same test method

3.11

significant change

variation in performance beyond the permitted tolerance for the characteristic

4 Requirements

4.1 Product description

For conformity purposes the basic alkaline earth silicate glass products manufacturer is responsible for the preparation and maintenance of the product description. This description shall describe the product and/or product families.

Disclosure of the product description shall be at the discretion of the basic alkaline earth silicate glass products manufacturer or his agent except in the case of regulatory requirements.

The product description shall contain at least the following: ai)

- a reference to prEN 14178-1:2017 and prEN 14178-2:2017 and all other standards with which the manufacturer claims compliance; catalog/standards/sist/a49e69a0-5d8f-4d3e-8f05-
 - 0936436a2e80/osist-pren-14178-2-2017
- a description of the product family(ies);
- the spectrophotometric properties of the basic alkaline earth silicate glass products.

The definition of product families shall be consistent with the product description.

4.2 Determination of the characteristic's performances

4.2.1 Characteristics of basic alkaline earth silicate glasses

Basic alkaline earth silicate glass products are made in accordance to prEN 14178-1:2017. For the characteristics listed in Table 1, the values given in prEN 14178-1:2017, 5.1 and 5.2 shall be used.

Table 1 — Information on the characteristics of basic alkaline earth silicate glass

Characteristic		Unit
Density	ρ	kg/m³
Hardness (Knoop hardness in accordance with ISO 9385)	HK _{0,1/20}	Dimensionless
Young's modulus	Е	GPa
Poisson's ratio	μ	Dimensionless
Characteristic bending strength		МРа
Resistance against temperature changes and temperature		К
Specific heat capacity	С	J/(kg·K)
Coefficient of linear expansion	α	K-1
Thermal conductivity	λ	W/(m·K)
Mean refractive index to visible radiation	η	Dimensionless

4.2.2 Determination of characteristics of basic alkaline earth silicate glass products

4.2.2.1 General

If the basic alkaline earth silicate glass manufacturer wishes to claim that any performance characteristic is independent of the production equipment used, then the factory production control system shall be in accordance with this document including his specific process control conditions.

4.2.2.2 Safety in the case of fire - Resistance to fire

oSIST prEN 14178-2:2017

Fire resistance shall be determined and classified in accordance with EN 13501-2.5-

EN 15998 specifies the testing methodology to be used for glass products that are claiming fire resistance.

4.2.2.3 Safety in the case of fire - Reaction to fire

Reaction to fire shall be determined and classified in accordance with EN 13501-1.

Basic alkaline earth silicate glass products are products/materials that do not require to be tested for reaction to fire (e.g. Products/materials of Classes A1 according to Commission Decision 96/603/EC, as amended 2000/605/EC).

4.2.2.4 Safety in the case of fire - External fire performance (for roof coverings only)

Where the manufacturer wishes to declare external fire performance (e.g. when subject to regulatory requirements), the product shall be tested in accordance with EN 13501-5.

4.2.2.5 Safety in use - Bullet resistance: shatter properties and resistance to attack

Bullet resistance shall be determined and classified in accordance with EN 1063.

4.2.2.6 Safety in use - Explosion resistance: impact behaviour and resistance to impact

Explosion resistance shall be determined and classified in accordance with EN 13541.

4.2.2.7 Safety in use - Burglar resistance: shatter properties and resistance to attack

Burglar resistance shall be determined and classified in accordance with EN 356.

4.2.2.8 Safety in use - Pendulum body impact resistance: shatter properties (safe breakability) and resistance to impact

Pendulum body impact resistance shall be determined and classified in accordance with EN 12600.

4.2.2.9 Safety in use - Mechanical resistance: Resistance against sudden temperature changes and temperature differentials

The resistance against sudden temperature changes and temperature differentials is a generally accepted value that is given in prEN 14178-1:2017 and shall be ensured by compliance with this standard.

4.2.2.10 Safety in use - Mechanical resistance: Resistance against wind, snow, permanent load and/or imposed loads of the glass unit

The mechanical resistance of basic alkaline earth silicate glass is a characteristic value that shall be ensured by compliance with this document.

The value to be declared is the characteristic bending strength, as defined in prEN 14178-1:2017, 5.2.

As long as prEN 16612 is not applicable for the glass design with respect to the concerned construction or building site, then the current method of determining mechanical resistance in the country of destination shall be applied.

4.2.2.11 Protection against noise - Direct airborne sound reduction

The sound reduction indexes shall be determined in accordance with EN 12758.

The values to be declared shall be rounded down to the nearest whole number.

4.2.2.12 Energy conservation and heat retention - Thermal properties

The thermal transmittance value (0-value) shall be determined in accordance with the following procedure:

0936436a2e80/osist-pren-14178-2-2017

- a) the emissivity shall be taken equal to 0,837, as given in prEN 14178-1:2017;
- b) the U-value shall be determined by calculation in accordance with EN 673, with the normal emissivity as defined above and the nominal thickness of the glass panes.

4.2.2.13 Energy conservation and heat retention - Radiation properties: Light transmittance and reflectance

The light transmittance and light reflectance shall be determined either:

- a) in accordance with the following procedure:
 - 1) The light transmittance and light reflectance of one sample of basic borosilicate glass product shall be determined in accordance with EN 410 and Annex B. The exact thickness of the glass shall be measured.
 - 2) The light transmittance and the light reflectance of any other thickness shall be calculated according to EN 410.
 - 3) The tool used to calculate the light transmittance and the light reflectance shall be validated.
- b) or measured following EN 410 and Annex B.

The tolerances on the calculated light transmittance and light reflectance are given in Annex B.

4.2.2.14 Energy conservation and heat retention - Radiation properties: Solar energy characteristics

The solar direct transmittance, the solar direct reflectance and the total solar energy transmittance (solar factor or g-value) shall be determined either:

- a) in accordance with the following procedure:
 - 1) The solar direct transmittance and solar direct reflectance of one sample of basic borosilicate glass product shall be determined in accordance with EN 410 and Annex B. The exact thickness of the glass shall be measured.
 - 2) The solar direct transmittance, the solar direct reflectance and the total solar energy transmittance (solar factor or g-value) of any other thickness shall be calculated according to EN 410.
 - 3) The tool used to calculate the solar direct transmittance, the solar direct reflectance and the total solar energy transmittance (solar factor or g-value) shall be validated.
- b) or measured following EN 410 and Annex B.

The tolerances on the calculated solar energy characteristics are given in Annex B.

4.2.2.15 Durability / conformity with the definition of basic alkaline earth silicate glass products

Products shall conform to the definition, to the manufacturer product description and fulfil the requirements of basic alkaline earth silicate glass products as defined in prEN 14178-1:2017.

The type testing concerns the product aspects as listed in Table 2.

Table 2 — Product aspects to be checked if product belongs to the group basic alkaline earth silicate glass products

Product aspect	Requirement	Number of samples
Chemical composition	prEN 14178-1:2017, 4.1	1
Thickness	prEN 14178-1:2017, 6.2	1
Light transmittance (distinction clear glass from tinted glass)	prEN 14178-1:2017, 5.3	1

When products conform to the definition of basic alkaline earth silicate glass, the other characteristics' performances in 4.2 are ensured during an economically reasonable working life.

The durability / conformity of basic alkaline earth silicate glass products, including their characteristics, is ensured by the following:

- compliance with this standard;
- compliance with instructions from the glass product manufacturer or supplier.

The manufacturer shall supply specific installation instructions or make reference to appropriate technical specifications.

NOTE The durability of glass products depends also on:

building and construction movements due to various actions;