

SLOVENSKI STANDARD
kSIST ISO/FDIS 80000-7:2019
01-april-2019

Veličine in enote - 7. del: Svetloba in sevanje

Quantities and units - Part 7: Light and radiation

Grandeurs et unités - Partie 7: Lumière et rayonnements

Ta slovenski standard je istoveten z: ISO/FDIS 80000-7

ICS:

01.060

Veličine in enote

Quantities and units

kSIST ISO/FDIS 80000-7:2019

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/6a6af-40c-80bd-40c-a7e8-1fdb36c679ed/ksist-iso-fdis-80000-7-2019>

FINAL
DRAFT

INTERNATIONAL
STANDARD

ISO/FDIS
80000-7

ISO/TC 12

Secretariat: SIS

Voting begins on:
2019-02-07

Voting terminates on:
2019-04-04

Quantities and units —

Part 7: Light and radiation

Grandeurs et unités —

Partie 7: Lumière et rayonnements

ITEH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/6a6a111c-80bd-440c-a7e8-11db36cc679ed/ksist-iso-fdis-80000-7-2019>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

This draft is submitted to a parallel vote in ISO and in IEC.



Reference number
ISO/FDIS 80000-7:2019(E)

© ISO 2019

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/6a6af-41c-80bd-40c-a7e8-11db36c679ed/ksist-iso-fdis-80000-7-2019>

**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents	Page
Foreword.....	iv
Introduction — Special remarks	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
Bibliography	32
Alphabetical index.....	33

ITeH STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/6a6af-41c-80bd-440c-a7e8-11db36cc679ed/ksist-iso-fdis-80000-7-2019>

ISO/FDIS 80000-7:2019(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 12, *Quantities and units*.

This second edition cancels and replaces the first edition (ISO 80000-7:2008), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the table giving the quantities and units has been simplified;
- some definitions and the remarks have been stated physically more precisely.

A list of all parts in the ISO 80000 and IEC 80000 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction — Special remarks

0.1 Quantities

ISO 80000-7 contains a selection of quantities pertaining to light and other electromagnetic radiation. Radiometric quantities relating to radiation in general may be useful for the whole range of electromagnetic radiations, whereas photometric quantities pertain only to visible radiation.

In several cases, the same symbol is used for a trio of corresponding radiant, luminous and photon quantities with the understanding that subscripts “e” for energetics, “v” for visible and “p” for photon will be added whenever confusion between these quantities might otherwise occur.

For ionizing radiation, however, see ISO 80000-10.

Several of the quantities in ISO 80000-7 can be defined for monochromatic radiation, i.e. radiation of a single frequency ν only. They are denoted by their reference quantity as an argument like $q(\nu)$. An example is speed of light in a medium $c(\nu)$, or the refractive index in a medium $n(\nu) = c_0/c(\nu)$. Some of those quantities are derivatives

$$q'(\lambda) = \frac{dq(\lambda)}{d\lambda} = \lim_{\Delta\lambda \rightarrow 0} \frac{q(\lambda + \Delta\lambda) - q(\lambda)}{\Delta\lambda}$$

of a quantity which are also frequently described as fractions $\Delta q(\lambda)$ of a quantity q corresponding to the radiation with wavelength in the interval $[\lambda, \lambda + \Delta\lambda]$ divided by the range $\Delta\lambda$ of that interval to point to the physical measurement process behind. Such fractions must be additive so that the integral yields the overall quantity, e.g. radiance (item 7-8.1) and spectral radiance (item 7-8.2). These derivatives of quantities are called spectral quantities and are denoted by subscript λ .

On the other hand, some multidimensional quantities like radiant intensity $I_e(\vartheta, \varphi)$, irradiance $E_e(x, y)$, radiance $L_e(x, y, \vartheta, \varphi)$, etc., are quantities that are strictly defined as values of a derivative at a certain point, a certain direction or at a certain point and direction in space. Hence, the most fundamental definition according to ISO 80000-2 would be e.g. in case of the most complex term “radiance” (item 7-8.1):

“at a given point (x_1, y_1) of a real or imaginary surface, in a given direction (ϑ_1, φ_1) ,

$$L_e(x, y, \vartheta, \varphi) = \frac{\partial^2 \Phi_e(x, y, \vartheta, \varphi)}{\partial A(x, y) \cdot \cos \varepsilon \cdot \partial \Omega(\vartheta, \varphi)} = \left(\frac{\partial^2 \Phi_e}{\partial A \cdot \cos \varepsilon \cdot \partial \Omega} \right)_{\substack{x=x_1 \\ y=y_1 \\ \vartheta=\vartheta_1 \\ \varphi=\varphi_1}}$$

where $\Phi_e(x, y, \vartheta, \varphi)$ represents the radiant flux transmitted through an area $A(x, y)$ at a given point (x_1, y_1) and propagating in a given direction (ϑ_1, φ_1) , and ε is the angle between the normal $\underline{A(x_1, y_1)}$ to that area at the given point and the given direction (ϑ_1, φ_1) ”.

To ease the use of the table in Clause 3, the simplified definitions (like item 7-8.1 in case of radiance) are used which assume that fractions of quantities are always isotropic and uniform and continuous. In this case, the given definitions are equivalent to the fundamental approach given above.

Instead of frequency ν , other reference quantities of light may be used: angular frequency $\omega = 2\pi\nu$, wavelength in a medium $\lambda = c_0/n\nu$, wavelength in vacuum $\lambda_0 = c_0/\nu$, wavenumber in medium $\sigma = 1/\lambda$, wavenumber in vacuum $\tilde{\nu} = \nu/c_0 = \sigma/n = 1/\lambda_0$, etc. As an example, the refractive index may be given as $n(\lambda = 555 \text{ nm}) \approx 1,333$.

ISO/FDIS 80000-7:2019(E)

Spectral quantities corresponding to different reference quantities are related, e.g.

$$dq = q_\nu(\nu)d\nu = q_\omega(\omega)d\omega = q_{\tilde{\nu}}(\tilde{\nu})d\tilde{\nu} = q_\lambda(\lambda)d\lambda = q_\sigma(\sigma)d\sigma$$

thus

$$q_\nu(\nu) = 2\pi \cdot q_\omega(\omega) = q_{\tilde{\nu}}(\tilde{\nu})/c_0 = q_\lambda(\lambda) \cdot c_0/n = q_\sigma(\sigma) \cdot n/c_0$$

From the theoretical point of view, the frequency ν is the more fundamental reference quantity, keeping its value when a light beam passes through media with different refractive index, n . For historical reasons, the wavelength, λ , is still mostly used as a reference quantity being the most accurately measured quantity in the past. In this respect, spectral quantities, as the spectral radiance (item 7-8.2), $L_{e,\lambda}(\lambda)$, have the meaning of spectral “densities” corresponding to the respective integrated quantities – i.e. in the case of radiance, $L_e(\lambda)$ (item 7-8.1),

$$L_{e,\lambda} = \frac{\partial L_e}{\partial \lambda}$$

0.2 Units

In photometry and radiometry, the unit steradian is retained for convenience.

0.3 Photopic quantities

In the great majority of instances, photopic vision (provided by the cones in the human visual system and used for vision in daylight) is dealt with. Standard values of the spectral luminous efficiency function $V(\lambda)$ for photopic vision were originally adopted by the CIE in 1924. These values were adopted by the International Committee for Weights and Measures (CIPM) [see BIPM Monograph: Principles Governing Photometry (1983)].

0.4 Scotopic quantities

For scotopic vision (provided by the rods and used for vision at night), corresponding quantities are defined in the same manner as the photopic ones (items 7-12 to 7-20), using symbols with a prime.

For the term “spectral luminous efficiency” (item 7-12.2) the remarks would read:

“Standard values of luminous efficiency function $V'(\lambda)$ for scotopic vision were originally adopted by CIE in 1951. They were later adopted by the CIPM^[11].”

For the term “maximum luminous efficacy” (item 7-13.3) the definition would read:

“<for scotopic vision> maximum value of the spectral luminous efficacy for scotopic vision”

In the Remark it would read:

“The value is calculated by

$$K'_m = \frac{683 \text{ lm W}^{-1}}{V'(\lambda_{\text{cd}})} \approx 1700 \text{ lm W}^{-1}$$

where $V'(\lambda)$ is the spectral luminous efficiency in terms of wavelength λ for scotopic vision and λ_{cd} is the wavelength in air corresponding to the frequency $540 \cdot 10^{12}$ Hz given in the definition of the SI unit candela.”

0.5 Mesopic quantities

For mesopic vision (provided by the rods and cones and used for vision intermediate between photopic and scotopic vision), corresponding quantities are defined in the same manner as the photopic ones (items 7-12 to 7-20), using symbols with the subscript “mes”.

For the term “spectral luminous efficiency” (item 7-12.2) the remarks would read:

“Standard values of spectral luminous efficiency functions $V_{\text{mes}}(\lambda)$ for mesopic vision depend on the used adaptation level m and were originally recommended by CIE in 2010.^[12] They are adopted by the CIPM (see BIPM Monograph: Principles Governing Photometry:—¹).”

For the term “maximum luminous efficacy” (item 7-13.3) the definition would read:

“<for mesopic vision> adaptation level m dependent maximum value of the spectral luminous efficacy for mesopic vision”

In the Remark it would read:

“The value is calculated by

$$K_{m,\text{mes};m} = \frac{683 \text{ lm W}^{-1}}{V_{\text{mes};m}(\lambda_{\text{cd}})}$$

where $V_{\text{mes};m}(\lambda)$ is the spectral luminous efficiency for mesopic vision at an adaptation level m and λ_{cd} is the wavelength in air corresponding to the frequency $540 \cdot 10^{12}$ Hz given in the definition of the SI unit candela.”

¹ To be published.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/6a6af-40c-80bd-40c-a7e8-1fdb36c679ed/ksist-iso-fdis-80000-7-2019>

Quantities and units — Part 7: Light and radiation

1 Scope

This document gives names, symbols, definitions and units for quantities used for light and optical radiation in the wavelength range of approximately 1 nm to 1 mm. Where appropriate, conversion factors are also given.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

Names, symbols, definitions and units for quantities used in light and optical radiation in the wavelength range of approximately 1 nm to 1 mm are given in Table 1.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

In the field of light, the CIE maintains the Electronic international lighting vocabulary, available at <http://einv.cie.co.at/>.

Table 1 — Quantities and units used in light and optical radiation in the wavelength range of approximately 1 nm to 1 mm

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
7-1.1	speed of light in a medium	c	phase speed of an electromagnetic wave at a given point in a medium	See also ISO 80000-3. The value of the speed of light in a medium can depend on the frequency, polarization, and direction. For the definition of the speed of electromagnetic waves in vacuum, c_0 , see ISO 80000-1.
7-1.2	refractive index	n	quotient of speed of light in vacuum and speed of light in a medium (item 7-1.1)	The value of the refractive index can depend on the frequency, polarization, and direction. The refractive index is expressed by $n = c_0/c$, where c_0 is the speed of light in vacuum and c is the speed of light in the medium. For a medium with absorption, the complex refractive index \underline{n} is defined by $\underline{n} = n + ik$ where k is spectral absorption index and i is imaginary unit. The refractivity is expressed by $n - 1$, where n is refractive index.