



Designation: D 5395 – 97

Standard Specification for Reclaimed Methylene Chloride^{1,2}

This standard is issued under the fixed designation D 5395; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers the grade of methylene chloride typically needed in various industries for noncritical applications, such as in paint stripping formulations. It may be used as a reference document by purchasers or by persons establishing in-house methylene chloride recovery programs.

2. Referenced Documents

2.1 ASTM Standards:

- D 2108 Test Method for Color of Halogenated Organic Solvents and Their Admixtures (Platinum-Cobalt Scale)³
- D 2109 Test Methods for Nonvolatile Matter in Halogenated Organic Solvents and Their Admixtures³
- D 2111 Test Methods for Specific Gravity of Halogenated Organic Solvents and Their Admixtures³
- D 2988 Test Method for Water-Soluble Halide Ion in Halogenated Organic Solvents and Their Admixtures³
- D 2989 Test Method for Acidity-Alkalinity of Halogenated Organic Solvents and Their Admixtures³
- D 3401 Test Methods for Water in Halogenated Organic Solvents and Their Admixtures³
- D 3447 Test Method for Purity of Trichlorotrifluoroethane³
- D 3741 Test Method for Appearance of Admixtures Con-

TABLE 1 Physical Properties

Property	Specification	Test Method
Specific gravity, 25/25	1.318 to 1.323	D 2111
Acidity, as HCl, ppm, max	1.0	D 2989
Water, ppm, max	500	D 3401 or E1064
Appearance	Clear and free from suspended matter	D 3741
Color, Pt-Co, max	50	D 2108
Nonvolatile residue, ppm, max	50	D 2109
Chloride, ppm, max	1.0	D 2988
Assay, weight %	95.0	D 3447
1,1,1-Trichloroethane content, weight %, max	0.5	D 3447

taining Halogenated Organic Solvents³
E 1064 Test Method for Water in Organic Liquids by Coulometric Karl Fischer Titration³

3. Properties

3.1 Reclaimed methylene chloride shall meet the requirements of Table 1.

4. Packaging and Package Marking

4.1 Industrial or commercial quantities shall be packaged and labeled in accordance with DOT regulations as found in 49 CFR 100 to 109 and state and local regulations with above usage in mind.

4.2 Department of Defense procurements shall be packaged and labeled in accordance with the applicable paragraphs of Federal Specification PPP-C-2020.

5. Keywords

5.1 dichloromethane; halogenated solvent; MCI; MCH; MeCl; methylene chloride; reclaimed

¹ This specification is under the jurisdiction of ASTM Committee D26 on Halogenated Organic Solvents and Fire Extinguishing Agents and is the direct responsibility of Subcommittee D26.02 on Vapor Degreasing.

Current edition approved May 10, 1997. Published May 1998. Originally published as D 5395 – 93.

² Methylene chloride: CAS #75-09-02.

³ Annual Book of ASTM Standards, Vol 15.05.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).