



SLOVENSKI STANDARD
oSIST prEN 15684:2019
01-julij-2019

Stavbno okovje - Mehatronski valji - Zahteve in preskusne metode

Building hardware - Mechatronic cylinders - Requirements and test methods

Schlösser und Baubeschläge - Mechatronische Schließzylinder - Anforderungen und Prüfverfahren

Quincaillerie pour le bâtiment - Cylindres mécatroniques - Exigences et méthodes d'essai

Ta slovenski standard je istoveten z: prEN 15684

ICS:

91.190 Stavbna oprema Building accessories

oSIST prEN 15684:2019

en,fr,de

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 15684

April 2019

ICS 91.190

Will supersede EN 15684:2012

English Version

Building hardware - Mechatronic cylinders - Requirements and test methods

Quincaillerie pour le bâtiment - Cylindres
mécatroniques - Exigences et méthodes d'essai

Schlösser und Baubeschläge - Mechatronische
Schließzylinder - Anforderungen und Prüfverfahren

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 33.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

	Page
European foreword.....	4
Introduction	5
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions	7
4 Requirements.....	9
4.1 General.....	9
4.2 Category of use	10
4.3 Durability requirements	11
4.4 Fire/smoke resistance	11
4.5 Environmental resistance.....	11
4.6 Key related security	13
4.7 System management.....	18
4.8 Attack resistance requirements	19
4.9 Requirements for product information.....	22
5 Testing, assessment and sampling methods.....	23
5.1 General.....	23
5.2 Operational test.....	23
5.3 Performance tests.....	25
5.4 Category of use	25
5.5 Durability tests.....	26
5.6 Fire/smoke resistance tests.....	27
5.7 Environmental resistance tests	28
5.8 Key related security	30
5.9 System Management.....	31
5.10 Attack resistance tests.....	31
6 Classification system.....	41
6.1 Classification.....	41
6.2 Category of use: (1st character).....	41
6.3 Durability (2nd character):	41
6.4 Fire/smoke resistance (3rd character):	41
6.5 Environmental resistance (4th character):	41
6.6 Mechanical key related security (5th character):	41
6.7 Credential related security (6th character):	41
6.8 System Management (7th character):	42
6.9 Attack resistance (8th character):	42
6.10 Example of classification	42
7 Marking.....	42
Annex A (normative) Suitability for use on fire/smoke resistant doors	43
Annex B (normative) Tool sets for attack resistance tests	44
Annex C (normative) Table of test procedures	46
Annex D (informative) Installation instructions.....	48

Annex E (informative) Manufacturer’s declaration of compliance	49
Annex F (informative) Examples of calculation of effective code variations for ICC.....	51
Bibliography	54

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 15684:2021

<https://standards.iteh.ai/catalog/standards/sist/f80ec0c0-647d-4a1c-8e9a-71ddbcd927b2/sist-en-15684-2021>

prEN 15684:2019 (E)

European foreword

This document (prEN 15684:2019) has been prepared by Technical Committee CEN/TC 33 “Doors, windows, shutters, building hardware and curtain walling”, the secretariat of which is held by AFNOR.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 15684:2012.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 15684:2021

<https://standards.iteh.ai/catalog/standards/sist/f80ec0c0-647d-4a1c-8e9a-71ddbcd927b2/sist-en-15684-2021>

Introduction

Mechanical cylinders have been used to provide security and control of locks. Increasing demand for higher security, flexibility of master key systems, flow control, copy control of keys, etc. have made it desirable to incorporate additional functions to such mechanical cylinders, and new technologies have made it possible to develop electronically controlled cylinders.

Mechanical performance of the mechatronic cylinder is based on EN 1303.

Mechatronic Cylinder can technically be described in three main designs:

- a cylinder with both electrically and mechanically operated locking parts;
- a cylinder with electrically operated locking part and a key for mechanically rotating the plug;
- a cylinder with electrically operated locking part and with manual operated opening/closing function.

Increasingly such Mechatronic Cylinders (MCs) form a part of the security system of a building and may involve the use of electrical locking and controlling elements.

The performance tests incorporated in this European Standard are considered to be reproducible and as such will provide a consistent and objective assessment of the performance of these devices throughout CEN Member States.

It is assumed that MC will conform to the legal regulations, i.e. RED – Radio Equipment Directive 2014/53/EU.

On occasions there may be a need for additional functions within the design of the cylinder. Purchasers should satisfy themselves that the products are suitable for their intended use. This is particularly important when the operation of such additional functions is safety-related. Accordingly, this European Standard includes assessment of such features when they are included in the cylinder design.

In comparison with EN 15684:2012, the following significant changes have been made:

- Classification –Minimum number of codes changed to credential security;
- Classification - attack resistance refers to EN 1303:2015;
- Credential security introduced, with the same principle as in prEN 16867:2018.

prEN 15684:2019 (E)**1 Scope**

This document specifies requirements for performance and testing of Mechatronic Cylinders and their keys and/or electronic keys.

It applies to cylinders for such locks designed to be normally used in buildings. It also applies to cylinders for use with other hardware products such as exit devices, door operators, etc. or monitoring facilities and alarm systems.

It establishes categories of use based on performance tests and grades of security based on design requirements and on performance tests that simulate attack.

This document includes assessment of additional features when they are included in the cylinder design.

This document does not cover any other element of a security system, other than those directly involved in the control of a cylinder.

The suitability of cylinders for use on fire or smoke-door assemblies is determined by fire performance tests conducted in addition to the performance testing specified by this document (see Annex A).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 636:2003+A1:2015, *Plywood — Specifications*

EN 1303:2015, *Building hardware — Cylinders for locks — Requirements and test methods*

EN 1634-1, *Fire resistance and smoke control tests for door, shutter and openable window assemblies and elements of building hardware — Part 1: Fire resistance tests for doors, shutters and openable windows*

EN 1634-2, *Fire resistance and smoke control tests for door, shutter and openable window assemblies and elements of building hardware — Part 2: Fire resistance characterisation test for elements of building hardware*

EN 1634-3, *Fire resistance and smoke control tests for door and shutter assemblies, openable windows and elements of building hardware — Part 3: Smoke control test for door and shutter assemblies*

EN 1670:2007, *Building hardware — Corrosion resistance — Requirements and test methods*

EN 1906, *Building hardware — Lever handles and knob furniture — Requirements and test methods*

EN 60068-2-1, *Environmental testing — Part 2-1: Tests — Test A: Cold (IEC 60068-2-1)*

EN 60068-2-2, *Environmental testing — Part 2-2: Tests — Test B: Dry heat (IEC 60068-2-2)*

EN 60068-2-6:2008, *Environmental testing — Part 2-6: Tests — Test Fc: Vibration (sinusoidal) (IEC 60068-2-6:2007)*

EN 60068-2-27, *Environmental testing — Part 2-27: Tests – Test Ea and guidance: Shock (IEC 60068-2-27)*

EN 60068-2-30:2005, *Environmental testing — Part 2-30: Tests — Test Db: Damp heat, cyclic (12 h + 12 h cycle) (IEC 60068-2-30:2005)*

EN 60529:1991¹⁾, *Degrees of protection provided by enclosures (IP Code) (IEC 60529:1989)*

EN 61000-4-2, *Electromagnetic compatibility (EMC) — Part 4-2: Testing and measurement techniques — Electrostatic discharge immunity test (IEC 61000-4-2)*

EN ISO 10666, *Drilling screws with tapping screw thread — Mechanical and functional properties (ISO 10666)*

EN ISO 15480, *Hexagon washer head drilling screws with tapping screw thread (ISO 15480)*

EN ISO 15481, *Cross recessed pan head drilling screws with tapping screw thread (ISO 15481)*

EN ISO 15482, *Cross recessed countersunk head drilling screws with tapping screw thread (ISO 15482)*

EN ISO 15483, *Cross recessed raised countersunk head drilling screws with tapping screw thread (ISO 15483)*

ISO/IEC 18033-3:2010, *Information technology - Security techniques- Encryption algorithms - Part 3: Block ciphers*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1 access card <https://standards.iteh.ai/catalog/standards/sist/f80ec0c0-647d-4a1c-8e9a-71ddbcd927b2/sist-en-15684-2021>

card or tag, read only or read write, without integrated circuit, does not provide encryption

Note 1 to entry: It can be used with contact or contactless.

EXAMPLES Magnetic stripe, Wigand, barcode.

3.2 audit trail capability

degree of functionality intended to provide a record of mechatronic cylinder and/or its electronic key events that will identify the individual credential used to operate the mechatronic cylinder

3.3 attack

unauthorized attempt to open a mechatronic cylinder by various techniques (destructive and or non-destructive techniques)

3.4 cam

component of the cylinder to provide the movement necessary to effect locking

1) This document is impacted by the amendments EN 60529:1991/A1:2000 and EN 60529:1991/A2:2013.

prEN 15684:2019 (E)**3.5****credential**

identification means containing information necessary to authorize operation of the MC

3.6**cylinder**

device, usually distinct from its associated lock or latch, operated by a key

3.7**direct coding**

marking on in the key where the mechanical and/or electronic coding can be determined without reference to another data source

3.8**effective differ**

difference between cylinders of similar design, achieved only by the movable detainer, which enables each cylinder to be operated only by its own key

Note 1 to entry: The number of effective differs is equal to the number of theoretical differs after deduction of the differs excluded by the manufacturer due to technical constraints and those differs excluded in accordance with the restraints of 4.8.4.

3.9**electronic dummy key**

electronic key which cannot electronically operate the mechatronic cylinder

Note 1 to entry: If applicable the electronic dummy key has the right mechanical code.

3.10**electronic key**

device containing credential(s) necessary to authorize operation of the (mechatronic) cylinder

3.11**False Acceptance Rate****FAR**

probability that the system incorrectly authorizes a non-authorized person, due to incorrectly matching the biometric input with a template

Note 1 to entry: The FAR is normally expressed as a percentage, following the FAR definition this is the percentage of invalid inputs which are incorrectly accepted.

3.12**FAR-1**

FAR-1 (1/FAR) is the inverse of FAR

3.13**ICC = Integrated Circuit Card**

card, tag or device with an integrated circuit which can be used with contact or contactless (RFID), active or passive

EXAMPLES RFID, Smartcard.

3.14**key**

separate device corresponding to the cylinder, which can mechanically operate the cylinder

3.15**key way**

aperture extending along the whole or part of the length of the plug into which the key is inserted

3.16**knob**

element of the cylinder for mechanical hand operation of the cylinder

3.17**mechatronic cylinder****MC**

device with an integrated or a remote electronic system, which is to be used with a lock for the purpose of operating the lock and/or detaining elements after verifying the authorization of an electronic key, and which can be replaced by a mechanical cylinder conforming to EN 1303 without replacing any door furniture

3.18**moveable detainer**

part of the mechanism of a cylinder, which should first be moved by the key into a pre-determined position before the key and/or plug can move

3.19**plug**

part of a cylinder that can be moved when the proper key is used

3.20**steps**

cuts in the surface of a bit or blade which operates movable detainers

3.21**thumb turn**

element of the cylinder for mechanical finger operation of the cylinder

3.22**time zone**

degree of functionality intended to provide security by limiting the time that a valid credential will operate the MC

3.23**manufacturer**

entity or organization that is legally responsible for putting the product on the market

4 Requirements

4.1 General

The structure of the following requirements and test procedures reflects the classification in accordance with Clause 6.

prEN 15684:2019 (E)**4.2 Category of use****4.2.1 Key strength**

When tested in accordance with 5.4.1, the electronic key shall not break under the applied maximum torque of 2.5 Nm.

After the test, the electronic key shall be capable of being removed from the MC and re-used to operate the same MC with a torque not exceeding 1.5 Nm.

Compliance is checked by the test method given in 5.4.1.

4.2.2 Stability of electronic key

The electronic key shall be able to withstand a freefall from 1.5 m height, without loss of function and without the need to reassemble it.

Compliance is checked by the test method given in 5.4.2.

4.2.3 Wrong electronic code

When using an electronic dummy key with the right mechanical code the MC shall be capable of resisting a torque on the key of 3.5 Nm (or the maximum torque that can be transmitted with the normal manufacturers key if less than 3.5 Nm) without loss of function.

Compliance is checked by the test method given in 5.10.5.3, however with a torque of 3.5 Nm.

If a MC is equipped with a knob or thumb turn on the outside (replacing the key function) and this MC is not protected by a clutch to prevent damage in case of excessive torque being applied to the knob or thumb turn, the MC shall be capable of resisting a torque of 5 Nm +0.25 Nm -0 Nm, without loss of function.

4.2.4 Bump requirements

The MC and its electronic keys shall be able to withstand bumps.

The MC shall conform to the requirements given in Table 1.

The MC and the electronic key may have temporary degradation or loss of function and/or data, but the MC shall remain in secured position. The loss of function and/or data shall be self-recoverable within 5 s.

Compliance is checked by the test methods given in 5.4.3.

4.2.5 Vibration requirements

The MC and its electronic keys shall be able to withstand vibrations.

The MC shall conform to the requirements given in Table 1.

The MC and the electronic keys may have temporary degradation or loss of function and/or data, but the MC shall remain in secured position. The loss of function and/or data shall be self-recoverable within 5 s. The loss of function and/or data shall be self-recoverable within 5 s after the vibration test.

Compliance is checked by the test methods given in 5.4.4.

Table 1 — Bump and Vibration requirements

Test method	Grade 1
1. Bump test EN 60068-2-27	40 g (100 bumps / 3 directions) duration per bump 6 ms
3.a Vibrations EN 60068-2-6:2008	<ul style="list-style-type: none"> - Frequency range: 10 Hz to 150 Hz - Displacement amplitude: 0,35 mm - Acceleration amplitude: 5 g - Duration of endurance in sweep cycles for each axis: 5 - Cross-over frequency : 58 Hz to 62 Hz - Sweep rate: 1 octave per minute

4.2.6 Electrostatic discharge requirement

The MC and its electronic keys shall be able to withstand high voltage and static electricity. It shall conform to the requirements given in EN 61000-4-2 and conform to the specification in Table 7, grade 0.

The MC and the electronic keys may have temporary degradation or loss of function and/or data, but the electric blocking of the MC shall remain in secured position. The loss of function and/or data shall be self-recoverable within 5 s.

Compliance is checked by the test method given in 5.10.9.

4.2.7 Minimum knob transmission

If a MC is equipped with a blocked knob on the outside and this MC is protected by a clutch to prevent damage in case of excessive torque being applied to the knob, the clutch shall be able to transmit a minimum torque of 1,5 Nm having been released 100 times within 20 min.

Compliance is checked by the test method given in 5.10.11.

4.3 Durability requirements

When tested in accordance with 5.5, it shall be possible to operate the MC with a new original authorized electronic key with a torque not exceeding 1.5 Nm after the number of completed test cycles specified in 6.3.

Compliance is checked by the test method given in 5.2.

4.4 Fire/smoke resistance

The MC shall conform to the requirements of Annex A.

4.5 Environmental resistance

4.5.1 Corrosion resistance requirements

After the corrosion test of 5.7.1, The MC shall operate with authorization not exceeding a torque of 1.5 Nm.

Compliance is checked by the test method in 5.2.

Corrosion resistance is applicable for environmental resistance, grades 2, 3 and 4 (see Table 2). This corrosion test shall apply to functionality only.

prEN 15684:2019 (E)

No distinction is made between the inside and the outside of cylinder and/or door.

4.5.2 Resistance of MC against water

The MCs shall have protection, against water.

After been tested as in 5.7.2 for grades 2, 3 and 4 in Table 2 the MC shall operate with its authorized electronic key.

4.5.3 Dry Heat

The MC and its electronic key shall be able to function correctly at different temperatures. It shall also be able to function correctly after being exposed to thermal shocks. See Tables 2 and 3 for environmental resistance MC and electronic keys.

Compliance is checked by the test methods of 5.7.3.

4.5.4 Cold

The MC and its electronic key shall be able to function correctly at different low temperatures. It shall also be able to function correctly after being exposed to thermal shocks. See Tables 2 and 3 for environmental resistance MC and electronic keys.

Compliance is checked by the test methods of 5.7.4.

4.5.5 Damp heat cyclic

The MC and its electronic keys shall be able to function correctly in an environment of high relative humidity. See Tables 2 and 3 for environmental resistance MC and electronic keys.

Compliance is checked by the test method of 5.7.5.

4.5.6 Resistance of electronic key against water

The electronic keys shall be able to operate its MC after they have been exposed to water in accordance with the test described in 5.7.6.

Table 2 — Environmental resistance MC

Requirement	Test clause	Grade				
		0	1	2	3	4
4.5.1 Corrosion resistance	5.7.1	-	-	Yes	Yes	Yes
4.5.2 Protection of MC against water	5.7.2	-	-	Yes	Yes	Yes
4.5.3 Dry heat	5.7.3	-	+55° C, 16 h	+55° C, 16 h	+55° C, 16 h	+65° C, 16 h
4.5.4 Cold	5.7.4	-	+5° C, 16h	+5° C, 16 h	-10° C, 16 h	-25° C, 16 h
4.5.5 Damp Heat (cyclic)	5.7.5	-	-	-	-	+55° C, 6 cycles

Table 3 — Environmental resistance MC Key

Requirement	Test clause	Grade				
		0	1	2	3	4
4.5.6 Resistance of electronic key against water	5.7.6	-	-	Yes	Yes	Yes
4.5.3 Dry heat	5.7.3	-	+55° C, 16 h	+55° C, 16 h	+55° C, 16 h	+65° C, 16 h
4.5.4 Cold	5.7.4	-	+5° C, 16 h	+5° C, 16 h	-10° C, 16 h	-25° C, 16 h
4.5.5 Damp Heat (cyclic)	5.7.5	-	-	-	-	+55° C, 6 cycles

4.6 Key related security

4.6.1 General

For classification of mechanical code variation (5th character), the following requirements shall be fulfilled:

- 4.6.2;
- 4.6.3;
- 4.6.4;
- 4.6.5;
- 4.6.6.

For classification of electronic code variation (6th character), the following requirements shall be fulfilled:

- 4.6.5;
- 4.6.6;
- 4.6.7.

In case of a double cylinder, it is assumed that the grades for both categories apply to the attack side/outside of the cylinder. This side shall have a proper indication/markings, either on the product or on the documents with the product.

4.6.2 Minimum number of effective mechanical code variations

The minimum number of effective mechanical code variations of the MC shall be as specified in Table 4.

Compliance is checked by the test method of 5.8.2.

NOTE Grade 0 includes MCs without mechanical code variations.