

SLOVENSKI STANDARD oSIST prEN ISO 13408-6:2019

01-julij-2019

Aseptična proizvodnja izdelkov za zdravstveno nego - 6. del: Sistemi izolatorjev (ISO/DIS 13408-6:2019)

Aseptic processing of health care products - Part 6: Isolator systems (ISO/DIS 13408-6:2019)

Aseptische Herstellung von Produkten für die Gesundheitsfürsorge - Teil 6: Isolatorensysteme (ISO/PIS 13408-6:2019) ARD PREVIEW

Traitement aseptique des produits de santé - Partie 6. Systèmes isolateurs (ISO/DIS 13408-6:2019)

<u>kSIST FprEN ISO 13408-6:2020</u> https://standards.iteh.ai/catalog/standards/sist/987aad95-ec10-40ab-9b13-

Ta slovenski standard je istoveten 2.4/ksist-prEN ISO 13408-6

ICS:

11.080.01 Sterilizacija in dezinfekcija na Sterilization and disinfection

splošno in general

oSIST prEN ISO 13408-6:2019 en

oSIST prEN ISO 13408-6:2019

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>kSIST FprEN ISO 13408-6:2020</u> https://standards.iteh.ai/catalog/standards/sist/987aad95-ec10-40ab-9b13-2763136ce014/ksist-fpren-iso-13408-6-2020

DRAFT INTERNATIONAL STANDARD ISO/DIS 13408-6

ISO/TC **198** Secretariat: **ANSI**

Voting begins on: Voting terminates on:

2019-04-03 2019-06-26

Aseptic processing of health care products —

Part 6:

Isolator systems

Traitement aseptique des produits de santé — Partie 6: Systèmes isolateurs

ICS: 11.080.01

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>kSIST FprEN ISO 13408-6:2020</u> https://standards.iteh.ai/catalog/standards/sist/987aad95-ec10-40ab-9b13-2763136ce014/ksist-fpren-iso-13408-6-2020

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number ISO/DIS 13408-6:2019(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

kSIST FprEN ISO 13408-6:2020 https://standards.iteh.ai/catalog/standards/sist/987aad95-ec10-40ab-9b13-2763136ce014/ksist-fpren-iso-13408-6-2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents				
For	eword		v	
Intr	oductio	n	vi	
1		e		
	-			
2		native references		
3	Tern	is and definitions	1	
4	Qual	ity system elements	2	
5	Basic principal of Isolator systems			
	5.1	General		
	5.2	Negative pressure isolators	3	
6	Isolator System Specification			
	6.1	General	3	
	6.2	Risk management		
		6.2.1 General		
	6.0	6.2.2 Negative pressure isolators		
	6.3	User requirement specification		
7		gn of isolator systems		
	7.1	General		
	7.2 7.3	Materials of construction American PREVIEW Air-handling system	5	
	7.3	7.3.1 General		
		7.3.1 General (standards.iteh.ai) 7.3.2 Air change rate	6	
		7.3.3 Airflow pattern	6	
		7.3.4 Temperature/humidity ISO 13408-6:2020	6	
		7.3.3 Airflow pattern 7.3.4 Temperature/humidity/ISO 13408-6:2020 7.3.5 https://particulate.air/specification/ssist/987aad95-ec10-40ab-9b13- 7.3.6 Recirculation of air/ksist-firen-iso-13408-6-2020	6	
		7.3.6 Recirculation of air ksist-tpren-iso-13408-6-2020	7	
		7.3.7 Pressure differentials		
	7.4	Operator interface		
		7.4.1 Isolator gloves/sleeves		
		7.4.2 Suits/han-suits		
		7.4.4 Transfer ports		
	7.5	Ancillary isolator equipment		
		7.5.1 Portable and mobile equipment	8	
	7.6	Surrounding room classification		
	7.7	Process utilities	9	
8	Validation			
	8.1	General		
	8.2	Design qualification		
		8.2.1 General		
		8.2.2 Product/process application		
		8.2.4 Cleaning		
		8.2.5 Bio-decontamination		
		8.2.6 Development and validation of bio-decontamination processes		
		8.2.7 Selection of bio-decontamination agent	11	
		8.2.8 Bio-decontamination agent generation and testing		
		8.2.9 Bio-decontamination parameters		
		8.2.10 Aeration and residue limits		
		8.2.11 Spore log reduction		
		8.2.13 Development and validation of sterilization processes		
		Development and variable of the interest		

iii

oSIST prEN ISO 13408-6:2019

ISO/DIS 13408-6:2019(E)

	8.3	Installation qualification 8.3.1 General		
	8.4 8.5 8.6 8.7	8.3.2 Installation Operational qualification Performance qualification 8.5.1 General 8.5.2 Cleaning 8.5.3 Bio-decontamination 8.5.4 Process simulation tests Review and approval of validation Requalification	141515151616	
9	_	ne monitoring and control		
	9.1	Procedures	17	
	9.2	System integrity		
	9.3	Bio-decontamination process monitoring		
	9.4 9.5	Environmental monitoring		
	9.6	Maintenance and calibration		
10	Person	nnel training	18	
Annex	A (info	ormative) Transfer ports for portable and mobile equipment	20	
Annex		ormative) Isolator system - principal figure of term and flow diagram of air aterial	24	
Annex	C (info	rmative) Isolator system - Critical surfaces in isolator system	25	
Annex		formative) Relationship between this European Standard and the essential rements of Directive 90/385/EEC [OJ L 189] aimed to be covered	26	
	requir	formative) Relationship between this European Standard and the essential rements of Directive 93/42/EEC [Q] L 169] aimed to be covered 1.3	28	
Annex		formative) Relationship between this European Standard and the essential rements of Directive 98/79/EC [OJ L 331] aimed to be covered	30	
Annex	nnex ZD (informative) Relationship between this European Standard and the General Safety and Performance requirements of Regulation (EU) 2017/745 aimed to be covered			
Annex	Safety	formative) Relationship between this European Standard and the General and Performance Requirements of Regulation (EU) 2017/746 aimed to be	35	
Riblio			30	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 198, Sterilization of health care products.

This second edition cancels and replaces the firsts edition (ISO 13408-6:2005), which has been technically revised https://standards.iteh.ai/catalog/standards/sist/987aad95-ec10-40ab-9b13-

2763136ce014/ksist-fpren-iso-13408-6-2020 The main changes compared to the previous edition are as follows:

- changes to the Introduction;
- changes to the Scope;
- addition of the new item No.5 Basic principle of Isolator system;
- addition of risk management approach in chapter 6 "Isolator system specification";
- addition of new informative Annex A "Transfer ports for portable and mobile equipment";
- addition of new informative <u>Annex B</u> "Isolator system principal figure of term and flow diagram of air and material";
- addition of new informative <u>Annex C</u> "Critical surface of Isolator systems(ex.)"

A list of all parts in the ISO 13408- series can be found on the ISO website.

Introduction

A health care product that is labelled "sterile" is manufactured using suitably designed, validated and controlled processes. Wherever possible, it is terminally sterilized in its final, sealed container. When this is not possible, the product is aseptically processed.

Aseptic processing is an exacting and demanding discipline designed to maintain sterility through all stages of preparation, manufacturing, filling and sealing in final containers. It relies on a number of independent factors for prevention of recontamination of previously sterilized components during the assembly or filling of product into a final container.

An effective risk management system addressing aseptic processing design (including the use of barrier separation technology), validation and control, and which identifies, assesses, eliminates (where applicable) and controls contamination risks is a prerequisite to provide assurance of sterility for aseptically processed product.

Various separation systems exist to protect the critical processing zone of an aseptic processing area from non-viable particulate and microbiological contamination and to separate process operators from the critical processing zone.

These systems range from controlled airflow devices based on aerodynamic protection through to separation barriers that combine physical and aerodynamic protection to separate the external cleanroom environment from the critical processing zone, minimizing exposure of this zone to process operators and thereby reducing the opportunities for contamination during processing.

Isolator systems provide physical separation whilst facilitating operator intervention into the controlled processing environment under barrier conditions typically via sealed glove-sleeve systems that are physically connected with glove-ports to the isolator barrier screen(s). To establish a controlled environment, reduction of viable and non-viable particulates within isolators is achieved by validated and reproducible cleaning and bio-decontamination processes, principally achieved through the use of automated methods.

2763136ce014/ksist-fpren-iso-13408-6-2020

In addition to control of bio-contamination and non-viable particulates, isolator systems can include control features, which together with operating practices provide product containment to control cross contamination between process contaminants and product batches, and to manage risk to operators.

Aseptic processing of health care products —

Part 6:

Isolator systems

1 Scope

This document specifies the requirements for and provides guidance on the specification, selection, qualification, bio-decontamination, validation, operation and control of isolator systems related to aseptic processing of health care products and processing of cell based health care products.

This document does not specify requirements for restricted access barrier systems (RABS).

This document does not supersede or replace national regulatory requirements such as Good Manufacturing Practices (GMPs) and/or compendia requirements that pertain in particular to national or regional jurisdictions.

This document does not specify requirements for isolators used for sterility testing; however, some of the principles and information in this document could be applicable to this application.

This International Standard does not define biosafety containment requirements.

(standards.iteh.ai)

2 Normative references

kSIST FprEN ISO 13408-6:2020

The following documents in whole or in partuace normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10648-1:1997, Containment enclosures — Part 1: Design principles

ISO 13408-1:2008, Aseptic processing of health care products — Part 1: General requirements

ISO 13408-1:2008/Amd, 1, Aseptic processing of health care products — Part 1: General requirements

ISO 13408-4, Aseptic processing of health care products — Part 4: Clean-in-place technologies

ISO 13408-5, Aseptic processing of health care products — Part 5: Sterilization in place

ISO 14644-7:2004, Cleanrooms and associated controlled environments — Part 7: Separative devices (clean air hoods, gloveboxes, isolators and mini-environments)

ISO/IEC 90003, Software engineering — Guidelines for the application of ISO 9001:2000 to computer software

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11139:2018 and the following apply.

3.1

ancillary isolator equipment

equipment that can be attached to or detached from the isolator whilst ensuring separation of the internal and external environment

3 2

bio-decontamination

removal and/or reduction of biological contaminants to an acceptable level

3.3

decontamination device

device used to deliver the agent for the decontamination process

3.4

isolator

<aseptic processing> enclosure capable of preventing ingress of contaminants by means of physical separation of the interior from the exterior that is capable of being subject to reproducible interior biodecontamination and where operators always remain separated from the interior of the enclosure by means of an absolute physical barrier

Note 1 to entry: If containment requirements apply (i.e. aseptic processing of hazardous materials) egress also has to be prevented.

3.5

isolator system

isolator with transfer system(s), and ancillary isolator equipment

3.6

safety data sheet

SDS

document specifying the properties of a substance, its potential hazardous effects for humans and the environment, and the precautions necessary to handle and dispose of the substance safely

3.7

(standards.iteh.ai)

transfer port

device acting as interface between the interfers of an isolator and ancillary isolator equipment https://standards.itch.ai/catalog/standards/sist/987aad95-ec10-40ab-9b13-

Note 1 to entry: See example figures in Antitex Acce014/ksist-fpren-iso-13408-6-2020

3.8

transfer system

equipment and process that allows ingress and/or egress of material to an isolator without compromising its environmental quality

4 Quality system elements

Quality elements as defined in ISO 13408-1:2008, Clause 4 shall be implemented to assure control over all activities affecting isolator systems.

5 Basic principal of Isolator systems

5.1 General

An isolator system comprises a piece of equipment, or collection of equipment that provides a controlled environment suitable for aseptic processing that shall be separated from the operator and the surrounding environment using barrier technologies. An isolator system consists of an isolator, its utilities and its surrounding environment, and can include transfer systems and ancillary isolator equipment.

Movement of materials in and out of the isolator is a principal risk in maintaining the quality of the controlled environment. Materials are generally loaded into the isolator before bio-decontamination. After bio-decontamination of the isolator and during operation, ingress of materials to and egress from the isolator shall occur via transfer systems that maintain the quality of the controlled environment.

Isolator systems shall be classified into open and closed systems according to the construction and operation of their transfer systems.

Closed isolator systems shall exclusively incorporate transfer systems that separate the controlled environment from the surrounding environment during operation through the use of a solid physical barrier. A closed system shall restrict the movement of materials through the system to defined batches.

NOTE 1 Examples include autoclaves, pass-through chambers and rapid transfer port (RTP) containers.

Open isolator systems shall incorporate at least one transfer system that provides separation of the controlled environment from the surrounding environment through use of a fluid barrier. Open systems shall allow for the continuous movement of material through the isolator system.

NOTE 2 Examples include exit mouse holes, depyrogenation tunnels and electron beam systems.

Portable and mobile equipment with aseptic transfer ports can allow for connection of an isolator to another aseptic environment during operation.

Specification of a transfer system shall consider the quality of the surrounding environment, whether the transfer system is for ingress and/or egress of items and the characteristics of the items to be transferred.

Isolator system design shall include protective measures for maintaining the quality of the controlled environment based on risk management.

Air supplied to the isolator and the transfer systems shall pass through a filter, usually a high efficiency particulate air (HEPA) or better, which shall render the air at a cleanliness level equivalent to the controlled environment. Surfaces of the isolator system shall be bio-decontaminated. Materials entering the controlled environment shall possess a level of cleanliness equivalent to or better than the controlled environment.

Direct product contact surfaces of items within the controlled environment shall be sterilized. Operators shall access items located within the isolator system via a physical barrier (e.g. glove). Direct product contact surfaces of items within the controlled environment shall be sterilized by a validated process (see 8.2.1).

NOTE 3 Most isolators are operated under positive pressure conditions.

NOTE 4 See Annex B for an example layout of an isolator system.

5.2 Negative pressure isolators

A negative pressure isolator protects the operator and the surrounding environment by providing containment during the processing of hazardous or potent product. It can be used to assist in the management of product quality, containment, bio-contamination risk (where applicable) and safety issues. To effect containment, the critical work zone within the isolator shall be maintained at a negative pressure to the environment surrounding the isolator system. Risk management shall consider the impact of the quality of the surrounding environment, the transfer systems of the isolator and its degree of integrity or leak tightness in relation to the maintenance of the controlled environment.

6 Isolator System Specification

6.1 General

The purpose of this activity is to define the isolator system for aseptic processing. The design specification is driven by the risk assessment of the intended use(s) of the isolator system.

6.2 Risk management

6.2.1 General

The following additional requirements to ISO 13408-1:2008, 5.2, concerning risk management apply:

The risk management process shall consist of a continuous cycle of risk assessment, risk control and risk review. It may make reference to ICH Q9 and/or ISO 14971. Risk assessment shall be used during the development, specification, validation and operation of the isolator system.

The risk assessment for the isolator system shall include, but is not limited to, the following:

- a) surrounding environment;
- b) materials of construction;
- c) configuration including suitability for its intended purpose;
- d) isolator;
- e) transfer system (especially where mouse hole and/or portable mobile equipment exist);
- f) operator interface;
- g) air handling system;
- h) operating control system; Teh STANDARD PREVIEW
- i) internal environmental monitoring (standards.iteh.ai)
- j) cleaning;

<u>kSIST FprEN ISO 13408-6:2020</u>

- k) bio-decontamination; https://standards.iteh.ai/catalog/standards/sist/987aad95-ec10-40ab-9b13-2763136ce014/ksist-fpren-iso-13408-6-2020
- l) maintenance;
- m) the use of suitable safeguards to maintain assurance of sterility and achieve isolator operator safety objectives;
- n) containment.

6.2.2 Negative pressure isolators

The risk assessment for a negative pressure isolator system shall address additional risks that are specific to this type of isolator system, including (but not restricted to), the risk that air containing microorganisms and particulates might enter the isolator system and contaminate product, as well as the risk that air and material exiting the isolator system might pose a contamination risk to the operator and surrounding environment. The rationale for the decision concerning the surrounding room classification shall be documented in the risk assessment.

6.3 User requirement specification

The specification details the design requirement of the isolator system according to the output of the risk assessment process.

This shall include but is not limited to:

- a) physical size and weight constraints;
- b) material transfer requirements;
- c) the airflow requirements;

- d) bio-decontamination requirements;
- e) the requirements for monitoring and detection of contamination;
- f) required operator interactions/interfaces;
- g) materials of construction;
- h) cleaning requirements;
- i) maintenance requirements.

7 Design of isolator systems

7.1 General

7.1.1 ISO 14644-7 shall apply to the design of isolator systems.

For design principles of containment enclosures, see ISO 10648-1.

- **7.1.2** The documentation of the isolator systems design shall include
- all necessary specifications;
- critical operation control points identified via the risk assessment in 6.2;
- a justification for design decisions taken.

kSIST FprEN ISO 13408-6:2020

NOTE 1 Equipment and material transfer is one of the greatest challenges to an isolator system.

NOTE 2 In applications which require both aseptic conditions and protection of the operator, such as the manufacture of bio-hazardous, cytotoxic or radioactive products, the design of the isolator system addresses pressure control (negative or positive) and location and integrity of the isolator system. The design, based on risk assessment, typically considers "safety-specific requirements" for location and environment.

7.2 Materials of construction

- **7.2.1** Materials used in the construction of an isolator system, including gasket materials, fans, ventilation systems, piping, viewing windows and associated fittings shall be chemically, mechanically and thermally compatible with the intended processes and shall have appropriate sorption and outgassing properties (where applicable). Construction materials shall be resistant to corrosion, degradation and heat/fire (where applicable). Materials used shall be cleanable and shall be compatible with cleaning and bio-decontamination agents. Viewing window (panel) materials shall be transparent and shall allow for the required light levels to be maintained.
- **7.2.2** All exposed surfaces within the isolator system (excluding HEPA filters) shall be designed to minimise the accumulation of particles or microorganisms, for example, surfaces are smooth and impervious.
- **7.2.3** Flexible walls shall be thick enough to resist puncture. They shall allow an operator to work safely and efficiently.