
**Fireworks — Category 4 —
Part 2:
Requirements**

*Artifices de divertissement — Catégorie 4 —
Partie 2: Exigences*

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[ISO 26261-2:2017](https://standards.iteh.ai/catalog/standards/sist/c43a83ea-3a82-41be-8619-db2d436c4023/iso-26261-2-2017)

[https://standards.iteh.ai/catalog/standards/sist/c43a83ea-3a82-41be-8619-
db2d436c4023/iso-26261-2-2017](https://standards.iteh.ai/catalog/standards/sist/c43a83ea-3a82-41be-8619-db2d436c4023/iso-26261-2-2017)



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 26261-2:2017

<https://standards.iteh.ai/catalog/standards/sist/c43a83ea-3a82-41be-8619-db2d436c4023/iso-26261-2-2017>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Pyrotechnic composition	2
5 Construction (type test and batch test)	2
6 Means of ignition	2
6.1 Identification (type test and batch test).....	2
6.2 Protection (type test and batch test).....	2
7 Performance	2
7.1 Properties to be checked before functioning tests.....	2
7.1.1 Loose pyrotechnic composition after mechanical conditioning (type test).....	2
7.1.2 Integrity (type test and batch test).....	2
7.2 Properties to be checked during functioning tests.....	3
7.2.1 Principal effects (type test and batch test).....	3
7.2.2 Functioning (type test and batch test).....	3
7.2.3 Stability during functioning (type test and batch test).....	3
7.2.4 Performance parameters (type test and batch test).....	3
7.2.5 Sound pressure level (type test and batch test).....	3
7.2.6 Extinguishing of flames (type test).....	4
7.2.7 Projected debris (type test and batch test).....	4
7.2.8 Burning or incandescent matter (type test and batch test).....	4
8 Protective pack (type test and batch test)	4
9 Type testing	4
9.1 General.....	4
9.2 Number of items to be tested.....	4
9.3 Fireworks supplied in protective packs.....	5
9.4 Test report.....	5
10 Batch testing	5
10.1 General.....	5
10.2 Sampling plans.....	5
10.2.1 General sampling plans.....	5
10.2.2 Sample size for small batches (destructive tests).....	6
10.3 Fireworks in protective packs.....	6
10.4 Nonconformities.....	6
10.4.1 Construction and performances.....	6
10.4.2 Labelling.....	7
10.5 Test report.....	7
10.6 Acceptance or rejection of a batch.....	8
10.6.1 Nonconforming units.....	8
10.6.2 Critical nonconforming units.....	8
10.6.3 Major nonconforming units.....	8
10.6.4 Minor nonconforming units.....	8
Annex A (normative) Mandatory performance parameters	9
Annex B (normative) List of nonconformities for Category 4 fireworks regarding safety in functioning	12

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 264, *Fireworks*.

A list of all the parts in the ISO 26261 series can be found on the ISO website.

<https://standards.iteh.ai/catalog/standards/sist/c43a83ea-3a82-41be-8619-db2d436c4023/iso-26261-2-2017>

Fireworks — Category 4 —

Part 2: Requirements

1 Scope

This document specifies requirements for the construction, performance and protective packaging of Category 4 fireworks, as listed in ISO 26261-1.

This document does not apply for articles containing pyrotechnic compositions that include any of the following substances:

- arsenic or arsenic compounds;
- polychlorobenzenes;
- lead or lead compounds (except for igniters);
- mercury compounds;
- white phosphorus;
- picrates or picric acid.

This document does not apply for theatrical pyrotechnic articles which are designed for indoor or outdoor stage use, including film and television productions or similar use.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2859-1, *Sampling procedures for inspection by attributes — Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*

ISO 26261-1, *Fireworks — Category 4 — Part 1: Terminology*

ISO 26261-3:2017, *Fireworks — Category 4 — Part 3: Test methods*

ISO 26261-4:2017, *Fireworks — Category 4 — Part 4: Minimum labelling requirements and instructions for use*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 26261-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Pyrotechnic composition

No limits are given for the net explosive content (NEC) of Category 4 articles in this document.

The NEC has an influence (directly or indirectly) on the safety distances. For Category 4 fireworks, it is agreed that no fixed minimum safety distances are defined, contrary to Category 1, 2 and 3 fireworks. The safe use of Category 4 fireworks is one of the major responsibilities of the person with specialist knowledge who should determine the minimum safety distance by using the information given in ISO 26261-4:2017, Clause 4.

5 Construction (type test and batch test)

When tested in accordance with ISO 26261-3:2017, 6.1 and 6.2, the article dimensions and gross mass shall be in accordance with the manufacturer's declaration (including tolerances).

The orientation of mortars shall be verified by inspection according to ISO 26261-3:2017, 6.3, during type test.

When the orientation of mortars in combinations is not visible, the maximum firing angle shall be displayed on the label and verified by visual inspection according to ISO 26261-3:2017, 6.7.

6 Means of ignition

6.1 Identification (type test and batch test)

The means of ignition shall be clearly visible or shall be indicated by labelling or instructions, where applicable.

Conformity to this requirement shall be verified by visual examination according to ISO 26261-3:2017, 6.7.

6.2 Protection (type test and batch test)

Where appropriate, the means of ignition shall be protected to avoid accidental ignition of the fireworks.

Conformity to this requirement shall be verified by visual examination according to ISO 26261-3:2017, 6.7.

7 Performance

7.1 Properties to be checked before functioning tests

7.1.1 Loose pyrotechnic composition after mechanical conditioning (type test)

When tested in accordance with ISO 26261-3:2017, 6.8, the loose pyrotechnic composition found outside the article after mechanical conditioning shall be weighed. The mass of the whole loose material shall comply with manufacturer's specifications (if any) and the mass of loose pyrotechnic composition shall not exceed 3 % of the NEC and not more than 1 g for each item tested. If the pyrotechnic composition cannot be separated from the loose material, the same limits shall apply to the whole loose material.

7.1.2 Integrity (type test and batch test)

7.1.2.1 General requirements

There shall be no holes, splits, dents or bulges either in the body of the firework case or in the end closures, except those technically necessary for the correct functioning of the firework. If the end closures are separate components, they shall be in place. There shall be no pyrotechnic leakage of the article to be tested when it is received for testing.

Conformity to these requirements shall be verified by visual examination according to ISO 26261-3:2017, 6.7.

7.1.2.2 Specific requirements

For combinations, each individual element shall be securely attached to the other elements or to the framework. Attachment by the transmitting fuse(s) alone shall be allowed if it is sufficient to keep the elements joined together during normal handling.

Conformity to above requirements shall be checked by visual examination according to ISO 26261-3:2017, 6.7.

7.2 Properties to be checked during functioning tests

7.2.1 Principal effects (type test and batch test)

When tested in accordance with ISO 26261-3:2017, 6.10, the principal effects of each firework shall conform to those specified by the manufacturer or importer as described in ISO 26261-1.

7.2.2 Functioning (type test and batch test)

For type test only, functioning test in accordance with ISO 26261-3:2017, 6.10, shall be performed in as received conditions and, after mechanical and thermal conditions in accordance with ISO 26261-3:2017, 6.8 and 6.9.

For type test and batch test, when tested in accordance with ISO 26261-3:2017, 6.10, the article shall function as intended and shall not function in an erratic and unforeseeable manner.

7.2.3 Stability during functioning (type test and batch test)

When used according to the instructions for use the article shall remain in its initial position and maintain its integrity while functioning, if applicable. Conformity to these requirements shall be checked by the method described in ISO 26261-3:2017, 6.10.

7.2.4 Performance parameters (type test and batch test)

The mandatory parameters listed in [Table A.1](#) shall be measured and recorded according to ISO 26261-3:2017, 6.4, 6.5, 6.10.3 and 6.10.4 (if applicable).

During type tests, all test results shall be within a tolerance of $\pm 20\%$ of the measured average, except as otherwise justified by the manufacturers. The measured average value shall be displayed on the label. This value may be rounded. Tolerances regarding performance parameters are only applicable to articles in as-received condition. During batch tests, all test results shall be within a tolerance of $\pm 30\%$ from the value which is displayed on the label.

These tolerances are not applicable for sound pressure.

7.2.5 Sound pressure level (type test and batch test)

For articles which have report, explosion and/or whistling effects as part of their performance, the sound pressure level shall be measured and recorded at a predefined distance from the firing point according to ISO 26261-3:2017, 6.5.

The maximum measured value or a higher value if specified by the manufacturer shall be displayed on label.

During batch test, the measured value shall not exceed the displayed value.

7.2.6 Extinguishing of flames (type test)

When tested in accordance with ISO 26261-3:2017, 6.6, the existence of flames observed more than 2 min after the end of functioning of the article shall be displayed on the label or in the instructions for use.

Conformity to this requirement shall be tested by visual examination according to ISO 26261-3:2017, 6.7.

7.2.7 Projected debris (type test and batch test)

If the type test has shown projection of debris, the design of the firework shall be examined in accordance with ISO 26261-3:2017, 6.2 to establish whether the debris is a result of the design or malfunction of the article.

If the debris is the result of design, the instructions for use shall be checked according to ISO 26261-3:2017, 6.7, to establish whether the projection of debris has been addressed (including expected distance according to ISO 26261-3:2017, 6.10.2).

When tested in accordance with ISO 26261-3:2017, 6.7, the maximum debris distance found during batch tests shall not exceed the distance displayed on the label.

7.2.8 Burning or incandescent matter (type test and batch test)

The fall of burning or incandescent matter to the ground shall be checked during the functioning test (see ISO 26261-3:2017, 6.10).

8 Protective pack (type test and batch test)

Protective packs (if any) shall provide on their label the necessary information as required by ISO 26261-4:2017, 4.10. This shall be verified according to ISO 26261-3:2017, 6.7, by visual examination.

The means of ignition of pyrotechnic articles within protective pack shall be protected according to 6.2. This shall be verified by visual examination according to ISO 26261-3:2017, 6.7.

9 Type testing

9.1 General

Each firework to be type tested shall meet the requirements indicated in the following:

- [Clause 5](#);
- [Clause 6](#);
- [Clause 7](#);
- [Clause 8](#);
- ISO 26261-4.

9.2 Number of items to be tested

A total number of nine pyrotechnic articles shall be tested in accordance with [Table 1](#).

Table 1 — Number of items to be tested

Number of fireworks to be tested	Condition	Tests in accordance with
3	As received	— Clause 5 — Clause 6 — Clause 7 — ISO 26261-4 — Clause 8
3	After thermal conditioning (see ISO 26261-3:2017, 6.9)	— Clause 6 — Clause 7
3	After mechanical conditioning (see ISO 26261-3:2017, 6.8)	— Clause 6 — Clause 7

For aquatic fireworks and for each condition presented in [Table 1](#), two items shall be tested to determine the effect range and one to check the waterproofness in accordance with ISO 26261-3:2017, 6.10.4.

9.3 Fireworks supplied in protective packs

Fireworks that are supplied in protective packs shall be tested for thermal and mechanical conditioning within the protective pack.

9.4 Test report

The test report shall include at least the following:

- a reference to this document, i.e. ISO 26261-2;
- the complete identification of the sample under test;
- the date of completion of testing;
- the relevant observations concerning the applicable test requirements for the articles under test according to [Table 1](#);
- information about the observations concerning the labelling, instructions for use, the chosen protection of the means of ignition (where appropriate) and whether a protective pack is used for labelling.

For combinations, the participating elements should be listed.

10 Batch testing

10.1 General

For the purposes of batch testing, acceptance sampling in accordance with [10.2](#) to [10.4](#) shall be applied.

10.2 Sampling plans

10.2.1 General sampling plans

Sampling shall be in accordance with ISO 2859-1 using double sampling plans and applying the switching procedures for normal, tightened and reduced inspection. Inspection level S-4 shall apply.