

SLOVENSKI STANDARD SIST EN ISO 12215-8:2018

01-december-2018

Nadomešča:

SIST EN ISO 12215-8:2009

SIST EN ISO 12215-8:2009/AC:2011

Mala plovila - Konstrukcija trupa in zahtevane lastnosti - 8. del: Krmila (ISO 12215-8:2009, vključuje popravek Cor 1:2010)

Small craft - Hull construction and scantlings - Part 8: Rudders (ISO 12215-8:2009, including Cor 1:2010)

iTeh STANDARD PREVIEW

Kleine Wasserfahrzeuge - Rumpfbauweise und Dimensionierung - Teil 8: Ruder (ISO 12215-8:2009, einschließlich Cor 1:2010)

SIST EN ISO 12215-8:2018

Petits navires - Construction de coques et echantillonnage Partie 8: Gouvernails (ISO 12215-8:2009; y compris Cor 1:2010) 2505/sist-en-iso-12215-8-2018

Ta slovenski standard je istoveten z: EN ISO 12215-8:2018

ICS:

47.020.10 Ladijski trupi in njihovi Hulls and their structure

konstrukcijski elementi elements

47.080 Čolni Small craft

SIST EN ISO 12215-8:2018 en,fr,de

SIST EN ISO 12215-8:2018

iTeh STANDARD PREVIEW (standards.iteh.ai)

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN ISO 12215-8

October 2018

ICS 47.080

Supersedes EN ISO 12215-8:2009

English Version

Small craft - Hull construction and scantlings - Part 8: Rudders (ISO 12215-8:2009, including Cor 1:2010)

Petits navires - Construction de coques et échantillonnage - Partie 8: Gouvernails (ISO 12215-8:2009; y compris Cor 1:2010) Kleine Wasserfahrzeuge - Rumpfbauweise und Dimensionierung - Teil 8: Ruder (ISO 12215-8:2009, einschließlich Cor 1:2010)

This European Standard was approved by CEN on 16 April 2018.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom. /standards.ieh.a/catalog/standards/sist/317/3204-6684-45aa-b/64-

387e9b4a95e5/sist-en-iso-12215-8-2018



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN ISO 12215-8:2018 (E)

Contents	Page
European foreword	3
Annex ZA (informative) Relationship between this European Standard and the Essential	
Requirements of Directive 2013/53/EU aimed to be covered	4

iTeh STANDARD PREVIEW (standards.iteh.ai)

European foreword

The text of ISO 12215-8:2009, including Cor 1:2010 has been prepared by Technical Committee ISO/TC 188 "Small craft" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 12215-8:2018.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2019, and conflicting national standards shall be withdrawn at the latest by April 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 12215-8:2009.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 2013/53/EU.

For relationship with EU Directive 2013/53/EU, see informative Annex ZA, which is an integral part of this document.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

SISTEN ISO 12215-82018

https://standards.iteh.ai/catalog/standards/sist/3f773204-6c84-45aa-b764-

387e9b**Endorsement notice**

The text of ISO 12215-8:2009, including Cor 1:2010 has been approved by CEN as EN ISO 12215-8:2018 without any modification.

Annex ZA

(informative)

Relationship between this European Standard and the Essential Requirements of Directive 2013/53/EU aimed to be covered

This European standard has been prepared under a Commission's standardization request M/542 C(2015) 8736 final to provide one voluntary means of conforming to Essential Requirements of Directive 2013/53/EU.

Once this standard is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of this standard given in Table ZA.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding Essential Requirements of that Directive and associated EFTA regulations.

Table ZA.1 — Correspondence between this European Standard and Annex I of Directive 2013/53/EU

Essential Requirements of Directive 2013/53/EU	Clause(s)/sub- clause(s) of this EN	Remarks/Notes
Annex I, Part A, 2.5 – Owner's manual	7.2, 7.3, 12.1 (stand	These clauses specify warnings and information to be included in the owner's manual, if relevant.
Annex I, Part A, 3.1 - Structure	All clauses SIST E ://standards.iteh.ai/catalog 387e9b4a95e	This part of this standard provides scantling requirements applicable to five types of rudder configuration. Type I to Type V, as shown in Figures 2 and 3 of clause 6.2. It applies only to monohulls.
		The application of this part of this standard does not ensure proper steering capabilities.
		Single bearing spade rudders and single hull bearing skeg rudders are not addressed by this standard.
Annex I, Part A, 5.4.2 - Steering system - Emergency arrangements	6.1.6	In respect of the ability of emergency tiller components to transmit rudder torque.

WARNING 1 — Presumption of conformity stays valid only as long as a reference to this European Standard is maintained in the list published in the Official Journal of the European Union. Users of this standard should consult frequently the latest list published in the Official Journal of the European Union.

WARNING 2 — Other Union legislation may be applicable to the product(s) falling within the scope of this standard.

SIST EN ISO 12215-8:2018

INTERNATIONAL STANDARD

ISO 12215-8

First edition 2009-05-15

Small craft — Hull construction and scantlings —

Part 8: **Rudders**

Petits navires — Construction de coques et échantillonnage —

iTeh STParlie 8 Gouvernail PREVIEW (standards.iteh.ai)



ISO 12215-8:2009(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN ISO 12215-8:2018</u> https://standards.iteh.ai/catalog/standards/sist/3f773204-6c84-45aa-b764-387e9b4a95e5/sist-en-iso-12215-8-2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Page

Contents

	ord	
Introdu	ıction	
1	Scope	
2	Normative references	1
3	Terms and definitions	1
4	Symbols	2
5 5.1	Design stressesRudder material	
6	Rudder and steering arrangement, rudder types	
6.1	General	
6.2	Rudder types	б
7	Design rudder force calculation	
7.1 7.2	General	
7.2 7.3	Force F_1 and corresponding load case	. 11 12
	Rudder bending moment and reactions at bearings all.	
8 8.1	GeneralGeneral	. 13 13
8.2	Analysis of spade rudder (Type 1) EN 180 12215-82018	. 13 . 13
8.3	Analysis of skeg rudders (Types II to V) ards/sist/3f773204-6c84-45aa-b764-	. 14
9	Rudder design torque, \$\varphi\$87e9b4a95e5/sist-en-iso-12215-8-2018	. 16
10	Rudder and rudder stock design	. 17
10.1	Load bearing parts of the rudder	
10.2 10.3	Metal rudder stock material Design stress for metal rudder stock	
10.3	Required diameter for solid circular metal rudder stocks	
10.5	Vertical variation of the diameter of a Type I rudder (spade)	. 18
10.6	Round tubular stocks	
10.7 10.8	Non-circular metal rudder stocks	
10.9	Complex structural rudders and rudder stocks in composite	
10.10	Check of deflection of Type I rudder stocks between bearings	
11	Equivalent diameter at the level of notches	. 22
12	Rudder bearings, pintles and gudgeons	
12.1 12.2	Bearing arrangement Clearance between stock and bearings	
	•	
13 13.1	Rudder stock structure and rudder construction	
13.1 13.2	Rudder construction	
13.3	FRP rudder blades	. 24
13.4	Non-FRP rudder blades	. 25
14	Skeg structure	
14.1 14.2	General Design stress	
Annex	A (normative) Metal for rudder stock	. 26

SIST EN ISO 12215-8:2018

ISO 12215-8:2009(E)

Annex B (normative) Complex composite rudder stock design	30
Annex C (normative) Complete calculation for rudders with skeg	32
Annex D (informative) Geometrical properties of some typical rudder blade shapes	36
Annex E (informative) Vertical variation of diameter for Type I rudders	39
Annex F (informative) Type I rudders — Deflection of stock between bearings	41
Bibliography	44

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12215-8 was prepared by Technical Committee ISO/TC 188, Small craft.

ISO 12215 consists of the following parts, under the general title Small craft — Hull construction and scantlings:

- (standards.iteh.ai)

 Part 1: Materials: Thermosetting resins, glass-fibre reinforcement, reference laminate
- Part 2: Materials: Core materials for sandwich construction, embedded materials
- Part 3: Materials: Steel, aluminium alloys, wood, other materials
- Part 4: Workshop and manufacturing
- Part 5: Design pressures for monohulls, design stresses, scantlings determination
- Part 6: Structural arrangements and details
- Part 8: Rudders

ISO 12215-8:2009(E)

Introduction

The reason underlying the preparation of this part of ISO 12215 is that standards and recommended practices for loads on the hull and the dimensioning of small craft differ considerably, thus limiting the general worldwide acceptability of craft. This part of ISO 12215 has been set towards the lower boundary range of common practice.

The objective of this part of ISO 12215 is to achieve an overall structural strength that ensures the watertight and weathertight integrity of the craft.

The working group considers this part of ISO 12215 to have been developed applying present practice and sound engineering principles. The design loads and criteria of this part of ISO 12215 may be used with the scantling determination equations of this part of ISO 12215 or using equivalent engineering methods such as continuous beam theory, matrix-displacement method and classical lamination theory, as indicated within.

Considering future development in technology and craft types, and small craft presently outside the scope of this part of ISO 12215, provided that methods supported by appropriate technology exist, consideration may be given to their use as long as equivalent strength to this part of ISO 12215 is achieved.

The dimensioning according to this part of ISO 12215 is regarded as reflecting current practice, provided the craft is correctly handled in the sense of good seamanship and equipped and operated at a speed appropriate to the prevailing sea state.

(standards.iteh.ai)

Small craft — Hull construction and scantlings —

Part 8:

Rudders

1 Scope

This part of ISO 12215 gives requirements on the scantlings of rudders fitted to small craft with a length of hull, $L_{\rm H}$, of up to 24 m, measured according to ISO 8666. It applies only to monohulls.

This part of ISO 12215 does not give requirements on rudder characteristics required for proper steering capabilities.

This part of ISO 12215 only considers pressure loads on the rudder due to craft manoeuvring. Loads on the rudder or its skeg, where fitted, induced by grounding or docking, where relevant, are out of scope and need to be considered separately to STANDARD PREVIEW

NOTE Scantlings derived from this part of ISO 12215 are primarily intended to apply to recreational craft including charter craft.

SIST EN ISO 12215-8:2018

2 Normative references ds.iteh.ai/catalog/standards/sist/3f773204-6c84-45aa-b764-387e9b4a95e5/sist-en-iso-12215-8-2018

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8666, Small craft — Principal data

ISO 12215-5:2008, Small craft — Hull construction and scantlings — Part 5: Design pressures for monohulls, design stresses, scantlings determination

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

design categories

sea and wind conditions for which a craft is assessed by this part of ISO 12215 to be suitable, provided the craft is correctly handled in the sense of good seamanship and operated at a speed appropriate to the prevailing sea state

3.1.1

design category A ("ocean")

category of craft considered suitable to operate in seas with significant wave heights above 4 m and wind speeds in excess of Beaufort Force 8, but excluding abnormal conditions such as hurricanes

ISO 12215-8:2009(E)

3.1.2

design category B ("offshore")

category of craft considered suitable to operate in seas with significant wave heights up to 4 m and winds of Beaufort Force 8 or less

3.1.3

design category C ("inshore")

category of craft considered suitable to operate in seas with significant wave heights up to 2 m and a typical steady wind force of Beaufort Force 6 or less

3.1.4

design category D ("sheltered waters")

category of craft considered suitable to operate in waters with significant wave heights up to and including 0,3 m with occasional waves of 0,5 m height, for example from passing vessels, and a typical steady wind force of Beaufort Force 4 or less

3.2

loaded displacement mass

 $m_{\rm LDC}$

mass of the craft, including all appendages, when in the fully loaded ready-for-use condition as defined in ISO 8666

3.3

sailing craft

craft for which the primary means of propulsion is wind power, having $A_S > 0.07 (m_{LDC})^{2/3}$ where A_S is the total profile area of all sails that may be set at one time when sailing closed hauled; as defined in ISO 8666 and expressed in square metres

NOTE 1 For the headsails, $A_{\rm S}$ is the area of the fore triangle.

SIST EN ISO 12215-8:2018

NOTE 2 In the rest of this part of ISO 12215, non-sailing craft are called motor craft. 45aa-b764

387e9b4a95e5/sist-en-iso-12215-8-2018

4 Symbols

For the purposes of this document, unless specifically otherwise defined, the symbols given in Table 1 apply.

NOTE The symbols used in the annexes are not listed in Table 1.

Table 1 — Symbols, coefficients, parameters

Symbol	Unit	Designation/meaning of symbol	(Sub)clause/table concerned
A	m ²	Total area of the moving part of the rudder	6.2.1, 6.2.3
A_{0}	m ²	Rudder effective area (Types II to IV)	6.2.3
A_{1}	m ²	Rudder blade area (Types II to IV) or top blade area (Type V)	6.2.3
A_2	m ²	Bottom rudder blade area (Type V)	6.2.3
A_3	m ²	Rudder skeg area [only used to determine type (see Figure 3)]	6.2.3
С	m	Rudder chord length at centre of area level	6.2.1, 6.2.2
c ₁	m	Length of the top chord (Type I)	6.2.1
c_2	m	Length of the bottom chord (Type I)	6.2.1
^{co} 1	m	Compensation at top chord (distance from LE to rotation axis) (Type I)	6.2.2
co_2	m	Compensation at bottom chord (distance from LE to stock CL) (Type I)	6.2.2
d	mm	Required solid stock diameter	10.4
d_{i}	mm	Inner diameter of tubular stock	10.6
d_{o}	mm	Outer diameter of tubular stock	10.6
F	N	Final side force on rudder	7.1
F_1	N	Side force on rudder in design category sea state.	7.2
F_2	N	Side force on rudder during a turn at speed in slight sea	7.3
h_{b}	m	Height between rudder top and centre of hull bearing	6.2.1
h_{C}	m	Height between rudder top and centre of area	6.2.1
h_{d}	m	Height between rudder top and centre of skeg bearing (Type V)	6.2.3
h_{e}	m	Height between rudder bottom and centre of skeg bearing (Type V)	6.2.3
h_{in}	m	Height between centre of upper bearing and a point inside the hull (Type I)	6.2.1
h_{ou}	m	Height between bottom of spade and a point outside the hull (Type I)	6.2.1
h_{r}	m	Average height of rudder blade (see Figure 1)	6.2.1
h_{S}	m	Height of skeg from hull attachment to skeg bearing (Types II to V)	6.2.3
h_{u}	m	Height between centres of hull (lower) bearing and upper bearing	6.2.1
k_{b}	1	Rudder bending coefficient	6.2.1
k_{FLAT}	1	Coefficient lowering force for flat or wedge rudder blade shape	7.3
$k_{\sf GAP}$	1	Coefficient lowering force due to gap hull/rudder top	7.2
k_{LD}	1	Length displacement coefficient	7.2
k _S	1	Coefficient for skeg deflection	8.3.4
$k_{\sf SEA}$	1	Coefficient considering extra load due to sea in design categories A and B	7.2
k _{SERV}	1	Coefficient considering lower required service in design categories C and D	7.3
k _{SIG}	1	Coefficient lowering design stress for F_2	7.3
k _{USE}	1	Coefficient considering lower usage of craft with damage survey	7.2
k ₅	1	Fibre type factor	13.3.1.2
L_{S}	m	Effective length of the skeg	8.3.4