

SLOVENSKI STANDARD SIST EN 301 487-1 V1.1.1:2005

01-januar-2005

ü]fc_cdUgcjbc`X][]hUbc`cafYÿ^Y`n`]bhY[f]fUb]a]`ghcf]hjUa]`f6!=G8BŁ'Ë`Dfchc_c` X][]hUbY`bUfcb]ý_Y`g][bU]nUV]^Y`ýh''&`fBGG&Ł'Ë`Nacÿbcgh_caih]fUbY`bUj]XYnbY dch]`Ë`%'XY`.`GdYW]Z_UW]^Udfchc_c`U`Qhf]dcfc]`c`=Hl!H'E"&-'(`f1%---Łž gdfYaYb^YbcQ

Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling No. two (DSS2) protocol; Switched virtual path capability; Part 1: Protocol Specification [ITU-T Recommendation Q.2934 (1999), modified]

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 487-1 V1.1.1:2005 https://standards.iteh.ai/catalog/standards/sist/bb29d195-c43f-4784-9c73-aaae11919fdd/sist-en-301-487-1-v1-1-1-2005

en

Ta slovenski standard je istoveten z: EN 301 487-1 Version 1.1.1

ICS:

33.080 Digitalno omrežje z

integriranimi storitvami

(ISDN)

Integrated Services Digital

Network (ISDN)

SIST EN 301 487-1 V1.1.1:2005

SIST EN 301 487-1 V1.1.1:2005

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 301 487-1 V1.1.1:2005</u> https://standards.iteh.ai/catalog/standards/sist/bb29d195-c43f-4784-9c73-aaae11919fdd/sist-en-301-487-1-v1-1-1-2005

ETSI EN 301 487-1 V1.1.1 (2000-09)

European Standard (Telecommunications series)

Broadband Integrated Services Digital Network (B-ISDN);
Digital Subscriber Signalling No. two (DSS2) protocol;
Switched virtual path capability;
Part 1: Protocol Specification

[ITU-T Recommendation Q.2934 (1999), modified]

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 487-1 V1.1.12005 https://standards.iteh.ai/catalog/standards/sist/bb29d195-c43f-4784-9c73-aaae11919fdd/sist-en-301-487-1-v1-1-1-2005



2

Reference
DEN/SPAN-05175-1

Keywords
B-ISDN, DSS2, protocol

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la

Teh Sous-Préfecture de Grasse (06) N° 7803/88/ IEW

(standards.iteh.ai)

<u>SIST EN 301 487-1 V1.1.1:2005</u> https://standards.iteh.ai/catalog/standards/sist/bb29d195-c43f-4784-9c73-aaae11919fdd/sist-en-301-487-1-v1-1-1-2005

Important notice

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at http://www.etsi.org/tb/status/

If you find errors in the present document, send your comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Intellectual Property Rights

proforma specification for the network".

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://www.etsi.org/ipr).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN).

The present document is part 1 of a multi-part EN covering the Broadband Integrated Services Digital Network (B-ISDN); Digital Sibscriber Signalling No. two (DSS2) protocol; Switched virtual path capability, as described below:

.,,	
Part 1:	"Protocol specification [ITU-T Recommendation Q.2934 (1998), modified]";
Part 2:	"Protocol Implementation Conformance Statement (PICS) proforma specification";
Part 3:	"Test Suite Structure and Test Purposes (TSS&TP) specifications for the user";
Part 4:	"Abstract test Suite (ATS) and partial Protocol Implementation eXtra Information for the Testing (PIXIT) proforma specification for the user";
Part 5:	"Test Suite Structure and Test Purpose (TSS&TP) specification for the network"; https://standards.iteh.ai/catalog/standards/sist/bb29d195-c43f-4784-9c73-
Part 6:	"Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT)

National transposition da	ites
Date of adoption of this EN:	25 August 2000
Date of latest announcement of this EN (doa):	30 November 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2001
Date of withdrawal of any conflicting National Standard (dow):	31 May 2001

Endorsement notice

The element of ITU-T Recommendation Q.2934 (1998) apply, with the following modifications:

NOTE: New or modified text is indicated using sidebars. In addition, underlining and/or strike-out are used to highlight detailed modifications where necessary.

Clause 1

Replace clause 1 by:

1 Scope

The present document specifies the stage three of: Signalling protocol for establishing, maintaining and clearing switched virtual path capability for the Broadband-Integrated Services Digital Network (B-ISDN) at the T_B reference point or coincident S_B and T_B reference point (as defined in CCITT Recommendation I.413 [33]) by means of the Digital Subscriber Signalling System No. two (DSS2) protocol. Stage three identifies the protocol procedures and switching functions needed to support a telecommunications service (see CCITT Recommendation I.130 [32]).

In addition, the present document specifies the protocol requirements at the T_B reference point where the service is provided to the user via a private B-ISDN.

NOTE 1: Procedures at the T_B reference point, to support the access of a private B-ISDN to the public B-ISDN, are **not** explicitly identified in the present document, however, some procedures are applicable only at the T_B reference point.

A basic telecommunications service is a fundamental type of service. It forms the basis on which supplementary services may be added.

NOTE 2: Specific requirements of individual B-ISDN connection-oriented basic telecommunication services are not covered by the present document.

Further parts of the present document provide the method of testing and detailed application specific requirements to determine conformance to the present document.

The present document is applicable to equipment supporting connection-oriented basic B-ISDN telecommunication services, to be attached at either side of a T_B reference point or coincident S_B and T_B reference points when used as an access to the public B-ISDN.

The provision of this service requires the support of the protocol for the basic point-to-point call/bearer connections as defined in the EN 300 443-1 [18], and the Additional Traffic Capabilities defined in the EN 301 068 series [19].

Subclause 2

Insert the following references at the end of subclause 2:

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
 - [16] ITU-T Recommendation I.371 (1995): "Traffic control and congestion control in B-ISDN".
 - [17] ITU-T Recommendation I.356 (1996): "B-ISDN ATM layer cell transfer performance".
 - [18] EN 300 443-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".
 - [19] EN 301 068 (all parts): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM transfer capability and traffic parameter indication".
 - [20] EN 301 067-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Negotiation during call/connection establishment phase; Part 1: Protocol specification [TTU-T Recommendation Q.2962 (1996), modified] "fid/sist-en-301-487-1-v1-1-1-2005
 - [21] EN 301 003-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Peak cell rate modification by the connection owner; Part 1: Protocol specification [ITU-T Recommendation Q.2963.1 (1996), modified]".
 - [22] EN 301 276-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Modification procedures for sustainable cell rate parameters; Part 1: Protocol specification [ITU-T Recommendation Q.2963.2 (1997), modified]".
 - [23] ETS 300 661-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Direct Dialling In (DDI) supplementary service; Part 1: Protocol specification [ITU-T Recommendation Q.2951, clause 1 (1995), modified]".
 - [24] ETS 300 662-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Multiple Subscriber Number (MSN) supplementary service; Part 1: Protocol specification [ITU-T Recommendation Q.2951, clause 2 (1995), modified]".
 - [25] ETS 300 663-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Calling Line Identification Presentation (CLIP) supplementary service; Part 1: Protocol specification [ITU-T Recommendation Q.2951, clause 3 (1995), modified]".
 - [26] ETS 300 664-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Calling Line Identification Restriction (CLIR) supplementary service; Part 1: Protocol specification [ITU-T Recommendation Q.2951, clause 4 (1995), modified]".

[27]	ETS 300 665-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connected Line Identification Presentation (COLP) supplementary service; Part 1: Protocol specification [ITU-T Recommendation Q.2951, clause 5 (1995), modified]".
[28]	ETS 300 666-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connected Line Identification Restriction (COLR) supplementary service; Part 1: Protocol specification [ITU-T Recommendation Q.2951, clause 6 (1995), modified]".
[29]	ETS 300 667-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Subaddressing (SUB) supplementary service; Part 1: Protocol specification [ITU-T Recommendation Q.2951, clause 8 (1995), modified]".
[30]	ETS 300 770-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Closed User Group (CUG) supplementary service; Part 1: Protocol specification [ITU-T Recommendation Q.2955.1 (1996), modified]".
[31]	ETS 300 668-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; User-to-User Signalling (UUS) supplementary service; Part 1: Protocol specification [ITU-T Recommendation Q.2957, clause 1 (1995), modified]".
[32]	CCITT Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN
[33]	CCITT Recommendation I.413: "B-ISDN user-network interface".
[34]	EN 301 485-1; "Broadband Integrated Services Network (B-ISDN); Digital Subscriber Signalling No. two (DSS2) protocol; Support of ATM end system addressing format by Number identification supplementary services; Part 1: Protocol Specification [ITU-T Recommendation Q.2951.9 (1999) modified]".
[35]	EN 301 486-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM traffic descriptor modification with negotiation by the connection owner; Part 1: Protocol specification [endorsement of ITU-T Recommendation Q.2963.3]".

Throughout the text of ITU-T Recommendation Q.2934

Replace references as shown in the following table.

Reference in ITU-T Recommendation	Modified reference
Q.2934	
ITU-T Recommendation Q.2931 [1]	ITU-T Recommendation Q.2931 as modified by EN 300 443-1 [18]
ITU-T Recommendation Q.2961.1 [2]	ITU-T Recommendation Q.2961.1 as modified by EN 301 068-1 [19]
ITU-T Recommendation Q.2961.2 [3]	ITU-T Recommendation Q.2961.2 as modified by EN 301 068-1 [19]
ITU-T Recommendation Q.2961.3 [4]	ITU-T Recommendation Q.2961.3 as modified by EN 301 068-1 [19]
ITU-T Recommendation Q.2961.4 [5]	ITU-T Recommendation Q.2961.4 as modified by EN 301 068-1 [19]
ITU-T Recommendation Q.2961.6 [6]	ITU-T Recommendation Q.2961.6 as modified by EN 301 068-1 [19]
ITU-T Recommendation Q.2962.1 [7]	ITU-T Recommendation Q.2962.1 as modified by EN 301 067-1 [20]
ITU-T Recommendation Q.2963.1 [8]	ITU-T Recommendation Q.2963.1 as modified by EN 301 003-1 [21]
ITU-T Recommendation Q.2963.2 [9]	ITU-T Recommendation Q.2963.2 as modified by EN 301 276-1 [22]
ITU-T Recommendation Q.2963.3 [10]	ITU-T Recommendation Q.2963.3 as modified by EN 301 486-1 [35]
ITU-T Recommendation Q.2951 [11]	ITU-T Recommendation Q.2951 as modified by ETS 300 661-1 [23] to
	ETS 300 666-1 [28] and EN 301 485-1 [34] (AESA)
ITU-T Recommendation Q.2955 [12]	ITU-T Recommendation Q.2955 as modified by ETS 300 770-1 [30]
ITU-T Recommendation Q.2957 [13]	ITU-T Recommendation Q.2957 as modified by ETS 300 668-1 [31]