

ETSI TS 138 141-1 V17.5.0 (2022-04)



iTeh STANDARD
5G;
NR;
PREVIEW

Base Station (BS) conformance testing
Part 1: Conducted conformance testing
(3GPP TS 38.141-1 version 17.5.0 Release 17)

<https://standards.iteh.ai/catalog/standards/sist/36e4579c-a5a0-493e-90d6-a5a23da85939/etsi-ts-138-141-1-v17-5-0-2022-04>



Reference

RTS/TSGR-0438141-1vh50

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	15
1 Scope	17
2 References	17
3 Definitions, symbols and abbreviations	19
3.1 Definitions	19
3.2 Symbols.....	21
3.3 Abbreviations	23
4 General conducted test conditions and declarations.....	24
4.1 Measurement uncertainties and test requirements	24
4.1.1 General.....	24
4.1.2 Acceptable uncertainty of Test System.....	24
4.1.2.1 General	24
4.1.2.2 Measurement of transmitter	25
4.1.2.3 Measurement of receiver.....	27
4.1.2.4 Measurement of performance requirements.....	31
4.1.3 Interpretation of measurement results.....	31
4.2 Conducted requirement reference points.....	31
4.2.1 BS type 1-C	31
4.2.2 BS type 1-H.....	32
4.3 Base station classes	33
4.4 Regional requirements.....	33
4.5 BS configurations.....	35
4.5.1 BS type 1-C	35
4.5.1.1 Transmit configurations.....	35
4.5.1.1.1 General.....	35
4.5.1.1.2 Transmission with multiple transmitter antenna connectors.....	35
4.5.1.2 Receive configurations.....	35
4.5.1.2.1 General	35
4.5.1.2.2 Reception with multiple receiver antenna connectors, receiver diversity.....	36
4.5.1.3 Duplexers	36
4.5.1.4 Power supply options	36
4.5.1.5 Ancillary RF amplifiers.....	36
4.5.2 BS type 1-H.....	37
4.5.2.1 Transmit configurations	37
4.5.2.2 Receive configurations.....	38
4.5.2.3 Power supply options	38
4.5.3 BS with integrated Iuant BS modem	39
4.6 Manufacturer declarations.....	39
4.7 Test configurations	45
4.7.1 General.....	45
4.7.2 Test signal used to build Test Configurations.....	45
4.7.3 NRTC1: Contiguous spectrum operation.....	45
4.7.3.1 NRTC1 generation	46
4.7.3.2 NRTC1 power allocation	46
4.7.4 NRTC2: Contiguous CA occupied bandwidth.....	46
4.7.4.1 NRTC2 generation	46
4.7.4.2 NRTC2 power allocation	47
4.7.5 NRTC3: Non-contiguous spectrum operation	47
4.7.5.1 NRTC3 generation	47
4.7.5.2 NRTC3 power allocation	47
4.7.6 NRTC4: Multi-band test configuration for full carrier allocation.....	47

4.7.6.1	NRTC4 generation	47
4.7.6.2	NRTC4 power allocation	48
4.7.7	NRTC5: Multi-band test configuration with high PSD per carrier	48
4.7.7.1	NRTC5 generation	48
4.7.7.2	NRTC5 power allocation	49
4.7.8	NRTC6: Non-contiguous spectrum operation in band n46, n96 and n102	49
4.7.8.1	NRTC6 generation	49
4.7.8.2	NRTC6 power allocation	49
4.8	Applicability of requirements	50
4.8.1	General	50
4.8.2	Requirement set applicability	50
4.8.3	Applicability of test configurations for single-band operation	50
4.8.4	Applicability of test configurations for multi-band operation	51
4.9	RF channels and test models	52
4.9.1	RF channels	52
4.9.2	Test models	53
4.9.2.1	General	53
4.9.2.2	FR1 test models	53
4.9.2.2.1	FR1 test model 1.1 (NR-FR1-TM1.1)	55
4.9.2.2.2	FR1 test model 1.2 (NR-FR1-TM1.2)	56
4.9.2.2.3	FR1 test model 2 (NR-FR1-TM2)	56
4.9.2.2.4	FR1 test model 2a (NR-FR1-TM2a)	57
4.9.2.2.4A	FR1 test model 2b (NR-FR1-TM2b)	57
4.9.2.2.5	FR1 test model 3.1 (NR-FR1-TM3.1)	57
4.9.2.2.6	FR1 test model 3.1a (NR-FR1-TM3.1a)	58
4.9.2.2.6A	FR1 test model 3.1b (NR-FR1-TM3.1b)	58
4.9.2.2.7	FR1 test model 3.2 (NR-FR1-TM3.2)	58
4.9.2.2.8	FR1 test model 3.3 (NR-FR1-TM3.3)	59
4.9.2.2.9	NB-IoT operation in NR in-band test model (NR-N-TM)	60
4.9.2.3	Data content of Physical channels and Signals for NR-FR1-TM	60
4.9.2.3.1	PDCCH	60
4.9.2.3.2	PDSCH	61
4.9.2.4	Data content of Physical channels and Signals for NR-N-TM	62
4.9.3	NB-IoT testing	62
4.10	Requirements for contiguous and non-contiguous spectrum	62
4.11	Requirements for BS capable of multi-band operation	63
4.12	Format and interpretation of tests	63
5	Operating bands and channel arrangement	65
6	Conducted transmitter characteristics	66
6.1	General	66
6.1.1	BS type 1-C	66
6.1.2	BS type 1-H	66
6.2	Base station output power	66
6.2.1	Definition and applicability	66
6.2.2	Minimum requirement	67
6.2.3	Test purpose	67
6.2.4	Method of test	67
6.2.4.1	Initial conditions	67
6.2.4.2	Procedure	68
6.2.5	Test requirement	68
6.3	Output power dynamics	68
6.3.1	General	68
6.3.2	RE power control dynamic range	69
6.3.2.1	Definition and applicability	69
6.3.2.2	Minimum requirement	69
6.3.2.3	Test purpose	69
6.3.3	Total power dynamic range	69
6.3.3.1	Definition and applicability	69
6.3.3.2	Minimum requirement	69
6.3.3.3	Test purpose	69

6.3.3.4	Method of test	69
6.3.3.4.1	Initial conditions	69
6.3.3.4.2	Procedure	69
6.3.3.5	Test requirements	70
6.3.4	NB-IoT RB power dynamic range	71
6.3.4.1	Definition and applicability	71
6.3.4.2	Minimum requirement	71
6.3.4.3	Test purpose	71
6.3.4.4	Method of test	71
6.3.4.5	Test requirements	71
6.4	Transmit ON/OFF power	71
6.4.1	Transmitter OFF power	71
6.4.1.1	Definition and applicability	71
6.4.1.2	Minimum requirement	72
6.4.1.3	Test purpose	72
6.4.1.4	Method of test	72
6.4.1.5	Test requirements	72
6.4.2	Transmitter transient period	72
6.4.2.1	Definition and applicability	72
6.4.2.2	Minimum requirement	73
6.4.2.3	Test purpose	73
6.4.2.4	Method of test	73
6.4.2.4.1	Initial conditions	73
6.4.2.4.2	Procedure	73
6.4.2.5	Test requirements	74
6.5	Transmitted signal quality	74
6.5.1	General	74
6.5.2	Frequency error	74
6.5.2.1	Definition and applicability	74
6.5.2.2	Minimum Requirement	74
6.5.2.3	Test purpose	74
6.5.2.4	Method of test	74
6.5.2.5	Test Requirements	74
6.5.3	Modulation quality	75
6.5.3.1	Definition and applicability	75
6.5.3.2	Minimum Requirement	75
6.5.3.3	Test purpose	75
6.5.3.4	Method of test	75
6.5.3.4.1	Initial conditions	75
6.5.3.4.2	Procedure	75
6.5.3.5	Test requirements	76
6.5.4	Time alignment error	78
6.5.4.1	Definition and applicability	78
6.5.4.2	Minimum requirement	79
6.5.4.3	Test purpose	79
6.5.4.4	Method of test	79
6.5.4.4.1	Initial conditions	79
6.5.4.4.2	Procedure	79
6.5.4.5	Test requirement	80
6.6	Unwanted emissions	80
6.6.1	General	80
6.6.2	Occupied bandwidth	81
6.6.2.1	Definition and applicability	81
6.6.2.2	Minimum Requirements	81
6.6.2.3	Test purpose	81
6.6.2.4	Method of test	81
6.6.2.4.1	Initial conditions	81
6.6.2.4.2	Procedure	82
6.6.2.5	Test requirements	82
6.6.3	Adjacent Channel Leakage Power Ratio (ACLR)	82
6.6.3.1	Definition and applicability	82
6.6.3.2	Minimum requirement	83

6.6.3.3	Test purpose	83
6.6.3.4	Method of test	83
6.6.3.4.1	Initial conditions	83
6.6.3.4.2	Procedure	83
6.6.3.5	Test requirements	84
6.6.3.5.1	General requirements	84
6.6.3.5.2	Limits and <i>basic limits</i>	84
6.6.3.5.3	<i>BS type 1-C</i>	88
6.6.4	Operating band unwanted emissions	89
6.6.4.1	Definition and applicability	89
6.6.4.2	Minimum requirement	90
6.6.4.3	Test purpose	90
6.6.4.4	Method of test	90
6.6.4.4.1	Initial conditions	90
6.6.4.4.2	Procedure	90
6.6.4.5	Test requirements	92
6.6.4.5.1	General requirements	92
6.6.4.5.2	Basic limits for Wide Area BS (Category A)	92
6.6.4.5.3	Basic limits for Wide Area BS (Category B)	93
6.6.4.5.3.1	Category B requirements (Option 1)	93
6.6.4.5.3.2	Category B requirements (Option 2)	94
6.6.4.5.4	Basic limits for Medium Range BS (Category A and B)	95
6.6.4.5.5	Basic limits for Local Area BS (Category A and B)	97
6.6.4.5.5A	Basic limits for Local Area and Medium Range BS for band n46, n96 and n102 (Category A and B)	98
6.6.4.5.6	Basic limits for additional requirements	101
6.6.4.5.6.1	Limits in FCC Title 47	101
6.6.4.5.6.2	Protection of DTT	101
6.6.4.5.6.3	Additional operating band unwanted emissions limits for Band n48	101
6.6.4.5.6.4	Additional operating band unwanted emissions limits for Band n53	101
6.6.4.5.6.5	Protection of GPS	102
6.6.4.5.7	<i>BS type 1-C</i>	103
6.6.4.5.8	<i>BS type 1-H</i>	103
6.6.5	Transmitter spurious emissions	103
6.6.5.1	Definition and applicability	103
6.6.5.2	Minimum requirement	103
6.6.5.3	Test purpose	103
6.6.5.4	Method of test	104
6.6.5.4.1	Initial conditions	104
6.6.5.4.2	Procedure	104
6.6.5.5	Test requirements	105
6.6.5.5.1	Basic limits	105
6.6.5.5.1.1	Tx spurious emissions	105
6.6.5.5.1.2	Protection of the BS receiver of own or different BS	105
6.6.5.5.1.3	Additional spurious emissions requirements	106
6.6.5.5.1.4	Co-location with other base stations	116
6.6.5.5.2	(void)	121
6.6.5.5.3	<i>BS type 1-C</i>	121
6.6.5.5.4	<i>BS type 1-H</i>	122
6.7	Transmitter intermodulation	122
6.7.1	Definition and applicability	122
6.7.2	Minimum requirement	122
6.7.3	Test purpose	123
6.7.4	Method of test	123
6.7.4.1	Initial conditions	123
6.7.4.2	Procedure	123
6.7.5	Test requirements	124
6.7.5.1	<i>BS type 1-C</i>	124
6.7.5.1.1	Co-location minimum requirements	124
6.7.5.1.2	Additional requirements	125
6.7.5.2	<i>BS type 1-H</i>	125
6.7.5.2.1	Co-location minimum requirements	125

6.7.5.2.2	Intra-system minimum requirements	126
6.7.5.2.3	Additional requirements	126
7	Conducted receiver characteristics	127
7.1	General	127
7.2	Reference sensitivity level.....	127
7.2.1	Definition and applicability	127
7.2.2	Minimum requirement	127
7.2.3	Test purpose.....	127
7.2.4	Method of test	128
7.2.4.1	Initial conditions	128
7.2.4.2	Procedure	128
7.2.5	Test requirements.....	128
7.3	Dynamic range	133
7.3.1	Definition and applicability	133
7.3.2	Minimum requirement	133
7.3.3	Test purpose.....	133
7.3.4	Method of test	133
7.3.4.1	Initial conditions	133
7.3.4.2	Procedure	133
7.3.5	Test requirements.....	133
7.4	In-band selectivity and blocking	143
7.4.1	Adjacent Channel Selectivity (ACS)	143
7.4.1.1	Definition and applicability.....	143
7.4.1.2	Minimum requirement	143
7.4.1.3	Test purpose	143
7.4.1.4	Method of test	144
7.4.1.4.1	Initial conditions.....	144
7.4.1.4.2	Procedure.....	144
7.4.1.5	Test requirements.....	144
7.4.2	In-band blocking.....	146
7.4.2.1	Definition and applicability.....	146
7.4.2.2	Minimum requirement	146
7.4.2.3	Test purpose	146
7.4.2.4	Method of test	147
7.4.2.4.1	Initial conditions	147
7.4.2.4.2	Procedure for general blocking.....	147
7.4.2.4.3	Procedure for narrowband blocking	147
7.4.2.5	Test requirements.....	148
7.5	Out-of-band blocking	151
7.5.1	Definition and applicability	151
7.5.2	Minimum requirement	151
7.5.3	Test purpose.....	151
7.5.4	Method of test	152
7.5.4.1	Initial conditions	152
7.5.4.2	Procedure	152
7.5.5	Test requirements.....	152
7.5.5.1	General requirements	152
7.5.5.2	Co-location requirements.....	153
7.5.5.3	Additional requirement	154
7.5.5.3.1	Additional requirement for Band n101.....	154
7.6	Receiver spurious emissions.....	155
7.6.1	Definition and applicability	155
7.6.2	Minimum requirement	155
7.6.3	Test purpose.....	155
7.6.4	Method of test	155
7.6.4.1	Initial conditions	155
7.6.4.2	Procedure	155
7.6.5	Test requirements.....	156
7.6.5.1	Basic limits.....	156
7.6.5.2	BS type 1-C.....	156
7.6.5.3	BS type 1-H.....	157

7.7	Receiver intermodulation	157
7.7.1	Definition and applicability	157
7.7.2	Minimum requirement	157
7.7.3	Test purpose.....	157
7.7.4	Method of test	157
7.7.4.1	Initial conditions	157
7.7.4.2	Procedure	158
7.7.5	Test requirements.....	158
7.8	In-channel selectivity	164
7.8.1	Definition and applicability	164
7.8.2	Minimum requirement	164
7.8.3	Test purpose.....	164
7.8.4	Method of test	164
7.8.4.1	Initial conditions	164
7.8.4.2	Procedure	164
7.8.5	Test requirements.....	165
8	Conducted performance characteristics.....	173
8.1	General	173
8.1.1	Scope and definitions.....	173
8.1.2	Applicability rule	174
8.1.2.0	General	174
8.1.2.1	Applicability of PUSCH performance requirements.....	174
8.1.2.1.1	Applicability of requirements for different subcarrier spacings	174
8.1.2.1.2	Applicability of requirements for different channel bandwidths	174
8.1.2.1.3	Applicability of requirements for different configurations.....	174
8.1.2.1.7	Applicability of 2-step RA type requirements for different subcarrier spacings	175
8.1.2.2	Applicability of PUCCH performance requirements	175
8.1.2.2.1	Applicability of requirements for different formats.....	175
8.1.2.2.2	Applicability of requirements for different subcarrier spacings	175
8.1.2.2.3	Applicability of requirements for different channel bandwidths	175
8.1.2.2.4	Applicability of requirements for different configurations.....	175
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH.....	175
8.1.2.3	Applicability of PRACH performance requirements	176
8.1.2.3.1	Applicability of requirements for different formats.....	176
8.1.2.3.2	Applicability of requirements for different subcarrier spacings	176
8.1.2.3.3	Applicability of requirements for different channel bandwidths	176
8.1.2.3.4	Applicability of requirements for different restricted set types of long PRACH format 0	176
8.1.2.4	Applicability of PUSCH for high speed train performance requirements.....	176
8.1.2.4.1	Applicability of requirements for different speeds	176
8.1.2.4.2	Applicability of requirements for 1T1R	176
8.1.2.5	Applicability of interlaced PUSCH performance requirements	176
8.1.2.5.1	General applicability of interlaced PUSCH performance requirements	176
8.1.2.5.2	Applicability of requirements for different subcarrier spacings	176
8.1.2.5.3	Applicability of requirements for different channel bandwidths	177
8.1.2.5.4	Applicability of requirements for different configurations.....	177
8.1.2.5.5	Applicability of CG-UCI multiplexed on PUSCH requirements.....	177
8.1.2.6	Applicability of interlaced PUCCH performance requirements.....	177
8.1.2.6.1	General applicability of interlaced PUCCH performance requirements.....	177
8.1.2.6.2	Applicability of requirements for different formats.....	177
8.1.2.6.3	Applicability of requirements for different subcarrier spacings	177
8.1.2.6.4	Applicability of requirements for different channel bandwidths	177
8.1.2.7	Applicability of performance requirements for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	178
8.1.2.7.1	Applicability of requirements for different formats.....	178
8.1.2.7.2	Applicability of requirements for different subcarrier spacings	178
8.1.2.7.3	Applicability of requirements for different channel bandwidths	178
8.2	Performance requirements for PUSCH	178
8.2.1	Performance requirements for PUSCH with transform precoding disabled	178
8.2.1.1	Definition and applicability.....	178
8.2.1.2	Minimum Requirement	178
8.2.1.3	Test Purpose	178
8.2.1.4	Method of test	178

8.2.1.4.1	Initial Conditions	178
8.2.1.4.2	Procedure	178
8.2.1.5	Test Requirement	179
8.2.2	Performance requirements for PUSCH with transform precoding enabled	187
8.2.2.1	Definition and applicability	187
8.2.2.2	Minimum Requirement	187
8.2.2.3	Test Purpose	187
8.2.2.4	Method of test	187
8.2.2.4.1	Initial Conditions	187
8.2.2.4.2	Procedure	188
8.2.2.5	Test Requirement	189
8.2.3	Performance requirements for UCI multiplexed on PUSCH	189
8.2.3.1	Definition and applicability	189
8.2.3.2	Minimum Requirements	190
8.2.3.3	Test purpose	190
8.2.3.4	Method of test	190
8.2.3.4.1	Initial conditions	190
8.2.3.4.2	Procedure	190
8.2.3.5	Test Requirement	191
8.2.4	Performance requirements for PUSCH for high speed train	192
8.2.4.1	Definition and applicability	192
8.2.4.2	Minimum Requirement	193
8.2.4.3	Test Purpose	193
8.2.4.4	Method of test	193
8.2.4.4.1	Initial Conditions	193
8.2.4.4.2	Procedure	193
8.2.4.5	Test Requirement	194
8.2.5	Performance requirements for UL timing adjustment	197
8.2.5.1	Definition and applicability	197
8.2.5.2	Minimum Requirement	197
8.2.5.3	Test Purpose	197
8.2.5.4	Method of test	197
8.2.5.4.1	Initial Conditions	197
8.2.5.4.2	Procedure	197
8.2.5.5	Test Requirement for High Speed Train	200
8.2.6	Performance requirements for PUSCH with 0.001% BLER	201
8.2.6.1	Definition and applicability	201
8.2.6.2	Minimum Requirement	201
8.2.6.3	Test Purpose	201
8.2.6.4	Method of test	201
8.2.6.4.1	Initial Conditions	201
8.2.6.4.2	Procedure	201
8.2.6.5	Test Requirement	202
8.2.7	Performance requirements for PUSCH repetition Type A	203
8.2.7.1	Definition and applicability	203
8.2.7.2	Minimum Requirement	204
8.2.7.3	Test Purpose	204
8.2.7.4	Method of test	204
8.2.7.4.1	Initial Conditions	204
8.2.7.4.2	Procedure	204
8.2.7.5	Test Requirement	205
8.2.8	Performance requirements for PUSCH Mapping Type B with non-slot transmission	207
8.2.8.1	Definition and applicability	207
8.2.8.2	Minimum Requirement	207
8.2.8.3	Test Purpose	207
8.2.8.4	Method of test	207
8.2.8.4.1	Initial Conditions	207
8.2.8.4.2	Procedure	207
8.2.8.5	Test Requirement	208
8.2.9	Performance requirements for PUSCH msgA for 2-step RA type	209
8.2.9.1	Definition and applicability	209
8.2.9.2	Minimum Requirement	209

8.2.9.3	Test Purpose	209
8.2.9.4	Method of test	209
8.2.9.4.1	Initial Conditions	209
8.2.9.4.2	Procedure	209
8.2.9.5	Test Requirement	211
8.2.10	Requirements for interlaced PUSCH	212
8.2.10.1	Definition and applicability	212
8.2.10.2	Minimum Requirement	212
8.2.10.3	Test Purpose	212
8.2.10.4	Method of test	212
8.2.10.4.1	Initial Conditions	212
8.2.10.4.2	Procedure	213
8.2.10.5	Test Requirement	214
8.2.11	Performance requirements for CG-UCI multiplexed on interlaced PUSCH	214
8.2.11.1	Definition and applicability	214
8.2.11.2	Minimum Requirements	215
8.2.11.3	Test purpose	215
8.2.11.4	Method of test	215
8.2.11.4.1	Initial conditions	215
8.2.11.4.2	Procedure	215
8.2.11.5	Test Requirement	216
8.3	Performance requirements for PUCCH	217
8.3.1	Performance requirements for PUCCH format 0	217
8.3.1.1	Definition and applicability	217
8.3.1.2	Minimum Requirement	217
8.3.1.3	Test purpose	218
8.3.1.4	Method of test	218
8.3.1.4.1	Initial conditions	218
8.3.1.4.2	Procedure	218
8.3.1.5	Test Requirement	219
8.3.2	Performance requirements for PUCCH format 1	220
8.3.2.1	NACK to ACK detection	220
8.3.2.1.1	Definition and applicability	220
8.3.2.1.2	Minimum Requirement	220
8.3.2.1.3	Test purpose	220
8.3.2.1.4	Method of test	220
8.3.2.1.4.1	Initial Conditions	220
8.3.2.1.4.2	Procedure	220
8.3.2.1.5	Test Requirement	221
8.3.2.2	ACK missed detection	222
8.3.2.2.1	Definition and applicability	222
8.3.2.2.2	Minimum Requirement	222
8.3.2.2.3	Test purpose	222
8.3.2.2.4	Method of test	223
8.3.2.2.4.1	Initial Conditions	223
8.3.2.2.4.2	Procedure	223
8.3.2.2.5	Test Requirement	224
8.3.3	Performance requirements for PUCCH format 2	224
8.3.3.1	ACK missed detection	224
8.3.3.1.1	Definition and applicability	224
8.3.3.1.2	Minimum requirements	225
8.3.3.1.3	Test purpose	225
8.3.3.1.4	Method of test	225
8.3.3.1.4.1	Initial Condition	225
8.3.3.1.4.2	Procedure	225
8.3.3.1.5	Test requirements	226
8.3.3.2	UCI BLER performance requirements	226
8.3.3.2.1	Definition and applicability	226
8.3.3.2.2	Minimum Requirement	226
8.3.3.2.3	Test purpose	227
8.3.3.2.4	Method of test	227
8.3.3.2.4.1	Initial Condition	227

8.3.3.2.4.2	Procedure	227
8.3.3.2.5	Test requirements	228
8.3.4	Performance requirements for PUCCH format 3	228
8.3.4.1	Definition and applicability	228
8.3.4.2	Minimum requirement	228
8.3.4.3	Test purpose	228
8.3.4.4	Method of test	229
8.3.4.4.1	Initial conditions	229
8.3.4.4.2	Procedure	229
8.3.4.5	Test requirement	230
8.3.5	Performance requirements for PUCCH format 4	231
8.3.5.1	Definition and applicability	231
8.3.5.2	Minimum requirement	231
8.3.5.3	Test purpose	231
8.3.5.4	Method of test	231
8.3.5.4.1	Initial conditions	231
8.3.5.4.2	Procedure	231
8.3.5.5	Test requirement	232
8.3.6	Performance requirements for multi-slot PUCCH	233
8.3.6.1	Performance requirements for multi-slot PUCCH format 1	233
8.3.6.1.1	NACK to ACK detection	233
8.3.6.1.1.1	Definition and applicability	233
8.3.6.1.1.2	Minimum Requirement	233
8.3.6.1.1.3	Test purpose	233
8.3.6.1.1.4	Method of test	233
8.3.6.1.1.4.1	Initial conditions	233
8.3.6.1.1.4.2	Procedure	234
8.3.6.1.1.5	Test Requirement	234
8.3.6.1.2	ACK missed detection	235
8.3.6.1.2.1	Definition and applicability	235
8.3.6.1.2.2	Minimum Requirement	235
8.3.6.1.2.3	Test purpose	235
8.3.6.1.2.4	Method of test	235
8.3.6.1.2.4.1	Initial conditions	235
8.3.6.1.2.4.2	Procedure	235
8.3.6.1.2.5	Test Requirement	236
8.3.7	Performance requirements for interlaced PUCCH format 0	237
8.3.7.1	Definition and applicability	237
8.3.7.2	Minimum Requirement	237
8.3.7.3	Test purpose	237
8.3.7.4	Method of test	237
8.3.7.4.1	Initial conditions	237
8.3.7.4.2	Procedure	237
8.3.7.5	Test Requirement	238
8.3.8	Performance requirements for interlaced PUCCH format 1	239
8.3.8.1	NACK to ACK detection	239
8.3.8.1.1	Definition and applicability	239
8.3.8.1.2	Minimum Requirement	239
8.3.8.1.3	Test purpose	239
8.3.8.1.4	Method of test	239
8.3.8.1.4.1	Initial Conditions	239
8.3.8.1.4.2	Procedure	239
8.3.8.1.5	Test Requirement	240
8.3.8.2	ACK missed detection	241
8.3.8.2.1	Definition and applicability	241
8.3.8.2.2	Minimum Requirement	241
8.3.8.2.3	Test purpose	241
8.3.8.2.4	Method of test	241
8.3.8.2.4.1	Initial Conditions	241
8.3.8.2.4.2	Procedure	241
8.3.8.2.5	Test Requirement	242
8.3.9	Performance requirements for interlaced PUCCH format 2	242

8.3.9.1	Definition and applicability.....	242
8.3.9.2	Minimum requirement	243
8.3.9.3	Test purpose	243
8.3.9.4	Method of test	243
8.3.9.4.1	Initial conditions.....	243
8.3.9.4.2	Procedure.....	243
8.3.9.5	Test requirement	244
8.3.10	Performance requirements for interlaced PUCCH format 3	244
8.3.10.1	Definition and applicability.....	244
8.3.10.2	Minimum requirement	245
8.3.10.3	Test purpose	245
8.3.10.4	Method of test	245
8.3.10.4.1	Initial conditions.....	245
8.3.10.4.2	Procedure.....	245
8.3.10.5	Test requirement	246
8.4	Performance requirements for PRACH.....	246
8.4.1	PRACH false alarm probability and missed detection.....	246
8.4.1.1	Definition and applicability.....	246
8.4.1.2	Minimum requirement	247
8.4.1.3	Test purpose	247
8.4.1.4	Method of test	247
8.4.1.4.1	Initial conditions.....	247
8.4.1.4.2	Procedure.....	247
8.4.1.5	Test requirement for Normal Mode.....	249
8.4.1.6	Test requirement for high speed train	250
8.4.1.7	Test requirement for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	251
Annex A (normative): Reference measurement channels.....		252
A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, $R=1/3$).....	252
A.2	Fixed Reference Channels for dynamic range (16QAM, $R=2/3$).....	253
A.3	Fixed Reference Channels for performance requirements (QPSK, $R=193/1024$)	255
A.3A	Fixed Reference Channels for performance requirements (QPSK, $R=99/1024$)	257
A.3B	Fixed Reference Channels for performance requirements (QPSK, $R=308/1024$)	258
A.4	Fixed Reference Channels for performance requirements (16QAM, $R=658/1024$)	259
A.5	Fixed Reference Channels for performance requirements (64QAM, $R=567/1024$)	261
A.6	PRACH test preambles.....	263
A.7	Fixed Reference Channels for performance requirements (QPSK, $R=157/1024$)	263
A.8	Fixed Reference Channels for performance requirements (256QAM, $R=682.5/1024$)	264
Annex B (normative): Environmental requirements for the BS equipment.....		266
B.1	General	266
B.2	Normal test environment	266
B.3	Extreme test environment.....	266
B.3.1	Extreme temperature	266
B.4	Vibration.....	267
B.5	Power supply	267
B.6	Measurement of test environments.....	267
Annex C (informative): Test tolerances and derivation of test requirements.....		268
C.1	Measurement of transmitter.....	268

C.2	Measurement of receiver	270
C.3	Measurement of performance requirements	271
Annex D (informative): Measurement system set-up		274
D.1	<i>BS type 1-C</i> transmitter	274
D.1.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for <i>BS type 1-C</i>	274
D.1.2	Transmitter intermodulation for <i>BS type 1-C</i>	274
D.1.3	Time alignment error for <i>BS type 1-C</i>	275
D.2	<i>BS type 1-C</i> receiver	275
D.2.1	Reference sensitivity level for <i>BS type 1-C</i>	275
D.2.2	Dynamic range for <i>BS type 1-C</i>	276
D.2.3	In-channel selectivity for <i>BS type 1-C</i>	276
D.2.4	Adjacent Channel Selectivity (ACS) and narrowband blocking for <i>BS type 1-C</i>	277
D.2.5	Blocking characteristics for <i>BS type 1-C</i>	277
D.2.6	Receiver spurious emission for <i>BS type 1-C</i>	278
D.2.7	Intermodulation characteristics for <i>BS type 1-C</i>	278
D.3	<i>BS type 1-H</i> transmitter	279
D.3.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for <i>BS type 1-H</i>	279
D.3.2	Transmitter intermodulation for <i>BS type 1-H</i>	280
D.3.3	Transmitter spurious emissions for <i>BS type 1-H</i>	280
D.3.4	Time alignment error for <i>BS type 1-H</i>	282
D.4	<i>BS type 1-H</i> receiver	282
D.4.1	Reference sensitivity level for <i>BS type 1-H</i>	282
D.4.2	Receiver dynamic range for <i>BS type 1-H</i>	283
D.4.3	Receiver adjacent channel selectivity and narrowband blocking for <i>BS type 1-H</i>	283
D.4.4	Receiver spurious emissions	283
D.4.5	Receiver In-channel selectivity for <i>BS type 1-H</i>	285
D.4.6	Receiver intermodulation for <i>BS type 1-H</i>	286
D.5	<i>BS type 1-C</i> performance requirements	286
D.5.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions and for high speed condition	286
D.5.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	287
D.5.3	Performance requirements for PUSCH and PRACH in static conditions	287
D.5.4	Performance requirements for UL timing adjustment	288
D.6	<i>BS type 1-H</i> performance requirements	288
D.6.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions and for high speed condition	288
D.6.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	289
D.6.3	Performance requirements for PUSCH and PRACH in static conditions	289
D.6.4	Performance requirements for UL timing adjustment	290
Annex E (normative): Characteristics of interfering signals		291
Annex F (normative): Void		292
Annex G (normative): Propagation conditions		293
G.1	Static propagation condition	293
G.2	Multi-path fading propagation conditions	293
G.2.1	Delay profiles	293
G.2.1.1	Delay profiles for FR1	294
G.2.2	Combinations of channel model parameters	295
G.2.3	MIMO channel correlation matrices	296
G.2.3.1	MIMO correlation matrices using Uniform Linear Array	296
G.2.3.1.1	Definition of MIMO correlation matrices	296

G.2.3.1.2	MIMO correlation matrices at high, medium and low level	297
G.2.3.2	Multi-antenna channel models using cross polarized antennas.....	299
G.2.3.2.1	Definition of MIMO correlation matrices using cross polarized antennas.....	300
G.2.3.2.2	Spatial correlation matrices at UE and gNB sides.....	300
G.2.3.2.2.1	Spatial correlation matrices at UE side.....	300
G.2.3.2.2.2	Spatial correlation matrices at gNB side	300
G.2.3.2.3	MIMO correlation matrices using cross polarized antennas	301
G.3	High speed train condition	301
G.4	Moving propagation conditions.....	305
Annex H (normative): In-channel TX tests		307
H.1	General	307
H.2	Basic principles	307
H.2.1	Output signal of the TX under test	307
H.2.2	Ideal signal	307
H.2.3	Measurement results.....	308
H.2.4	Measurement points	308
H.3	Pre-FFT minimization process	309
H.4	Timing of the FFT window	309
H.5	Resource element TX power.....	310
H.6	Post-FFT equalisation.....	311
H.7	EVM.....	312
H.7.0	General.....	312
H.7.1	Averaged EVM (FDD).....	313
H.7.2	Averaged EVM (TDD).....	313
Annex I (normative): General rules for statistical testing		315
I.1	Testing methodology of PUSCH performance requirements with 0.001% BLER	315
I.1.1	General	315
I.1.2	Numerical definition of the pass-fail limits for testing PUSCH 0.001% BLER.....	316
I.1.3	Theory to derive the early pass/fail limits in I.1.2 (informative).....	317
I.1.3.1	Numerical definition of the pass-fail limits for testing PUSCH 0.001% BLER	317
I.1.3.2	Simulation to derive the pass-fail limits for testing PUSCH 0.001% BLER	317
Annex J (informative): Change history		319
History		328