



Designation: ~~D3585-98 (Reapproved 2002)~~ Designation: D 3585 - 08

Standard Specification for ASTM Reference Fluid for Coolant Tests¹

This standard is issued under the fixed designation D 3585; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers a reference ethylene glycol-base test fluid to be used in providing base line data for ASTM coolant test procedures.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

D 501 Test Methods of Sampling and Chemical Analysis of Alkaline Detergents

D 538 Specification for Trisodium Phosphate (~~Discontinued 2001~~)

D 891 Test Methods for Specific Gravity, Apparent, of Liquid Industrial Chemicals

D 1078 Test Method for Distillation Range of Volatile Organic Liquids

D 1119 Test Method for Percent Ash Content of Engine Coolants ~~and Antirusts~~³

D 1120 Test Method for Boiling Point of Engine Coolants

D 1121 Test Method for Reserve Alkalinity of Engine Coolants and Antirusts

D 1122 Test Method for Density or Relative Density of Engine Coolant Concentrates and Engine Coolants ~~by the~~ By The Hydrometer

D 1123 Test Methods for Water in Engine Coolant Concentrate by the Karl Fischer Reagent Method

D 1176 ~~Test Method- Practice~~ Practice for Sampling and Preparing Aqueous Solutions of Engine Coolants or Antirusts for Testing Purposes

D 1177 Test Method for Freezing Point of Aqueous Engine Coolants

D 1287 Test Method for pH of Engine Coolants and Antirusts

D 1384 Test Method for Corrosion Test for Engine Coolants in Glassware

D 1613 Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer, and Related Products

D 1881 Test Method for Foaming Tendencies of Engine Coolants in Glassware

D 3634 Test Method for Trace Chloride Ion in Engine Coolants

D 5827 Test Method for Analysis of Engine Coolant for Chloride and Other Anions by Ion Chromatography

D 5931 Test Method for Density and Relative Density of Engine Coolant Concentrates and Aqueous Engine Coolants by Digital Density Meter

E 202 Test Methods for Analysis of Ethylene Glycols and Propylene Glycols

3. Chemical Composition Requirements

3.1 The reference test fluid concentrate shall be prepared to conform to the requirements as to chemical composition prescribed in Table 1.

4. Ingredient Requirements

4.1 The materials used to prepare the reference test fluid shall meet the requirements given in Annex A1-Annex A5.

¹ This specification is under the jurisdiction of ASTM Committee D15 on Engine Coolants and is the direct responsibility of Subcommittee D15.01 on Reference Test Materials.

~~Current edition approved April 10, 1998. Published December 1998. Originally published as D3583-89. Last previous edition D3585-95.~~

~~Current edition approved Oct. 1, 2008. Published November 2008. Originally approved in 1989. Last previous edition approved in 2002 as D 3585 - 98(2002).~~

² Annual Book of ASTM Standards, Vol 15.04.

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

TABLE 1 Chemical Composition Requirements

NOTE 1—The reference coolant shall be colored blue-green using Alizarine Cyanine Green G Extra 100 % added in the proportion of 0.3 g of dye/gal of coolant.

Ingredient	Mass %	lb/100 gal ^A	kg/m ³
Ethylene glycol	89.86	847.9	1016.0
Diethylene glycol	5.00	47.2	56.5
Sodium tetraborate, pentahydrate	3.06	28.9	34.6
Trisodium phosphate, dodecahydrate	0.30	2.8	3.4
Sodium mercaptobenzo-thiazole solution (50 mass % aqueous)	0.40	3.8	4.5
Pluronic L-61 ^B			
Water ^C	0.02	0.2	0.2
	1.36	12.8	15.4

^ABased on a test fluid relative density of 1.133 at 60/60°F (15.5/15.5°C).

^BA nonionic polyol manufactured by BASF Corporation, 100 Cherry Hill Rd., Parsippany, NJ 07054.

^CCalculated value; the total water content (water originally present in the base materials, added water, water of hydration, and water of reaction and quantitative interference by the reaction of the reagent used (in Test Method D 1123) with the ingredients) should be adjusted to 4.0 ± 0.2 mass % as the final step in the preparation.

5. Significance and Use

5.1 The data obtained for the reference test fluid are intended to be used by laboratory personnel to determine their capability to perform tests properly. If a particular determination does not fall within the prescribed limits, it has to be assumed that an error occurred in the application of the test procedure.

5.2 The coolant composition given in this specification is not intended to be a commercial product.

6. Chemical and Physical Requirements

6.1 The formulated reference test fluid concentrate shall conform to the requirements for physical and chemical properties prescribed in Table 2.

7. Performance Requirements

7.1 The formulated reference test fluid concentrate shall conform to the requirements for laboratory test performance prescribed in Table 3.

8. Sampling

8.1 To obtain a sample of the concentrated reference test fluid from the storage container, allow the material to come to room temperature (not below 68°F (20°C)) and shake well before withdrawing the sample.

8.2 All aqueous solutions to be used for test purposes shall be prepared in accordance with Section 5 of Test Method D 1176.

9. Mixing Procedure

9.1 Weigh the ingredients according to the batch size required.

9.2 Mix the ethylene and diethylene glycols.

TABLE 2 Physical and Chemical Requirements

Property	Requirements		ASTM Test Method
	min	max	
pH, concentrate	6.1	6.3	D 1287
33 volume % solution	7.7	8.0	
50 volume % solution	7.5	7.8	
Reserve alkalinity, mL	26.5	27.5	D 1121
Water content, weight %	3.8	4.2	D 1123
Freezing protection:			D 1177
—Concentrate	–23°C (–10°F)	–25°C (–13°F)	
—Concentrate	–23°C (–9°F)	–25°C (–13°F)	
33 volume % solution	–18°C (0°F)	–19°C (–2°F)	
50 volume % solution	–36°C (–33°F)	–38°C (–36°F)	
Relative Density at 15.6°C	1.131	1.134	D 1122, D 5931
at 20°C	1.129	1.132	
Boiling point, °C (°F)	330 (166)	340 (171)	D 1120
Ash, weight %	1.4	1.6	D 1119
Chloride, ppm	–	25	D 3634, D 5827