



iTeh STANDARD
LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 17.5.0 Release 17)

[ETSI TS 136 101 V17.5.0 \(2022-05\)](https://standards.iteh.ai/catalog/standards/sist/e7f320a2-cfa1-48f2-a205-f7248f034db7/etsi-ts-136-101-v17-5-0-2022-05)
<https://standards.iteh.ai/catalog/standards/sist/e7f320a2-cfa1-48f2-a205-f7248f034db7/etsi-ts-136-101-v17-5-0-2022-05>



Reference

RTS/TSGR-0436101vh50

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.

All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal notice	2
Modal verbs terminology	2
Foreword	32
1 Scope	34
2 References	34
3 Definitions, symbols and abbreviations	34
3.1 Definitions	34
3.2 Symbols	36
3.3 Abbreviations	39
4 General	41
4.1 Relationship between minimum requirements and test requirements	41
4.2 Applicability of minimum requirements	41
4.3 Void	41
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category M2, UE category 1bis, UE category NB1 and NB2, V2X Communication, MBMS UE)	41
4.4 RF requirements in later releases	43
5 Operating bands and channel arrangement	43
5.1 General	43
5.2 Void	43
5.3 Void	43
5.4 Void	43
5.5 Operating bands	43
5.5A Operating bands for CA	46
5.5B Operating bands for UL-MIMO	67
5.5C Operating bands for Dual Connectivity	67
5.5D Operating bands for ProSe	70
5.5E Operating bands for UE category 0, UE category M1 and M2 and UE category 1bis	71
5.5F Operating bands for category NB1 and NB2	71
5.5G Operating bands for V2X Communication	72
5.6 Channel bandwidth	73
5.6.1 Channel bandwidths per operating band	74
5.6A Channel bandwidth for CA	77
5.6A.1 Channel bandwidths per operating band for CA	79
5.6B Channel bandwidth for UL-MIMO	195
5.6B.1 Void	195
5.6C Channel bandwidth for Dual Connectivity	195
5.6C.1 Void	195
5.6D Channel bandwidth for ProSe	195
5.6D.1 Channel bandwidths per operating band for ProSe	195
5.6F Channel bandwidth for category NB1 and NB2	196
5.6G Channel bandwidth for V2X Communication	197
5.6G.1 Channel bandwidths per operating band for V2X Communication	197
5.7 Channel arrangement	199
5.7.1 Channel spacing	199
5.7.1A Channel spacing for CA	199
5.7.1F Channel spacing for category NB1 and NB2	200
5.7.2 Channel raster	200
5.7.2A Channel raster for CA	200
5.7.2F Channel raster for category NB1 and NB2	200
5.7.3 Carrier frequency and EARFCN	200
5.7.3F Carrier frequency and EARFCN for category NB1 and NB2	203

5.7.4	TX–RX frequency separation	204
5.7.4A	TX–RX frequency separation for CA	204
5.7.4E	TX–RX frequency separation for category M1 and M2	205
5.7.4F	TX–RX frequency separation for category NB1 and NB2	205
6	Transmitter characteristics	205
6.1	General	205
6.2	Transmit power	205
6.2.1	Void	205
6.2.2	UE maximum output power	205
6.2.2A	UE maximum output power for CA	208
6.2.2B	UE maximum output power for UL-MIMO	213
6.2.2C	Void	216
6.2.2D	UE maximum output power for ProSe	216
6.2.2E	UE maximum output power for Category M1 and M2 UE	216
6.2.2F	UE maximum output power for category NB1 and NB2	217
6.2.2G	UE maximum output power for V2X Communication	218
6.2.3	UE maximum output power for modulation / channel bandwidth	220
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	221
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	226
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	226
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2	227
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	229
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	229
6.2.3G.1	MPR for Power class 3 V2X UE	229
6.2.3G.2	MPR for Power class 2 V2X UE	231
6.2.4	UE maximum output power with additional requirements	231
6.2.4A	UE maximum output power with additional requirements for CA	250
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	252
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	253
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	253
6.2.4A.4	A-MPR for CA_NS_04	254
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	257
6.2.4A.6	A-MPR for CA_NS_06	258
6.2.4A.7	A-MPR for CA_NS_07	259
6.2.4A.8	A-MPR for CA_NS_08	260
6.2.4A.9	Void	261
6.2.4A.10	A-MPR for CA_NS_10	261
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	266
6.2.4D	UE maximum output power with additional requirements for ProSe	266
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE	266
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE	277
6.2.4G	UE maximum output power with additional requirements for V2X Communication	277
6.2.5	Configured transmitted power	279
6.2.5A	Configured transmitted power for CA	316
6.2.5B	Configured transmitted power for UL-MIMO	319
6.2.5C	Configured transmitted power for Dual Connectivity	320
6.2.5D	Configured transmitted power for ProSe	321
6.2.5F	Configured transmitted Power for category NB1 and NB2	323
6.2.5G	Configured transmitted power for V2X Communication	324
6.3	Output power dynamics	328
6.3.1	(Void)	328
6.3.2	Minimum output power	328
6.3.2.1	Minimum requirement	328
6.3.2A	UE Minimum output power for CA	328
6.3.2A.1	Minimum requirement for CA	328
6.3.2B	UE Minimum output power for UL-MIMO	328
6.3.2B.1	Minimum requirement	329
6.3.2C	Void	329
6.3.2D	UE Minimum output power for ProSe	329
6.3.2F	UE Minimum output power for category NB1 and NB2	329
6.3.2G	UE Minimum output power for V2X Communication	329

6.3.3	Transmit OFF power.....	330
6.3.3.1.	Minimum requirement	330
6.3.3A	UE Transmit OFF power for CA	330
6.3.3A.1	Minimum requirement for CA	330
6.3.3B	UE Transmit OFF power for UL-MIMO.....	331
6.3.3B.1	Minimum requirement	331
6.3.3D	Transmit OFF power for ProSe.....	331
6.3.3F	Transmit OFF power for category NB1 and NB2.....	331
6.3.3G	Transmit OFF power for V2X Communication.....	332
6.3.4	ON/OFF time mask.....	332
6.3.4.1	General ON/OFF time mask	332
6.3.4.2	PRACH and SRS time mask	333
6.3.4.2.1	PRACH time mask	333
6.3.4.2.2	SRS time mask	334
6.3.4.3	Slot / Sub frame boundary time mask for subframe TTI.....	336
6.3.4.4	PUCCH / PUSCH / SRS time mask for subframe TTI	338
6.3.4.5	Symbol / Subslot boundary time mask for subslot TTI.....	340
6.3.4.6	Subslot PUCCH / subslot PUSCH / SRS time mask for subslot TTI.....	341
6.3.4.7	Symbol / Slot boundary time mask for slot TTI.....	344
6.3.4.8	Slot PUCCH / slot PUSCH / SRS time mask for slot TTI	345
6.3.4.9	Consecutive subslot and slot TTI or consecutive subslot and subframe TTI time mask.....	345
6.3.4.10	Consecutive subframe and subslot TTI or consecutive slot and subslot TTI time mask.....	345
6.3.4.11	Consecutive TTI and slot TTI or consecutive slot TTI and TTI time mask	346
6.3.4A	ON/OFF time mask for CA	347
6.3.4B	ON/OFF time mask for UL-MIMO	347
6.3.4D	ON/OFF time mask for ProSe.....	347
6.3.4D.1	General time mask for ProSe.....	347
6.3.4D.2	PSSS/SSSS time mask	348
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	349
6.3.4D.4	PSSCH / SRS time mask.....	349
6.3.4F	ON/OFF time mask for category NB1 and NB2.....	349
6.3.4F.1	General ON/OFF time mask	349
6.3.4F.2	NPRACH time mask	350
6.3.4G	ON/OFF time mask for V2X Communication.....	350
6.3.4G.1	PSSS / SSSS / PSBCH time mask	351
6.3.5	Power Control.....	351
6.3.5.1	Absolute power tolerance.....	351
6.3.5.1.1	Minimum requirements	351
6.3.5.2	Relative Power tolerance.....	352
6.3.5.2.1	Minimum requirements	352
6.3.5.3	Aggregate power control tolerance	353
6.3.5.3.1	Minimum requirement.....	353
6.3.5A	Power control for CA.....	353
6.3.5A.1	Absolute power tolerance.....	353
6.3.5A.1.1	Minimum requirements	353
6.3.5A.2	Relative power tolerance	354
6.3.5A.2.1	Minimum requirements	354
6.3.5A.3	Aggregate power control tolerance	354
6.3.5A.3.1	Minimum requirements	354
6.3.5B	Power control for UL-MIMO	355
6.3.5D	Power Control for ProSe.....	355
6.3.5D.1	Absolute power tolerance.....	355
6.3.5E	Power control for category M1 and M2.....	355
6.3.5E.1	Absolute power tolerance.....	355
6.3.5E.2	Relative Power tolerance.....	355
6.3.5E.3	Aggregate power control tolerance	356
6.3.5E.3.1	Minimum requirement.....	356
6.3.5F	Power Control for category NB1 and NB2.....	356
6.3.5F.1	Absolute power tolerance.....	357
6.3.5F.2	Relative power tolerance.....	357
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	358
6.3.5F.3.1	Minimum requirement.....	358

6.3.5G	Power Control for V2X Communication	358
6.3.5G.1	Absolute power tolerance	358
6.4	Void	359
6.5	Transmit signal quality	359
6.5.1	Frequency error	359
6.5.1A	Frequency error for CA	359
6.5.1B	Frequency error for UL-MIMO	359
6.5.1D	Frequency error for ProSe	359
6.5.1E	Frequency error for UE category M1 and M2	359
6.5.1F	Frequency error for UE category NB1 and NB2	360
6.5.1G	Frequency error for V2X Communication	360
6.5.2	Transmit modulation quality	360
6.5.2.1	Error Vector Magnitude	361
6.5.2.1.1	Minimum requirement	361
6.5.2.2	Carrier leakage	361
6.5.2.2.1	Minimum requirements	362
6.5.2.3	In-band emissions	362
6.5.2.3.1	Minimum requirements	362
6.5.2.4	EVM equalizer spectrum flatness	363
6.5.2.4.1	Minimum requirements	363
6.5.2A	Transmit modulation quality for CA	364
6.5.2A.1	Error Vector Magnitude	365
6.5.2A.2	Carrier leakage for CA	365
6.5.2A.2.1	Minimum requirements	365
6.5.2A.3	In-band emissions	365
6.5.2A.3.1	Minimum requirement for CA	365
6.5.2B	Transmit modulation quality for UL-MIMO	368
6.5.2B.1	Error Vector Magnitude	368
6.5.2B.2	Carrier leakage	368
6.5.2B.3	In-band emissions	368
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	368
6.5.2D	Transmit modulation quality for ProSe	368
6.5.2D.1	Error Vector Magnitude	368
6.5.2D.2	Carrier leakage	369
6.5.2D.3	In-band emissions	369
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	369
6.5.2E	Transmit modulation quality for category M1 and M2	369
6.5.2E.1	Error Vector Magnitude	369
The Error Vector Magnitude is defined in section 6.5.2.1.		369
6.5.2E.2	Carrier leakage	369
6.5.2E.2.1	Minimum requirements	369
6.5.2E.3	In-band emissions	369
6.5.2E.3.1	Minimum requirements	369
6.5.2F	Transmit modulation quality for Category NB1 and NB2	371
6.5.2F.1	Error Vector Magnitude	371
6.5.2F.2	Carrier leakage	371
6.5.2F.3	In-band emissions	371
6.5.2G	Transmit modulation quality for V2X Communication	372
6.5.2G.1	Error Vector Magnitude	372
6.5.2G.2	Carrier leakage	373
6.5.2G.3	In-band emissions	373
6.5.2G.4	EVM equalizer spectrum flatness	373
6.6	Output RF spectrum emissions	373
6.6.1	Occupied bandwidth	373
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value “NS_29”)	374
6.6.1A	Occupied bandwidth for CA	374
6.6.1B	Occupied bandwidth for UL-MIMO	374
6.6.1F	Occupied bandwidth for category NB1 and NB2	375
6.6.1G	Occupied bandwidth for V2X Communication	375
6.6.2	Out of band emission	375
6.6.2.1	Spectrum emission mask	375
6.6.2.1.1	Minimum requirement	375

6.6.2.1A	Spectrum emission mask for CA.....	376
6.6.2.2	Additional spectrum emission mask	377
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21")..	377
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	378
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	378
6.6.2.2.4	Minimum requirement (network signalled value "NS_33" or "NS_34")	379
6.6.2.2.5	Minimum requirement (network signalled value "NS_27" and "NS_43")	379
6.6.2.2.6	Minimum requirement (network signalled value "NS_28")	380
6.6.2.2.7	Minimum requirement (network signalled value "NS_35")	380
6.6.2.2A	Additional Spectrum Emission Mask for CA.....	381
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04").....	381
6.6.2.2A.2	Minimum requirement CA_66B (network signalled value "CA_NS_09")	381
6.6.2.2A.3	Minimum requirement CA_66C (network signalled value "CA_NS_09")	382
6.6.2.2A.4	Minimum requirement CA_48B and CA_48C (network signalled value "CA_NS_10").....	382
6.6.2.3	Adjacent Channel Leakage Ratio.....	383
6.6.2.3.1	Minimum requirement E-UTRA	383
6.6.2.3.1a	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	384
6.6.2.3.1A	Void.....	385
6.6.2.3.1Aa	Void.....	385
6.6.2.3.2	Minimum requirements UTRA	385
6.6.2.3.2A	Minimum requirement UTRA for CA.....	386
6.6.2.3.3A	Minimum requirements for CA E-UTRA.....	388
6.6.2.4	Void.....	389
6.6.2.4.1	Void.....	389
6.6.2A	Void	389
6.6.2B	Out of band emission for UL-MIMO.....	389
6.6.2C	Void.....	389
6.6.2D	Out of band emission for ProSe.....	389
6.6.2F	Out of band emission for category NB1 and NB2	390
6.6.2F.1	Spectrum emission mask.....	390
6.6.2F.2	Additional Spectrum Emission Mask for Category NB1 and NB2.....	390
6.6.2F.2.1	Minimum requirement (network signalled value "NS_02")	390
6.6.2F.2.2	Minimum requirement (network signalled value "NS_03")	390
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1 and NB2.....	391
6.6.2G	Out of band emission for V2X Communication	391
6.6.3	Spurious emissions	392
6.6.3.1	Minimum requirements.....	392
6.6.3.1A	Minimum requirements for CA.....	393
6.6.3.2	Spurious emission band UE co-existence	394
6.6.3.2A	Spurious emission band UE co-existence for CA	403
6.6.3.3	Additional spurious emissions	419
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	420
6.6.3.3.2	Minimum requirement (network signalled value "NS_07").....	420
6.6.3.3.3	Minimum requirement (network signalled value "NS_08").....	420
6.6.3.3.4	Minimum requirement (network signalled value "NS_09").....	420
6.6.3.3.5	Minimum requirement (network signalled value "NS_12")	421
6.6.3.3.6	Minimum requirement (network signalled value "NS_13").....	421
6.6.3.3.7	Minimum requirement (network signalled value "NS_14").....	421
6.6.3.3.8	Minimum requirement (network signalled value "NS_15").....	422
6.6.3.3.9	Minimum requirement (network signalled value "NS_16").....	422
6.6.3.3.10	Minimum requirement (network signalled value "NS_17").....	422
6.6.3.3.11	Minimum requirement (network signalled value "NS_18").....	422
6.6.3.3.12	Minimum requirement (network signalled value "NS_19").....	423
6.6.3.3.13	Minimum requirement (network signalled value "NS_11").....	423
6.6.3.3.14	Minimum requirement (network signalled value "NS_20").....	423
6.6.3.3.15	Minimum requirement (network signalled value "NS_21").....	423
6.6.3.3.16	Minimum requirement (network signalled value "NS_22").....	424
6.6.3.3.17	Minimum requirement (network signalled value "NS_23").....	424
6.6.3.3.18	Void.....	425
6.6.3.3.19	Minimum requirement (network signalled value "NS_04")	425
6.6.3.3.20	Minimum requirement (network signalled value "NS_24").....	425
6.6.3.3.21	Minimum requirement (network signalled value "NS_25").....	426

6.6.3.3.22	Minimum requirement (network signalled value "NS_26").....	426
6.6.3.3.23	Minimum requirement (network signalled value "NS_27" and "NS_43")	426
6.6.3.3.24	Minimum requirement (network signalled value "NS_28").....	426
6.6.3.3.25	Minimum requirement (network signalled value "NS_29").....	427
6.6.3.3.26	Minimum requirement (network signalled value "NS_30").....	427
6.6.3.3.27	Minimum requirement (network signalled value "NS_31").....	428
6.6.3.3.28	Minimum requirement (network signalled value "NS_36").....	429
6.6.3.3.29	Minimum requirement (network signalled value "NS_38").....	429
6.6.3.3.30	Minimum requirement (network signalled value "NS_39").....	429
6.6.3.3.31	Minimum requirement (network signalled value "NS_40" and "NS_41")	430
6.6.3.3.32	Minimum requirement (network signalled value "NS_42").....	430
6.6.3.3.33	Minimum requirement (network signalled value "NS_44").....	430
6.6.3.3.34	Minimum requirement (network signalled value "NS_45").....	430
6.6.3.3.35	Minimum requirement (network signalled value "NS_56").....	431
6.6.3.3A	Additional spurious emissions for CA	431
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01").....	432
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02").....	432
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03").....	432
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05").....	433
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06").....	433
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07").....	433
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08").....	433
6.6.3.3A.8	Minimum requirement for CA_41C and CA_41D (network signalled value "CA_NS_04").....	434
6.6.3.3A.9	Void.....	434
6.6.3.3A.10	Minimum requirement for CA_48B and CA_48C (network signalled value "CA_NS_10").....	434
6.6.3A	Void.....	434
6.6.3B	Spurious emission for UL-MIMO	435
6.6.3C	Void.....	435
6.6.3D	Spurious emission for ProSe.....	435
6.6.3F	Spurious emission for category NB1 and NB2.....	435
6.6.3G	Spurious emission for V2X Communication	435
6.6A	Void.....	439
6.6B	Void.....	439
6.7	Transmit intermodulation	439
6.7.1	Minimum requirement.....	439
6.7.1A	Minimum requirement for CA	440
6.7.1B	Minimum requirement for UL-MIMO.....	440
6.7.1F	Minimum requirement for category NB1 and NB2	440
6.7.1G	Minimum requirement for V2X Communication	441
6.8	Void.....	441
6.8A	Void.....	441
6.8B	Time alignment error for UL-MIMO	441
6.8B.1	Minimum Requirements	441
6.8C	Void.....	442
6.8D	Void.....	442
6.8E	Void.....	442
6.8F	Void.....	442
6.8G	Time alignment error.....	442
7	Receiver characteristics	442
7.1	General	442
7.2	Diversity characteristics	443
7.3	Reference sensitivity power level.....	443
7.3.1	Minimum requirements (QPSK).....	443
7.3.1A	Minimum requirements (QPSK) for CA.....	483
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	541
7.3.1D	Minimum requirements (QPSK) for ProSe.....	541
7.3.1E	Minimum requirements (QPSK) for UE category 0, M1, M2 and 1bis.....	543
7.3.1F	Minimum requirements for UE category NB1 and NB2	553
7.3.1F.1	Reference sensitivity for UE category NB1 and NB2.....	553
7.3.1F.2	Void.....	554

7.3.1G	Minimum requirements (QPSK) for V2X	554
7.3.2	Void	556
7.4	Maximum input level	556
7.4.1	Minimum requirements.....	557
7.4.1A	Minimum requirements for CA	557
7.4.1B	Minimum requirements for UL-MIMO	558
7.4.1D	Minimum requirements for ProSe	558
7.4.1F	Minimum requirements for category NB1 and NB2.....	559
7.4.1G	Minimum requirements for V2X	559
7.4A	Void.....	560
7.4A.1	Void	560
7.5	Adjacent Channel Selectivity (ACS).....	560
7.5.1	Minimum requirements.....	560
7.5.1A	Minimum requirements for CA	561
7.5.1B	Minimum requirements for UL-MIMO	565
7.5.1D	Minimum requirements for ProSe	565
7.5.1F	Minimum requirements for category NB1 and NB2.....	566
7.5.1G	Minimum requirements for V2X	567
7.6	Blocking characteristics	569
7.6.1	In-band blocking.....	569
7.6.1.1	Minimum requirements.....	569
7.6.1.1A	Minimum requirements for CA.....	571
7.6.1.1D	Minimum requirements for ProSe.....	574
7.6.1.1F	Minimum requirements for category NB1 and NB2.....	575
7.6.1.1G	Minimum requirements for V2X.....	575
7.6.2	Out-of-band blocking.....	577
7.6.2.1	Minimum requirements.....	577
7.6.2.1A	Minimum requirements for CA.....	579
7.6.2.1D	Minimum requirements for ProSe.....	582
7.6.2.1F	Minimum requirements for category NB1 and NB2.....	582
7.6.2.1G	Minimum requirements for V2X.....	583
7.6.3	Narrow band blocking	584
7.6.3.1	Minimum requirements.....	584
7.6.3.1A	Minimum requirements for CA.....	585
7.6.3.1D	Minimum requirements for ProSe.....	586
7.6A	Void.....	587
7.6B	Blocking characteristics for UL-MIMO	587
7.7	Spurious response.....	587
7.7.1	Minimum requirements.....	587
7.7.1A	Minimum requirements for CA	588
7.7.1B	Minimum requirements for UL-MIMO	589
7.7.1D	Minimum requirements for ProSe	589
7.7.1F	Minimum requirements for UE category NB1 and NB2	590
7.7.1G	Minimum requirements for V2X	590
7.8	Intermodulation characteristics	591
7.8.1	Wide band intermodulation.....	591
7.8.1.1	Minimum requirements.....	591
7.8.1A	Minimum requirements for CA	592
7.8.1B	Minimum requirements for UL-MIMO	595
7.8.1D	Minimum requirements for ProSe	595
7.8.1F	Minimum requirements for category NB1 and NB2.....	596
7.8.1G	Minimum requirements.....	596
7.8.2	Void	597
7.9	Spurious emissions	597
7.9.1	Minimum requirements.....	598
7.9.1A	Minimum requirements.....	598
7.10	Receiver image.....	599
7.10.1	Void	599
7.10.1A	Minimum requirements for CA	599
7.10.1G	Minimum requirements for V2X Communication.....	599
8	Performance requirement	600

8.1	General	600
8.1.1	Receiver antenna capability	600
8.1.1.1	Simultaneous unicast and MBMS operations.....	601
8.1.1.2	Dual-antenna receiver capability in idle mode.....	601
8.1.2	Applicability of requirements	601
8.1.2.1	Applicability of requirements for different channel bandwidths.....	601
8.1.2.2	Definition of CA capability	601
8.1.2.2A	Definition of dual connectivity capability.....	606
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets.....	607
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	610
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets.....	611
8.1.2.3C	Applicability and test rules for SDR tests for 4Rx capable UEs	613
8.1.2.3D	Applicability and test rules for different CA with LAA SCell(s) configurations and bandwidth combination sets.....	613
8.1.2.3E	Applicability and test rules for SDR tests for 8Rx capable UEs	614
8.1.2.4	Test coverage for different number of component carriers	615
8.1.2.5	Applicability of performance requirements for Type B receiver	616
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	616
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	616
8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	618
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	618
8.1.2.6.4	Applicability rule for 256QAM tests.....	619
8.1.2.6.5	Applicability rule and antenna connection for CA and DC tests with 4Rx	619
8.1.2.6.6	Applicability rule for Type C with 4Rx	623
8.1.2.6.7	Applicability rule for 1024QAM tests.....	623
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	623
8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations.....	625
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	625
8.1.2.9	Applicability of SDR requirements for CA and LAA	626
8.1.2.10	Applicability of performance requirements for Multi-user Superposed Transmission	627
8.1.2.11	Applicability CRS interference mitigation receivers performance requirements.....	627
8.1.2.12	Applicability of performance requirements for 8Rx capable UEs	628
8.1.2.12.1	Applicability rule and antenna connection for single carrier PDSCH tests	628
8.1.2.12.2	Applicability rule and antenna connection for control channel tests	634
8.1.2.12.3	Applicability rule and antenna connection for CA and DC tests	634
8.1.3	UE category and UE DL category	635
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	635
8.2.1	FDD (Fixed Reference Channel)	635
8.2.1.1	Single-antenna port performance	636
8.2.1.1.1	Minimum Requirement	636
8.2.1.1.2	Void	642
8.2.1.1.3	Void	642
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	642
8.2.1.1.4A	Minimum Requirement 1 PRB allocation in presence of FeMBMS Unicast-mixed Cell under CA	642
8.2.1.2	Transmit diversity performance	643
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	643
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	644
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS).....	644
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	646
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	648
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	650
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	651
8.2.1.2.7	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	652

8.2.1.3	Open-loop spatial multiplexing performance.....	652
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	652
8.2.1.3.1A	Soft buffer management test	656
8.2.1.3.1B	Enhanced Performance Requirement Type C –2Tx Antenna Ports	657
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	658
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	659
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	659
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	663
8.2.1.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	665
8.2.1.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation).....	666
8.2.1.4	Closed-loop spatial multiplexing performance	667
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	667
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	668
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	668
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	670
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	673
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	675
8.2.1.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	676
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	677
8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports.....	678
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	678
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	682
8.2.1.4.4	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	684
8.2.1.5	MU-MIMO	685
8.2.1.6	[Control channel performance: D-BCH and PCH]	685
8.2.1.7	Carrier aggregation with power imbalance	685
8.2.1.7.1	Minimum Requirement	685
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset.....	686
8.2.1.8.1	Minimum Requirement	686
8.2.1.9	HST-SFN performance	687
8.2.1.9.1	Minimum Requirement	687
8.2.1.9.2	Minimum Requirement for Rel-16 further enhanced HST.....	690
8.2.1.10	Intra-band contiguous carrier aggregation with minimum channel spacing.....	690
8.2.1.10.1	Minimum Requirement	691
8.2.2	TDD (Fixed Reference Channel)	691
8.2.2.1	Single-antenna port performance	692
8.2.2.1.1	Minimum Requirement	692
8.2.2.1.2	Void	697
8.2.2.1.3	Void	697
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	697
8.2.2.2	Transmit diversity performance	697
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	697
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	698
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	699
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	700
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	702
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	704

8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	704
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	706
8.2.2.2.8	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	707
8.2.2.3	Open-loop spatial multiplexing performance	708
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	708
8.2.2.3.1A	Soft buffer management test	711
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	711
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	712
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	713
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS)	714
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	718
8.2.2.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	720
8.2.2.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation)	721
8.2.2.4	Closed-loop spatial multiplexing performance	722
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	722
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	723
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	723
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	725
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	727
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	729
8.2.2.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	730
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	732
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	732
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	733
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	737
8.2.2.4.4	Void	738
8.2.2.4.5	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	738
8.2.2.5	MU-MIMO	739
8.2.2.6	[Control channel performance: D-BCH and PCH]	739
8.2.2.7	Carrier aggregation with power imbalance	739
8.2.2.7.1	Minimum Requirement	739
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing	740
8.2.2.8.1	Minimum Requirement	740
8.2.2.9	HST-SFN performance	741
8.2.2.9.1	Minimum Requirement	741
8.2.2.9.2	Minimum Requirement for Rel-16 further enhanced HST	743
8.2.3	TDD FDD CA (Fixed Reference Channel)	744
8.2.3.1	Single-antenna port performance	745
8.2.3.1.1	Minimum Requirement for FDD PCell	745
8.2.3.1.2	Minimum Requirement for TDD PCell	749
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port	753
8.2.3.2.1	Minimum Requirement for FDD PCell	753
8.2.3.2.1A	Soft buffer management test for FDD PCell	757
8.2.3.2.2	Minimum Requirement for TDD PCell	758
8.2.3.2.2A	Soft buffer management test for TDD PCell	762
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port	763
8.2.3.3.1	Minimum Requirement for FDD PCell	763
8.2.3.3.2	Minimum Requirement for TDD PCell	767
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	771

8.2.3.5	HST-SFN performance	773
8.2.3.5.0	General	773
8.2.3.5.1	Minimum Requirement for FDD PCell	773
8.2.3.5.2	Minimum Requirement for TDD PCell	776
8.2.4	LAA	779
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port	779
8.2.4.1.1	FDD PCell (FDD single carrier)	779
8.2.4.1.2	TDD PCell (TDD single carrier)	783
8.3	Demodulation of PDSCH (User-Specific Reference Symbols)	786
8.3.1	FDD	786
8.3.1.1	Single-layer Spatial Multiplexing	787
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model	789
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	792
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model	795
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model	797
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model	798
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	799
8.3.1.1G	Single-layer Spatial Multiplexing (CRS assistance information is configured)	801
8.3.1.1H	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured)	803
8.3.1.1I	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH)	804
8.3.1.2	Dual-Layer Spatial Multiplexing	806
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	807
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	808
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource)	808
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources)	810
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	812
8.3.1.3.4	Minimum requirement with Different Cell ID and non-colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured)	814
8.3.1.3.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured)	816
8.3.1.3.6	Minimum requirements for QCL Type C and 2 Layers Spatial Multiplexing	819
8.3.1.4	Performance Requirements for semiOpenLoop transmission	821
8.3.2	TDD	823
8.3.2.1	Single-layer Spatial Multiplexing	823
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	825
8.3.2.1B	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model	827
8.3.2.1C	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	830
8.3.2.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference	833
8.3.2.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model	835
8.3.2.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference	837
8.3.2.1G	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	838
8.3.2.1H	Single-layer Spatial Multiplexing (CRS assistance information is configured)	840
8.3.2.1I	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured)	842
8.3.2.1J	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH)	843
8.3.2.2	Dual-Layer Spatial Multiplexing	845
8.3.2.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	845
8.3.2.3	Dual-Layer Spatial Multiplexing (with multiple CSI-RS configurations)	846

8.3.2.4	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	847
8.3.2.4.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource)	847
8.3.2.4.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources)	849
8.3.2.4.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	851
8.3.2.4.4	Minimum requirement with Different Cell ID and non-Colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured)	853
8.3.2.4.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured)	855
8.3.2.4.6	Minimum requirements for QCL Type C and 2 Layers Spatial Multiplexing	858
8.3.2.5	Performance Requirements for semiOpenLoop transmission	860
8.3.3	LAA	862
8.3.3.1	Dual-Layer Spatial Multiplexing with DM-RS	862
8.3.3.1.1	FDD PCell (FDD single carrier)	862
8.3.3.1.2	TDD Pcell (TDD single carrier)	867
8.4	Demodulation of PDCCH/PCFICH	871
8.4.1	FDD	871
8.4.1.1	Single-antenna port performance	872
8.4.1.2	Transmit diversity performance	872
8.4.1.2.1	Minimum Requirement 2 Tx Antenna Port	872
8.4.1.2.2	Minimum Requirement 4 Tx Antenna Port	872
8.4.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	873
8.4.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	878
8.4.1.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port under Asynchronous Network	884
8.4.1.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	885
8.4.1.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer	886
8.4.1.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	887
8.4.1.2.9	Enhanced Downlink Control Channel Performance Requirement Type A - 4 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	888
8.4.2	TDD	889
8.4.2.1	Single-antenna port performance	890
8.4.2.2	Transmit diversity performance	890
8.4.2.2.1	Minimum Requirement 2 Tx Antenna Port	890
8.4.2.2.2	Minimum Requirement 4 Tx Antenna Port	891
8.4.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	891
8.4.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	895
8.4.2.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Colliding CRS Dominant Interferer	899
8.4.2.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	900
8.4.2.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer	901
8.4.2.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	902
8.4.2.2.9	Enhanced Downlink Control Channel Performance Requirement Type A - 4 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	903
8.4.3	LAA	904
8.4.3.1	Transmit diversity performance	904
8.4.3.1.1	FDD Pcell (FDD single carrier)	904
8.4.3.1.2	TDD Pcell (TDD single carrier)	905
8.5	Demodulation of PHICH	906
8.5.1	FDD	907
8.5.1.1	Single-antenna port performance	907
8.5.1.2	Transmit diversity performance	907
8.5.1.2.1	Minimum Requirement 2 Tx Antenna Port	907