

---

---

**Reciprocating internal combustion  
engines — Exhaust emission  
measurement —**

**Part 4:  
Steady-state and transient test cycles  
for different engine applications**

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

*Moteurs alternatifs à combustion interne — Mesurage des émissions  
de gaz d'échappement —*

*Partie 4: Cycles d'essai en régime permanent pour différentes  
applications des moteurs*

<https://standards.iteh.ai/catalog/standards/sist/020c40cc-41e1-43fb-88d7-998376ff9312/iso-8178-4-2017>



**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 8178-4:2017](https://standards.iteh.ai/catalog/standards/sist/626e40ec-41e1-43fb-88d7-998376ff9312/iso-8178-4-2017)

<https://standards.iteh.ai/catalog/standards/sist/626e40ec-41e1-43fb-88d7-998376ff9312/iso-8178-4-2017>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
[copyright@iso.org](mailto:copyright@iso.org)  
[www.iso.org](http://www.iso.org)

# Contents

	Page
<b>Foreword</b> .....	<b>vi</b>
<b>Introduction</b> .....	<b>vii</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Symbols and abbreviated terms</b> .....	<b>11</b>
4.1 Quantities and units — Numbers.....	11
4.2 General symbols.....	12
4.3 Symbols and abbreviated terms for fuel composition.....	14
4.4 Symbols and abbreviated terms for chemical components.....	15
4.5 Abbreviated terms.....	16
<b>5 Test conditions</b> .....	<b>17</b>
5.1 Engine test conditions.....	17
5.1.1 Laboratory test conditions.....	17
5.1.2 Test validity.....	17
5.2 Engine power.....	17
5.2.1 Auxiliaries to be fitted.....	18
5.2.2 Auxiliaries to be removed.....	18
5.2.3 Determination of auxiliary power.....	18
5.2.4 Engine cycle work.....	18
5.3 Engine intake air.....	18
5.3.1 Introduction.....	18
5.3.2 Intake air restriction.....	19
5.3.3 Engines with charge air cooling.....	19
5.4 Engine exhaust system.....	19
5.4.1 Introduction.....	19
5.4.2 Exhaust restriction.....	19
5.4.3 Engine with exhaust after-treatment system.....	20
5.5 Specific test conditions.....	20
5.5.1 Engine with exhaust after-treatment system.....	20
5.5.2 Crankcase emissions.....	24
5.6 Cooling system.....	24
5.7 Lubricating oil.....	24
<b>6 Test fuels</b> .....	<b>24</b>
<b>7 Test cycles</b> .....	<b>25</b>
7.1 Introduction.....	25
7.2 Test speeds.....	25
7.2.1 Maximum test speed (MTS).....	25
7.2.2 Rated speed.....	27
7.2.3 Intermediate speed.....	27
7.2.4 Idle speed.....	27
7.2.5 Test speed for constant speed engines.....	28
7.3 Torque and power.....	28
7.3.1 Torque.....	28
7.3.2 Power.....	29
7.4 Engine mapping.....	30
7.4.1 Engine mapping for transient cycles.....	31
7.4.2 Engine mapping for variable speed steady-state cycles.....	31
7.4.3 Engine mapping for constant-speed engines.....	32
7.5 Steady-state test cycles.....	33
7.5.1 Discrete mode test cycles.....	33
7.5.2 Ramped modal test cycles.....	34

7.5.3	Cycle types and applicability.....	35
7.6	Transient cycles.....	39
7.6.1	Introduction.....	39
7.6.2	Non-road transient cycle (NRTC).....	39
7.6.3	Large spark-ignition non-road transient cycle.....	39
7.7	Test cycle generation.....	40
7.7.1	Generation of steady-state discrete-mode or RMC test cycles.....	40
7.7.2	Generation of NRTC and LSI-NRTC.....	41
<b>8</b>	<b>Test run.....</b>	<b>43</b>
8.1	General test sequence.....	43
8.2	Instrument validation for test.....	45
8.2.1	Validation of proportional flow control for batch sampling and minimum dilution ratio for PM batch sampling.....	45
8.2.2	Gas analyser range validation, drift validation and drift correction.....	46
8.2.3	PM sampling media (e.g. filters) preconditioning and tare weighing.....	46
8.3	Sample system decontamination and preconditioning.....	48
8.3.1	Verification of HC contamination.....	49
8.4	Pre-test procedures.....	50
8.4.1	Preparation of the sampling filters.....	50
8.4.2	Preconditioning.....	50
8.4.3	Engine cool down (NRTC).....	51
8.4.4	Preparation of measurement equipment for sampling.....	51
8.4.5	Calibration of gas analysers.....	52
8.4.6	Adjustment of the dilution system.....	52
8.5	Engine starting and restarting.....	52
8.5.1	Engine start.....	52
8.5.2	Engine stalling.....	52
8.6	Test cycle running procedure.....	53
8.6.1	Test sequence for discrete steady-state test cycles.....	53
8.6.2	Ramped modal test cycles.....	54
8.6.3	Transient test cycle (NRTC and LSI-NRTC).....	55
8.7	Post-test procedures.....	58
8.7.1	Verification of proportional sampling.....	58
8.7.2	Post-test PM conditioning and weighing.....	58
8.7.3	Analysis of gaseous batch sampling.....	59
8.7.4	Drift verification.....	60
<b>9</b>	<b>Data evaluation and calculation.....</b>	<b>60</b>
9.1	Gaseous emissions.....	60
9.1.1	General.....	60
9.1.2	Sampling for gaseous emissions.....	60
9.1.3	Data evaluation.....	62
9.1.4	Calculation of mass emission.....	62
9.1.5	Dry/wet correction.....	68
9.1.6	NO <sub>x</sub> correction for humidity and temperature.....	72
9.1.7	Cycle work and specific emissions.....	72
9.1.8	NH <sub>3</sub> data evaluation.....	74
9.2	Particulate mass emission.....	74
9.2.1	General.....	74
9.2.2	Particulate sampling.....	75
9.2.3	Data evaluation.....	75
9.2.4	Calculation of mass emission.....	75
9.2.5	Effective weighting factor (steady-state discrete cycles only).....	80
9.3	Adjustment for emission controls that are regenerated on an infrequent (periodic) basis.....	81
9.4	Particle number emission.....	81
9.4.1	Time alignment.....	81

9.4.2	Determination of particle numbers for transient and ramped modal cycles (RMC) with a partial flow dilution or raw gas sampling system.....	81
9.4.3	Determination of particle numbers for transient and ramped modal cycles (RMC) with a full flow dilution system.....	82
9.4.4	Determination of particle numbers for discrete-mode cycles with a partial flow dilution system.....	82
9.4.5	Determination of particle numbers for discrete-mode cycles with a full flow dilution system.....	83
9.4.6	Test result.....	84
9.4.7	Determination of particle number background.....	85
9.5	Specific requirements for dual-fuel engines.....	86
9.5.1	Emission test procedure requirements for dual-fuel engines.....	86
9.5.2	Determination of molar component ratios and $u_{\text{gas}}$ values for dual-fuel engines.....	89
<b>10</b>	<b>Engine control area.....</b>	<b>91</b>
10.1	General remarks.....	91
10.2	Control area for engines tested to cycles C1, C2, E1 and H.....	91
10.3	Control area for engines tested to cycles D1, D2, E2, G1, G2 and G3.....	94
10.4	Control area for engines tested to test cycle I.....	94
10.5	Control area for engines tested to E3 and E5 test cycle.....	95
10.5.1	Control area for CI marine engines.....	95
10.5.2	Control area for engines tested to the E4 test cycle.....	97
10.5.3	Control area for engines tested to the F cycle.....	98
<b>Annex A</b> (normative)	<b>Steady-state discrete mode test cycles.....</b>	<b>100</b>
<b>Annex B</b> (normative)	<b>Steady-state ramped modal test cycles (RMCs).....</b>	<b>105</b>
<b>Annex C</b> (normative)	<b>Transient test cycles.....</b>	<b>111</b>
<b>Annex D</b> (informative)	<b>Calculation of the exhaust gas mass flow and/or of the combustion air mass flow.....</b>	<b>169</b>
<b>Annex E</b> (informative)	<b>Example programme for calculation of exhaust mass flows.....</b>	<b>189</b>
<b>Annex F</b> (informative)	<b>Example of calculation procedure (raw/partial flow).....</b>	<b>191</b>
<b>Annex G</b> (normative)	<b>Installation requirements for equipment and auxiliaries.....</b>	<b>194</b>
<b>Annex H</b> (normative)	<b>Molar based emission calculations.....</b>	<b>196</b>
<b>Bibliography</b>	<b>.....</b>	<b>236</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

The committee responsible for this document is ISO/TC 70, *Reciprocating internal combustion engines*, Subcommittee SC 8, *Exhaust emission measurement*.

This third edition cancels and replaces the second edition (ISO 8178-4:2007) which has been technically revised.

A list of all the parts in the ISO 8178- series, can be found on the ISO website.

## Introduction

In comparison with engines for on-road applications, engines for non-road use are made in a much wider range of power output and configuration and are used in a great number of different applications.

The objective of this document is to rationalize the test procedures for non-road engines in order to simplify and make more cost effective the drafting of legislation, the development of engine specifications and the certification of engines to control gaseous and particulate emissions.

This document embraces three concepts in order to achieve the objectives.

The first principle is to group applications with similar engine operating characteristics in order to reduce the number of test cycles to a minimum, but ensure that the test cycles are representative of actual engine operation.

The second principle is to express the emissions results on the basis of brake power as defined in ISO 8178-1. This ensures that alternative engine applications do not result in a multiplicity of tests.

The third principle is the incorporation of an engine family concept in which engines with similar emission characteristics and of similar design may be represented by the highest emitting engine within the group.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 8178-4:2017](https://standards.iteh.ai/catalog/standards/sist/626e40ec-41e1-43fb-88d7-998376ff9312/iso-8178-4-2017)

<https://standards.iteh.ai/catalog/standards/sist/626e40ec-41e1-43fb-88d7-998376ff9312/iso-8178-4-2017>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 8178-4:2017

<https://standards.iteh.ai/catalog/standards/sist/626e40ec-41e1-43fb-88d7-998376ff9312/iso-8178-4-2017>



# Reciprocating internal combustion engines — Exhaust emission measurement —

## Part 4: Steady-state and transient test cycles for different engine applications

### 1 Scope

This document specifies the test cycles, the test procedures and the evaluation of gaseous and particulate exhaust emissions from reciprocating internal combustion (RIC) engines coupled to a dynamometer. With certain restrictions, this document can also be used for measurements at site. The tests are carried out under steady-state and transient operation using test cycles which are representative of given applications.

This document is applicable to RIC engines for mobile, transportable and stationary use, excluding engines for on-road transport of passengers and goods. It may be applied to engines for non-road use, e.g. for earth-moving machines, generating sets and for other applications. For engines used in machinery covered by additional requirements (e.g. occupational health and safety regulations, regulations for power plants) additional test conditions and special evaluation methods may apply.

### 2 Normative references

ISO 8178-4:2017

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8178-1, *Reciprocating internal combustion engines — Exhaust emission measurement — Part 1: Test-bed measurement of gaseous and particulate exhaust emissions*

ISO 8178-5, *Reciprocating internal combustion engines — Exhaust emission measurement — Part 5: Test fuels*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

#### 3.1

##### adjustment factors

additive (upward adjustment factor and downward adjustment factor) or multiplicative factors to be used for engines equipped with emission controls, that are regenerated on an infrequent (periodic) basis

#### 3.2

##### applicable emission limit

emission limit to which an engine is subject

**3.3**  
**aqueous condensation**

precipitation of water-containing constituents from a gas phase to a liquid phase

Note 1 to entry: Aqueous condensation is a function of humidity, pressure, temperature, and concentrations of other constituents such as sulphuric acid. These parameters vary as a function of engine intake-air humidity, dilution-air humidity, engine air-to-fuel ratio, and fuel composition - including the amount of hydrogen and sulphur in the fuel

**3.4**  
**atmospheric pressure**

wet, absolute, atmospheric static pressure

Note 1 to entry: If the atmospheric pressure is measured in a duct, negligible pressure losses shall be ensured between the atmosphere and the measurement location, and changes in the duct's static pressure resulting from the flow shall be accounted for

**3.5**  
**calibration**

process of setting a measurement system's response so that its output agrees with a range of reference signals

Note 1 to entry: Contrast with *verification* (3.80)

**3.6**  
**calibration gas**

purified gas mixture used to calibrate gas analysers meeting the specifications of ISO 8178-1, 9.2

Note 1 to entry: Calibration gases and span gases are qualitatively the same, but differ in terms of their primary function. Various performance verification checks for gas analysers and sample handling components might refer to either calibration gases or span gases

**3.7**  
**certification**

relating to the process of obtaining a certificate of conformity

ISO 8178-4:2017  
<https://standards.iteh.ai/catalog/standards/sist/626e40ec-41e1-43fb-88d7-998376ff9312/iso-8178-4-2017>

**3.8**  
**compression ignition engine**

CI engine

engine that works on the compression-ignition principle

**3.9**  
**constant-speed engine**

engine whose type approval or certification is limited to constant-speed operation

Note 1 to entry: Engines whose constant-speed governor function is removed or disabled are no longer constant-speed engines

**3.10**  
**constant-speed operation**

engine operation with a governor that automatically controls the operator demand to maintain engine speed, even under changing load

Note 1 to entry: Governors do not always maintain speed exactly constant. Typically, speed can decrease (0,1 to 10) % below the speed at zero load, such that the minimum speed occurs near the engine's point of maximum power

**3.11**  
**continuous regeneration**

regeneration process of an exhaust after-treatment system that occurs either in a sustained manner or at least once over the applicable transient test cycle or ramped-modal cycle; in contrast to infrequent (periodic) regeneration

### 3.12 conversion efficiency of non-methane cutter (NMC)

**E**

efficiency of the conversion of an NMC that is used for the removal of the non-methane hydrocarbons from the sample gas by oxidizing all hydrocarbons except methane

Note 1 to entry: Ideally, the conversion for methane is 0 % ( $E_{\text{CH}_4} = 0$ ) and for the other hydrocarbons represented by ethane 100 % ( $E_{\text{C}_2\text{H}_6} = 100$  %). For the accurate measurement of NMHC, the two efficiencies shall be determined and used for the calculation of the NMHC emission mass flow rate for methane and ethane. Contrast with *penetration fraction* (3.54)

### 3.13 delay time

difference in time between the change of the component to be measured at the reference point and a system response of 10 % of the final reading ( $t_{10}$ ) with the sampling probe being defined as the reference point

Note 1 to entry: For the gaseous components, this is the transport time of the measured component from the sampling probe to the detector (see [Figure 1](#))

### 3.14 deNO<sub>x</sub> system

exhaust after-treatment system designed to reduce emissions of oxides of nitrogen (NO<sub>x</sub>)

EXAMPLE passive and active lean NO<sub>x</sub> catalysts, NO<sub>x</sub> adsorbers and selective catalytic reduction (SCR) systems

### 3.15 dew point

measure of humidity stated as the equilibrium temperature at which water condenses under a given pressure from moist air with a given absolute humidity

Note 1 to entry: Dew point is specified as a temperature in °C or K, and is valid only for the pressure at which it is measured

### 3.16 discrete-mode

relating to a discrete-mode type of steady-state test, as described in [7.5.1](#) and [Annex A](#)

### 3.17 drift

difference between a zero or calibration signal and the respective value reported by a measurement instrument immediately after it was used in an emission test, as long as the instrument was zeroed and spanned just before the test

### 3.18 dual-fuel engine

engine system that is designed to simultaneously operate with liquid fuel and a gaseous fuel, both fuels being metered separately, where the consumed amount of one of the fuels relative to the other one may vary depending on the operation

### 3.19 emission-control system

device, system, or element of design that controls or reduces the emissions of regulated pollutants from an engine

### 3.20 engine family

manufacturers grouping of engines which, through their design as defined in ISO 8178-7, have similar exhaust emission characteristics

Note 1 to entry: All members of the family shall comply with the applicable emission limit values.

**3.21**

**engine governed speed**

engine operating speed when it is controlled by the installed governor

**3.22**

**engine type**

category of engines which do not differ in essential engine characteristics

**3.23**

**exhaust after-treatment system**

catalyst, particulate filter, deNO<sub>x</sub> system, combined deNO<sub>x</sub> particulate filter or any other emission-reducing device that is installed downstream of the engine

Note 1 to entry: This definition excludes exhaust gas recirculation (EGR) and turbochargers, which are considered an integral part of the engine.

**3.24**

**exhaust-gas recirculation**

technology that reduces emissions by routing exhaust gases that had been exhausted from the combustion chamber(s) back into the engine to be mixed with incoming air before or during combustion

Note 1 to entry: The use of valve timing to increase the amount of residual exhaust gas in the combustion chamber(s) that is mixed with incoming air before or during combustion is not considered exhaust-gas recirculation for the purposes of this standard

**3.25**

**full flow dilution method**

process of mixing the total exhaust flow with dilution air prior to separating a fraction of the diluted exhaust stream for analysis

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

**3.26**

**gas energy ratio**

**GER**

the energy content (for a dual-fuel engine) of the gaseous fuel divided by the energy content of both fuels (liquid and gaseous), the energy content of the fuels being defined as the lower heating value

ISO 8178-4:2017  
<https://standards.iteh.ai/catalog/standards/sist/626e40ec-41e1-43fb-88d7-998376ff9312/iso-8178-4-2017>

**3.27**

**gaseous fuel**

fuel which is wholly gaseous at standard ambient conditions

Note 1 to entry: Ambient temperature 298 K (25 °C), absolute ambient pressure 101,3 kPa.

**3.28**

**gaseous pollutants**

carbon monoxide, hydrocarbons and/or non-methane hydrocarbons (assuming a ratio of CH<sub>1,85</sub> for diesel), methane and oxides of nitrogen (expressed as nitrogen dioxide (NO<sub>2</sub>) equivalent)

**3.29**

**good engineering judgement**

judgement made consistent with generally accepted scientific and engineering principles and available relevant information

**3.30**

**governor**

device or control strategy that automatically controls engine speed or load that is not an over-speed limiter

**3.31**  
**hydrocarbon**  
**HC**

THC, NMHC as applicable

Note 1 to entry: Hydrocarbon generally means the hydrocarbon group on which the emission standards are based for each type of fuel and engine.

**3.32**  
**high speed**

$n_{hi}$   
highest engine speed where 70 % of the maximum power occurs

**3.33**  
**idle speed**

engine speed declared by the manufacturer that conforms to the requirements of [7.2.4](#)

**3.34**  
**infrequent (periodic) regeneration**

regeneration process of an exhaust after-treatment system that occurs periodically in typically less than 100 hours of normal engine operation

Note 1 to entry: During cycles where regeneration occurs, emission standards may be exceeded

**3.35**  
**intermediate speed**

engine speed declared by the manufacturer that conforms to the requirements of [7.2.3](#)

**3.36**  
**internationally traceable recognized standard**

international standard which includes but is not limited to the list quoted in the following table:

<https://standards.iteh.ai/catalog/standards/sist/626e40ec-41e1-43fb-88d7-909376f80313/iso-8178-4:2017>

**Table 1 — Internationally traceable recognized standard**

Internationally recognized standard	Where copies of the documents may be purchased
American Society for Testing and Materials (ASTM)	American Society for Testing and Materials, 100 Barr Harbour Dr., P.O. Box C700, West Conshohocken, PA 19428 or <a href="http://www.astm.com">www.astm.com</a>
International Organization for Standardization (ISO)	International Organization for Standardization, Case Postale 401, CH-1214 Vernier, Geneva, Switzerland or <a href="http://www.iso.org">www.iso.org</a>
National Institute of Standards and Technology (NIST)	Government Printing Office, Washington, DC 20402 or download them free from the Internet at <a href="http://www.nist.gov">www.nist.gov</a>
Society of Automotive Engineering (SAE)	Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096 or <a href="http://www.sae.org">www.sae.org</a>
Institute of Petroleum	Energy Institute, 61 New Cavendish Street, London, W1G 7AR, UK, +44 (0)20 7467 7100 or <a href="http://www.energyinst.org.uk">www.energyinst.org.uk</a>
The National Metrology Institute of Japan (NMIJ)	AIST Tsukuba Headquarters, 1-1-1 Umezono, Tsukuba, Ibaraki 305-8568, Japan or <a href="http://www.nmij.jp/english/info/">www.nmij.jp/english/info/</a>
Japanese Industrial Standards (JIS)	Japanese Standards Association (JSA), 4-1-12 Akasaka, Minato-ku, 107-8440, Japan or <a href="http://www.jsa.org.jp/default_english.asp">www.jsa.org.jp/default_english.asp</a>

**3.37**  
**linearity**

degree to which measured values agree with respective reference values quantified using a linear regression of pairs of measured values and reference values over a range of values expected or observed during testing

**3.38**

**liquid fuel**

fuel which exists in the liquid state under standard ambient conditions (298K, absolute ambient pressure 101,3 kPa)

**3.39**

**low speed**

$n_{l0}$

lowest engine speed where 50 % of the maximum power occurs

**3.40**

**maximum no load speed**

engine speed at which an engine governor function controls engine speed with operator demand at maximum and with zero load applied

**3.41**

**maximum power**

maximum power in kW as designed by the manufacturer

**3.42**

**maximum test speed**

engine speed determined from the curve of engine speed versus power according to [7.2.1](#)

**3.43**

**maximum torque speed**

engine speed at which the maximum torque is obtained from the engine, as designed by the manufacturer

**3.44**

**mode**

engine operating point characterized by a speed and a torque (or a power output)

**3.45**

**mode length**

time between leaving the speed and/or torque of the previous mode or the preconditioning phase and the beginning of the following mode

Note 1 to entry: It includes the time during which speed and/or torque is being changed and the stabilization at the beginning of each mode.

**3.46**

**non-methane hydrocarbons**

NMHC

sum of all hydrocarbon species except methane

**3.47**

**normalized speed and torque**

speed and torque values expressed as a percentage of a maximum value

**3.48**

**open crankcase emissions**

flow from an engine's crankcase that is emitted directly into the environment

Note 1 to entry: Crankcase emissions are not "open crankcase emissions" if the engine is designed to always route all crankcase emissions back into the engine (for example, through the intake system or an aftertreatment system) such that all the crankcase emissions, or their products, are emitted into the environment only through the engine exhaust system.

### 3.49 operator demand

engine operator's input to control engine output

Note 1 to entry: The "operator" may be a person (i.e. manual), or a governor (i.e. automatic) that mechanically or electronically signals an input that demands engine output. Input may be from an accelerator pedal or signal, a throttle-control lever or signal, a fuel lever or signal, a speed lever or signal, or a governor setpoint or signal. Output means engine power,  $P$ , which is the product of engine speed,  $n$ , and engine torque,  $T$ .

### 3.50 oxides of nitrogen

compounds containing only nitrogen and oxygen as measured by the procedures specified in this document

Note 1 to entry: Oxides of nitrogen are expressed quantitatively as if the NO is in the form of NO<sub>2</sub>, such that an effective molar mass is used for all oxides of nitrogen equivalent to that of NO<sub>2</sub>.

### 3.51 partial pressure

pressure,  $p$ , attributable to a single gas in a gas mixture

Note 1 to entry: For an ideal gas, the partial pressure divided by the total pressure is equal to the constituent's molar concentration,  $x$ .

### 3.52 partial flow dilution method

process of separating a part from the total exhaust flow, then mixing it with an appropriate amount of dilution air prior to the particulate sampling filter

### 3.53 particulate matter PM

material collected on a specified filter medium after diluting exhaust with clean filtered air to a temperature and a point as specified in ISO 8178-1, 8.1.3

Note 1 to entry: This is primarily carbon, condensed hydrocarbons, and sulphates with associated water.

### 3.54 penetration fraction PF

deviation from ideal functioning of a non-methane cutter

Note 1 to entry: See *conversion efficiency of non-methane cutter* (NMC)  $E$ , 3.12.

Note 2 to entry: An ideal non-methane cutter would have a methane penetration factor,  $PF_{CH_4}$ , of 1,000 (that is, a methane conversion efficiency  $E_{CH_4}$  of 0), and the penetration fraction for all other hydrocarbons would be 0,000, as represented by  $PF_{C_2H_6}$  (that is, an ethane conversion efficiency  $E_{C_2H_6}$  of 1). The relationship is:  $PF_{CH_4} = 1 - E_{CH_4}$  and  $PF_{C_2H_6} = 1 - E_{C_2H_6}$

### 3.55 per cent load

fraction of the maximum available torque at an engine speed

### 3.56 probe

first section of the transfer line which transfers the sample to the next component in the sampling system

### 3.57 procedures

all aspects of engine testing, including the equipment specifications, calibrations, calculations and other protocols and specifications needed to measure emissions, unless otherwise specified